

**Product Code:** 

CARC7SY40

Selling UOM:

Each

Pack Size:



Anti Static



**Arc Flash Protection** 



Cat 3 - High Risk Fire Retardant





Hi Visibility



Protection for Welding and Allied Processes

## SPECIFICATION

## **HIVIS YELLOW COVERALL 40**



- Fire Retardant, Hi Vis, Anti-static, ARC Flash coverall.
- 300gsm 60/40 Modacrylic/cotton blend.
- Triple stitch construction.
- 2 hip pockets.
- Large bellows pocket to each leg with hook and loop closure flap.
- Right leg mobile phone pocket with hook and loop closure flap.
- All pocket flaps with Retro-reflective tape feature.
- Internal knee pad pouches.
- · Large qualifying icons on left leg pocket.
- EN ISO 13688:2013 General requirements for protective clothing
- EN ISO 20471:2013 Class 3 Test method for high visibility
- EN 1149-3:2004 Anti Static Test methods for measurements of charge decay
- EN 1149-5:2008 Anti Static Material performance and design requirements
- EN ISO 11611:2015 (Class 1 A1 A2) Protective clothing for use in
- EN ISO 11612:2015 (A1 A2 B1 C1) Protection against heat and flame

## ARC FLASH

IEC 61482-2:2009 - Performance requirements and design requirements EN 61482-1-2:2007 (Class 1 = 4kA) - Box Arc testing EN 61482-1-1:2009 (ATPV = 10.8 Cal/cm2) - Open Arc testing

- Each garment style is independently tested to both box and open ARC standards.
- Click ARC production is covered by article 11B certification.



Packaging Waste	Туре	Units	Weight(g)	Length(mm)	Width(mm)	Height(mm)
Cardboard	Outer	1	980.00	604.00	418.00	304.00
Plastic	Inner	10	30.03			
Tissue Paper	Inner	10	0.61			
Paper	Inner	10	7.17			
Cardboard	Inner	10	1 11			

1.41

15.78ka

Carton Weight: