

PRODUCT SAFETY DATA SHEET



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Finish Power Essential

SDS number: D8400725

Code: D8400725 / 3261397 3260936 3262539 3260930

1.2. Relevant identified uses of the substance or mixture and uses advised against

Automatic dishwashing detergents - household use

Consumer use

1.3. Details of the Supplier of the Safety Data Sheet

The United Kingdom:

RB UK Hygiene Home Commercial Ltd
Wellcroft House
Wellcroft Road
Slough, Berkshire SL1 4AQ
Tel: 0800 376 8181
Email: ConsumerCare_UK@reckitt.com

The Republic Of Ireland:

RB Ireland Hygiene Home Commercial Ltd
7 Riverwalk
Citywest Business Campus
Dublin 24
Ireland
Tel: 01 661 7318
Email: ConsumerHealth_IE@reckitt.com

1.4 Emergency telephone number

GB - NHS 111/NHS 24 Tel: 111

NI - www.gpoutofhours.hscni.net/

IE - Poisons Information Centre of Ireland: 01 809 2166 8am-10pm 7 days a week.

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Eye Irrit. 2, H319

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

D8400725

SECTION 2: Hazards identification

Hazard pictograms :



Signal word :

Warning

Hazard statements :

Causes serious eye irritation.

Precautionary statements

General :

If medical advice is needed, have product container or label at hand.
Keep out of reach of children.

Prevention :

Not applicable.

Response :

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice.

Storage :

Not applicable.

Disposal :

Not applicable.

Supplemental label elements :

75% or over but less than 30% oxygen-based bleaching agents
5% or over but less than 15% phosphonates and polycarboxylates
less than 5% non-ionic surfactants
Contains enzymes (subtilisin, amylase)
Contains perfumes

Special packaging requirements

Containers to be fitted with child-resistant fastenings :

Not applicable.

Tactile warning of danger :

Not applicable.

2.3 Other hazards

Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII :

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Other hazards which do not result in classification :

None known.

SECTION 3: Composition/information on ingredients

3.2 Mixtures :

Mixture

| Product/ingredient name | Identifiers | % | Classification | Specific Conc. Limits, M-factors and ATEs | Type |
|---------------------------|---|-----------|--|---|------|
| SODIUM CARBONATE | REACH #: 01-2119485498-19 EC: 207-838-8 CAS: 497-19-8 Index: 011-005-00-2 | ≥10 - ≤25 | Eye Irrit. 2, H319 | - | [1] |
| SODIUM CARBONATE PEROXIDE | REACH #: 01-2119457268-30 EC: 239-707-6 CAS: 15630-89-4 | ≥10 - ≤16 | Ox. Sol. 3, H272 Acute Tox. 4, H302 Eye Dam. 1, H318 | Ox. Sol. 3, H272: C ≥ 25% ATE [Oral] = 1034 mg/kg Eye Dam. 1, H318: C ≥ 25% Eye Irrit. 2, H319: 7.5% ≤ C < 25% | [1] |

D8400725

SECTION 3: Composition/information on ingredients

| | | | | | |
|---|---|-----|---|---------------------------|-----|
| TETRASODIUM ETIDRONATE | REACH #: 01-2119647955-23 EC: 223-267-7 CAS: 3794-83-0 | ≤10 | Acute Tox. 4, H302 Eye Irrit. 2, H319 | ATE [Oral] = 940 mg/kg | [1] |
| Alcohols, C16-18, ethoxylated (>25 EO) | EC: 500-212-8 CAS: 68439-49-6 | ≤5 | Eye Irrit. 2, H319 | - | [1] |
| SODIUM SILICATE | REACH #: 01-2119448725-31 EC: 215-687-4 CAS: 1344-09-8 | ≤1 | Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H335 Aquatic Chronic 3, H412 See Section 16 for the full text of the H statements declared above. | - | [1] |

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

[1] Substance classified with a health or environmental hazard

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Skin contact** : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

4.2 Most important symptoms and effects, both acute and delayed

Over-exposure signs/symptoms

D8400725

SECTION 4: First aid measures

- Eye contact** : Adverse symptoms may include the following:
pain or irritation
watering
redness
- Inhalation** : No specific data.
- Skin contact** : No specific data.
- Ingestion** : No specific data.

4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician** : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Specific treatments** : No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media** : Use an extinguishing agent suitable for the surrounding fire.
- Unsuitable extinguishing media** : None known.

5.2 Special hazards arising from the substance or mixture

- Hazards from the substance or mixture** : No specific fire or explosion hazard.
- Hazardous combustion products** : Decomposition products may include the following materials:
carbon dioxide
carbon monoxide
nitrogen oxides
sulfur oxides
phosphorus oxides
metal oxide/oxides

5.3 Advice for firefighters

- Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

- 6.2 Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

D8400725

SECTION 6: Accidental release measures

6.3 Methods and materials for containment and cleaning up

- Small spill** : Move containers from spill area. Avoid dust generation. Using a vacuum with HEPA filter will reduce dust dispersal. Place spilled material in a designated, labeled waste container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Dispose of via a licensed waste disposal contractor.

- 6.4 Reference to other sections** : See Section 1 for emergency contact information.
See Section 8 for information on appropriate personal protective equipment.
See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Do not store above the following temperature: 30°C (86°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)

- Recommendations** : Machine dishwashing (powder, liquid, tablet) for consumer use
- Industrial sector specific solutions** : Not available.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits

No exposure limit value known.

DNELs/DMELs

D8400725

SECTION 8: Exposure controls/personal protection

| Product/ingredient name | Type | Exposure | Value | Population | Effects |
|--|------|-----------------------|-------------------------|--------------------|----------|
| SODIUM CARBONATE | DNEL | Long term Inhalation | 10 mg/m ³ | General population | Local |
| | DNEL | Short term Inhalation | 10 mg/m ³ | General population | Local |
| | DNEL | Long term Inhalation | 10 mg/m ³ | Workers | Local |
| SODIUM CARBONATE PEROXIDE | DNEL | Short term Inhalation | 5 mg/m ³ | Workers | Local |
| | DNEL | Long term Inhalation | 5 mg/m ³ | Workers | Local |
| | DNEL | Short term Dermal | 6.4 mg/cm ² | General population | Local |
| | DNEL | Long term Dermal | 6.4 mg/cm ² | General population | Local |
| | DNEL | Short term Dermal | 12.8 mg/cm ² | Workers | Local |
| TETRASODIUM ETIDRONATE | DNEL | Long term Oral | 2.4 mg/kg bw/day | General population | Systemic |
| | DNEL | Long term Inhalation | 4.2 mg/m ³ | General population | Systemic |
| | DNEL | Long term Inhalation | 10 mg/m ³ | General population | Local |
| | DNEL | Long term Inhalation | 10 mg/m ³ | Workers | Local |
| | DNEL | Long term Inhalation | 16.9 mg/m ³ | Workers | Systemic |
| | DNEL | Long term Dermal | 24 mg/kg bw/day | General population | Systemic |
| | DNEL | Long term Dermal | 48 mg/kg bw/day | Workers | Systemic |
| Alcohols, C16-18, ethoxylated (>25 EO) | DNEL | Long term Oral | 25 mg/kg bw/day | General population | Systemic |
| | DNEL | Long term Inhalation | 87 mg/m ³ | General population | Systemic |
| | DNEL | Long term Inhalation | 294 mg/m ³ | Workers | Systemic |
| | DNEL | Long term Dermal | 1250 mg/kg bw/day | General population | Systemic |
| | DNEL | Long term Dermal | 2080 mg/kg bw/day | Workers | Systemic |
| SODIUM SILICATE | DNEL | Long term Oral | 0.8 mg/kg bw/day | General population | Systemic |
| | DNEL | Long term Dermal | 0.8 mg/kg bw/day | General population | Systemic |
| | DNEL | Long term Inhalation | 1.38 mg/m ³ | General population | Systemic |
| | DNEL | Long term Dermal | 1.59 mg/kg bw/day | Workers | Systemic |
| | DNEL | Long term Inhalation | 5.61 mg/m ³ | Workers | Systemic |

PNECs

| Product/ingredient name | Compartment Detail | Value | Method Detail |
|---------------------------|------------------------|------------|--------------------|
| SODIUM CARBONATE PEROXIDE | Sewage Treatment Plant | 16.24 mg/l | Assessment Factors |
| | Fresh water | 0.035 mg/l | Assessment Factors |
| | Marine water | 0.035 mg/l | Assessment Factors |

SECTION 8: Exposure controls/personal protection

8.2 Exposure controls

Appropriate engineering controls : Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

Individual protection measures

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

Skin protection

Hand protection : EN 16523-1:2015
Tested for protection against chemical permeation.
Low chemical resistant or waterproof gloves.
(EN 16523-1:2015 supersedes EN 374-3:2003)
EN 374-2:2003
Tested for protection against liquid penetration and micro-organisms.
EN 388:2003
Tested for protection against mechanical risks (abrasion, blade cut resistance, tear resistance and puncture resistance).
ISO 374-1:2016/Type A
Protective glove with permeation resistance of at least 30 minutes each for at least 6 test chemicals.
ISO 374-1:2016/Type B
Protective glove with permeation resistance of at least 30 minutes each for at least 3 test chemicals.
ISO 374-1:2016/Type C
Protective glove with permeation resistance of at least 10 minutes for at least 1 test chemical.
Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Body protection : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Environmental exposure controls : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

D8400725

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Appearance

| | |
|--|---|
| Physical state | : Solid. |
| Color | : White. Blue. Red. |
| Odor | : Fragrant. |
| Odor threshold | : Not relevant/applicable due to nature of the product. |
| Melting point/freezing point | : Not relevant/applicable due to nature of the product. |
| Initial boiling point and boiling range | : Not relevant/applicable due to nature of the product. |
| Flammability (solid, gas) | : Not relevant/applicable due to nature of the product. |
| Upper/lower flammability or explosive limits | : Not relevant/applicable due to nature of the product. |
| Flash point | : Not relevant/applicable due to nature of the product. |
| Auto-ignition temperature | : Not relevant/applicable due to nature of the product. |
| Decomposition temperature | : Not relevant/applicable due to nature of the product. |
| pH | : 9.9 to 10.5 [Conc. (% w/w): 10%] |
| Viscosity | : Not relevant/applicable due to nature of the product. |
| Solubility(ies) | : |

| Media | Result |
|------------|---------|
| cold water | Soluble |
| hot water | Soluble |

Partition coefficient: n-octanol/ water : Not relevant/applicable due to nature of the product.

Vapor pressure : Not relevant/applicable due to nature of the product.

Vapor density : Not relevant/applicable due to nature of the product.

Particle characteristics

Median particle size : > 10 µm

9.2 Other information

SADT : >55°C

Heat of reaction : <300 J/g

SECTION 10: Stability and reactivity

10.1 Reactivity : No specific test data related to reactivity available for this product or its ingredients.

10.2 Chemical stability : Do not expose to temperatures exceeding 50 °C/122 °F.

10.3 Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will not occur.

10.4 Conditions to avoid : Keep away from heat and direct sunlight. Protect from moisture.

10.5 Incompatible materials : No specific data.

10.6 Hazardous decomposition products : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

D8400725

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

| Product/ingredient name | Result | Species | Dose | Exposure |
|---|-------------|--------------------------|------------|----------|
| SODIUM CARBONATE | LD50 Dermal | Mouse - Female | 2210 mg/kg | - |
| SODIUM CARBONATE PEROXIDE | LD50 Oral | Rat | 2800 mg/kg | - |
| | LD50 Dermal | Rabbit | 2001 mg/kg | - |
| TETRASODIUM ETIDRONATE | LD50 Oral | Rat | 1034 mg/kg | - |
| | LD50 Dermal | Rabbit - Male, Female | 2001 mg/kg | - |
| Alcohols, C16-18, ethoxylated (>25 EO) | LD50 Oral | Rat | 940 mg/kg | - |
| | LD50 Oral | Rat | 1260 mg/kg | - |
| | LD50 Oral | Rat | 5000 mg/kg | - |

Conclusion/Summary : Based on available data, the classification criteria are not met.

Acute toxicity estimates

| Product/ingredient name | Oral (mg/kg) | Dermal (mg/kg) | Inhalation (gases) (ppm) | Inhalation (vapors) (mg/l) | Inhalation (dusts and mists) (mg/l) |
|--|--------------|----------------|--------------------------|----------------------------|-------------------------------------|
| Finish Power Essential Shaolin Tabs Fresh_3232012_D8400725_EU | 4220.2 | N/A | N/A | N/A | N/A |
| SODIUM CARBONATE | 2800 | 5000 | N/A | N/A | N/A |
| SODIUM CARBONATE PEROXIDE | 1034 | 2001 | N/A | N/A | N/A |
| TETRASODIUM ETIDRONATE | 940 | 2001 | N/A | N/A | N/A |

Irritation/Corrosion

| Product/ingredient name | Result | Species | Score | Exposure | Observation |
|---|--------------------------|---------|-------|-----------------------|-------------|
| SODIUM CARBONATE | Eyes - Mild irritant | Rabbit | - | 0.5 minutes 100 mg | - |
| | Eyes - Moderate irritant | Rabbit | - | 24 hours 100 mg | - |
| Alcohols, C16-18, ethoxylated (>25 EO) | Eyes - Moderate irritant | Rabbit | - | 24 hours 100 uL | - |
| | Skin - Moderate irritant | Rabbit | - | 24 hours 500 uL | - |
| SODIUM SILICATE | Eyes - Severe irritant | Rabbit | - | 24 hours 10 mg | - |
| | Skin - Severe irritant | Rabbit | - | 24 hours 500 mg | - |

Conclusion/Summary

Skin : Based on available data, the classification criteria are not met.

Eyes : Calculation method Causes serious eye irritation.

Respiratory : Based on available data, the classification criteria are not met.

Sensitization

Conclusion/Summary

Skin : Based on available data, the classification criteria are not met.

Respiratory : Based on available data, the classification criteria are not met.

Mutagenicity

Conclusion/Summary : Based on available data, the classification criteria are not met.

Carcinogenicity

Conclusion/Summary : Based on available data, the classification criteria are not met.

Reproductive toxicity

D8400725

SECTION 11: Toxicological information

Conclusion/Summary : Based on available data, the classification criteria are not met.

Teratogenicity

Conclusion/Summary : Based on available data, the classification criteria are not met.

Specific target organ toxicity (single exposure)

| Product/ingredient name | Category | Route of exposure | Target organs |
|-------------------------|------------|-------------------|------------------------------|
| SODIUM SILICATE | Category 3 | - | Respiratory tract irritation |

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Information on the likely routes of exposure : Not available.

Potential acute health effects

- Eye contact** : Causes serious eye irritation.
Inhalation : No known significant effects or critical hazards.
Skin contact : No known significant effects or critical hazards.
Ingestion : No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

- Eye contact** : Adverse symptoms may include the following:
pain or irritation
watering
redness
- Inhalation** : No specific data.
Skin contact : No specific data.
Ingestion : No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

- Potential immediate effects** : Not available.
Potential delayed effects : Not available.

Long term exposure

- Potential immediate effects** : Not available.
Potential delayed effects : Not available.

Potential chronic health effects

Not available.

- Conclusion/Summary** : Based on available data, the classification criteria are not met.
General : No known significant effects or critical hazards.
Carcinogenicity : No known significant effects or critical hazards.
Mutagenicity : No known significant effects or critical hazards.
Reproductive toxicity : No known significant effects or critical hazards.

11.2 Information on other hazards

D8400725

SECTION 11: Toxicological information

11.2.1 Endocrine disrupting properties

Not available.

11.2.2 Other information

Not available.

SECTION 12: Ecological information

12.1 Toxicity

| Product/ingredient name | Result | Species | Exposure |
|---------------------------|------------------------------------|--|----------|
| SODIUM CARBONATE | Acute EC50 242000 µg/l Fresh water | Algae - Navicula seminulum | 96 hours |
| | Acute LC50 176000 µg/l Fresh water | Crustaceans - Amphipoda | 48 hours |
| | Acute LC50 265000 µg/l Fresh water | Daphnia - Daphnia magna | 48 hours |
| | Acute LC50 300000 µg/l Fresh water | Fish - Lepomis macrochirus | 96 hours |
| | Acute EC50 4.9 mg/l | Daphnia - Daphnia Pulex | 48 hours |
| SODIUM CARBONATE PEROXIDE | | | |
| SODIUM SILICATE | Acute EC50 33.53 mg/l Fresh water | Crustaceans - Ceriodaphnia dubia - Neonate | 48 hours |
| | Acute LC50 494000 µg/l Fresh water | Daphnia - Daphnia magna | 48 hours |

Conclusion/Summary : Based on available data, the classification criteria are not met.

12.2 Persistence and degradability

| Product/ingredient name | Test | Result | Dose | Inoculum |
|--|-----------|---------------------------|------|----------|
| Alcohols, C16-18, ethoxylated (>25 EO) | OECD 303A | 90 % - Readily - 28 days | - | - |
| | OECD 301B | >60 % - Readily - 28 days | - | - |

Conclusion/Summary : The surfactant(s) contained in this preparation complies(comply) with the biodegradability criteria as laid down in Regulation (EC) No.648/2004 on detergents. Data to support this assertion are held at the disposal of the competent authorities of the Member States and will be made available to them, at their direct request or at the request of a detergent manufacturer.

| Product/ingredient name | Aquatic half-life | Photolysis | Biodegradability |
|--|-------------------|------------|------------------|
| Alcohols, C16-18, ethoxylated (>25 EO) | - | - | Readily |

12.3 Bioaccumulative potential

| Product/ingredient name | LogP _{ow} | BCF | Potential |
|-------------------------|--------------------|-----|-----------|
| TETRASODIUM ETIDRONATE | -3 | 71 | low |

12.4 Mobility in soil

Soil/water partition coefficient (K_{oc}) : Not available.

Mobility : Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Endocrine disrupting properties

Not available.

12.7 Other adverse effects

D8400725

SECTION 12: Ecological information

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product

Methods of disposal : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Hazardous waste : The classification of the product may meet the criteria for a hazardous waste.

Packaging

Methods of disposal : The generation of waste should be avoided or minimized wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Special precautions : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

For long distance transport of bulk material or shrunk pallet take into consideration sections 7 and 10.

| | ADR/RID | ADN | IMDG | IATA |
|--|----------------|----------------|----------------|----------------|
| 14.1 UN number or ID number | Not regulated. | Not regulated. | Not regulated. | Not regulated. |
| 14.2 UN proper shipping name | - | - | - | - |
| 14.3 Transport hazard class(es) | - | - | - | - |
| 14.4 Packing group | - | - | - | - |
| 14.5 Environmental hazards | No. | No. | No. | No. |

14.6 Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Maritime transport in bulk according to IMO instruments : Not available.

D8400725

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorization

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions : None.
on the manufacture,
placing on the market
and use of certain
dangerous substances,
mixtures and articles

Other EU regulations

Ozone depleting substances (1005/2009/EU)

Not listed.

Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

Persistent Organic Pollutants

Not listed.

Seveso Directive

This product is not controlled under the Seveso Directive.

15.2 Chemical Safety Assessment : No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

✔ Indicates information that has changed from previously issued version.

Abbreviations and acronyms

: ATE = Acute Toxicity Estimate
CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
DMEL = Derived Minimal Effect Level
DNEL = Derived No Effect Level
EUH statement = CLP-specific Hazard statement
PBT = Persistent, Bioaccumulative and Toxic
PNEC = Predicted No Effect Concentration
RRN = REACH Registration Number
vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

| Classification | Justification |
|--------------------|--------------------|
| Eye Irrit. 2, H319 | Calculation method |

Full text of abbreviated H statements

| | |
|------|--|
| H272 | May intensify fire; oxidizer. |
| H302 | Harmful if swallowed. |
| H315 | Causes skin irritation. |
| H318 | Causes serious eye damage. |
| H319 | Causes serious eye irritation. |
| H335 | May cause respiratory irritation. |
| H412 | Harmful to aquatic life with long lasting effects. |

Full text of classifications [CLP/GHS]

D8400725

SECTION 16: Other information

| | |
|---|--|
| Acute Tox. 4 Aquatic Chronic 3 Eye Dam. 1 Eye Irrit. 2 Ox. Sol. 3 Skin Irrit. 2 STOT SE 3 | ACUTE TOXICITY - Category 4 AQUATIC HAZARD (LONG-TERM) - Category 3 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2 OXIDIZING SOLIDS - Category 3 SKIN CORROSION/IRRITATION - Category 2 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) - Category 3 |
|---|--|

Date of printing : 15/01/2023
Date of issue/ Date of revision : 15/01/2023
Date of previous issue : No previous validation
Version : 1

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.