

Trade name: edding refill ink whiteboard marker (blue) BTK25 contained in : edding 360, edding 363

Current version : 9.2.0, issued: 23.01.2025

Replaced version: 9.1.1, issued: 17.12.2024

Region: GB

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name

edding refill ink whiteboard marker (blue) BTK25 contained in : edding 360, edding 363

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

Ink for use in felt pens

Uses advised against

No data available.

1.3 Details of the supplier of the safety data sheet

Address

edding International GmbH

Bookkoppel 7

D-22926 Ahrensburg

Telephone no. +49 (0) 41 02 / 80 8-0

Information provided by / telephone

+49 (0)4102 - 808-0

Advice on Safety Data Sheet

sdb_info@umco.de

1.4 Emergency telephone number

For medical advice (in German and English):

+49 (0)30 30686 790 (Giftnotruf Berlin)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification in accordance with Regulation (EC) No 1272/2008 (CLP)

Eye Irrit. 2; H319

Flam. Liq. 2; H225

Classification information

This product is assessed and classified using the methods and criteria below referred to in Article 9 of Regulation (EC) n° 1272/2008:

Physical hazards: determined through assessment data based on the methods or standards referred to in part 2 of Annex I to CLP

Health hazards and environmental hazards: determined through toxicological and ecotoxicological assessment data based on the methods or standards referred to in Part 3, 4 and 5 of Annex I to CLP.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 (CLP Regulation)

Hazard pictograms



GHS02



GHS07

Signal word

Danger

Hazard statement(s)

H225

Highly flammable liquid and vapour.

H319

Causes serious eye irritation.

Trade name: edding refill ink whiteboard marker (blue) BTK25 contained in : edding 360, edding 363

Current version : 9.2.0, issued: 23.01.2025

Replaced version: 9.1.1, issued: 17.12.2024

Region: GB

Precautionary statement(s)

P101 If medical advice is needed, have product container or label at hand.
 P102 Keep out of reach of children.
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P370+P378 In case of fire: Use water spray, extinguishing powder, foam or CO2 to extinguish.
 P501 Dispose of contents/container to a facility in accordance with local and national regulations.

2.3 Other hazards

No data available.

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable. The product is not a substance.

3.2 Mixtures

Hazardous ingredients

No	Substance name	Additional information	
	CAS / EC / Index / REACH no	Classification (EC) 1272/2008 (CLP)	Concentration %
1	ethanol		
	64-17-5 200-578-6 603-002-00-5 01-2119457610-43	Flam. Liq. 2; H225 Eye Irrit. 2; H319	< 75.00 wt%
2	propan-2-ol		
	67-63-0 200-661-7 603-117-00-0 01-2119457558-25-0085	Eye Irrit. 2; H319 Flam. Liq. 2; H225 STOT SE 3; H336	< 15.00 wt%

Full text of H- and EUH-phrases, if not already mentioned in section 2.2: see section 16.

No	Note	Specific concentration limits	M-factor (acute)	M-factor (chronic)
1	-	Eye Irrit. 2; H319: C >= 50%	-	-

3.3 Other information

The data subject of this Material Safety Data sheet refer to the ink contained in this product (marker).

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

In case of persisting adverse effects, consult a physician. Remove contaminated clothing and shoes immediately, and launder thoroughly before reusing.

After inhalation

Remove affected person from the immediate area. Ensure supply of fresh air.

After skin contact

Rinse with plenty of water.

After eye contact

Remove contact lenses. Rinse eye thoroughly under running water keeping eyelids wide open and protecting the unaffected eye (at least 10 to 15 minutes). Seek medical assistance.

After ingestion

Rinse out mouth and give plenty of water to drink. Do not induce vomiting. Call a doctor immediately. Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

Trade name: edding refill ink whiteboard marker (blue) BTK25 contained in : edding 360, edding 363

Current version : 9.2.0, issued: 23.01.2025

Replaced version: 9.1.1, issued: 17.12.2024

Region: GB

No data available.

4.3 Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Alcohol-resistant foam; Extinguishing powder; Carbon dioxide; Water spray jet

Unsuitable extinguishing media

High power water jet

5.2 Special hazards arising from the substance or mixture

In the event of fire, the following can be released: Carbon dioxide (CO₂); Carbon monoxide (CO)

5.3 Advice for firefighters

Cool endangered containers with water spray jet. Use self-contained breathing apparatus. Suppress gases/vapours/mists with water spray jet. Wear protective clothing.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Refer to protective measures listed in sections 7 and 8. Avoid contact with skin, eyes and clothing. Ensure adequate ventilation. Keep away from ignition sources.

For emergency responders

No data available. Personal protective equipment (PPE) - see Section 8.

6.2 Environmental precautions

Do not discharge into the drains/surface waters/groundwater. Do not discharge into the subsoil/soil.

6.3 Methods and material for containment and cleaning up

Take up with absorbent material (e.g., sand, kieselguhr, universal binder). Send in suitable containers for recovery or disposal.

6.4 Reference to other sections

No data available.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling

Provide good ventilation at the work area (local exhaust ventilation, if necessary). If workplace exposure limits are exceeded, respiratory protection approved for this particular job must be worn. Risks inherent to handling the product must be minimised by applying the appropriate protective and preventive measures. Working processes should - so far as possible, according to the state of the art - be designed to rule out bodily contact or the release of hazardous substances.

General protective and hygiene measures

Do not eat, drink or smoke during work time. Keep away from foodstuffs and beverages. Avoid contact with eyes and skin. Remove soiled or soaked clothing immediately. Do not inhale vapours. Clean skin thoroughly after work; apply skin cream.

Advice on protection against fire and explosion

Vapours can form an explosive mixture with air. Take precautionary measures against static charges. Keep away from sources of heat and ignition. Use explosion-proof equipment/fittings and non-sparking tools.

7.2 Conditions for safe storage, including any incompatibilities

Technical measures and storage conditions

Keep container tightly closed and dry in a cool, well-ventilated place. Protect from heat and direct sunlight.

Requirements for storage rooms and vessels

Trade name: edding refill ink whiteboard marker (blue) BTK25 contained in : edding 360, edding 363

Current version : 9.2.0, issued: 23.01.2025

Replaced version: 9.1.1, issued: 17.12.2024

Region: GB

Containers which are opened must be carefully closed and kept upright to prevent leakage. Always keep in containers of same material as the original.

Incompatible products

Do not store together with: Alkali metals; Earth alkali metals; oxidizing agents; Acids

7.3 Specific end use(s)

No data available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values

No	Substance name	CAS no.	EC no.
1	ethanol	64-17-5	200-578-6
List of approved workplace exposure limits (WELs) / EH40			
Ethanol			
	WEL long-term (8-hr TWA reference period)	1920	mg/m ³ 1000 ppm
2	propan-2-ol	67-63-0	200-661-7
List of approved workplace exposure limits (WELs) / EH40			
Propan-2-ol			
	WEL short-term (15 min reference period)	1250	mg/m ³ 500 ppm
	WEL long-term (8-hr TWA reference period)	999	mg/m ³ 400 ppm

DNEL, DMEL and PNEC values

DNEL values (worker)

No	Substance name	CAS / EC no		
	Route of exposure	Exposure time	Effect	Value
1	ethanol	64-17-5 200-578-6		
	dermal	Long term (chronic)	systemic	8238 mg/kg/day
	inhalative	Long term (chronic)	systemic	380 mg/m ³
2	propan-2-ol	67-63-0 200-661-7		
	dermal	Long term (chronic)	systemic	888 mg/kg/day
	inhalative	Long term (chronic)	systemic	500 mg/m ³

DNEL value (consumer)

No	Substance name	CAS / EC no		
	Route of exposure	Exposure time	Effect	Value
1	ethanol	64-17-5 200-578-6		
	inhalative	Long term (chronic)	systemic	114 mg/m ³
2	propan-2-ol	67-63-0 200-661-7		
	oral	Long term (chronic)	systemic	26 mg/kg/day
	dermal	Long term (chronic)	systemic	319 mg/kg/day
	inhalative	Long term (chronic)	systemic	89 mg/m ³

PNEC values

No	Substance name	CAS / EC no	
	ecological compartment	Type	Value
1	ethanol		64-17-5 200-578-6
	water	fresh water	0.96 mg/L
	water	marine water	0.79 mg/L
	water	fresh water sediment	3.6 mg/kg dry weight
	water	marine water sediment	2.9 mg/L

Trade name: edding refill ink whiteboard marker (blue) BTK25 contained in : edding 360, edding 363

Current version : 9.2.0, issued: 23.01.2025

Replaced version: 9.1.1, issued: 17.12.2024

Region: GB

	soil	-	0.63	mg/kg dry weight
	sewage treatment plant	-	580	mg/L
	secondary poisoning with reference to: food	-	0.38	g/kg
2	propan-2-ol		67-63-0 200-661-7	
	soil	-	28	mg/kg
	sewage treatment plant	-	2251	mg/L
	secondary poisoning with reference to: food	-	160	mg/kg

8.2 Exposure controls

Appropriate engineering controls

No data available.

Personal protective equipment

Respiratory protection

If workplace exposure limits are exceeded, a respiration protection approved for this particular job must be worn. In case of aerosol and mist formation, take appropriate measures for breathing protection in the event workplace threshold values are not specified.

Respirator A

Eye / face protection

Safety glasses with side protection shield (EN 166)

Hand protection

Sufficient protection is given wearing suitable protective gloves checked according to i.e. EN 374, in the event of risk of skin contact with the product. Before use, the protective gloves should be tested in any case for its specific work-station suitability (i.e. mechanical resistance, product compatibility and antistatic properties). Adhere to the manufacturer's instructions and information relating to the use, storage, care and replacement of protective gloves. Protective gloves shall be replaced immediately when physically damaged or worn. Design operations thus to avoid permanent use of protective gloves.

Appropriate Material butyl rubber
Material thickness 0.5 mm

Other

Normal chemical work clothing.

Environmental exposure controls

No data available.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

State of aggregation	
liquid	
Form	
liquid	
Colour	
blue	
Odour	
alcohol-like	
pH value	
Value	7 - 10
Concentration	100 %
Source	manufacturer
Boiling point / boiling range	
Value	78.3 °C
Reference substance	CAS 64-17-5

Trade name: edding refill ink whiteboard marker (blue) BTK25 contained in : edding 360, edding 363

Current version : 9.2.0, issued: 23.01.2025

Replaced version: 9.1.1, issued: 17.12.2024

Region: GB

Source	manufacturer		
Melting point/freezing point			
No data available			
Decomposition temperature			
No data available			
Flash point			
Value	12	°C	
Reference substance	CAS 67-63-0		
Source	manufacturer		
Ignition temperature			
No data available			
Flammability			
No data available			
Lower explosion limit			
No data available			
Upper explosion limit			
No data available			
Vapour pressure			
No data available			
Relative vapour density			
No data available			
Relative density			
No data available			
Density			
Value	0.83	g/cm ³	
Reference temperature	20	°C	
Source	manufacturer		
Solubility in water			
Source	manufacturer		
Comments	miscible		
Solubility			
No data available			
Partition coefficient n-octanol/water (log value)			
No	Substance name	CAS no.	EC no.
1	ethanol	64-17-5	200-578-6
log Pow		-0.35	
Reference temperature with reference to		24	°C
Method		pH 7,4 OECD 107	
Source		ECHA	
2	propan-2-ol	67-63-0	200-661-7
log Pow		0.05	
Reference temperature		25	°C
Source		ECHA	
Kinematic viscosity			
Value	4 - 10	mm ² /s	
Source	manufacturer		
Particle characteristics			
No data available			

9.2 Other information

Trade name: edding refill ink whiteboard marker (blue) BTK25 contained in : edding 360, edding 363

Current version : 9.2.0, issued: 23.01.2025

Replaced version: 9.1.1, issued: 17.12.2024

Region: GB

Other information

No data available.

SECTION 10: Stability and reactivity

10.1 Reactivity

No data available.

10.2 Chemical stability

Stable under recommended storage and handling conditions (See section 7).

10.3 Possibility of hazardous reactions

Vapours may form an explosive mixture with air.

10.4 Conditions to avoid

Heat, naked flames and other ignition sources. Protect from sun.

10.5 Incompatible materials

Alkali metal; Earth alkali metals; Oxidizing agents; Acids

10.6 Hazardous decomposition products

In case of fire: see section 5.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute oral toxicity			
No	Substance name	CAS no.	EC no.
1	ethanol	64-17-5	200-578-6
LD50		10470	mg/kg bodyweight
Species	rat		
with reference to	95% ethanol in water		
Method	OECD 401		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
2	propan-2-ol	67-63-0	200-661-7
LD50		5840	mg/kg bodyweight
Species	rat		
Method	OECD 401		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		

Acute dermal toxicity

No data available

Acute inhalational toxicity			
No	Substance name	CAS no.	EC no.
1	ethanol	64-17-5	200-578-6
LC50		124.7	mg/l
Duration of exposure		4	h
State of aggregation	Vapour		
Species	rat		
Method	OECD 403		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
2	propan-2-ol	67-63-0	200-661-7
LC50	>	10000	ppmV
Duration of exposure		6	h
State of aggregation	Vapour		
Species	rat		
Method	OECD 403		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		

Trade name: edding refill ink whiteboard marker (blue) BTK25 contained in : edding 360, edding 363

Current version : 9.2.0, issued: 23.01.2025

Replaced version: 9.1.1, issued: 17.12.2024

Region: GB

Skin corrosion/irritation			
No	Substance name	CAS no.	EC no.
1	ethanol	64-17-5	200-578-6
	Species	rabbit	
	Method	OECD 404	
	Source	ECHA	
	Evaluation	non-irritant	
	Evaluation/classification	Based on available data, the classification criteria are not met.	
2	propan-2-ol	67-63-0	200-661-7
	Species	rabbit	
	Source	ECHA	
	Evaluation	non-irritant	
	Evaluation/classification	Based on available data, the classification criteria are not met.	
Serious eye damage/irritation			
No	Substance name	CAS no.	EC no.
1	ethanol	64-17-5	200-578-6
	Species	rabbit	
	Method	OECD 405	
	Source	ECHA	
	Evaluation	irritant	
	Evaluation/classification	Based on available data, the classification criteria are met.	
2	propan-2-ol	67-63-0	200-661-7
	Species	rabbit	
	Method	OECD 405	
	Source	ECHA	
	Evaluation	irritant	
	Evaluation/classification	Based on available data, the classification criteria are met.	
Respiratory or skin sensitisation			
No	Substance name	CAS no.	EC no.
1	ethanol	64-17-5	200-578-6
	Route of exposure	respiratory tract	
	Source	ECHA	
	Evaluation	non-sensitizing	
	Evaluation/classification	Based on available data, the classification criteria are not met.	
	Route of exposure	Skin	
	Species	mouse	
	Source	ECHA	
	Evaluation	non-sensitizing	
	Evaluation/classification	Based on available data, the classification criteria are not met.	
2	propan-2-ol	67-63-0	200-661-7
	Route of exposure	Skin	
	Species	guinea pig	
	Method	OECD 406	
	Source	ECHA	
	Evaluation	non-sensitizing	
	Evaluation/classification	Based on available data, the classification criteria are not met.	
Germ cell mutagenicity			
No	Substance name	CAS no.	EC no.
1	ethanol	64-17-5	200-578-6
	Type of examination	in vitro gene mutation study in bacteria	
	Species	Salmonella typhimurium	
	Method	OECD 471	
	Source	ECHA	
	Evaluation/classification	Based on available data, the classification criteria are not met.	
	Type of examination	in vitro gene mutation study in mammalian cells	
	Species	mouse lymphoma cells	
	Method	OECD 476	
	Source	ECHA	
	Evaluation/classification	Based on available data, the classification criteria are not met.	

Trade name: edding refill ink whiteboard marker (blue) BTK25 contained in : edding 360, edding 363

Current version : 9.2.0, issued: 23.01.2025

Replaced version: 9.1.1, issued: 17.12.2024

Region: GB

Type of examination	Genotoxicity in vivo
Species	mouse
Method	OECD 478
Source	ECHA
Evaluation/classification	Based on available data, the classification criteria are not met.
2	propan-2-ol 67-63-0 200-661-7
Source	ECHA
Evaluation/classification	Based on available data, the classification criteria are not met.

Reproduction toxicity			
No	Substance name	CAS no.	EC no.
1	ethanol	64-17-5	200-578-6
Route of exposure		oral	
NOAEL			
Type of examination	2 generation study		
Species	mouse		
Method	OECD 416		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
Route of exposure		inhalational	
NOAEL		>=	20000 ppm
Type of examination	Prenatal Developmental Toxicity Study		
Species	rat		
Method	OECD 414		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
2	propan-2-ol	67-63-0	200-661-7
Route of exposure		oral	
NOAEL		1000	mg/kg bw/d
Type of examination	Two-Generation Reproduction Toxicity Study		
Species	rats (male/female)		
Method	OECD 416		
Source	ECHA		
Evaluation/classification	Based on the available data, the classification criteria are not met.		

Carcinogenicity			
No	Substance name	CAS no.	EC no.
1	ethanol	64-17-5	200-578-6
Source		ECHA	
Evaluation/classification		Based on available data, the classification criteria are not met.	
2	propan-2-ol	67-63-0	200-661-7
Route of exposure		inhalational	
NOEL		5000	ppm
Species	rats (male/female)		
Method	OECD 451		
Source	ECHA		

STOT - single exposure			
No data available			

STOT - repeated exposure			
No	Substance name	CAS no.	EC no.
1	ethanol	64-17-5	200-578-6
Route of exposure		oral	
Duration of exposure		14	week/s
Species	rat		
Target organ	kidneys		
Method	OECD 408		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
2	propan-2-ol	67-63-0	200-661-7
Route of exposure		inhalational	
NOAEC		12500	mg/m ³

Trade name: edding refill ink whiteboard marker (blue) BTK25 contained in : edding 360, edding 363

Current version : 9.2.0, issued: 23.01.2025

Replaced version: 9.1.1, issued: 17.12.2024

Region: GB

Species	rat
Method	OECD 451
Source	ECHA
Evaluation/classification	Based on available data, the classification criteria are not met.

Aspiration hazard
No data available

Endocrine disrupting properties
No data available

11.2 Information on other hazards

Other information

No data available.

SECTION 12: Ecological information

12.1 Toxicity

Toxicity to fish (acute)			
No	Substance name	CAS no.	EC no.
1	ethanol	64-17-5	200-578-6
LC50		14200	mg/l
Duration of exposure		96	h
Species	Pimephales promelas		
Method	EPA		
Source	ECHA		
2	propan-2-ol	67-63-0	200-661-7
LC50		9640	mg/l
Duration of exposure		96	h
Species	Pimephales promelas		
Method	OECD 203		
Source	ECHA		

Toxicity to fish (chronic)
No data available

Toxicity to Daphnia (acute)			
No	Substance name	CAS no.	EC no.
1	ethanol	64-17-5	200-578-6
EC50		5012	mg/l
Duration of exposure		48	h
Species	Ceriodaphnia dubia		
Method	ASTM Standard E 729-80		
Source	ECHA		

Toxicity to Daphnia (chronic)			
No	Substance name	CAS no.	EC no.
1	ethanol	64-17-5	200-578-6
NOEC		9.6	mg/l
Duration of exposure		9	day(s)
Species	Daphnia magna		
Source	ECHA		

Toxicity to algae (acute)			
No	Substance name	CAS no.	EC no.
1	ethanol	64-17-5	200-578-6
EC50		275	mg/l
Duration of exposure		72	h
Species	Chlorella vulgaris		
Method	OECD 201		
Source	ECHA		

Toxicity to algae (chronic)

Trade name: edding refill ink whiteboard marker (blue) BTK25 contained in : edding 360, edding 363

Current version : 9.2.0, issued: 23.01.2025

Replaced version: 9.1.1, issued: 17.12.2024

Region: GB

No data available

Bacteria toxicity

No data available

12.2 Persistence and degradability

Biodegradability			
No	Substance name	CAS no.	EC no.
1	ethanol	64-17-5	200-578-6
Type		aerobic biodegradation	
Value		appr. 84	%
Duration		20	day(s)
Source		ECHA	
Evaluation		readily biodegradable	
2	propan-2-ol	67-63-0	200-661-7
Type		BOD/COD	
Value		53	%
Duration		5	day(s)
Source		ECHA	
Evaluation		readily biodegradable	

12.3 Bioaccumulative potential

Partition coefficient n-octanol/water (log value)			
No	Substance name	CAS no.	EC no.
1	ethanol	64-17-5	200-578-6
log Pow		-0.35	
Reference temperature		24	°C
with reference to		pH 7,4	
Method		OECD 107	
Source		ECHA	
2	propan-2-ol	67-63-0	200-661-7
log Pow		0.05	
Reference temperature		25	°C
Source		ECHA	

12.4 Mobility in soil

No data available.

12.5 Results of PBT and vPvB assessment

No data available.

12.6 Endocrine disrupting properties

No data available.

12.7 Other adverse effects

No data available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Allocation of a waste code number, according to the European Waste Catalogue, should be carried out in agreement with the regional waste disposal company.

Packaging

Residues must be removed from packaging and when emptied completely disposed of in accordance with the regulations for waste removal. Incompletely emptied packaging must be disposed of in the form of disposal specified by the regional disposer.

SECTION 14: Transport information

14.1 UN number or ID number

ADR/RID/ADN

UN1263

Trade name: edding refill ink whiteboard marker (blue) BTK25 contained in : edding 360, edding 363

Current version : 9.2.0, issued: 23.01.2025

Replaced version: 9.1.1, issued: 17.12.2024

Region: GB

IMDG UN1263
ICAO-TI / IATA UN1263

14.2 UN proper shipping name

ADR/RID/ADN PAINT
Technical name ethanol

IMDG PAINT
Technical name ethanol

ICAO-TI / IATA Paint
Technical name ethanol

14.3 Transport hazard class(es)

ADR/RID/ADN - Class 3
Label 3
Classification code F1
Tunnel restriction code D/E
Hazard identification no. 33
Special Provision 640 640D

IMDG - Class 3
Label 3

ICAO-TI / IATA - Class 3
Label 3

14.4 Packing group

ADR/RID/ADN II
IMDG II
ICAO-TI / IATA II

14.5 Environmental hazards

EmS F-E, S-E

14.6 Special precautions for user

No data available.

14.7 Maritime transport in bulk according to IMO instruments

Not relevant

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations

Regulation (EC) No 1907/2006 (REACH) Annex XIV (List of substances subject to authorisation)

According to the data available and/or specifications supplied by upstream suppliers, this product does not contain any substances considered as substances requiring authorisation as listed on Annex XIV of the REACH regulation (EC) 1907/2006.

REACH candidate list of substances of very high concern (SVHC) for authorisation

According to available data and the information provided by preliminary suppliers, the product does not contain substances that are considered substances meeting the criteria for inclusion in annex XIV (List of Substances Subject to Authorisation) as laid down in Article 57 and article 59 of REACH (EC) 1907/2006.

Regulation (EC) No 1907/2006 (REACH) Annex XVII: RESTRICTIONS ON THE MANUFACTURE, PLACING ON THE MARKET AND USE OF CERTAIN DANGEROUS SUBSTANCES, MIXTURES AND ARTICLES

The product is considered being subject to REACH regulation (EC) 1907/2006 annex XVII. No 3, 40
The product contains following substance(s) that are considered being subject to REACH regulation (EC) 1907/2006 annex XVII.

No	Substance name	CAS no.	EC no.	No
1	propan-2-ol	67-63-0	200-661-7	75

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances

This product is subject to Part I of Annex I, risk category: P5b

Trade name: edding refill ink whiteboard marker (blue) BTK25 contained in : edding 360, edding 363

Current version : 9.2.0, issued: 23.01.2025

Replaced version: 9.1.1, issued: 17.12.2024

Region: GB

15.2 Chemical safety assessment

A chemical safety assessment has not been carried out for this mixture.

SECTION 16: Other information

Sources of key data used to compile the data sheet:

Regulation (EC) No 1907/2006 (REACH), 1272/2008 (CLP) as amended in each case.

Directives 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164.

National Threshold Limit Values of the corresponding countries as amended in each case.

Transport regulations according to ADR, RID, IMDG, IATA as amended in each case.

The data sources used to determine physical, toxic and ecotoxic data, are indicated directly in the corresponding section.

Full text of the H- and EUH- phrases drawn up in sections 2 and 3 (provided not already drawn up in these sections)

H336 May cause drowsiness or dizziness.

Creation of the safety data sheet

UMCO GmbH

Georg-Wilhelm-Str. 187, D-21107 Hamburg

Tel.: +49 40 / 555 546 300 Fax: +49 40 / 555 546 357 e-mail: umco@umco.de

This information is based on our present knowledge and experience.

The safety data sheet describes products with a view to safety requirements.

It does not however, constitute a guarantee for any specific product properties and shall not establish a legally valid contractual relationship.

Alterations/supplements:

Alterations to the previous edition are marked in the left-hand margin.

Document protected by copyright. Alterations or reproductions require the express written permission of UMCO GmbH.

Prod-ID 17412