

**Trade name:** edding industry paint marker ink (black) contained in: edding 8750

**Current version :** 2.2.0, issued: 14.10.2021

**Replaced version:** 2.1.0, issued: 27.08.2019

**Region:** GB

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

**Trade name**

**edding industry paint marker ink (black) contained in: edding 8750**

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Relevant identified uses of the substance or mixture**

Ink for use in felt pens

**Uses advised against**

No data available.

### 1.3 Details of the supplier of the safety data sheet

**Address**

edding International GmbH

Bookkoppel 7

D-22926 Ahrensburg

Telephone no. +49 (0) 41 02 / 80 8-0

**Information provided by / telephone**

+49 (0)4102 - 808-0

**Advice on Safety Data Sheet**

sdb\_info@umco.de

### 1.4 Emergency telephone number

For medical advice (in German and English):

+49 (0)30 30686 790 (Giftnotruf Berlin)

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

**Classification in accordance with Regulation (EC) No 1272/2008 (CLP)**

Flam. Liq. 3; H226

Skin Irrit. 2; H315

**Classification information**

This product is assessed and classified using the methods and criteria below referred to in Article 9 of Regulation (EC) n° 1272/2008:

Physical hazards: determined through assessment data based on the methods or standards referred to in part 2 of Annex I to CLP

Health hazards and environmental hazards: determined through toxicological and ecotoxicological assessment data based on the methods or standards referred to in Part 3, 4 and 5 of Annex I to CLP.

### 2.2 Label elements

**Labelling according to Regulation (EC) No 1272/2008 (CLP Regulation)**

**Hazard pictograms**



GHS02



GHS07

**Signal word**

Warning

**Hazard statement(s)**

H226

Flammable liquid and vapour.

H315

Causes skin irritation.

**Precautionary statement(s)**

**Trade name:** edding industry paint marker ink (black) contained in: edding 8750

**Current version :** 2.2.0, issued: 14.10.2021

**Replaced version:** 2.1.0, issued: 27.08.2019

**Region:** GB

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P370+P378	In case of fire: Use water spray, extinguishing powder, foam or CO2 to extinguish.
P501	Dispose of contents/container to a facility in accordance with local and national regulations.

**Labelling information**

The data subject of this Material Safety Data sheet refer to the ink contained in this product (marker).

**2.3 Other hazards**

No data available.

**SECTION 3: Composition/information on ingredients**
**3.1 Substances**

Not applicable. The product is not a substance.

**3.2 Mixtures**
**Chemical characterization**

Mixture (preparation)

**Hazardous ingredients**

No	Substance name	Additional information	
	CAS / EC / Index / REACH no	Classification (EC) 1272/2008 (CLP)	Concentration
			%
1	<b>xylene</b>		
	1330-20-7 215-535-7 601-022-00-9 -	Acute Tox. 4*; H312 Acute Tox. 4*; H332 Flam. Liq. 3; H226 Skin Irrit. 2; H315	>= 50.00 - < 70.00 wt%
2	<b>DESTILLATES (PETROLEUM), HYDRODESULFURIZED MIDDLE</b>		pls. refer to footnote (1)
	64742-80-9 265-183-3 649-223-00-0 -	Asp. Tox. 1; H304 EUH066	< 5.00 wt%
3	<b>ETHYLCYCLOHEXANE</b>		
	1678-91-7 216-835-0 - -	Flam. Liq. 2; H225	< 2.50 wt%
4	<b>CARBON BLACK</b>		
	1333-86-4 215-609-9 - -	-	>= 10.00 - < 25.00 wt%

Full Text for all H-phrases and EUH-phrases: pls. see section 16

(\*, \*\*, \*\*\*, \*\*\*\*) Detailed explanation pls. refer to CLP regulation No. 1272/2008, annex VI, 1.2

(1) Aberrant from/in addition to the classification set out in Annex VI, this substance is classified according to European Regulation (EC) No 1272/2008 (CLP), Article 4 (3), paragraph 2.

No	Note	Specific concentration limits	M-factor (acute)	M-factor (chronic)
1	C	-	-	-
2	N	-	-	-

Full text for the notes: pls. see section 16 "Notes relating to the identification, classification and labelling of substances ((EC) No 1272/2008, Annex VI)".

**Acute toxicity estimate (ATE) values**

**Trade name:** edding industry paint marker ink (black) contained in: edding 8750

**Current version :** 2.2.0, issued: 14.10.2021

**Replaced version:** 2.1.0, issued: 27.08.2019

**Region:** GB

No	oral	dermal	inhalative
1		2000 mg/kg bodyweight	

### 3.3 Other information

The data subject of this Material Safety Data sheet refer to the ink contained in this product (marker).

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

#### General information

In case of persisting adverse effects, consult a physician. Remove contaminated clothing and shoes immediately, and launder thoroughly before reusing.

#### After inhalation

Remove affected person from the immediate area. Ensure supply of fresh air.

#### After skin contact

Wash off immediately with soap and water.

#### After eye contact

Separate eyelids, wash the eyes thoroughly with water (15 min.).

#### After ingestion

Rinse the mouth thoroughly with water. Call a doctor immediately. Never give anything by mouth to an unconscious person.

### 4.2 Most important symptoms and effects, both acute and delayed

No data available.

### 4.3 Indication of any immediate medical attention and special treatment needed

No data available.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

#### Suitable extinguishing media

Foam; Extinguishing powder; Carbon dioxide

#### Unsuitable extinguishing media

No data available.

### 5.2 Special hazards arising from the substance or mixture

In the event of fire, the following can be released: Carbon dioxide (CO<sub>2</sub>); Carbon monoxide (CO)

### 5.3 Advice for firefighters

Cool endangered containers with water spray jet. Use self-contained breathing apparatus. Wear protective clothing. Suppress gases/vapours/mists with water spray jet.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

#### For non-emergency personnel

Refer to protective measures listed in sections 7 and 8. Avoid contact with skin, eyes and clothing. Ensure adequate ventilation. Keep away from ignition sources.

#### For emergency responders

No data available. Personal protective equipment (PPE) - see Section 8.

### 6.2 Environmental precautions

Do not discharge into the drains/surface waters/groundwater. Do not discharge into the subsoil/soil.

### 6.3 Methods and material for containment and cleaning up

Take up with absorbent material (e.g., sand, kieselguhr, universal binder). When collected, handle material as described under the section heading "Disposal considerations".

### 6.4 Reference to other sections

**Trade name:** edding industry paint marker ink (black) contained in: edding 8750

**Current version :** 2.2.0, issued: 14.10.2021

**Replaced version:** 2.1.0, issued: 27.08.2019

**Region:** GB

No data available.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

#### Advice on safe handling

Provide good ventilation at the work area (local exhaust ventilation, if necessary). Risks inherent to handling the product must be minimised by applying the appropriate protective and preventive measures. Working processes should - so far as possible, according to the state of the art - be designed to rule out bodily contact or the release of hazardous substances.

#### General protective and hygiene measures

Do not eat, drink or smoke during work time. Keep away from foodstuffs and beverages. Avoid contact with eyes and skin. Remove soiled or soaked clothing immediately. Do not inhale vapours. Provide eye wash fountain in work area. Have emergency shower available.

#### Advice on protection against fire and explosion

Vapours can form an explosive mixture with air. Take precautionary measures against static charges. Keep away from sources of heat and ignition. Use explosion-proof equipment/fittings and non-sparking tools.

### 7.2 Conditions for safe storage, including any incompatibilities

#### Technical measures and storage conditions

Keep container tightly closed in a cool, well-ventilated place. Protect from heat and direct sunlight.

#### Requirements for storage rooms and vessels

Containers which are opened must be carefully closed and kept upright to prevent leakage. Always keep in containers of same material as the original.

#### Incompatible products

None known

### 7.3 Specific end use(s)

No data available.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational exposure limit values

No	Substance name	CAS no.	EC no.
1	xylene	1330-20-7	215-535-7
	<b>2000/39/EC</b>		
	Xylene, mixed isomers, pure		
	WEL short-term (15 min reference period)	442	mg/m <sup>3</sup> 100 ppm
	WEL long-term (8-hr TWA reference period)	221	mg/m <sup>3</sup> 50 ppm
	Skin resorption / sensibilisation	Skin	
	<b>List of approved workplace exposure limits (WELs) / EH40</b>		
	Xylene, o-, m-, p- or mixed isomers		
	WEL short-term (15 min reference period)	441	mg/m <sup>3</sup> 100 ppm
	WEL long-term (8-hr TWA reference period)	220	mg/m <sup>3</sup> 50 ppm
	Comments	Sk, BMGV	
2	<b>CARBON BLACK</b>	<b>1333-86-4</b>	<b>215-609-9</b>
	<b>List of approved workplace exposure limits (WELs) / EH40</b>		
	Carbon black		
	WEL short-term (15 min reference period)	7	mg/m <sup>3</sup>
	WEL long-term (8-hr TWA reference period)	3.5	mg/m <sup>3</sup>

### 8.2 Exposure controls

#### Appropriate engineering controls

No data available.

#### Personal protective equipment

**Trade name:** edding industry paint marker ink (black) contained in: edding 8750

**Current version :** 2.2.0, issued: 14.10.2021

**Replaced version:** 2.1.0, issued: 27.08.2019

**Region:** GB

#### Respiratory protection

If workplace exposure limits are exceeded, a respiration protection approved for this particular job must be worn. In case of aerosol and mist formation, take appropriate measures for breathing protection in the event workplace threshold values are not specified.

#### Eye / face protection

Safety glasses with side protection shield (EN 166)

#### Hand protection

Sufficient protection is given wearing suitable protective gloves checked according to i.e. EN 374, in the event of risk of skin contact with the product. Before use, the protective gloves should be tested in any case for its specific work-station suitability (i.e. mechanical resistance, product compatibility and antistatic properties). Adhere to the manufacturer's instructions and information relating to the use, storage, care and replacement of protective gloves. Protective gloves shall be replaced immediately when physically damaged or worn. Design operations thus to avoid permanent use of protective gloves.

#### Other

Normal chemical work clothing.

#### Environmental exposure controls

No data available.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

<b>State of aggregation</b>	
liquid	
<b>Form/Colour</b>	
liquid	
black	
<b>Odour</b>	
aromatic	
<b>pH value</b>	
No data available	
<b>Boiling point / boiling range</b>	
Value	138 °C
<b>Melting point/freezing point</b>	
No data available	
<b>Decomposition temperature</b>	
No data available	
<b>Flash point</b>	
Value	23 °C
<b>Ignition temperature</b>	
Value	200 - 564 °C
<b>Flammability</b>	
No data available	
<b>Lower explosion limit</b>	
Value	1.00 % vol
<b>Upper explosion limit</b>	
Value	8.40 % vol
<b>Vapour pressure</b>	
Value	10 mm Hg
Reference temperature	28 °C
<b>Relative vapour density</b>	

**Trade name:** edding industry paint marker ink (black) contained in: edding 8750

**Current version :** 2.2.0, issued: 14.10.2021

**Replaced version:** 2.1.0, issued: 27.08.2019

**Region:** GB

No data available	
<b>Relative density</b>	
No data available	
<b>Density</b>	
Value	0.88 g/cm <sup>3</sup>
Reference temperature	20 °C
<b>Solubility in water</b>	
Comments	insoluble
<b>Solubility</b>	
No data available	
<b>Partition coefficient n-octanol/water (log value)</b>	
No data available	
<b>Viscosity</b>	
Value	800 mPa*s
Type	dynamic
<b>Particle characteristics</b>	
No data available	

## 9.2 Other information

<b>Other information</b>
No data available.

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No data available.

### 10.2 Chemical stability

No data available.

### 10.3 Possibility of hazardous reactions

No data available.

### 10.4 Conditions to avoid

Heat

### 10.5 Incompatible materials

None known.

### 10.6 Hazardous decomposition products

No hazardous decomposition products known.

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute oral toxicity			
No	Substance name	CAS no.	EC no.
1	xylene	1330-20-7	215-535-7
LD50		8700	mg/kg bodyweight
Species	rat		
Source	Manufacturer		
Acute dermal toxicity (result of the ATE calculation for the mixture)			
No	Product Name		
1	edding industry paint marker ink (black) contained in: edding 8750		
Comments	The result of the applied calculation method according to the		

**Trade name:** edding industry paint marker ink (black) contained in: edding 8750

**Current version :** 2.2.0, issued: 14.10.2021

**Replaced version:** 2.1.0, issued: 27.08.2019

**Region:** GB

	European Regulation (EC) 1272/2008 (CLP), Paragraph 3.1.3.6, Part 3 of Annex I is outside the values that imply a classification / labelling of this mixture according to table 3.1.1 defining the respective categories (ATE dermal > 2000 mg/kg).
--	---

Acute dermal toxicity			
No	Substance name	CAS no.	EC no.
1	xylene	1330-20-7	215-535-7
LD50		2000	mg/kg bodyweight
Species	rabbit		
Source	Manufacturer		

Acute inhalational toxicity (result of the ATE calculation for the mixture)	
No	Product Name
1	edding industry paint marker ink (black) contained in: edding 8750
Comments	The result of the applied calculation method according to the European Regulation (EC) 1272/2008 (CLP), Paragraph 3.1.3.6, Part 3 of Annex I is outside the values that imply a classification / labelling of this mixture according to table 3.1.1 defining the respective categories (ATE for inhalation: > 20.000 ppmV (gases), > 20 mg/l (vapours), > 5 mg/l (dusts/mists).

Acute inhalational toxicity			
No	Substance name	CAS no.	EC no.
1	xylene	1330-20-7	215-535-7
LC50		6350	mg/l
Duration of exposure		4	h
State of aggregation	Vapour		
Species	rat		
Source	Manufacturer		
Evaluation/classification	Based on available data, the classification criteria are met.		

Skin corrosion/irritation
No data available

Serious eye damage/irritation
No data available

Respiratory or skin sensitisation
No data available

Germ cell mutagenicity
No data available

Reproduction toxicity
No data available

Carcinogenicity
No data available

STOT - single exposure
No data available

STOT - repeated exposure
No data available

Aspiration hazard
No data available

Delayed and immediate effects as well as chronic effects from short and long-term exposure
Inhalation of vapours may lead to headache, drowsiness and dizziness. Repeated and prolonged skin contact may cause removal of natural fat from the skin and irritation of the skin. Eye contact with the product may lead to irritation.

## 11.2 Information on other hazards

**Trade name:** edding industry paint marker ink (black) contained in: edding 8750

**Current version :** 2.2.0, issued: 14.10.2021

**Replaced version:** 2.1.0, issued: 27.08.2019

**Region:** GB

**Endocrine disrupting properties**

No data available.

**Other information**

No data available.

## SECTION 12: Ecological information

### 12.1 Toxicity

**Toxicity to fish (acute)**

No data available

**Toxicity to fish (chronic)**

No data available

**Toxicity to Daphnia (acute)**

No data available

**Toxicity to Daphnia (chronic)**

No data available

**Toxicity to algae (acute)**

No data available

**Toxicity to algae (chronic)**

No data available

**Bacteria toxicity**

No data available

### 12.2 Persistence and degradability

No data available.

### 12.3 Bioaccumulative potential

No data available.

### 12.4 Mobility in soil

No data available.

### 12.5 Results of PBT and vPvB assessment

No data available.

### 12.6 Endocrine disrupting properties

No data available.

### 12.7 Other adverse effects

No data available.

### 12.8 Other information

**Other information**

Ecological data are not available.

Do not discharge product unmonitored into the environment.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

**Product**

Allocation of a waste code number, according to the European Waste Catalogue, should be carried out in agreement with the regional waste disposal company.

**Packaging**

Residues must be removed from packaging and when emptied completely disposed of in accordance with the regulations for waste removal. Incompletely emptied packaging must be disposed of in the form of disposal specified by the regional disposer.



**Trade name:** edding industry paint marker ink (black) contained in: edding 8750

**Current version :** 2.2.0, issued: 14.10.2021

**Replaced version:** 2.1.0, issued: 27.08.2019

**Region:** GB

## SECTION 14: Transport information

### 14.1 Transport ADR/RID/ADN

Class	3
Classification code	F1
Packing group	III
Hazard identification no.	30
UN number	UN1263
Proper shipping name	PAINT
Tunnel restriction code	D/E
Label	3
Comments	Containers with a capacity <= 450 ltrs are not subject to ADR-regulations (refer to 2.2.3.1.5.)

### 14.2 Transport IMDG

Class	3
Packing group	III
UN number	UN1263
Proper shipping name	PAINT
EmS	F-E, S-E
Label	3
Comments	Containers with a capacity <= 450 ltrs are not subjected to IMDG regulations, chapter 4.1, 5.2 and 6.1 (see IMDG-Code 2.3.2.5)

### 14.3 Transport ICAO-TI / IATA

Class	3
Packing group	III
UN number	UN1263
Proper shipping name	Paint
Label	3

### 14.4 Other information

No data available.

### 14.5 Environmental hazards

Information on environmental hazards, if relevant, please see 14.1 - 14.3.

### 14.6 Special precautions for user

No data available.

### 14.7 Maritime transport in bulk according to IMO instruments

Not relevant

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU regulations

#### **Regulation (EC) No 1907/2006 (REACH) Annex XIV (List of substances subject to authorisation)**

According to the data available and/or specifications supplied by upstream suppliers, this product does not contain any substances considered as substances requiring authorisation as listed on Annex XIV of the REACH regulation (EC) 1907/2006.

#### **REACH candidate list of substances of very high concern (SVHC) for authorisation**

According to available data and the information provided by preliminary suppliers, the product does not contain substances that are considered substances meeting the criteria for inclusion in annex XIV (List of Substances Subject to Authorisation) as laid down in Article 57 and article 59 of REACH (EC) 1907/2006.

#### **Regulation (EC) No 1907/2006 (REACH) Annex XVII: RESTRICTIONS ON THE MANUFACTURE, PLACING ON THE MARKET AND USE OF CERTAIN DANGEROUS SUBSTANCES, MIXTURES AND ARTICLES**

The product is considered being subject to REACH regulation (EC) 1907/2006 annex XVII.	No 3, 40
--	----------

**Trade name:** edding industry paint marker ink (black) contained in: edding 8750

**Current version :** 2.2.0, issued: 14.10.2021

**Replaced version:** 2.1.0, issued: 27.08.2019

**Region:** GB

**Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances**

This product is subject to Part I of Annex I, risk category:	P5c
--	-----

**15.2 Chemical safety assessment**

No data available.

**SECTION 16: Other information**

**Sources of key data used to compile the data sheet:**

Regulation (EC) No 1907/2006 (REACH), 1272/2008 (CLP) as amended in each case.

Directives 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164.

National Threshold Limit Values of the corresponding countries as amended in each case.

Transport regulations according to ADR, RID, IMDG, IATA as amended in each case.

The data sources used to determine physical, toxic and ecotoxic data, are indicated directly in the corresponding section.

**Full text of the H- and EUH- phrases drawn up in sections 2 and 3 (provided not already drawn up in these sections)**

EUH066	Repeated exposure may cause skin dryness or cracking.
H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H332	Harmful if inhaled.

**Notes relating to the identification, classification and labelling of substances and mixtures ((EC) No 1272/2008, Annex VI)**

C	Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.
N	The harmonised classification as a carcinogen applies unless the full refining history is known and it can be shown that the substance from which it is produced is not a carcinogen, in which case a classification in accordance with Title II of this Regulation shall be performed also for that hazard class.

**Creation of the safety data sheet**

UMCO GmbH

Georg-Wilhelm-Str. 187, D-21107 Hamburg

Tel.: +49 40 / 555 546 300 Fax: +49 40 / 555 546 357 e-mail: umco@umco.de

This information is based on our present knowledge and experience.

The safety data sheet describes products with a view to safety requirements.

It does not however, constitute a guarantee for any specific product properties and shall not establish a legally valid contractual relationship.

**Alterations/supplements:**

Alterations to the previous edition are marked in the left-hand margin.

Document protected by copyright. Alterations or reproductions require the express written permission of UMCO GmbH.

Prod-ID 25825