TECHNICAL SHEET

KARA

CHARACTERISTICS

WORKTOPS

WORKTOPS	
MELAMINE	Melamine covered particle board panels, thickness 38 mm. 2 sides treated with an anti-reflective coating Panel density 650kg/m3 Bonded ABS edge banding, thickness 2 mm, rounded on upper and lower edges. Edge banding to match worktop finish Panels sourced from sustainably managed forests (PEFC). Fire rating M3 (combustible, moderately flammable) in accordance with the standard NF EN 13501-1 Panels are certified E1 (control of formaldehyde emissions), emitting 6.5 mg HCNO/100 mg and compliant with standard NF EN 717-2 Melamine panels (except Brunswick oak R3 and Coffee oak M9) comply with the standard ISO 22196 for antibacterial properties. Cable management options (see corresponding Technical Data Sheets for details): > Desk worktops with pre-drilled holes for cable ports Ø 80 mm > Closed panel return: desktops drilled for cable ports in 2 places. Cable ports Ø 80 included
GLASS TOP	For pedestal or closed panel return > Toughened safety glass 6 mm thick, enamelled on the underside > Flat polished joints, 5mm rounded corners > Attached to melamine worktop with screws and metal inserts

LEGS AND STRUCTURE



Melamine panel leg, thickness 38mm, ABS edge banding thickness 2 mm adapted to the finish. Consists of a panel the depth of the worktop with an L. 200 mm return to the front face. Structural Aluminium grey metal crossbeam, cross-section 60 x 30 mm, thickness 2 mm Melamine modesty board H 300 mmm thickness 19 mm

Worktop and legs joined by Aluminium grey metal brace L. 200 x D. 38 mm

Aluminium grey metal pads with adjustable stabiliser feet Ø 25, adjustment through 15 mm.

MEETING See ELOISE range, 38 mm thick worktops










1

EASY REACH STORAGE

STRUCTURAL CLOSED PANEL RETURN



Closed panel return dimensions: L. 2000 x H. 691 x D. 600 mm

- > Melamine worktop 38 mm thick, finishes coordinated with desktops (see shade card)
- > Melamine panel leg 38 mm thick, melamine modesty board 19 mm thick with 2 strips of imitation metal PVC trim
- > 2 Zamac alloy cable ports with brush
- > Optional top in toughened glass (to order with the product)

Structural pedestal dimensions: L. 600 x H. 691 x D. 900 mm

> Aluminium grey metal pads with adjustable stabiliser feet \emptyset 25, adjustment through 15 mm

STRUCTURAL PEDESTAL

Always positioned overhanging the worktop, thereby providing an additional working space

Shell



- > Melamine covered particle board panels, top 38 mm thick, body and facades 19 mm thick, finishes coordinated with desktops (see shade card)
- > Optional top in toughened glass (to order with the product)
- > With 4 adjustable stabiliser feet ø 25 mm with adjustment through 15 mm

Drawers

- > 3 flat storage drawers on ball-bearing runners with 100% extraction
- > Top drawer with black ABS compartmentalised pen tray
- > Plastic handles

MOBILE PEDESTALS



Mobile pedestal dimensions: L. 420 x H. 591 x D. 560 mm

Pedestals with 2 (one for SF) and 3 drawers:

Melamine panels 19 mm thick for the body, 25 mm for the top.

4 castors ø 50 mm, (5 for the SF version), 2 with brakes

Metal drawers: metal with ball-bearing runners and soft closing mechanism, selective opening,

Central locking with locking bar, 2 keys.

Top drawer with ABS pen tray, 80% extraction, 100% extraction for SF drawer.

Lacquered metal handles (96 mm between centres) specific to the range

For more information consult the MELINA technical sheet

DECORATIVE STORAGE UNITS



Structure

- > Melamine body 38 mm thick, shelves 38 and 19 mm thick, finishes coordinated with desktops (see shade card)
- > Back and front panels 19 mm thick. Finish: White MG only
- > High unit H. 1936 mm, medium unit H 1154 cm and low unit H. 782 mm; the high unit consists of one low and one medium unit
- > Units have 4 compartments (low unit) 12 compartments (medium unit) L. 1200 x D. 460 mm
- > Assembly system: cam lock nuts located on pin
- > ABS Aluminium grey legs L. $75 \times D$. $75 \times H$. 17 mm fitted with adjustable stabiliser feet Ø 20, adjustment through 15 mm.





Compartments can be ordered empty or with the following fittings:

- $\,>$ Swing doors H. 330 mm in 19 mm thick melamine, with push-release mechanism
- > 2-drawer unit H. 330 mm in 19 mm thick melamine, with push-release mechanism
- > Sliding doors H. 700 mm in 19 mm thick melamine (with handles), or 4 mm thick glass (with grip holes) with frame in aluminium; fitted with lock; units sold with sliding doors are fitted with rails at the top and base of the unit; these fittings must be mentioned on the order.
- > Sliding melamine doors H. 700 mm (19 mm thick) with handles and lock; units that include sliding doors are fitted with guide rails in the upper and lower portions; this configuration must be specified at the point of purchase. Swing doors and drawer units can be positioned as desired.



See ARMAND range









DIMENSIONS

OVERALL DIMENSIONS (in mm)				
INDIVIDUAL DESKS	RECTANGULAR 2000 * 900			
Depth	900			
Width	1700 / 2000			
Fixed leg height	735			

	RECTANGULAR		
DESK WITH STRUCTURAL PEDESTAL 3 drawers	900 3400 1700 3000		
Depth	900		
Width	2100 / 2400		
Fixed leg height	735		

DESKS WITH CLOSED PANEL RETURN	RECTANGULAR aligned return	RECTANGULAR offset return 2100 2000 1700 2000 2000
Depth	2000	2000
Width	1700 / 2000	2100 / 2400
Fixed leg height	735	735

DESKS WITH CLOSED PANEL RETURN & STRUCTURAL PEDESTAL	RECTANGULAR aligned return 2100 1700 2000 900	RECTANGULAR offset return
Depth	2000	2000
Width	2100 / 2400	2500 / 2800
Fixed leg height	735	735