

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

EVO-STIK FLOORING ADHESIVE Supercedes Date: 23-Dec-2020

Revision date 28-Sep-2021 Revision Number 3.02

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Name EVO-STIK FLOORING ADHESIVE

Pure substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Adhesive.
Uses advised against None known

1.3. Details of the supplier of the safety data sheet

Company Name
Bostik Limited
Common Rd
ST16 3EH
Stafford UK

Tel: +44 (1785) 27 26 25 Fax: +44 (1785) 25 72 36

E-mail address SDS.box-EU@bostik.com

1.4. Emergency telephone number

United Kingdom +44 (1785) 272650

+353 (1) 8624900 (Monday- Friday 9am-5pm)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Skin sensitisation Category 1 - (H317)

2.2. Label elements

Contains 2-methyl-2H-isothiazol-3-one [MIT], 1,2-benzisothiazol-3(2H)-one [BIT], reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT]



Signal word Warning

Hazard statements

H317 - May cause an allergic skin reaction.

Precautionary Statements - EU (§28, 1272/2008)

P101 - If medical advice is needed, have product container or label at hand

P102 - Keep out of reach of children

P261 - Avoid breathing vapours

United Kingdom - BE Page 1 / 13

EVO-STIK FLOORING ADHESIVE Supercedes Date: 23-Dec-2020

Revision date 28-Sep-2021 Revision Number 3.02

P280 - Wear protective gloves and eye/face protection

P302 + P352 - IF ON SKIN: Wash with plenty of water and soap

P501 - Dispose of contents/ container to an approved waste disposal plant

2.3. Other hazards

Combustible liquid.

PBT & vPvB

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2 Mixtures

Chemical name	EC No	CAS No	Weight-%	Classification according to Regulation (EC) No. 1272/2008	Specific concentration limit (SCL)	REACH registration number
1,2-benzisothiazol-3(2H) -one [BIT]	220-120-9	2634-33-5	0.01 - <0.05	CLP] Acute Tox. 4 (H302) Skin Irrit. 2 (H315) Eye Dam. 1 (H318) Skin Sens. 1 (H317) Aquatic Acute 1 (H400) Acute Tox. 2 (H330) Aquatic Chronic 2 (H411) M Factor Acute	Skin Sens. 1 :: C>=0.05%	01-2120761540- 60-XXXX
2-methyl-2H-isothiazol-3 -one [MIT]	220-239-6	2682-20-4	0.0015 - <0.01	=1 Skin Corr. 1B (H314) Eye Dam. 1 (H318) Skin Sens. 1A (H317) Acute Tox. 3 (H301) Acute Tox. 3 (H311) Acute Tox. 2 (H330) Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410) M Factor Acute =10 M Factor Chronic = 1	Skin Sens. 1 :: C>=0.0015%	01-2120764690- 50-xxxx

United Kingdom - BE Page 2 / 13

Supercedes Date: 23-Dec-2020 Revision Number 3.02

Revision date 28-Sep-2021

reaction mass of	611-341-5	55965-84-9	< 0.0015	Acute Tox. 3	Eye Dam. 1 ::	01-2120764691-
5-chloro-2-methyl-2H-iso				(H301)	C>=0.6% Irrit. 2 ::	48-XXXX
thiazol-3-one and				Acute Tox. 2	0.06%<=C<0.6%	
2-methyl-2H-isothiazol-3				(H310)	Skin Corr. 1C::	
-one (3:1) [C(M)IT/MIT]				Acute Tox. 2	C>=0.6%	
				(H330)	Skin Irrit. 2 ::	
				Skin Corr. 1C	0.06%<=C<0.6%	
				(H314)	Skin Sens. 1 ::	
				Eye Dam. 1	C>=0.0015%	
				(H318)		
				Skin Sens. 1A		
				(H317)		
				Aquatic Acute 1		
				(H400)		
				Aquatic Chronic		
				1 (H410)		
				M Factor Acute =		
				100		
				M Factor Chronic		
				= 100		

NOTE [5] - This substance is exempted from registration according to the provisions of Article 2(7)(a) and Annex V of REACH

Full text of H- and EUH-phrases: see section 16

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

SECTION 4: First aid measures

EVO-STIK FLOORING ADHESIVE

4.1. Description of first aid measures

General advice Show this safety data sheet to the doctor in attendance.

Inhalation Remove to fresh air. IF exposed or concerned: Get medical advice/attention.

Eye contact Rinse thoroughly with plenty of water for at least 15 minutes, lifting lower and upper

eyelids. Consult a doctor.

Skin contact Wash with soap and water. May cause an allergic skin reaction. In the case of skin

irritation or allergic reactions see a doctor.

Ingestion Clean mouth with water. Do NOT induce vomiting. Drink 1 or 2 glasses of water. Never

give anything by mouth to an unconscious person.

Self-protection of the first aider Remove all sources of ignition. Ensure that medical personnel are aware of the

material(s) involved, take precautions to protect themselves and prevent spread of

contamination. Wear personal protective clothing (see section 8).

4.2. Most important symptoms and effects, both acute and delayed

Symptoms Itching. Rashes. Hives.

4.3. Indication of any immediate medical attention and special treatment needed

Note to doctorsMay cause sensitisation in susceptible persons. Treat symptomatically.

SECTION 5: Firefighting measures

United Kingdom - BE Page 3 / 13

Supercedes Date: 23-Dec-2020 Revision Number 3.02

5.1. Extinguishing media

Dry chemical. Carbon dioxide (CO2). Water spray. Alcohol resistant foam. **Suitable Extinguishing Media**

Unsuitable extinguishing media No information available.

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the

EVO-STIK FLOORING ADHESIVE

chemical

Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Product is or contains a sensitiser. May cause

Revision date 28-Sep-2021

sensitisation by skin contact.

Hazardous combustion products Carbon dioxide (CO2).

5.3. Advice for firefighters

precautions for fire-fighters

Special protective equipment and Firefighters should wear self-contained breathing apparatus and full firefighting turnout

gear. Use personal protection equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate personnel to safe areas. Use personal protective equipment as required. See Personal precautions

section 8 for more information. Take precautionary measures against static discharges. Do not touch or walk through spilled material. Avoid contact with skin, eyes or clothing.

Ensure adequate ventilation. Keep people away from and upwind of spill/leak.

For emergency responders Use personal protection recommended in Section 8.

6.2. Environmental precautions

Environmental precautions Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or

spillage if safe to do so.

6.3. Methods and material for containment and cleaning up

Methods for containment Stop leak if you can do it without risk. Do not touch or walk through spilled material. Dyke

far ahead of liquid spill for later disposal.

Take precautionary measures against static discharges. Dam up. Soak up with inert Methods for cleaning up

absorbent material. Pick up and transfer to properly labelled containers.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

6.4. Reference to other sections

Reference to other sections See section 8 for more information. See section 13 for more information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Handle in accordance with good industrial hygiene and safety practice. Avoid contact Advice on safe handling

> with skin, eyes or clothing. Ensure adequate ventilation. In case of insufficient ventilation, wear suitable respiratory equipment. Do not eat, drink or smoke when using this product.

Take off contaminated clothing and wash it before reuse.

Handle in accordance with good industrial hygiene and safety practice. General hygiene considerations

7.2. Conditions for safe storage, including any incompatibilities

United Kingdom - BE Page 4 / 13

EVO-STIK FLOORING ADHESIVE Supercedes Date: 23-Dec-2020 Revision date 28-Sep-2021 Revision Number 3.02

Storage Conditions Keep containers tightly closed in a dry, cool and well-ventilated place. Store locked up.

Keep out of the reach of children.

Recommended storage

temperature

Keep at temperatures between 5 and 35 °C.

7.3. Specific end use(s)

Specific use(s)

Adhesive.

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

Other information Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure Limits

Chemical name	European Union	United Kingdom
Limestone	-	TWA: 10 mg/m ³
1317-65-3		TWA: 4 mg/m ³
		STEL: 30 mg/m ³
		STEL: 12 mg/m ³
Potassium hydroxide	-	STEL: 2 mg/m ³
1310-58-3		_

Derived No Effect Level (DNEL) No information available

Derived No Effect Level (DN	EL)		
1,2-benzisothiazol-3(2H)-one	e [BIT] (2634-33-5)		
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Inhalation	6.81 mg/m³	
worker Long term Systemic health effects	Dermal	0.966 mg/kg bw/d	

Derived No Effect Level (DN	Derived No Effect Level (DNEL)					
1,2-benzisothiazol-3(2H)-one	e [BIT] (2634-33-5)					
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor			
Consumer Long term Systemic health effects	Inhalation	1.2 mg/m ³				
Consumer Long term Systemic health effects	Dermal	0.345 mg/kg bw/d				

Predicted No Effect Concentration No information available. **(PNEC)**

Predicted No Effect Concentration (PNEC)

United Kingdom - BE Page 5 / 13

EVO-STIK FLOORING ADHESIVE Supercedes Date: 23-Dec-2020 Revision date 28-Sep-2021 Revision Number 3.02

	
1,2-benzisothiazol-3(2H)-one [BIT] (2634-33-	5)
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	4.03 μg/l
Marine water	0.403 μg/l
Sewage treatment plant	1.03 mg/l
Freshwater sediment	49.9 μg/l
Marine sediment	4.99 μg/l
Soil	3 mg/kg dry weight

8.2. Exposure controls

Engineering controls Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles). Avoid contact with eyes. Eye

protection must conform to standard EN 166.

Hand protection Wear protective gloves. Gloves must conform to standard EN 374. Ensure that the

breakthrough time of the glove material is not exceeded. Refer to glove supplier for

information on breakthrough time for specific gloves.

Skin and body protection Respiratory protection

Wear protective gloves and protective clothing. Avoid contact with skin, eyes or clothing.

During spraying wear suitable respiratory equipment.

Environmental exposure controls No information available.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical stateLiquidAppearancePasteColourBrownOdourOrganic

Odour threshold No information available

Property Values Remarks • Method

100 °C

pH 8 - 10 pH (as aqueous solution) No data available Melting point / freezing point No data available

Initial boiling point and boiling

range

Flash point > 80 °C
Evaporation rate No data available
Flammability Not applicable for liquids .

Flammability Limit in Air

Upper flammability or explosive No data available

limits

Lower flammability or explosive No data available

limits

Vapour pressureNo data availableRelative vapour densityNo data available

Relative density 1.27

Water solubility
Solubility(ies)
Partition coefficient
Autoignition temperature
Decomposition temperature
Kinematic viscosity

Miscible in water
No data available
No data available
No data available
No data available

Dynamic viscosity 89000 mPa s @ 23 °C

Explosive propertiesNo data available **Oxidising properties**No data available

United Kingdom - BE Page 6 / 13

EVO-STIK FLOORING ADHESIVE Supercedes Date: 23-Dec-2020

Revision date 28-Sep-2021 Revision Number 3.02

9.2. Other information

Solid content (%) No information available

VOC Content (%) 5 g/L Directive 2004/42/EC on the limitation of emissions of volatile organic compounds

Density No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity No information available.

10.2. Chemical stability

Stability Stable under normal conditions.

Explosion data

Sensitivity to mechanical

impact

Sensitivity to static discharge None.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

10.4. Conditions to avoid

Conditions to avoid None known based on information supplied.

None.

10.5. Incompatible materials

Incompatible materialsNone known based on information supplied.

10.6. Hazardous decomposition products

Hazardous decomposition

products

Carbon monoxide. Carbon dioxide (CO2). Hydrocarbons.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Information on likely routes of exposure

Product Information

Inhalation Based on available data, the classification criteria are not met.

Eye contact Based on available data, the classification criteria are not met.

Skin contact May cause sensitisation by skin contact. Specific test data for the substance or mixture

is not available. Repeated or prolonged skin contact may cause allergic reactions with

susceptible persons. (based on components).

Ingestion Based on available data, the classification criteria are not met.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Itching. Rashes. Hives.

United Kingdom - BE Page 7 / 13

EVO-STIK FLOORING ADHESIVE Supercedes Date: 23-Dec-2020

Revision date 28-Sep-2021

Revision Number 3.02

Numerical measures of toxicity

Acute toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (dermal) 38,626.00 mg/kg

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
1,2-benzisothiazol-3(2H)-one	=670 mg/kg (Rattus)	LD50 > 2000 mg/kg (Rattus)	
[BIT]			
2634-33-5			
2-methyl-2H-isothiazol-3-one	LD50 =285 mg/Kg (Rattus)	LD50 >242 mg/Kg (Rattus)	=0.11 mg/L (Rattus) 4 h
[MIT]			
2682-20-4			
reaction mass of	=53 mg/kg (Rattus)	LD50 = 87.12 mg/kg	
5-chloro-2-methyl-2H-isothiazo		(Oryctolagus cuniculus)	
I-3-one and			
2-methyl-2H-isothiazol-3-one			
(3:1) [C(M)IT/MIT]			
55965-84-9			

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritationBased on available data, the classification criteria are not met.

Serious eye damage/eye irritation Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation May cause sensitisation by skin contact.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT - single exposure Based on available data, the classification criteria are not met.

STOT - repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

Endocrine disrupting properties No information available.

United Kingdom - BE Page 8 / 13

EVO-STIK FLOORING ADHESIVE Supercedes Date: 23-Dec-2020

Revision date 28-Sep-2021 Revision Number 3.02

11.2.2. Other information

Other adverse effects No information available.

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity

Chemical name	Algae/aquatic	Fish	Toxicity to	Crustacea	M-Factor	M-Factor
	plants		microorganisms			(long-term)
1,2-benzisothiazol-3(2	EC50 3Hr	LC50 (96hr)	-	EC50(48hr) 2.94	1	
H)-one [BIT]	13mg/l	2.15 mg/l		mg/l (Daphnia		
2634-33-5	(activated	Cyprinodon		Magna) OECD		
	sludge) (OECD	variegatus EPA		202		
	209)	540/9-85-006				
2-methyl-2H-isothiazol-	EC50 (72hr)	EC50 (96hr)	-	EC50 (48hr)	10	1
3-one [MIT]	0.157 mg/l	5.71 mg/l		1.68 mg/l		
2682-20-4	(Pseudokirchner	(Oncorhynchus		(Daphnia)		
	iella	mykiss) OECD		(OECD 202)		
	subcapitata)	203				
	(OECD 201)					
reaction mass of	EC50 (72h)	EC50 (96h) =	-	EC50 (48h) =0.1	100	100
5-chloro-2-methyl-2H-is	=0.048 mg/L	0.22 mg/L		mg/L (Daphnia		
othiazol-3-one and	(Pseudokirchner	(Oncorhynchus		magna) (OECD		
2-methyl-2H-isothiazol-	iella	mykiss) (OECD		202)		
3-one (3:1)	subcapitata)	211)				
[C(M)IT/MIT]	(OECD 201)					
55965-84-9						

12.2. Persistence and degradability

Persistence and degradability No information available.

Component Information					
2-methyl-2H-isothiazol-3-one [MIT] (2682-20-4)				
Method	Exposure time	Value	Results		
OECD Test No. 308: Aerobic and		Half-life	1.28-2.1 days		
Anaerobic Transformation in					
Aquatic Sediment Systems					
OECD Test No. 309: Aerobic		biodegradation Half-life	Readily biodegradable 4.1		
Mineralization in Surface Water -			days		
Simulation Biodegradation Test					

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT] (55965-84-9)							
Method	Exposure time	Value	Results				
OECD Test No. 301B: Ready	28 days	biodegradation	Not readily biodegradable				
Biodegradability: CO2 Evolution	dability: CO2 Evolution						
Test (TG 301 B)							

12.3. Bioaccumulative potential

Bioaccumulation There is no data for this product.

Component Information

United Kingdom - BE Page 9 / 13

EVO-STIK FLOORING ADHESIVERevision date28-Sep-2021Supercedes Date:23-Dec-2020Revision Number3.02

Chemical name	Partition coefficient	Bioconcentration factor (BCF)
1,2-benzisothiazol-3(2H)-one [BIT]	0.7	6.95
2634-33-5		
2-methyl-2H-isothiazol-3-one [MIT] 2682-20-4	-0.32	3.16
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT] 55965-84-9	-	3.16

12.4. Mobility in soil

Mobility in soil No information available.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment The product does not contain any substance(s) classified as PBT or vPvB.

Chemical na	me	PBT and vPvB assessment
1,2-benzisothiazol-3(2	,	The substance is not PBT / vPvB
2634-33-5		TI
2-methyl-2H-isothiazol 2682-20-4		The substance is not PBT / vPvB
reaction mass of 5-chloro-2-methyl 2-methyl-2H-isothiazol-3-one 55965-84-	(3:1) [C(M)IT/MIT]	The substance is not PBT / vPvB

12.6. Other adverse effects

Other adverse effects No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused

products

Dispose of in accordance with local regulations. Dispose of waste in accordance with

environmental legislation.

Contaminated packaging Do not reuse empty containers.

Other information Waste codes should be assigned by the user based on the application for which the

product was used.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1 UN number or ID numberNot regulated14.2 Proper Shipping NameNot regulated14.3 Transport hazard class(es)Not regulated14.4 Packing groupNot regulated14.5 Environmental hazardsNot applicable

14.6 Special Provisions None

IMDG

14.1 UN number or ID number
Not regulated
Not regulated
Not regulated

United Kingdom - BE Page 10 / 13

EVO-STIK FLOORING ADHESIVE Supercedes Date: 23-Dec-2020

Revision date 28-Sep-2021

Revision Number 3.02

_

14.3 Transport hazard class(es)14.4 Packing groupNot regulatedNot regulated

14.5 Marine pollutant NP
14.6 Special Provisions None

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code Not applicable

Air transport (ICAO-TI / IATA-DGR)

14.1 UN number or ID numberNot regulated14.2 Proper Shipping NameNot regulated14.3 Transport hazard class(es)Not regulated14.4 Packing groupNot regulated14.5 Environmental hazardsNot applicable14.6 Special ProvisionsNone

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

Registration, Evaluation, Authorization, and Restriction of Chemicals (REACh) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Biocidal Products Regulation (EU) No 528/2012 (BPR)

Contains a biocide: Contains C(M)IT/MIT (3:1). May produce an allergic reaction

Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

Persistent Organic Pollutants

Not applicable

National regulations

United Kingdom - BE Page 11 / 13

Revision date 28-Sep-2021

Supercedes Date: 23-Dec-2020 Revision Number 3.02

15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture

SECTION 16: Other information

EVO-STIK FLOORING ADHESIVE

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of H-Statements referred to under section 3

H301 - Toxic if swallowed H302 - Harmful if swallowed

H310 - Fatal in contact with skin

H311 - Toxic in contact with skin

H314 - Causes severe skin burns and eye damage

H315 - Causes skin irritation

H317 - May cause an allergic skin reaction

H318 - Causes serious eye damage

H330 - Fatal if inhaled

H400 - Very toxic to aquatic life

H410 - Very toxic to aquatic life with long lasting effects

H411 - Toxic to aquatic life with long lasting effects

Legend

TWA TWA (time-weighted average)
STEL STEL (Short Term Exposure Limit)

Ceiling Ceiling Limit Value
* Skin designation

SVHC Substance(s) of Very High Concern

PBT Persistent, Bioaccumulative, and Toxic (PBT) Chemicals vPvB Very Persistent and very Bioaccumulative (vPvB) Chemicals

STOT RE Specific target organ toxicity - Repeated exposure STOT SE Specific target organ toxicity - Single exposure

EWC European Waste Catalogue

Key literature references and sources for data

No information available

Prepared By Product Safety & Regulatory Affairs

Revision date 28-Sep-2021

Indication of changes

Revision note Not applicable.

Training Advice No information available

Further information No information available

This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

United Kingdom - BE Page 12 / 13

EVO-STIK FLOORING ADHESIVE Supercedes Date: 23-Dec-2020 Revision date 28-Sep-2021 Revision Number 3.02

End of Safety Data Sheet

United Kingdom - BE Page 13 / 13