

Revision Date 23-Nov-2018

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

EVO-STIK ALL PURPOSE FLEXIBLE SILICONE SEALANT

CLEAR

Supercedes Date: 15-Nov-2018 Revision Number 3.01

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product Identifier

Product Name EVO-STIK ALL PURPOSE FLEXIBLE SILICONE SEALANT CLEAR

Pure substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Sealant.
Uses advised against None known

1.3. Details of the supplier of the safety data sheet

Company Name

Bostik Limited Common Rd ST16 3EH Stafford UK Tel: +44 (1785) 27 26 25

Fax: +44 (1785) 27 26 25 Fax: +44 (1785) 25 72 36

E-mail address SDS.box-EU@bostik.com

1.4. Emergency telephone number

United Kingdom +44 (1785) 272650

+353 (1) 8624900 (Monday- Friday 9am-5pm)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Not classified

2.2. Label Elements

Not classified

Signal word

None

Hazard statements

Not classified

EU Specific Hazard Statements

EUH208 - Contains 3(2H)-Isothiazolone, 4,5-dichloro-2-octyl-. May produce an allergic reaction

Precautionary statements

P101 - If medical advice is needed, have product container or label at hand

P102 - Keep out of reach of children

2.3. Other Hazards

EVO-STIK ALL PURPOSE FLEXIBLE SILICONE SEALANT

CLEAR

Supercedes Date: 15-Nov-2018 Revision Number 3.01

Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing Small amounts of ethanol (CAS 64-17-5) are formed by hydrolysis and released upon curing

PBT and vPvB assessment

This preparation contains substances considered to be persistent, bio-accumulating and toxic (PBT), or to be very persistent or very bioaccumulating (vPvB)

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2 Mixtures

Chemical Name	EC No.	CAS No.	Weight-%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	REACH Registration Number
Hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics	934-956-3		40 - <80	Asp. Tox. 1 (H304)		01-2119827000- 58-XXXX
Triacetoxy(propyl)silane	241-816-9	17865-07-5	1- <2.5	Skin Corr. 1B (H314)		01-2119966899- 07-XXXX
Dodecamethylcyclohexa siloxane	208-762-8	540-97-6	0.1 - <1	PBT vPvB		01-2119517435- 42-XXXX
3(2H)-Isothiazolone, 4,5-dichloro-2-octyl-	264-843-8	64359-81-5	0.01 - <0.1	Skin Corr. 1B (H314) Eye Dam. 1 (H318) Skin Sens. 1A (H317) Acute Tox. 4 (H302) Acute Tox. 2 (H330) Aquatic Acute 1 (H400) Aquatic Chronic 1 (410)		No data available

Full text of H- and EUH-phrases: see section 16

Note: ^ indicates not classifed, however, the substance is listed in section 3 as it has an OEL

This product contains one or more candidate substance(s) of very high concern (Regulation (EC) No. 1907/2006 (REACH), Article 59)

Chemical Name	CAS No.	SVHC candidates
Dodecamethylcyclohexasiloxane	540-97-6	X

SECTION 4: First aid measures

4.1. Description of first aid measures

General advice

Take a copy of the Safety Data Sheet when going for medical treatment.

EVO-STIK ALL PURPOSE FLEXIBLE SILICONE SEALANT

CLEAR

Supercedes Date: 15-Nov-2018 Revision Number 3.01

Remove to fresh air. IF exposed or concerned: Get medical advice/attention. Inhalation

Eye contact Rinse thoroughly with plenty of water for at least 15 minutes, lifting lower and upper

eyelids. Consult a doctor.

Skin contact Wash skin with soap and water. In the case of skin irritation or allergic reactions see a

doctor.

Ingestion Clean mouth with water. Do NOT induce vomiting. Drink 1 or 2 glasses of water. Never

give anything by mouth to an unconscious person.

4.2. Most important symptoms and effects, both acute and delayed

No information available. **Symptoms**

4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Use extinguishing measures that are appropriate to local circumstances and the Suitable extinguishing media

surrounding environment.

Unsuitable extinguishing media Full water jet. Do not scatter spilled material with high pressure water streams.

5.2. Special hazards arising from the substance or mixture

chemical

Specific hazards arising from the Thermal decomposition can lead to release of toxic and corrosive gases/vapours.

5.3. Advice for firefighters

Special protective equipment for

fire-fighters

Firefighters should wear self-contained breathing apparatus and full firefighting turnout

gear. Use personal protection equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Avoid contact with skin, eyes or clothing. **Personal precautions**

Other information Ventilate the area. Prevent further leakage or spillage if safe to do so.

Use personal protection recommended in Section 8. For emergency responders

6.2. Environmental precautions

Environmental precautions Do not flush into surface water or sanitary sewer system. Do not allow to enter into

soil/subsoil. See Section 12 for additional Ecological Information.

6.3. Methods and material for containment and cleaning up

Methods for containment Use a non-combustible material like vermiculite, sand or earth to soak up the product

and place into a container for later disposal.

Methods for cleaning up Take up mechanically, placing in appropriate containers for disposal.

EVO-STIK ALL PURPOSE FLEXIBLE SILICONE SEALANT

CLEAR

Supercedes Date: 15-Nov-2018 Revision Number 3.01

6.4. Reference to other sections

Reference to other sections See section 8 for more information. See section 13 for more information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling Ensure adequate ventilation. Use personal protective equipment as required. Avoid

contact with skin, eyes or clothing.

General hygiene considerations Handle in accordance with good industrial hygiene and safety practice. Do not eat, drink

or smoke when using this product. Wash thoroughly after handling. Take off all

contaminated clothing and wash it before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions Keep container tightly closed in a dry and well-ventilated place. Keep away from food,

drink and animal feedingstuffs.

7.3. Specific end use(s)

Specific Use(s)

Sealant.

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

Other information Observe technical data sheet.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Exposure Limits Small amounts of ethanol (CAS 64-17-5) are formed by hydrolysis and released upon

curing Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released

upon curing

Derived No Effect Level (DNEL) No information available

Predicted No Effect Concentration No information available.

(PNEC)

8.2. Exposure controls

Engineering controls Ensure adequate ventilation, especially in confined areas.

Personal Protective Equipment

Eye/face protection Skin and body protectionTight sealing safety goggles.
Suitable protective clothing.

Environmental exposure controls No information available.

SECTION 9: Physical and chemical properties

EVO-STIK ALL PURPOSE FLEXIBLE SILICONE SEALANT

CLEAR

Supercedes Date: 15-Nov-2018 Revision Number 3.01

hPa

9.1. Information on basic physical and chemical properties

Physical State Liquid
Appearance Paste
Colour Clear

Odour No information available Odour Threshold No information available

Property Values Remarks • Method

pH No data available
Melting point / freezing point No data available

Boiling point / boiling range 301 °C > 100 °C Flash Point > 100 °C No data available Flammability (solid, gas) No data available

Flammability Limit in Air

Upper flammability or explosive No data available

limits

Lower flammability or explosive No data available

limits

Vapour Pressure <100

Vapour Density No data available

Relative Density 0.94

Water SolubilityImmiscible in waterSolubility(ies)No data availablePartition coefficientNo data available

Autoignition Temperature >200 °C

Decomposition TemperatureNo data availableKinematic Viscosity> 50 mm²/sDynamic ViscosityNo data availableExplosive propertiesNo data availableOxidising propertiesNo data available

9.2. Other information

Solid content (%)

Softening Point

Molecular Weight

VOC (volatile organic compound)

Density

Bulk Density

No information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity No information available.

10.2. Chemical stability

Stability Stable under normal conditions.

Explosion Data

Sensitivity to mechanical None.

impact

Sensitivity to static discharge None.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

EVO-STIK ALL PURPOSE FLEXIBLE SILICONE SEALANT

CLEAR

Supercedes Date: 15-Nov-2018 Revision Number 3.01

10.4. Conditions to avoid

Conditions to avoidNone known based on information supplied.

10.5. Incompatible materials

Incompatible materials None known based on information supplied.

10.6. Hazardous decomposition products

Hazardous decomposition

products

None under normal use conditions. Stable under recommended storage conditions.

Revision Date 23-Nov-2018

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Information on likely routes of exposure

Product information

Inhalation Based on available data, the classification criteria are not met.

Eye contact Product not classified due to level of crosslinking agent of silicone sealant being below

level for classification based on in-vivo testing (Hygiene-Institut des Ruhergebiets-

Germany- May 2014).

Skin contact Based on available data, the classification criteria are not met.

Ingestion Based on available data, the classification criteria are not met.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms No information available.

Numerical measures of toxicity

Acute Toxicity

The following values are calculated based on chapter 3.1 of the GHS document

Component Information

Component information					
Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50		
Hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics	LD50 > 5000 mg/kg (rat) OECD 401	LD50 > 3160 mg/kg (rabbit) OECD 402	LC50 Inhalation(4h) >5266 MG/M3 Rat		
Dodecamethylcyclohexasiloxa ne 540-97-6	> 50 g/kg (Rat)				
3(2H)-Isothiazolone, 4,5-dichloro-2-octyl- 64359-81-5	= 1636 mg/kg (Rat)	> 2000 mg/kg(Rabbit)	= 0.26 mg/L (Rat)4 h		

Delayed and immediate effects as well as chronic effects from short and long-term exposure

EVO-STIK ALL PURPOSE FLEXIBLE SILICONE SEALANT

CLEAR

Supercedes Date: 15-Nov-2018 Revision Number 3.01

Skin corrosion/irritationBased on available data, the classification criteria are not met.

Serious eye damage/eye irritation Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicityBased on available data, the classification criteria are not met.

STOT - single exposureBased on available data, the classification criteria are not met.

STOT - repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity

Chemical Name	Algae/aquatic plants	Fish	Toxicity to Micro-organisms	Crustacea	M-Factor
Hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics	EL50 (72h) >10,000 mg/L (Skeletonema costatum) ISO 10253	LL50 (96h) > 1028 mg/L (Scophthalmus maximus) OECD 203	-	LL50 (48h)> 3193 mg/l (Acartia tonsa)	-
3(2H)-Isothiazolone, 4,5-dichloro-2-octyl- 64359-81-5	EC50 (72h) =0.025 mg/L Algae (Scenedesmus subspicatus)(OEC D 201)	LC50 (96h) 0.0078 mg/L Fish (Oncorhynchus mykiss)(OECD 203)	-	EC50 (48h) 0.0097 mg/L Daphnia magna (OECD 202)	-

12.2. Persistence and degradability

Persistence and degradability No information available.

12.3. Bioaccumulative potential

Bioaccumulation There is no data for this product.

Component Information

Chemical Name	Partition coefficient	Bioconcentration factor (BCF)
Dodecamethylcyclohexasiloxane 540-97-6	8.87	-
3(2H)-Isothiazolone, 4,5-dichloro-2-octyl- 64359-81-5	4.4	13

12.4. Mobility in soil

Mobility in soil No information available.

EVO-STIK ALL PURPOSE FLEXIBLE SILICONE SEALANT

CLEAR

Supercedes Date: 15-Nov-2018 Revision Number 3.01

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment This preparation contains substances considered to be persistent, bio-accumulating and

toxic (PBT), or to be very persistent or very bioaccumulating (vPvB). .

Chemical Name	PBT and vPvB assessment
Triacetoxy(propyl)silane 17865-07-5	The substance is not PBT / vPvB
Dodecamethylcyclohexasiloxane 540-97-6	PBT / vPvB substance

12.6. Other adverse effects

Other Adverse Effects No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused

products

Dispose of contents/container in accordance with local, regional, national, and

international regulations as applicable.

Contaminated packaging Do not reuse empty containers. Handle contaminated packages in the same way as the

product itself.

European Waste Catalogue 08 04 09* waste adhesives and sealants containing organic solvents or other dangerous

substances

Other information Waste codes should be assigned by the user based on the application for which the

product was used.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1 UN NumberNot regulated14.2 Proper Shipping NameNot regulated14.3 Transport hazard class(es)Not regulated14.4 Packing GroupNot regulated14.5 Environmental hazardsNot applicable14.6 Special ProvisionsNone

IMDG

14.1 UN NumberNot regulated14.2 Proper Shipping NameNot regulated14.3 Transport hazard class(es)Not regulated14.4 Packing GroupNot regulated

14.5 Marine Pollutant Np14.6 Special Provisions None

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code No information available

Air transport (ICAO-TI / IATA-DGR)

14.1 UN NumberNot regulated14.2 Proper Shipping NameNot regulated14.3 Transport hazard class(es)Not regulated14.4 Packing GroupNot regulated14.5 Environmental hazardsNot applicable

EVO-STIK ALL PURPOSE FLEXIBLE SILICONE SEALANT

CLEAR

Supercedes Date: 15-Nov-2018 Revision Number 3.01

14.6 Special Provisions None

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

Registration, Evaluation, Authorization, and Restriction of Chemicals (REACh) Regulation (EC 1907/2006)

EU-REACH (1907/2006) - Candidate List of Substances of Very High Concern (SVHC) for Authorization in accordance with Article 59

This product contains one or more candidate substance(s) of very high concern (Regulation (EC) No. 1907/2006 (REACH), Article 59)

Chemical Name	CAS No.
Dodecamethylcyclohexasiloxane	540-97-6

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

EU-REACH (1907/2006) - Annex XIV - List of substances subject to Authorization

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

Persistent Organic Pollutants

Not applicable

15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture

SECTION 16: Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of H-Statements referred to under section 3

H314 - Causes severe skin burns and eye damage

H318 - Causes serious eye damage

H317 - May cause an allergic skin reaction

H302 - Harmful if swallowed

H330 - Fatal if inhaled

EVO-STIK ALL PURPOSE FLEXIBLE SILICONE SEALANT

CLEAR

Supercedes Date: 15-Nov-2018 Revision Number 3.01

H400 - Very toxic to aquatic life

H304 - May be fatal if swallowed and enters airways

Legend

SVHC: Substances of Very High Concern for Authorisation:

Legend SECTION 8: Exposure controls/personal protection

TWA TWA (time-weighted average) STEL STEL (Short Term Exposure Limit)

Ceiling Maximum limit value * Skin designation

PBT Persistent, Bioaccumulative, and Toxic (PBT) Chemicals STOT RE Specific target organ toxicity - Repeated exposure STOT SE Specific target organ toxicity - Single exposure

EWC: European Waste Catalogue

Key literature references and sources for data

Classification and labeling data calculated from data received from raw material suppliers

Prepared By Product Safety & Regulatory Affairs

Revision Date 23-Nov-2018

Indication of changes

Revision note Not applicable.

Training Advice No information available

Further information No information available

This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet