## INFORMATION




# 27" QHD IPS monitor with 4-side slim bezel, ergonomic stand and USB hub

Designed to support your productivity, the ProLite XB2793QSU helps you stay focused and efficient throughout the day. The 27" QHD resolution (2560×1440) provides more space to work, letting you view documents side by side, edit with precision or keep multiple apps open at once, all in sharp detail.

The IPS panel ensures vivid colours and consistent clarity from any angle. Flicker free technology and a blue light reducer enhance eye comfort during long sessions.

The four side ultra slim bezel design brings a clean, modern look and suits multi monitor setups. The ergonomic stand offers height, tilt, swivel and pivot adjustment for better comfort throughout the day. Built-in speakers, a two-port USB hub, HDMI and DisplayPort inputs, and a headphone socket help reduce desk clutter.

With EPEAT registration and TCO compliance, the XB2793QSU combines reliable performance with responsible energy use.

## FEATURES




### Expand your view with QHD

QHD 2560x1440 resolution offers up to 77% more screen space than Full HD, giving you plenty of room to multitask efficiently, view more content at once, and work with greater precision, without constantly switching between windows.



### Multi-screen setup for a panoramic workspace

Connect multiple ultra-slim bezel monitors to create a panoramic workspace, keep your apps in view, streamline multitasking, and boost productivity.




### Adjustable stand for optimal comfort

Find your perfect screen position easily and maintain a healthy, comfortable posture all day long. Thanks to its fully adjustable stand, you can effortlessly adapt the monitor to your needs. Raise or lower the height, swivel left or right, or tilt the screen to reduce glare and find the optimal viewing angle. Whether you're working, designing, or attending long video calls, this flexibility helps reduce neck and back strain, improving both comfort and productivity throughout your day.




### Versatile connectivity for all your devices

Connect multiple devices and accessories in one simple step with HDMI, DisplayPort and the USB hub, streamlining your workspace for maximum efficiency and ensuring a tidy, uninterrupted workflow.

## SPECIFICATION

### 01 DISPLAY CHARACTERISTICS

| | |
|---|---|
| **Design** | 4-side slim bezel |
| **Diagonal** | 27", 68. 5cm |
| **Panel** | IPS panel technology LED, matte finish |
| **Native resolution** | 2560 x 1440 @75Hz (3.7 megapixel QHD) |
| **Aspect ratio** | 16:9 |
| **Panel brightness** | 350 cd/m² |
| **Static contrast** | 1000:1 |
| **Advanced contrast** | 80M:1 |
| **Response time (MPRT)** | 1ms |
| **Viewing zone** | horizontal/vertical: 178°/178°, right/left: 89°/89°, up/down: 89°/89° |
| **Colour support** | 16.7mln (sRGB: 100%; NTSC: 72%) |
| **Horizontal Sync** | 30 - 112kHz |
| **Viewable area W x H** | 596.7 x 335.7mm, 23.5 x 13.2" |
| **Pixel pitch** | 0.233mm |
| **Colour** | matte, black |

### 02 INTERFACES / CONNECTORS / CONTROLS

| | |
|---|---|
| **Signal input** | HDMI x1 (v.1.4)<br>DisplayPort x1 (v.1.2) |
| **USB HUB** | x2 (v. 2.0 (DC5V, 500mA)) |
| **HDCP** | yes |
| **Headphone connector** | yes |

### 03 FEATURES

| | |
|---|---|
| **Blue light reducer** | yes |
| **Flicker free** | yes |
| **Adaptive Sync support** | yes |
| **Extra** | i-Style colour |
| **OSD languages** | EN, DE, FR, ES, IT, RU, JP, CZ, NL, PL, UA |
| **Control buttons** | Joystick: (Centre) Power/Menu, Up/Signal Select, Down, Left/Submenu, Right/Volume |
| **User controls** | picture adjust (brightness, contrast, ECO, ACR, OD, motion blur reduction, Adaptive Sync), colour settings (i-Style colour, blue light reducer, RGB range, colour temperature, user preset), OSD (OSD H. position, OSD V. position, OSD rotate, OSD time, OSD background, DDC/CI control, display information), language, extra1 (sharpness, video mode adjust, opening logo, power LED), extra 2 (shortcut key, FW version), input select, audio settings (volume, mute audio), reset (reset all) |
| **Speakers** | 2 x 2W |
| **Convenience** | Kensington-lock™ prepared, DDC/CI, DDC2B, Mac OSX |

## 04 MECHANICAL

| | |
|---|---|
| **Display position adjustments** | height, swivel, tilt, pivot (rotation both sides) |
| **Height adjustment** | 150mm |
| **Rotation (PIVOT function)** | 90° |
| **Swivel stand** | 360°; 180° left; 180° right |
| **Tilt angle** | 23° up; 5° down |
| **VESA mounting** | 100 x 100mm |
| **Cable management system** | yes |

## 05 ACCESSORIES INCLUDED

| | |
|---|---|
| **Cables** | power (1.5m), USB (1.5m), HDMI (1.5m), DP (1.8m) |
| **Other** | quick start guide, safety guide |

## 06 POWER MANAGEMENT


| | |
|---|---|
| **Power supply unit** | internal |
| **Power supply** | AC 100 - 240V, 50/60Hz |
| **Power usage** | 17W default, 0.5W stand by, 0.3W off mode |

## 07 SUSTAINABILITY

| | |
|---|---|
| **Regulations** | TCO Certified, CE, TÜV-GS, EAC, VCCI-B, PSE, RoHS support, ErP, WEEE, REACH, UKCA |
| **Energy efficiency class (Regulation (EU) 2017/1369)** | D |
| **EPEAT Silver** | *registration varies by country, go to www.epeat.net for details |
| **REACH SVHC** | above 0.1%: Lead, Lead monoxide, Diboron trioxide |

## 08 DIMENSIONS / WEIGHT

| | |
|---|---|
| **Product dimensions W x H x D** | 613 x 404 (548) x 224.5mm |
| **Box dimensions W x H x D** | 691 x 442 x 142mm |
| **Weight (without box)** | 5.7kg |
| **Weight (with box)** | 8.1kg |
| **EAN code** | 4948570126781 |



4xM4 SCREW HOLE
(VESA MOUNT)
235.0
209.5
224.5
100.0
46.5
100.0
613.0
176.0
362.0
47.5
398.0(548.0)
404.0
24.0
32.5
32.5
627.0(675.0)

## GALLERY


iiyama
ProLite
XB2793QSU
27"
IPS


iiyama
ProLite
XB2793QSU
27"
IPS


iiyama
ProLite
XB2793QSU
27"
IPS



iiyama
ProLite
XB2793QSU
27"
IPS


iiyama
ProLite
XB2793QSU
27"
IPS


iiyama
ProLite
XB2793QSU
27"
IPS


iiyama


ProLite
XB2793QSU




27"
IPS








iiyama










All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-9241-307:2008 in connection with pixel defects. **© IIYAMA CORPORATION. ALL RIGHTS RESERVED**