## INFORMATION




# 27” QHD monitor with USB-C docking, KVM and LAN - everything you need in a single display

Stay connected and reduce cable clutter with the ProLite XB2797QSNP. The integrated USB-C dock with 96W power delivery lets you transfer video, audio, data and power through a single cable, keeping your workspace clean and efficient. The RJ45 port ensures a fast, stable wired network connection without additional adapters.


With the built-in KVM switch, you can control two computers using a single keyboard and mouse, making it easy to switch between systems and maintain a smooth workflow.

The 27” QHD IPS panel delivers high resolution and accurate colour reproduction with wide viewing angles, supporting detailed work such as content creation, spreadsheets or design tasks. The DisplayPort output enables quick setup of a dual-monitor configuration to expand your screen space and boost productivity.

The stand offers 15cm height adjustment along with tilt, swivel and pivot functions including portrait mode, so you can work comfortably in your preferred position. Tested and certified by TÜV Rheinland for Eye Comfort, the XB2797QSNP meets strict display standards to help reduce visual fatigue during extended use, supporting long-lasting focus and well-being at work.


Available also without USB-C dock: XB2797QSU-B1.

## FEATURES



### Easy multi-device control with KVM

Easily switch between multiple computers using one monitor, keyboard, and mouse, making multitasking smooth and efficient.




### USB-C dock for tidy desk & easy connectivity

Connect everything with just one cable - handle video, data, and power while keeping your desk clean and organized.




### Expand your view with QHD

QHD 2560x1440 resolution offers up to 77% more screen space than Full HD, giving you plenty of room to multitask efficiently, view more content at once, and work with greater precision, without constantly switching between windows.




### Adjustable stand for optimal comfort

Find your perfect screen position easily and maintain a healthy, comfortable posture all day long. Thanks to its fully adjustable stand, you can effortlessly adapt the monitor to your needs. Raise or lower the height, swivel left or right, or tilt the screen to reduce glare and find the optimal viewing angle. Whether you're working, designing, or attending long video calls, this flexibility helps reduce neck and back strain, improving both comfort and productivity throughout your day.

## SPECIFICATION

### 01 DISPLAY CHARACTERISTICS

| | |
|---|---|
| **Design** | 4-side slim bezel |
| **Diagonal** | 27", 68.5cm |
| **Panel** | IPS Panel Technology LED, matte finish |
| **Native resolution** | 2560 x 1440 @75Hz (3.7 megapixel QHD) |
| **Aspect ratio** | 16:9 |
| **Panel brightness** | 350 cd/m² |
| **Static contrast** | 1000:1 |
| **Advanced contrast** | 80M:1 |
| **Response time (MPRT)** | 1ms |
| **Viewing zone** | horizontal/vertical: 178°/178°, right/left: 89°/89°, up/down: 89°/89° |
| **Colour support** | 16.7mln (sRGB: 100%; NTSC: 72%) |
| **Horizontal Sync** | 30 - 112kHz |
| **Viewable area W x H** | 596.7 x 335.7mm, 23.5 x 13.2" |
| **Pixel pitch** | 0.233mm |
| **Colour** | matte, black |

### 02 INTERFACES / CONNECTORS / CONTROLS

| | |
|---|---|
| **Signal input** | HDMI x1 (v.1.4)<br>DisplayPort x1 (v.1.2)<br>USB-C x1 (PD 96W) |
| **Signal output** | DisplayPort x1 (2560;1440) |
| **USB HUB** | x4 (2x Type-A v.3.2 Gen 1 (5Gbps, 4.5W) 2x Type-C (7.5Gbps, 5W)) |
| **USB-C DOCK** | x1 (Power delivery 96W, LAN, DP out, USB v.3.2 (Gen 1, 5Gbit)) |
| **HDCP** | yes |
| **Headphone connector** | yes |
| **RJ45 (LAN)** | x1 |

### 03 FEATURES

| | |
|---|---|
| **KVM switch** | yes |
| **Flicker free** | yes |
| **Adaptive Sync support** | yes |
| **Extra** | i-Style colour, Eye Comfort |
| **OSD languages** | EN, DE, FR, ES, IT, RU, JP, CZ, NL, PL, UA |
| **Control buttons** | Joystick: Power/Menu (Centre), Up/Signal Select, Down, Left/Shortcut, Right/Volume |

| | |
|---|---|
| **User controls** | picture adjust (brightness, contrast, ECO, ACR, OD, MBR, Adaptive Sync), colour settings (i-Style colour, RGB range, colour temp., user preset), OSD (OSD H. position, OSD V. position, OSD rotate, OSD time, OSD background, DDC/CI control, display information), language, extra 1 (sharpness, video mode adjust, opening logo, power LED, USB charge, USB-C speed, MST DP-out), Extra 2 (shortcut key, Mac address, FW version), KVM (HDMI, DisplayPort, USB-C), input select, audio settings (volume, mute), reset (reset all?) |
| **Speakers** | 2 x 2W |
| **Convenience** | Kensington-lock™ prepared, DDC/CI, DDC2B |

## 04 MECHANICAL

| | |
|---|---|
| **Display position adjustments** | height, swivel, tilt, pivot (rotation both sides) |
| **Height adjustment** | 150mm |
| **Rotation (PIVOT function)** | 90° |
| **Swivel stand** | 120°; 60° left; 60° right |
| **Tilt angle** | 23° up; 5° down |
| **VESA mounting** | 100 x 100mm |
| **Cable management system** | yes |

## 05 ACCESSORIES INCLUDED

| | |
|---|---|
| **Cables** | power (1.5m), USB (1.5m), HDMI (1.5m), USB-C (1.0m) |
| **Other** | quick start guide, safety guide |

## 06 POWER MANAGEMENT

| | |
|---|---|
| **Power supply unit** | internal |
| **Power supply** | AC 100 - 240V, 50/60Hz |
| **Power usage** | 21W default, 0.5W stand by, 0.3W off mode |


## 07 SUSTAINABILITY

| | |
|---|---|
| **Regulations** | CE, TÜV-GS, EAC, VCCI-B, PSE, RoHS support, ErP, WEEE, REACH, UKCA, TCO Edge |
| **Energy efficiency class (Regulation (EU) 2017/1369)** | E |
| **EPEAT Silver** | *registration varies by country, go to www.epeat.net for details |
| **REACH SVHC** | above 0.1%: Lead, Lead monoxide, Diboron trioxide |
| **Warranty** | 5 years (for details and eligible countries please check the Warranty section of our website) |

## 08 DIMENSIONS / WEIGHT

| | |
|---|---|
| **Product dimensions W x H x D** | 613 x 403.5 (547.5) x 209.5mm |

| | |
|---|---|
| **Box dimensions W x H x D** | 691 x 447 x 142mm |
| **Weight (without box)** | 5.9kg |
| **Weight (with box)** | 8.0kg |
| **EAN code** | 4948570125944 |



## GALLERY


iiyama
ProLite
XB2797QSNP
27"
68.6cm
IPS
2560x1440
96W
USB-C
KVM
SWITCH
15cm


iiyama
ProLite
XB2797QSNP
27"
68.6cm
IPS
2560x1440
96W
USB-C
KVM
SWITCH
15cm


iiyama
ProLite
XB2797QSNP
27"
68.6cm
IPS
2560x1440
96W
USB-C
KVM
SWITCH
15cm


iiyama
ProLite
XB2797QSNP
27"
68.6cm
IPS
2560x1440
96W
USB-C
KVM
SWITCH
15cm


iiyama
ProLite
XB2797QSNP
27"
68.6cm
IPS
2560x1440
96W
USB-C
KVM
SWITCH
15cm
5 YEAR WARRANTY


iiyama
ProLite
XB2797QSNP
27"
68.6cm
IPS
2560x1440
96W
USB-C
KVM
SWITCH
15cm
5 YEAR WARRANTY


iiyama


ProLite
XB2797QSNP


KVM
SWITCH
15cm


27"
68.6cm
IPS
2560x1440


27"
68.6cm
IPS
2560x1440









All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-9241-307:2008 in connection with pixel defects. **© IIYAMA CORPORATION. ALL RIGHTS RESERVED**