optomaeurope.com



ML750e Ultra-compact LED projector





- HD Ready and LED technology Great for movies, gaming and PC-free presentations
- Great connectivity HDMI, MHL, micoSD and built in speaker
- Built in media play and optional wireless presentations
- Compact & Lightweight <0.4kg

The ML750e ultra-compact portable LED projector is easily transportable between your home and office. This tiny projector weights less than 0.4kg and comes with a convenient carry bag. Watch HD movies, play video games or even present that winning presentation, the ML750e has everything you need to impress your audience.



Specifications

Display/image	
Display technology	DLP
Resolution	WXGA (1280x800)
Brightness (LED)	700 LED brightness
Contrast ratio	20,000:1
Native aspect ratio	16:10
Aspect ratio - compatible	4:3,16:9
Keystone correction - vertical	+/-40°
Horizontal scan rate	15.375 ~ 91.146Khz
Vertical scan rate	24 ~ 85(120 for 3D)Hz
Uniformity	85%
Screen size	0.43m ~ 2.54m (17" ~ 100") diagonal
_amp info	
Light source type	LED
ED life	20,000 hours
Optical	
Throw ratio	1.5:1
Projection distance (m)	0.55m - 3.23m
Zoom type	Fixed
Focal length (mm)	14.95
lative offset	100%
Connectivity	
Connections	Inputs 1 x HDMI 1.4a 3D support + MHL, 1 x microSD card, 1 x USB-A reader
	Outputs 1 x Audio 3.5mm
General	
oise level (typical)	30dB
oise level (max)	32dB
C compatibility	FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac
D compatibility	480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz)
D compatibility	SVGA 120Hz, XGA 120Hz
3D	3D ready
Security	Security bar, Kensington Lock, Password protected interface
DSD / display languages	13 languages: Dutch, English, French, German, Greek, Italian, Polish, Portuguese, Russian, Spanish, Swedish, Turkish
Operating conditions	5°C ~ 35°C, Max. Humidity 85%, Max. Altitude 2500m
Remote control	Card style
Speaker count	1
Watts per speaker	1W
In the box	Carry bag Universal I/O cable
	AC power cord
	Remote control
	Battery
any star	Basic user manual
nput lag	16.00ms WUSB
Optional wireless models	MO2R
ower	
ower supply	100 ~ 240V, 50 ~ 60Hz
ower consumption	0.5W
-	
standby)	16W
standby) Power consumption (min)	16W 26W
standby) Power consumption (min) Power consumption (max)	
standby) Power consumption (min) Power consumption (max) Neight and dimensions	
Visandby) Power consumption (min) Power consumption (max) Weight and dimensions Net weight Dimensions (W x D x H)	26W





Copyright © 2018, Optoma and its logo is a registered trademark of Optoma Corporation. Optoma Europe Ltd is the licensee of the registered trademark. All other product names and company names used herein are for identification purposes only and may be trademarks or registered trademarks of their respective owners. Errors and omissions excepted, all specifications are subject to change without notice. All images are for representation purposes only and may be simulated. 12012021011519