

## DX349

Bright and portable

- Bright XGA projector – 3000 ANSI lumens
- Easy connectivity - HDMI, VGA, USB-A Power, 2W speaker
- Low ownership costs - up to 10,000 hours<sup>2</sup> lamp life
- Lightweight and portable



## DX349

Project your presentations effortlessly any time of day with the bright DX349. Designed for meeting rooms and classrooms, this small projector boasts sRGB accurate true to life colour reproduction, long lamp life and energy-saving features to provide you with a low overall cost of ownership.

This projector is easy to connect to with multiple inputs, a built-in speaker and USB Power. Perfect for connecting HDMI dongles such as the Google Chromecast and the Optoma HDCast Pro (sold separately) or a laptop, PC or Blu-ray player for clear projected images with sound. Portable and lightweight projector can be installed or taken on the move for off-site meetings with the optional carry bag (sold separately).

## Specification

Display Technology	Single 0.55" XGA DC3 DMD chip DLP® Technology by Texas Instruments
Resolution	XGA 1024 x 768
Brightness <sup>1</sup> (Bright Mode)	3000 ANSI Lumens
Contrast	20,000:1
Typical lamp life <sup>2</sup> Eco+/Dynamic/Eco/Bright/Education cycle	8000/7000/6000/5000/10000 (hrs)
Throw Ratio	1.94 - 2.16:1
Zoom Type	1.1x Manual
I/O Connectors	HDMI (1.4a 3D support), VGA (YPbPr/RGB), Composite, Audio in 3.5mm, VGA out, Audio out 3.5mm, RS232, USB-A Power (5V-1A)
Speaker (Watts)	2
Keystone Correction	± 40° Vertical
Weight (kg)	2.17
Dimensions (W x D x H)	298 x 230 x 96.5
Aspect Ratio	4:3 Native, 16:9 Compatible
Offset	115%
Projection Screen Size	0.71 - 7.73m (27.78" - 304.4") Diagonal 4:3
Projection Distance	1.2 - 12m
Projection Lens	F/2.4~2.53; f=21.85~24.01mm
Uniformity	75%
Computer Compatibility	FHD, HD, WXGA, UXGA, SXGA, XGA, SVGA, VGA, Mac
Video Compatibility	PAL (B, D, G, H, I, M, N, 4.43MHz), NTSC (M, J, 3.58MHz, 4.443MHz), SECAM (B, D, G, K, K1, L, 4.25MHz, 4.4MHz, 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz) 1080p(24/50/60Hz)
3D Support	Full 3D - The 3D features of Optoma projectors can only be used with compatible 3D content. Typical applications include use with 3D educational or 3D design and modelling systems. 3D TV broadcast systems, (SKY in the UK), Blu-ray 3D™ and 3D games from the Sony® PS3 or Microsoft® Xbox 360 are now supported as part of the HDMI v1.4a specification.
3D Compatibility	Side-by-Side: 1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60
Horizontal Scan Rate	15.3 - 91.1kHz
Vertical Scan Rate	24 - 85Hz (120Hz for 3D)
Displayable Colours	1073.4 Million
Noise Level (Eco mode)	29dB
Power Supply	100-240V, 50-60Hz
Power Consumption	225W Bright mode / 187W Eco mode (< 0.5W Standby)
Lamp Type	195W
Operating Conditions	5°C - 40°C, Max. Humidity 85%, Max. Altitude 3000m
Security	Security bar, Kensington lock, password protection
On Screen Display	26 Languages: English, German, French, Italian, Spanish, Portuguese, Swedish, Dutch, Norwegian/Danish, Polish, Russian, Finnish, Greek, Hungarian, Czech, Arabic, Traditional Chinese, Simplified Chinese, Japanese, Korean, Thai, Turkish, Farsi, Vietnamese, Romanian, Indonesian
Standard Accessories	AC power cord, VGA cable, remote control, battery, quick start card, CD user manual
Optional Accessories	DLP® Link™ 3D glasses, wireless, ceiling mount
Optional Wireless	Yes
RoHS	Compliant

