

# 1m (3 ft.) USB-C to HDMI Cable - 4K at 60Hz - White

Product ID: CDP2HD1MWNL



This USB-C<sup>™</sup> to HDMI® adapter cable offers a convenient solution for directly connecting your DisplayPort over USB Type-C<sup>™</sup> device to your HDMI monitor, television, or projector. The adapter offers a connection distance of up to 1 m (3 ft.) and works with USB-C devices that support DP Alt Mode, such as the MacBook, Chromebook Pixel<sup>™</sup> and Dell<sup>™</sup> XPS<sup>™</sup> models 15 and 13. It's also compatible with Thunderbolt<sup>™</sup> 3 ports.

### **Clutter-free installation**

While this white adapter looks great next to computers that match the look and feel of laptops like your MacBook or HP® Envy, it works with any USB-C computer that supports HDMI. At 1 m (3 ft.) in length, this adapter cable delivers a direct connection that eliminates excess adapters and cabling, ensuring a tidy and professional installation.



### **Data Sheet**

For longer installations, StarTech.com also offers a 2 m (6 ft.) USB-C to HDMI cable (CDP2HD2MWNL) and a 3 m (10 ft.) USB-C to HDMI cable (CDP2HD3MWNL), enabling you to choose the right cable length for your custom installation needs.

### **Astonishing picture quality**

At four times the resolution of high-definition 1080p, you'll be amazed at the picture quality of a 4K 60Hz monitor or television. This adapter cable lets you harness the video capabilities that are built into your USB Type-C connection, to deliver the astonishing quality of Ultra HD to your 4K display.

Plus, the adapter is still compatible with lower display resolutions, such as 1080p, which makes it a great accessory for your current home, office or other HD work environment, while future-proofing for 4K 60Hz implementation.

The CDP2HD1MWNL is backed by a 2-year StarTech.com warranty and free lifetime technical support.





## Certifications, Reports and Compatibility











### **Applications**

- Connect a USB Type-C computer to an HDMI projector or display in your classroom, auditorium or boardroom
- Install at your home workstation or office hot desk to make your USB-C computer compatible with your HDMI display

#### **Features**

- Reduce clutter with a 1 m (3 ft.) all-in-one solution with a combined cable and adapter
- A stylish look that complements your white monitors
- Hassle-free connection with the reversible USB-C connector
- Astonishing video quality with support for resolutions up to 4K at 60Hz



### **Data Sheet**

	Warranty	2 Years
Hardware	Adapter Style	Cable Adapters
	AV Input	USB Type-C
	AV Output	HDMI
	Chipset ID	VIA/VLI - VL100 Parade - PS176
	Ports	1
Performance	Audio Specifications	7.1 surround sound
	Maximum Digital Resolutions	3840x2160 @ 60 Hz
	Supported Resolutions	1024x768 1280x720 (High-definition 720p) 1920x1080 (High-definition 1080p) 1920x1200 2560x1440 2560x1600 3840x2160 (Ultra HD 4K)
	Wide Screen Supported	Yes
Connector(s)	Connector A	1 - USB-C (24 pin) DisplayPort Alt Mode Male Input
	Connector B	1 - HDMI (19 pin) Female Output
Special Notes / Requirements	Connector B  Note	1 - HDMI (19 pin) Female Output  Your USB-C port must support DisplayPort over USB-C (DP Alt mode) in order to work with this adapter.
=		Your USB-C port must support DisplayPort over USB-C (DP
Requirements	Note	Your USB-C port must support DisplayPort over USB-C (DP Alt mode) in order to work with this adapter.
Requirements	Note Humidity	Your USB-C port must support DisplayPort over USB-C (DP Alt mode) in order to work with this adapter.  5%-90% RH (no condensation)
Requirements	Note  Humidity Operating Temperature	Your USB-C port must support DisplayPort over USB-C (DP Alt mode) in order to work with this adapter.  5%-90% RH (no condensation)  0°C to 45°C (32°F to 113°F)
Requirements  Environmental  Physical	Note  Humidity Operating Temperature Storage Temperature	Your USB-C port must support DisplayPort over USB-C (DP Alt mode) in order to work with this adapter.  5%-90% RH (no condensation)  0°C to 45°C (32°F to 113°F)  -10°C to 70°C (14°F to 158°F)
Requirements  Environmental  Physical	Note  Humidity Operating Temperature Storage Temperature Cable Length	Your USB-C port must support DisplayPort over USB-C (DP Alt mode) in order to work with this adapter.  5%-90% RH (no condensation)  0°C to 45°C (32°F to 113°F)  -10°C to 70°C (14°F to 158°F)  3.3 ft [1 m]
Requirements  Environmental  Physical	Note  Humidity Operating Temperature Storage Temperature Cable Length Color	Your USB-C port must support DisplayPort over USB-C (DP Alt mode) in order to work with this adapter.  5%-90% RH (no condensation)  0°C to 45°C (32°F to 113°F)  -10°C to 70°C (14°F to 158°F)  3.3 ft [1 m]  White
Requirements  Environmental  Physical	Note  Humidity Operating Temperature Storage Temperature Cable Length  Color Product Height	Your USB-C port must support DisplayPort over USB-C (DP Alt mode) in order to work with this adapter.  5%-90% RH (no condensation)  0°C to 45°C (32°F to 113°F)  -10°C to 70°C (14°F to 158°F)  3.3 ft [1 m]  White  0.6 in [14 mm]
Requirements  Environmental  Physical	Note  Humidity Operating Temperature Storage Temperature  Cable Length  Color Product Height Product Length	Your USB-C port must support DisplayPort over USB-C (DP Alt mode) in order to work with this adapter.  5%-90% RH (no condensation)  0°C to 45°C (32°F to 113°F)  -10°C to 70°C (14°F to 158°F)  3.3 ft [1 m]  White  0.6 in [14 mm]  39.4 in [1000 mm]
Requirements  Environmental  Physical	Note  Humidity Operating Temperature Storage Temperature  Cable Length  Color Product Height Product Length  Product Weight	Your USB-C port must support DisplayPort over USB-C (DP Alt mode) in order to work with this adapter.  5%-90% RH (no condensation)  0°C to 45°C (32°F to 113°F)  -10°C to 70°C (14°F to 158°F)  3.3 ft [1 m]  White  0.6 in [14 mm]  39.4 in [1000 mm]  2.8 oz [80 g]
Requirements  Environmental  Physical Characteristics  Packaging	Note  Humidity Operating Temperature Storage Temperature  Cable Length  Color Product Height Product Length  Product Weight Product Width	Your USB-C port must support DisplayPort over USB-C (DP Alt mode) in order to work with this adapter.  5%-90% RH (no condensation)  0°C to 45°C (32°F to 113°F)  -10°C to 70°C (14°F to 158°F)  3.3 ft [1 m]  White  0.6 in [14 mm]  39.4 in [1000 mm]  2.8 oz [80 g]  0.9 in [22 mm]

Product appearance and specifications are subject to change without notice.