

USB 3.0 Front Panel 4 Port Hub - 3.5in or 5.25in Bay

Product ID: 35BAYUSB3S4



The 35BAYUSB3S4 3.5-inch Front Bay to 4-Port USB 3.0 Panel Hub is TAA compliant and turns any available 3.5-inch computer case front bay into a 4-Port USB 3.0 hub.

Using only a single USB connection, this front panel hub adds four easily accessible USB ports to the front of your computer case through a 3.5-inch bay, or through a 5.25-inch bay using the optional Front Bay Bracket Adapter (BRACKETFDBK) accessory. Each of the added ports is compliant with the USB 3.0 standard which supports up to 5 Gbps of bandwidth (10x faster than the USB 2.0 standard) and up to 900mA of power.


Accessorize with the PEXUSB3S11 PCI Express card to provide an internal USB 3.0 port, so as to keep the external ports free for external devices. Backed by a StarTech.com 2-year warranty and free lifetime technical support.





Certifications, Reports and Compatibility





Applications

- Expand your system's USB 3.0 capabilities with additional ports for connecting high speed external storage devices
- Add easier to access USB ports to the front of a computer system instead of the rear
- Make use of an internal USB port and unused 3.5" front bay to increase the system's expandability

Features

- TAA Compliant
- Four front accessible USB type-A ports
- Fits into any 3.5" computer case front bay
- SuperSpeed USB 3.0 compliant, supporting data transfer rates up to 5 Gbps
- Backward compatible with USB 2.0 and USB 1.0/1.1 specifications and devices
- Provides up to 900mA of power per port
- USB Link LED indicator for each port



Data Sheet

Hardware Chipset ID Fast-Charge Port(s) Interface VISB 3.0 Ports USB-C Device Port(s) No USB-C Host Connection Performance Type and Rate USB 3.0 - 5 Gbit/s Connector(s) External Ports Internal Ports 1 - SATA Power (15 pin) Plug 1 - USB Type-B (9 pin) USB 3.0 Female 1 - USB Type-B (9 pin) USB 3.0 Female 2 OS Compatibility OS Independent; No additional drivers or semantic sema	
Fast-Charge Port(s) Interface USB 3.0 Ports 4 USB-C Device Port(s) No USB-C Host Connection No Performance Type and Rate USB 3.0 - 5 Gbit/s Connector(s) External Ports 4 - USB Type-A (9 pin) USB 3.0 Female Internal Ports 1 - SATA Power (15 pin) Plug 1 - USB Type-B (9 pin) USB 3.0 Female	
Interface USB 3.0 Ports 4 USB-C Device Port(s) No USB-C Host Connection No Performance Type and Rate USB 3.0 - 5 Gbit/s Connector(s) External Ports 4 - USB Type-A (9 pin) USB 3.0 Female Internal Ports 1 - SATA Power (15 pin) Plug 1 - USB Type-B (9 pin) USB 3.0 Female	
Ports 4 USB-C Device Port(s) No USB-C Host Connection No Performance Type and Rate USB 3.0 - 5 Gbit/s Connector(s) External Ports 4 - USB Type-A (9 pin) USB 3.0 Female Internal Ports 1 - SATA Power (15 pin) Plug 1 - USB Type-B (9 pin) USB 3.0 Female	
USB-C Device Port(s) USB-C Host Connection No Performance Type and Rate USB 3.0 - 5 Gbit/s Connector(s) External Ports 4 - USB Type-A (9 pin) USB 3.0 Female Internal Ports 1 - SATA Power (15 pin) Plug 1 - USB Type-B (9 pin) USB 3.0 Female	
Performance Type and Rate USB 3.0 - 5 Gbit/s Connector(s) External Ports Internal Ports 1 - SATA Power (15 pin) USB 3.0 Female 1 - USB Type-B (9 pin) USB 3.0 Female	
Performance Type and Rate USB 3.0 - 5 Gbit/s Connector(s) External Ports 4 - USB Type-A (9 pin) USB 3.0 Female Internal Ports 1 - SATA Power (15 pin) Plug 1 - USB Type-B (9 pin) USB 3.0 Female	
Connector(s) External Ports 4 - USB Type-A (9 pin) USB 3.0 Female Internal Ports 1 - SATA Power (15 pin) Plug 1 - USB Type-B (9 pin) USB 3.0 Female	
Internal Ports 1 - SATA Power (15 pin) Plug 1 - USB Type-B (9 pin) USB 3.0 Female	
1 - USB Type-B (9 pin) USB 3.0 Female	
Software OS Compatibility OS Independent; No additional drivers or s	
	oftware required
Special Notes / System and Cable Requirements Available 3.5 inch front bay Requirements	
Available USB 3.0 type A port	
Indicators LED Indicators 4 - USB Device Link (Green)	
Power Power Source USB-Powered	
Environmental Humidity 20% ~ 80% RH	
Operating Temperature 5°C to 50°C (41°F to 122°F)	
Storage Temperature -25°C to 70°C (-13°F to 158°F)	
Physical Color Black Characteristics	
Enclosure Type Plastic	
Form Factor Drive Bay	
Form Factor Drive Bay Product Height 1 in [25 mm]	
Product Height 1 in [25 mm]	
Product Height 1 in [25 mm] Product Length 4.7 in [12 cm]	
Product Height 1 in [25 mm] Product Length 4.7 in [12 cm] Product Width 3.9 in [10 cm]	
Product Height 1 in [25 mm] Product Length 4.7 in [12 cm] Product Width 3.9 in [10 cm] Weight of Product 3.5 oz [98 g] Packaging Package Height 1.3 in [32 mm]	
Product Height 1 in [25 mm] Product Length 4.7 in [12 cm] Product Width 3.9 in [10 cm] Weight of Product 3.5 oz [98 g] Packaging Information Product Height 1.3 in [32 mm]	



Data Sheet

What's in the Box	Included in Package	1 - 3.5" Front Panel
		1 - USB 3.0 Cable
		1 - Mounting Screw Kit
		1 - Instruction Manual

Product appearance and specifications are subject to change without notice.