## Safety and security





CO2 and C.O.V meter

Ref: 23656



Time, temperature and humidity display

Smiley face indicates air quality

6.4x5.6 cm LCD screen

Designed for companies with a CSR approach

Contributes to the improvement of employees' well-being

Advantage: low price to democratize IAQ monitoring

Automatic calibration process: ABC Automatic Baseline Calibration, avoids a return to the factory for this calibration (to be done every year).

Material: ABS Dimensions: 8x2.5x8cm Weight: 100g

Colour: white

Power supply: USB cable supplied

Instructions in English, French and German.

As an indication, this meter is suitable for a room of 20m2.

For larger areas, it is advisable to install several meters.

Always place the meters in the centre of the room or in the centre of the people in the room so that the measurement is relevant.







Availa	Available references									
	Ref.	Cep Code	Barcode unit	Barcode box	Gencod cardboard	Barcode P				
	23656	2236560021	3661474236561	13661474236568	NC	NC				

## 23656 90271010

isti	stical data														
	PRODUCT			вох			CARDBOARD			PALLET					
	Ref.	Dimensions mm	Weight Unit. Kg	PCB	Dimensions mm	Gross Weight kg	Net Weight kg	PCB	Dimensions mm	Gross Weight kg	Net Weight kg	РСВ	Dimensions mm	Gross Weight kg	Net Weight kg
	23656	80x25x80	0,100	1	85x30x85	0,120		10	200x250x100			Never packed on pallets			



When using batteries: VOC and CO2 measurements are not performed automatically to save batteries. Perform the measurements manually as described. The new VOC and CO2 measurements are displayed at the end of the 5-minute countdown. Then the Quaelis meter is again in standby mode (no VOC and CO2 measurements).