

Technical Data Sheet

T-Rex Extreme Hold Mounting Tape

285665 – 25mm x 1.5m



Properties

- Works on most surfaces including metal, glass, wood, concrete, brick, tile, and ceramic for an easy alternative to nails, screws, staples and glue
- All weather UV resistance
- Ensure surfaces are clean, dry and free of moisture before applying.
- Apply firm pressure to double sided tape to enable the strong adhesive bond with surfaces.
- T-Rex Mounting Tape will build adhesion over time, achieving full strength after a 24 hour period.

Technical Data

Tape Thickness:	0.42 inches
Temperature Range:	-40°F to 200°F (93°C) (Only apply in temperatures above 50°F)
Max Holding Weight:	Holds up to 50 lbs Use 1.2" tape to hold 1 lb of weight (Based on objects no thicker than ¾")

Storage and Usage Conditions

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

Physical and technical data displayed in this document are based on international accepted test methods but are no guarantee for product characteristics or product performance. Individual rolls may vary slightly from these averages.

The user should determine whether a product is fit for a particular purpose and is suitable for the user's method of application before use.