



APC Home/Office SurgeArrest 1 Outlet 230V, 2 Port USB Charger, UK

PM1WU2-UK

Call for More Information 0800 2799254

- Includes: User manual

Output	
Number of Outlets	1.0
Receptacle Style	BS 1363 United Kingdom

Input	
Nominal Input Voltage	230V
Input frequency	50 Hz +/- 5 Hz
Input Connections	BS1363A British
Maximum Input Current	13.0A

Surge Protection and Filtering	
Surge energy rating	918Joules
ts_nm_surge_response	1ns
Peak Current Common Mode	24kAmps
Peak Current Normal Mode	12kAmps

Physical	
Maximum Height	100MM, 10.0CM
Maximum Width	63MM, 6.3CM
Maximum Depth	4826MM, 482.6CM
Net Weight	0.16KG
Shipping weight	0.21KG
Shipping Height	88MM, 8.8CM

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.

Technical Specifications

Physical	
Shipping Width	70MM, 7.0CM
Shipping Depth	106MM, 10.6CM
Color	White
Master Carton Dimensions (Length x Width x Height)	305 x 286 x 134MM
Master Carton Units	13.0
Master Carton Weight	2.83
Units per Pallet	1008.0
SCC Codes	10731304334795

Environmental	
Operating Temperature	0 - 40 °C
Operating Relative Humidity	0 - 95 %
Operating Elevation	0 - 3048meters
Storage Temperature	-5 - 40 °C
Storage Relative Humidity	0 - 95 (Non-condensing) %
Storage Elevation	0 - 4572meters

Conformance	
Approvals	CE
Equipment protection policy	Lifetime : 50000 euros
Standard warranty	Limited Lifetime (European Union countries only)

Sustainable Offer Status	
RoHS	Compliant

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.