

Technical Specifications

APC Smart-UPS On-Line, 3kVA, Rackmount 2U, 230V, 8x C13+2x C19 IEC outlets, Network Card, Extended runtime, W/ rail kit | SRT3000RMXLI-NC | Downloaded on 11/02/2022 (EST)

APC Smart-UPS On-Line, 3kVA, Rackmount 2U, 230V, 8x C13+2x C19 IEC outlets, Network Card, Extended runtime, W/ rail kit

SRT3000RMXLI-NC

Call for More Information 0800 2799254



- High density, double-conversion on-line power protection with scalable runtime.
- Includes: CD with software, Documentation CD, Installation guide, Network management card, Rack mounting brackets, Rack mounting support rails, USB cable, Warranty card

Output	
Output power capacity	2.7kWatts / 3.0kVA
Max Configurable Power (Watts)	2.7kWatts / 3.0kVA
Nominal Output Voltage	230V
Output Voltage Note	Configurable for 220 : 230 or 240 nominal output voltage
Output Voltage Distortion	Less than 2 %
Output Frequency (sync to mains)	50/60 Hz +/- 3 Hz Sync to mains
Other Output Voltages	220 V, 240 V
Load Crest Factor	3 : 1
Topology	Double conversion online
Waveform type	Sine wave
Output Connections	(2) IEC Jumpers (8) IEC 60320 C13 (2) IEC 60320 C19
Bypass	Internal bypass (automatic and manual)


Input	
Nominal Input Voltage	230V
Input frequency	40 - 70 Hz Auto-sensing
Input Connections	BS1363A British, IEC 60320 C20, Schuko CEE 7 / EU1-16P
Cord Length	2.4meters
Input voltage range for main operations	100 - 275 Adjustable (half load)V
Number of Power Cords	1

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.

Technical Specifications

APC Smart-UPS On-Line, 3kVA, Rackmount 2U, 230V, 8x C13+2x C19 IEC outlets, Network Card, Extended runtime, W/ rail kit | SRT3000RMXLI-NC | Downloaded on 11/02/2022 (EST)

Input	
Other Input Voltages	220 V, 240 V

Batteries & Runtime	
Battery type	Lead-acid battery
Included Battery Modules	1
Typical recharge time	3hour(s)
Nominal Battery Voltage	96 V
Replacement Battery	APCRBC152 
Expected Battery Life (years)	3 - 5
RBC Quantity	1
Battery Charge Power (Watts)	168 Watts
Extendable Run Time	1
Runtime	View Runtime Graph (Available in Technical Tab on site)
Efficiency	View Efficiency Graph (Available in Technical Tab on site)

Communications & Management	
Interface Port(s)	RJ-45 10/100 Base-T, RJ-45 Serial, Smart-Slot, USB
Control panel	Multifunction LCD status and control console
Audible Alarm	Audible and visible alarms prioritized by severity
Emergency Power Off (EPO)	Yes

Surge Protection and Filtering	
Surge energy rating	340Joules

Physical	
Maximum Height	85MM, 8.5CM
Maximum Width	432MM, 43.2CM
Maximum Depth	635MM, 63.5CM
Rack Height	2U
Net Weight	31.3KG
Shipping weight	39.92KG

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.

Technical Specifications

APC Smart-UPS On-Line, 3kVA, Rackmount 2U, 230V, 8x C13+2x C19 IEC outlets, Network Card, Extended runtime, W/ rail kit | SRT3000RMXLI-NC | Downloaded on 11/02/2022 (EST)

Physical	
Shipping Height	246MM, 24.6CM
Shipping Width	871MM, 87.1CM
Shipping Depth	599MM, 59.9CM
Color	Black
Units per Pallet	6.0

Environmental	
Operating Temperature	0 - 40 °C
Operating Relative Humidity	0 - 95 (Non-condensing) %
Operating Elevation	0 - 3048meters
Storage Temperature	-15 - 45 °C
Storage Relative Humidity	0 - 95 (Non-condensing) %
Storage Elevation	0 - 15240meters
Audible noise at 1 meter from surface of unit	55.0dBA
Online thermal dissipation	703.0BTU/hr
Protection Class	IP20

Conformance	
Approvals	CE, CE Mark, EAC, RCM, VDE
Standard warranty	3 years repair or replace (excluding battery) and 2 years for battery

Sustainable Offer Status	
RoHS	Compliant

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.