

Rack PDU, Switched, 1U, 12A/208V, 10A/230V, (8)C13

AP7920B

Call for More Information 0800 2799254



- This APC Switched Rack PDU power distribution unit has a wide range of standardized PDU features that increase network efficiency, manageability and functionality. The output and input connections are (8)C13. Network management capabilities allow you to configure and manage rack PDUs from remote locations. It has a local current monitoring display that gives a visible warning in case of an overload. The remote individual outlet control provides real-time monitoring of connected loads. It has a multi-tier user access that enables you to restrict unauthorized use of outlets. This rack has a single input power source making it easy to install.
- Includes: Installation guide, Rack mounting brackets, User manual

| Output | |
|--|-------------------------|
| Nominal Output Voltage | 208V, 230V |
| Maximum Total Current Draw | 10 |
| Output Connections | (8) IEC 60320 C13 |
| Different voltages and corresponding amperages | 10A @ 230V, 12A @ 208VA |

| Input | |
|--|------------------|
| Nominal Input Voltage | 200V, 208V, 230V |
| Input frequency | 50/60 Hz |
| Input Connections | IEC 60320 C14 |
| Cord Length | 2meters |
| Acceptable Input Voltage | 200 - 240VAC |
| Number of Power Cords | 1 |
| Load Capacity | 2300VA |
| Maximum Input Current | 15A |
| Regulatory Derated Input Current (North America) | 12A |

| Physical | |
|----------------|---------------|
| Maximum Height | 44MM, 4.4CM |
| Maximum Width | 445MM, 44.5CM |

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.

Technical Specifications

Rack PDU, Switched, 1U, 12A/208V, 10A/230V, (8)C13 | AP7920B | Downloaded on 11/01/2022 (EST)

| Physical | |
|-----------------|---------------|
| Maximum Depth | 108MM, 10.8CM |
| Rack Height | 1U |
| Net Weight | 2.27KG |
| Shipping weight | 3.45KG |
| Shipping Height | 70MM, 7.0CM |
| Shipping Width | 343MM, 34.3CM |
| Shipping Depth | 470MM, 47.0CM |
| Color | Black |

| Environmental | |
|-----------------------------|-----------------|
| Operating Temperature | 0 - 45 °C |
| Operating Relative Humidity | 0 - 95 % |
| Operating Elevation | 0 - 3048meters |
| Storage Temperature | -25 - 65 °C |
| Storage Relative Humidity | 0 - 95 % |
| Storage Elevation | 0 - 15240meters |

| Conformance | |
|-------------------|---|
| Approvals | CE, CSA, cUL listed, EN 55022 class A, EN 55024, EN 61000-3-2, EN 61000-3-3, GOST, IRAM, UL 60950, UL listed, VDE |
| Standard warranty | 2 years repair or replace |

| Sustainable Offer Status | |
|--------------------------|-----------|
| RoHS | Compliant |

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.