HP Color LaserJet Pro 4202dn Printer



Colourful productivity. Seamless set up.

Get a blazing fast colour printer and easy set up with LaserJet Pro.





This printer is intended to work only with cartridges that have a new or reused HP chip, and it uses dynamic security measures to block cartridges using a non-HP chip. Periodic firmware updates will maintain the effectiveness of these measures and block cartridges that previously worked. A reused HP chip enables the use of reused, remanufactured, and refilled cartridges. More at: http://www.hp.com/learn/ds

Highlights

- Fast print speed (33 ppm A4)
- HP Wolf Pro security
- Automatic two-sided printing standard
- High monthly duty cycle (50,000 pages)

Maximum productivity in full colour

- Support your business workteam with this compact, high-performing, colour printer, ideal for up to 10 users.
- Step up your workflow with blazing fast speed to meet high-demand environments.
- Look professional on every page with high-quality printing, true-to-life colours and sharp details.¹

Simple set up.

- Quickly set up your printers so you can focus more on your business.
- Streamlined set up makes it easy for your team to set up and get back to what matters.

Advance your security with HP Wolf Pro


- Get printer fleet security out of the box. Preconfigured settings mean it's ready when you are.
 - Add a layer of security. PIN/pull option authenticates your print jobs only when you're present.
- Strengthen and simplify compliance. This upgrade/solution applies your business policies across the fleet. $^{\rm 4}$

Sustainable printing^{5,6,7}

- Redesigned Original HP TerraJet Cartridge for reduced plastic use and energy consumption when printing. $^{7.8}$
- Trim your paper use. Default duplex setting prints on both sides of each page.
- Reduce your footprint. HP Auto-On/Auto-Off technology optimises printer energy usage and costs.⁹
- We take recycling full circle. Our toner cartridges reuse plastic and can be mailed back after use. 6

Product walkaround

- 1. Automatic 2-sided printing
- 2. Print speeds up to 33 ppm A4, 300-sheet standard paper capacity
- 3. Twist and click speed dial with 4-line LCD
- 4. High-Speed USB ports, built-in fast Ethernet
- 5. HP Smart app for productivity in your hand
- 6. Designed for workteams of up to 10 users
- 7. More true-to-life colors with HP TerraJet Toner
- 8. Pre-configured security settings



Accessories, Supplies and Support

Supplies	W2200A HP 220A Black Original LaserJet Toner Cartridge (~ 2,000 pages)
	W2200X HP 220X Black Original Laser Jet Toner Cartridge (~7,500 pages)
	W2201A HP 220A Cyan Original Laser.Jet Toner Cartridge (~1,800 pages)
	W2201X HP 220X Cyan Original LaserJet Toner Cartridge (~5,500 pages)
	W2202A HP 220A Yellow Original Laser Jet Toner Cartridge (~1,800 pages)
	W2202X HP 220X Yellow Original Laser Jet Toner Cartridge (~5,500 pages)
	W2203A HP 220A Magenta Original Laser Jet Toner Cartridge (~1,800 pages)
	W2203X HP 220X Magenta Original Laser Jet Toner Cartridge (~5,500 pages)
Service and Support	U51Y5E HP 3 year Next Business Day Onsite Service for Color LaserJet Pro 420x U51YGPE - HP 1 year Post Warranty Next Business Day Onsite Service for Color LaserJet Pro 420x

Technical specifications

Model	HP Color Laser let Pro 4202dn Printer
Product number	I down datafet to folder that
Functions	Pint Pint
Control panel	4-line LCD with rotational dial with push button for menu selection
Print	* wije LLU with Froutionial data with pash batton for mena selection.
Print technology	Laser
Print speed	Black (M4, normal): Up to 33 ppm Colour (A4, normal): Up to 33 ppm; Black (A4, duplex): Up to 29 ipm Colour (A4, duplex): Up to 29 ipm Colour (A4, normal): Up to 33 ppm Colour
First page out	Black (M4, ready): As fast as 9.5 sec Colour (A4, ready): As fast as 10.5 sec; Black (M4, sleep): As fast as 10.2 sec; Colour (A4, sleep): As fast as 10.5 sec
Print resolution	Black best/: Up to 600 x 600 dpi; Up to 38,400 x 600 enhanced dpi Colour (best): Up to 600 x 600 dpi; Technology. HP ImageREL 2400
Monthly duty cycle	Up to 50.000 pages A4; Recommended monthly page volume: 750 to 4,000
Printer smart software features	Automatic duplex, collation, watermarks, printable forms, quiet mode, HP premium print quality mode, accepts a variety of paper sizes and types
Standard print languages	HP PCL 6, HP PCL 5e, HP PCL 5c, HP Postscript level 3 emulation, PDF, URF, PWG Raster, Native Office
Fonts and typefaces	111 scalable TrueType fonts
Print area	Print margins Top: 4.23 mm, Bottom: 4.23 mm, Left: 4.23 mm, Right: 4.23 mm; Maximum print area : 212 x 352 mm
Duplex printing	Automatic
Fax	
Fax	No
Processor speed	1200 MHz
Connectivity	
Standard	1 Hi-Speed USB 2.0 (device); 1 Hi-Speed USB 2.0 (host); Authentication via 802.1x; Auto-crossover Ethernet; 1 Gigabit Ethernet 10/100TX network
Mobile printing capability	HP Smart App; Apple AirPrint ^{my} : Mobile Apps; Mopria TM Certified
Supported network protocols	TCP/IP: IP-V4. IP-V6; Print: TCP-IP port 9100 Direct Mode, LPD (raw queue support only), Web Services Printing, Apple AirPrint [™] , Mopria, IPP Print; Discovery; SLP, Bonjour, Web Services Discovery; IP Config: IP-V4 (DHCP, AutolP, Manual), IP-V6 (Stateliess Link-Local and via Router; Stateful via DHCP-V6), SSL Security and Certificate management; Nanagement; SNMPV1, SNMPV2, SNMPV2, SNMPV3, HTTP/HTTPS, Syslog
Network capabilities	Ves. via bulk-in 10/1008ses-Tx-Ehrenet, Giglabit, Auto-crossover Ethernet, Auto-Intentication via 802.1 x
Memory	Standard 117 OF 1000058 FX DIR MILL MARINUM STALL MARINUM AND ALL AND
	יארעם פויז גוב (אוגער בארג) אוגער בארג) אוגער בארג אוגער בארג אוגער בארג) אוגער בארג אוגער בארגער באר
Media handling	
Number of paper trays	Standard 2 Maximum 3
Media types	Paper (bond, brochure, colored, glossy, letterhead, photo, plain, preprinted, prepunched, recycled, rough), postcards, labels, envelopes
Media size	Custom (metric): Simplex: Tray 1: 76.2 x 127 to 216 x 356 mm; Tray 2: 98 x 148 mm to 216 x 356 mm; optional Tray 3: 100 x 148 to 216 x 356 mm; Duplex (all trays): 148 x 148 mm to 216 x 356 mm
Media handling	Standard input: 50-sheet multipurpose tray, 250-sheet input tray Standard output: 150-sheet output bin Optional input: Optional S50-sheet tray
Media weight	60 to 163 g/m ² (up to 176 g/m ² postcards, up to 200 g/m ² HP Color laser glossy photo papers)
Input capacity	Tray 1: Sheets: 50; envelopes: 5 Tray 2: Sheets: 250; envelopes: 10 Tray 3: Sheets: 550 Maximum: Up to 850 sheets (with Optional 550-sheet tray)
Output capacity	Standard: Up to 150 sheets Envelopes: Up to 20 envelopes Maximum: Up to 150 sheets
Compatible operating systems	Windows 11; Windows 10; Windows Client 05; Android; i05; Mobile 05; mac05 10.15 Catalina; mac05 11 Big Sur; mac05 12 Monterey; mac05 13 Ventura; mac05 15 Sequoia; Linux; Citrix; Chrome 0S
Compatible operating systems Compatible network operating systems	Windows 11; Windows 10; Windows Client OS; Android; iOS; Mobile OS; macOS 10.15 Catalina; macOS 11 Big Sur; macOS 12 Monterey; macOS 13 Ventura; macOS 15 Sequoia; Linux; Citrix; Chrome OS Windows Server; macOS 15 Sequoia; Linux; Citrix; UNIX; Novel; SAP
Compatible network operating systems	
Compatible network operating systems	Windows Server; macOS 15 Sequoia; Linux; Citrix; UNIX; Noveli; SAP Windows: 2 GB available hard disk space, Internet connection or USB port, Internet browser. For additional OS hardware requirements see microsoft.com; Mac 2 GB available hard drive space, Internet connection or USB port, Internet browser. For additional OS hardware requirements see apple.com;
Compatible network operating systems Minimum system requirements Software included	Windows Server; macOS 15 Sequoia; Linux; Citrix; UNIX; Novell; SAP Windows: 2 GB available hard disk space, Internet connection or USB port, Internet browser. For additional OS hardware requirements see microsoft.com;
Compatible network operating systems Minimum system requirements Software included Printer management	Windows Server; macOS 15 Sequoia; Linux; Citrix; UNIX; Noveli; SAP Windows: 2 GB available hard disk space, Internet connection or USB port, Internet browser. For additional OS hardware requirements see microsoft.com; Mac 2 GB available hard drive space, Internet connection or USB port, Internet browser. For additional OS hardware requirements see apple.com; Mac 2 GB available hard drive space, Internet connection or USB port, Internet browser. For additional OS hardware requirements see apple.com; No software solutions are included in the Box only on http://hp.com
Compatible network operating systems Minimum system requirements Software included Printer management Dimensions and weight	Windows Server; macOS 15 Sequoia; Linux; Citrix; UNIX; Noveli; SAP Windows: 2 GB available hard disk space, Internet connection or USB port, Internet browser. For additional OS hardware requirements see microsoft.com; Mac: 2 GB available hard drive space, Internet connection or USB port, Internet browser. For additional OS hardware requirements see apple.com; Mac: 2 GB available hard drive space, Internet connection or USB port, Internet browser. For additional OS hardware requirements see apple.com; No software solutions are included in the Box only on http://hp.com or http://123.hp.com HP Web JetAdmin Software; Security Manager; HP SNMP Proxy Agent (Part of HP WebJetAdmin); HP WS Pro Proxy Agent (Part of HP WebJetAdmin); Smart Printer Administrator Resource Kit for HP Smart Universal Print Driver (Driver Configuration; Utility - Driver; Deployment Utility - Managed Printing Administrator)
Compatible network operating systems Minimum system requirements Software included Printer management Dimensions and weight Printer dimensions (W x D x H)	Windows Server; mac0S 15 Sequoia; Linux; Citrix; UNIX; Novell; SAP Windows 2 GB available hard disk space, Internet connection or USB port, Internet browser. For additional OS hardware requirements see microsoft.com; Mac 2 GB available hard disk space, Internet connection or USB port, Internet browser. For additional OS hardware requirements see apple.com; No software solutions are included in the Box only on http://hp.com or http://123.hp.com HP Web_iteRdmin Software; Security Manager, HP SNNP Proxy Agent (Part of HP WebjetAdmin); HP WS Pro Proxy Agent (Part of HP WebjetAdmin); Smart Printer Administrator Resource Kit for HP Smart Universal Print Driver (Driver Coriver Coriver); Minimum 421 x 427 x 288 mm; Maximum: 421 x 636 x 420mm
Compatible network operating systems Minimum system requirements Software included Printer management Dimensions and weight Printer dimensions (W x D x H) Printer weight	Windows Server; mac0S 15 Sequoia; Linux; Citrix; UNIX; Noveli; SAP Windows 2 GB available hard disk spare, Internet connection or USB port, Internet browser, For additional 05 hardware requirements see apple.com; Mac 2 GB available hard drive space, Internet connection or USB port, Internet browser, For additional 05 hardware requirements see apple.com; No software solutions are included in the Box only on http://hp.com or http://123.hp.com HP Web JetAdmin Software; Security Manager; HP SNMP Proxy Agent (Part of HP WebJetAdmin); HP WS Pro Proxy Agent (Part of HP WebJetAdmin); Smart Printer Administrator Resource Kit for HP Smart Universal Print Driver (Driver Coniguration; Utility - Driver; Deployment Utility - Managed Printing Administrator) Minimum 421 x 427 x 288 mm; Maximum: 421 x 636 x 420mm ~16.33 kg
Competible network operating systems Minimum system requirements Software included Printer management Dimensions and weight Printer dimensions (W x D x H) Printer weight Operating environment	Windows Server; macOS 15 Sequoia; Linux; Citrix; UNIX; Noveli; SAP Windows 2 GB available hard disk space, Internet connection or USB port, Internet browser, For additional OS hardware requirements see microsoft.com; Mac 2 GB available hard disk space, Internet connection or USB port, Internet browser, For additional OS hardware requirements see apple.com; No software solutions are included in the Box only on http://hp.com or http://123.hp.com HP Web JetAdmin Software; Security Manager; HP SNMP Proxy Agent (Part of HP WebJetAdmin); HP WS Pro Proxy Agent (Part of HP WebJetAdmin); Smart Printer Administrator Resource Kit for HP Smart Universal Print Driver (Driver Corie) Windows 21 x 427 x 288 mm; Maximum: 421 x 636 x 420mm ~16.33 kg Temperature: 10 to 32.5°C Humidity: 30 to 70% RH (non-condensing)
Competible network operating systems Minimum system requirements Software included Printer management Dimensions and weight Printer dimensions (W x D x H) Printer weight Operating erwironment Storage conditions	Windows Server; macOS 15 Sequoia; Linux; Citrix; UNIX; Noveli; SAP Windows 2 GB available hard disk space, Internet connection or USB port, Internet browser, For additional OS hardware requirements see apple.com; Mac 2 GB available hard disk space, Internet connection or USB port, Internet browser, For additional OS hardware requirements see apple.com; No software solutions are included in the Box only on http://hp.com or http://123.hp.com HP Web JetAdmin Software, Security Manager, HP SNMP Proxy Agent (Part of HP WebJetAdmin); PM VS Pro Proxy Agent (Part of HP WebJetAdmin); Smart Printer Administrator Resource Kit for HP Smart Universal Print Driver (Driver Configuration; Utility - Driver; Deployment Utility - Managed Printing Administrator) Wininum 421 x 427 x 288 mm; Maximum: 421 x 636 x 420mm -16.33 kg Temperature: 10 to 32.5°C Humidity: 30 to 70% RH (non-condensing) Temperature: -20 to 40°C
Competible network operating systems Minimum system requirements Software included Printer management Dimensions and weight Printer dimensions (W x D x H) Printer weight Operating environment	Windows Server; macOS 15 Sequoia; Linux; Citrix; UNIX; Noveli; SAP Windows 2: GB available hard disk space, Internet connection or USB port, Internet browser. For additional OS hardware requirements see apple.com; Mac 2: GB available hard disk space, Internet connection or USB port, Internet browser. For additional OS hardware requirements see apple.com; No software solutions are included in the Box only on http://hp.com or http://123.hp.com HP Web JetAdmin Software; Security Manager, HP SNMP Proxy Agent (Part of HP Web/JetAdmini); Smart Printer Administrator Resource Kit for HP Smart Universal Print Driver (Driver Configuration; Utility - Driver; Deployment Utility - Managed Printing Administrator) Minimum 421 x 427 x 288 mm; Maximum: 421 x 636 x 420mm -16.33 kg Temperature: 10 to 32.5°C Humidity: 30 to 70% RH (non-condensing) Temperature: -20 to 40°C Acoustic power emissions: 6.2 8(A) Acoustic pressure emissions: 51 dB(A)
Competible network operating systems Minimum system requirements Software included Printer management Dimensions and weight Printer dimensions (W x D x H) Printer weight Operating erwironment Storage conditions	Windows Server; macOS 15 Sequoia; Linux; Citrix; UNIX; Noveli; SAP Windows 2 GB available hard disk space, Internet connection or USB port, Internet browser, For additional OS hardware requirements see apple.com; Mac 2 GB available hard disk space, Internet connection or USB port, Internet browser, For additional OS hardware requirements see apple.com; No software solutions are included in the Box only on http://hp.com or http://123.hp.com HP Web JetAdmin Software, Security Manager, HP SNMP Proxy Agent (Part of HP WebJetAdmin); PM VS Pro Proxy Agent (Part of HP WebJetAdmin); Smart Printer Administrator Resource Kit for HP Smart Universal Print Driver (Driver Configuration; Utility - Driver; Deployment Utility - Managed Printing Administrator) Wininum 421 x 427 x 288 mm; Maximum: 421 x 636 x 420mm -16.33 kg Temperature: 10 to 32.5°C Humidity: 30 to 70% RH (non-condensing) Temperature: -20 to 40°C
Compatible network operating systems Minimum system requirements Software included Printer management Dimensions and weight Printer dimensions (W × D × H) Printer weight Operating environment Storage conditions Accustics ⁶ Power ⁵	Windows Server; macOS 15 Sequoia; Linux; Citrix; UNIX; Noveli; SAP Windows 2 GB available hard disk spare, Internet connection or USB port, Internet browser. For additional OS hardware requirements see apple.com; Mac 2 GB available hard disk spare, Internet connection or USB port, Internet browser. For additional OS hardware requirements see apple.com; No software solutions are included in the Box only on http://hp.com or http://123.hp.com HP Web JetAdmin Software; Security Manager; HP SNMP Proxy Agent (Part of HP WebJetAdmin); HP WS Pro Proxy Agent (Part of HP WebJetAdmin); Smart Printer Administrator Resource Kit for HP Smart Universal Print Driver (Driver Configuration; Utility - Driver; Deployment Utility - Managed Printing Administrator) Minimum 421 x 427 x 288 mm; Maximum: 421 x 636 x 420mm ~16.33 kg Temperature: 10 to 32.5°C Humidity: 30 to 70% RH (non-condensing) Temperature: -20 to 40°C Acoustic power emissions: 6.2 G(A) Acoustic pressure emissions: 51 dB(A) Requirements: 220-voit input voltage: 220 to 240 VAC (+'- 19%; 50/60Hz (+'- 3 Hz); Consumption: 580 watts (active printing), 17 watts (selep), 07 watts (MP auto-off/auto-on), 0.07 watts (auto-off/manual-on), 0.07 watts (off); Typical Electricity Consumption (TEC). 037 okt/Wweek (Blue Angel);
Compatible network operating systems Minimum system requirements Software included Printer management Dimensions and weight Printer dimensions (W x D x H) Printer veight Operating environment Storage conditions Acoustics ⁶	Windows Server; macOS 15 Sequoia; Linux; Citrix; UNIX; Noveli; SAP Windows 2 GB available hard dike space, Internet connection or USB port, Internet browser, For additional OS hardware requirements see apple.com; Mac 2 GB available hard dike space, Internet connection or USB port, Internet browser, For additional OS hardware requirements see apple.com; No software solutions are included in the Box only on http://hp.com or http://123.hp.com HP Web JetAdmin Software; Security Manager, HP SINDP Proxy Agent (Part of HP WebJetAdmin); HP WS Pro Proxy Agent (Part of HP WebJetAdmin); Smart Printer Administrator Resource Kit for HP Smart Universal Print Driver (Driver Configuration; Utility - Driver; Deployment Utility - Managed Printing Administrator) Minimum 421 x 427 x 288 mm; Maximum; 421 x 636 x 420mm -16.33 kg Temperature: 10 to 32.5°C Humidity: 30 to 70% RH (non-condensing) Temperature: -20 to 40°C Acoustic power emissions: 5.1 dB(A) Requirements: 220-voit input voltage: 220 to 240 VAC (+/- 19k); S0/60Hz (+/- 3 Hz); Consumption: S80 wattis (actual voltage); S0/00Hz (+/- 3 Hz); Consumption: S80 wattis (actual voltage); S0/00Hz (+/- 3 Hz); Consumption: S80 wattis (actual voltage); S0/00Hz (+/- 3 Hz); Consumption: T(EC), 0.370 kWh/Week (Bue Angel); Power supply type: Internet (Intuit-In Power Supply) HP Auto-On/Auto-Off Technology, Instant-on Technology
Compatible network operating systems Minimum system requirements Software included Printer management Dimensions and weight Printer dimensions (W × D × H) Printer weight Operating environment Storage conditions Acoustics ⁶ Power ⁵ Energy savings feature technology	Windows Server; macOS 15 Sequoia; Linux; Citrix; UNIX; Noveli; SAP Windows 2 GB available hard disk space, Internet connection or USB port, Internet browser. For additional OS hardware requirements see apple.com; Mac 2 GB available hard disk space, Internet connection or USB port, Internet browser. For additional OS hardware requirements see apple.com; Mac 2 GB available hard dive space, Internet connection or USB port, Internet browser. For additional OS hardware requirements see apple.com; Mac 2 GB available hard dive space, Internet connection or USB port, Internet browser. For additional OS hardware requirements see apple.com; Mac 2 GB available hard dive space, Internet connection or USB port, Internet browser. For additional OS hardware requirements see apple.com; No software solutions are included in the Box only on http://hp.com or http://12.3 hp.com HP Web JetAdmin Software; Security Manager; HP SNMP Proxy Agent (Part of HP WebJetAdmin); HP WS Pro Proxy Agent (Part of HP WebJetAdmin); Smart Printer Administrator Resource Kit for HP Smart Universal Print Driver (Driver Configuration; Utility - Driver; Deployment Utility - Managed Printing Administrator) V Infinum 421 x 427 x 288 mm; Maximum: 421 x 636 x 420mm ~-16.33 kg Temperature: 10 to 32.5°C Humidity: 30 to 70% RH (non-condensing) Temperature: 20 to 40°C Acoustic power emissions: 6.2 B(A) Acoustic pressure emissions: 5.1 B(A) Requirements: 220-will toput voltage: 220 to 240 WAC (+'- 10%); 50/60Hz (+'- 3 Hz); Consumption: 580 watts (active printing), 17 watts (ready), 0.7 watts (sleep, 0.7 watts (HP auto-off/auto-on), 0.07 watts (auto-off/manual-on), 0.07 watts (off); Typical Electricity consumption (TEC: 0.37 ok MWr/ (Keremark); Department of Industrial Standards of Cambodia
Compatible network operating systems Minimum system requirements Software included Printer management Dimensions and weight Printer dimensions (W x D x H) Printer weight Operating environment Storage conditions Acoustics ⁶ Power ⁵ Energy savings feature technology	Windows Server; mac05 15 Sequoia; Linux; Citrix; UNIX; Novell; SAP Windows 2 GB available hard disk space, Internet connection or USB port, Internet browser. For additional OS hardware requirements see apple.com; Mac 2 GB available hard disk space, Internet connection or USB port, Internet browser. For additional OS hardware requirements see apple.com; No software solutions are included in the Box only on http://hp.com or http://12.3hp.com HP Web JetAdmin Software, Security Manager, HP SINP Proxy Agent (Part of HP WebJetAdmin); HP WS Pro Proxy Agent (Part of HP WebJetAdmin); Smart Printer Administrator Resource Kit for HP Smart Universal Print Driver (Driver Configuration; Utility - Driver, Deployment Utility - Managed Printing Administrator) Minimum 421 x 427 x 288 mm; Maximum; 421 x 636 x 420mm ~16.33 kg Temperature: 20 to 40°C Acoustic power emissions: 6.2 B(A) Acoustic pressure emissions: 5.1 B(A) Requirements: 220-voit input voltage: 220 to 240 VAC (*/ 10%); 50/60/L2 (*/ - 3 Hz); Consumption: 580 waits factive printing), 17 waits (Ready, 0.7 waits (Stepa), 0.7 waits (BP auto-off/auto-on), 0.07 waits (auto-off/manual-on), 0.07 waits (off); Typical Electricity Consumption (FEC) 0.37 (Autiveek Stepa), 0.7 waits (Stepa), 0.7 waits (BP auto-off/auto-on), 0.07 waits (auto-off/manual-on), 0.07 waits (auti-off/manual-on), 0.07 waits (auti-off/kite, engli); PWeet supply type. Internet Indian * Tower Supply Pin Auto-OnAuto-Of
Compatible network operating systems Minimum system requirements Software included Printer management Dimensions and weight Printer dimensions (W × D × H) Printer weight Operating environment Storage conditions Acoustics ⁶ Power ⁵ Energy savings feature technology	Windows Server; mac0S 15 Sequoia; Linux; Citrix; UNIX; Novell; SAP Windows 2 GB available hard disk spare, Internet connection or USB port, Internet browser, For additional 05 hardware requirements see apple.com; Mac 2 GB available hard disk spare, Internet connection or USB port, Internet browser, For additional 05 hardware requirements see apple.com; No software solutions are included in the Box only on http://hp.com or http://12.3 hp.com HP Web JetAdmin Software; Security Manager; HP SNMP Proxy Agent (Part of HP WebJetAdmin); HP WS Pro Proxy Agent (Part of HP WebJetAdmin); Smart Printer Administrator Resource Kit for HP Smart Universal Print Driver (Driver Configuration; Utility - Driver; Deployment Utility - Managed Printing Administrator) Minimum 421 x 427 x 288 mm; Maximum: 421 x 636 x 420mm ~16.33 kg Temperature: 10 to 32:5°C Humidity: 30 to 70% RH (non-condensing) Temperature: -20 to 40°C Acoustic power emissions: 5.2 B(A) Acoustic pressure emissions; 5.1 dB(A) Requirements; 220-voit input voltage; 220 to 240 VAC (+' 10%; 50/60Hz (+' - 3 Hz); Consumption; 580 watts (active printing), 17 watts (selep), 0.7 watts (selep), 0.7 watts (seluto-off/auto-on), 0.07 watts (auto-off/manual-on), 0.07 watts (off); Typical Electricity Consumption (TEC). 037 okt/Week (Blue Angel); Power supply type; Internet (Cutil-tin) Power Supply HP Auto-On/Auto-Off Technology; Instant-on Technology ULLULU, USCARDING Certification - CCC (Clina); Bureau of Industrial Standards of Cambodia; Bureau of Standards, Metrology and Inspection Ministry of Economic Affairs - BSMI (Taiwan); Certificate of China C
Competible network operating systems Minimum system requirements Software included Printer management Dimensions and weight Printer dimensions (W × D × H) Printer weight Operating environment Storage conditions Acoustics ⁶ Power ⁵	Windows Server; mac05 15 Sequoia; Linux: Citrix; UNIX: Novell; SAP Windows 2 GB available hard disk spare, Internet connection or USB port, Internet browser. For additional 05 hardware requirements see apple.com; Mac 2 GB available hard disk spare, Internet connection or USB port, Internet browser. For additional 05 hardware requirements see apple.com; No software solutions are included in the Box only on http://Ip.com or http://12.3.pc.com HP Web JetAdmin Software; Security Manager; HP SNMP Proxy Agent (Part of HP WebJetAdmin); HP WS Pro Proxy Agent (Part of HP WebJetAdmin); Smart Printer Administrator Resource Kit for HP Smart Universal Print Driver (Driver Configuration; Utility - Driver; Deployment Utility - Managed Printing Administrator) Vininum 421 x 427 x 288 mm; Maximum: 421 x 636 x 420mm ~16.33 kg Temperature: 10 to 32.5°C Humidity: 30 to 70% RH (non-condensing) Temperature: 2-01 to 40°C Acoustic power emissions: 6.2 B(A) Acoustic pressure emissions: 5.1 B(A) Requirements: 220-voit input voltage: 220 to 240 VAC (+' 10%; 50/60Hz (+'- 3 Hz); Consumption: 580 watts (active printing), 17 watts (steady), 0.7 watts (step), 0.7 watts (lauto-off/manual-on), 0.07 watts (off); Typical Electricity Consumption (TEC). 0.37 okt/Wweek (Blue Angel); Power supply type: Internal (Dual-in) Power Supply HP Auto-On/Auto-Off Technology; Instant-on Technology UL/LUL_UCSALAD; KDK Mucatala); TUW and GS Mark (Germany); Department of Industrial Standards of Cambodia; Bureau of Standards, Metrology and Inspection Ministry of Economic Affairs - BSMI (Taiwan); Certificate of China Compulsory Product
Compatible network operating systems Minimum system requirements Software included Printer management Dimensions and weight Printer dimensions (W × D × H) Printer weight Operating environment Storage conditions Acoustics ⁶ Power ⁵ Energy savings feature technology Certifications ¹	Windows Server; mac05 15 Sequoia; Linux; Citrix; UNIX; Novell; SAP Windows 2 GB available hard disk space, Internet connection or USB port, Internet browser. For additional OS hardware requirements see apple.com; Mac 2 GB available hard disk space, Internet connection or USB port, Internet browser. For additional OS hardware requirements see apple.com; No software solutions are included in the Box only on http://hp.com or http://123.hp.com HP Web JetAdmin Software, Security Manager. HP SINP Proxy Agent (Part of HP WebJetAdmin); HP WS Pro Proxy Agent (Part of HP WebJetAdmin); Smart Printer Administrator Resource Kit for HP Smart Universal Print Driver (Driver Configuration; Utility - Driver, Deployment Utility - Managed Printing Administrator) Minimum 421 x 427 x 288 mm; Maximum: 421 x 636 x 420mm ~16.33 kg Temperature: 20 to 40°C Acoustic power emissions: 6.2 B(A) Acoustic pressure emissions: 5.1 dB(A) Requirements: 220-voit input voltage: 220 to 240 VAC (*/ 10%); 50/60/L2 (*/ - 3 H2); Consumption: 580 waits factive printing). 17 waits (ready), 0.7 waits (Step Age); Power supply type. Internat (RL): 0.7 (AuAuto-Off (Auto-Off/auto-on), 0.07 waits (auto-off/manual-on), 0.07 waits (off); Typical Electricity Consumption: F20 value. New Suppl PM Pub.LONAUL-Off Technology. Instant-on Technology. UL/LU, US/Canada); RCM (Australia); TUV and CS Mark (Germany); Department of Industrial Standards of Cambodia; Bureau of Standards, Metrology and Inspection Ministry of Economic Affairs - BSM (Taiwan); Certificate of China Compulsory Product Certification - CEC (Dinna); Bureau of Industrial Standards of Cambodia; Bureau of Stand
Compatible network operating systems Minimum system requirements Software included Printer management Dimensions and weight Printer dimensions (W × D × H) Printer dimensions (W × D × H) Printer weight Operating environment Storage conditions Acoustics ⁶ Power ⁵ Energy savings feature technology Certifications ¹ Country of origin	Windows Server; mac05 15 Sequois; Linux: Citrix; UNIX: Novell; SAP Windows 2 GB available hard disk spare, Internet connection or USB port, Internet browser. For additional 05 hardware requirements see apple.com; Mac 2 GB available hard disk spare, Internet connection or USB port, Internet browser. For additional 05 hardware requirements see apple.com; No software solutions are included in the Box only on http://hp.com or http://12.3 hp.com HP Web JetAdmin Software, Security Manager; HP SNMP Proxy Agent (Part of HP WebJetAdmin); HP WS Pro Proxy Agent (Part of HP WebJetAdmin); Smart Printer Administrator Resource Kit for HP Smart Universal Print Driver (Driver Configuration; UNIII) - Driver; Deployment UNIII; - Managed Printing Administrator) Minimum 421 x 427 x 288 mm; Maximum: 421 x 636 x 420mm ~16.33 kg Temperature: 10 to 32.5°C Humidity: 30 to 70% RH (non-condensing) Temperature: -20 to 40°C Acoustic power emissions: 6.2 B(A) Acoustic pressure emissions: 51 dB(A) Requirements: 220-wolt input voltage: 220 to 240 WAC (+'- 19%; 50/60Hz (+'- 3 Hz); Consumption: 580 watts (active printing), 17 watts (selep), 07 watts (slep-off/auto-onl, 0.07 watts (slep-off/manual-onl, 0.07 watts (off); Typical Electricity Consumption (TEC).037 ok/Winek (Blue Angel); Power supply type: Internet (Driul-Tir) Power Supply HP Auto-OriAuto-Off Technology UL/LUL, UC/LUR, Citradia); TU Watts (GERTURA); DERTURATION; DERTURATION; DERTURATION (Citradia); Power 2 Gass B. 1/11:2020, Citradia Standards. Els Registration (Induk); PS B (Singapore); Eastern European country approvals; CE Marking: Other Safety & EMC Certification appr

Footnotes

¹ Standard print mode for HP Color Laser Jet Pro series with HP TerraJet technology compared to predecessors. See hp.com/TerraJetcolors.

² HP Web Jetadmin is available for download at no additional charge at hp.com/go/webjetadmin.

⁴ HP JetAdvantage Security Manager must be purchased separately. To learn more, please visit hp.com/go/securitymanager.
⁵ HP calculations based on ENERGY STAR® normalised TEC data comparing HP Laser Jet 200-500 series printers at launch. See hp.com/ecosmart.

⁶ Recycling: Program availability varies. Original HP cartridge return and recycling is currently available in more than 60 countries, territories and regions in Asia, Africa, Europe, and North and South America through the HP Planet Partners program. For details, see hp.com/recycle.

⁷ Plastic reduction calculated per page based on cartridge weight in grams and stated yield in HP TerraJet Cartridges compared to predecessors. See hp.com/TerraJet/plasticreductions.

⁸ HP calculations based on Energy Star[®] normalised TEC data in HP TerraJet Cartridges compared to predecessors. See hp.com/TerraJetenergysaving.

⁹ HP Auto-On/Auto-Off Technology capabilities subject to printer and settings; may require a firmware upgrade. ¹⁰ Requires the HP Smart app download. For details on local printing requirements see www.hp.com/go/mobileprinting. Certain features/software are available in English language only and differ between desktop and mobile applications. Subscription may be required.

Technical specifications disclaimers

¹ EPEAT® registered where applicable. EPEAT registration varies by country. See http://www.epeat.net for registration status by country. Please be aware that HP LaserJet Pro 4201 and MFP 4301 series products are ENERGY STAR 3.0 certified in the US and the functionally equivalent HP Laser Jet Pro 4202 and MFP 4302 series meet ecolabel energy efficiency limits.

² Typical Electricity Consumption (TEC) rating represents the typical electricity consumed by a product during 1 week, measured in kilowatt-hours (kWh). ENERGY STAR TEC data based on 115V test result; Blue Angel TEC based on 230V test result.

³ For yield information on the cartridge(s) included with your printer, see http://www.hp.com/go/toneryield. Yield values measured in accordance with ISO/IEC 19798 and continuous printing. Actual yields vary considerably based on images printed and other factors. ⁵ Values based on 115V test results based on Energy Star test method.

⁶ Configuration tested: base model, simplex printing, A4 paper at an average of 34 ppm.

⁷ Measured using ISO 24734 Feature Test, A5 Landscape Feed. Speed may vary based on content, PC, media orientation, and media type.

© Copyright 2025 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein. gb-en February 2025

