

Rugged Mini

MOBILE DRIVE
Data Sheet

Rugged Design. Mini Size.

- Shock, rain, and pressure resistant
- Password protection
- USB 3.0: up to 4x faster than USB 2.0

design by neil poulton

Product Overview

The LaCie Rugged Mini drive shares features with our popular Rugged mobile hard drive, like shock resistance, drop resistance, and a rubber sleeve for added protection. But the Rugged Mini is also rain and pressure resistant, meaning you can drive over it with a 1-ton car, and it still works¹. With the Rugged Mini, LaCie has reduced the size and added tons of new features, making it perfect for on-the-go data transport.



Use Cases

- Students: Store music, video, and confidential school documents on a secure device that fits in a backpack.
- Travelers: Protect valuable data from loss, theft, or accident while on the road
- Photographers: Small form factor and toughness make this product perfect for use in the field or to safely deliver large files to customers and partners, and encryption² adds an extra layer of protection against unauthorized access.
- Videographers: Perfect for shuttling dailies or other footage to the studio and transfering files quickly thanks to USB 3.0.

1 Determined by a test that approximates a real-world scenario in which the hard drive remained functional, despite aesthetic damage, after the product was driven over by an approximately 1-ton car (1000 kg / 2205 lbs).

2 Encryption software is only available via download and is not available in Russia.





Rugged Mini

MOBILE DRIVE

Specifications									
Retail Packaging	Product Dimensions	Product Dimensions Box Dimensions Master Carton Dimensions		Pallet Dimensions					
Length (in/mm)	5.319 in/135.1 mm	7.323 in/186 mm	10.472 in/266 mm	41.338 in/1,050 mm					
Width (in/mm)	3.386 in/86 mm	5.079 in/129 mm	7.402 in/188 mm	46.85 in/1,190 mm					
Depth (in/mm)	1.024 in/26 mm	2.047 in/52 mm	5.315 in/135 mm	40.945 in/1,040 mm					
Weight (lb/kg)	0.882 lb/0.4 kg	1.102 lb/0.5 kg	5.512 lb/2.5 kg	722.675 lb/327.8 kg					
Quantities									
Boxes per Master Carton	5								
Master Cartons per Pallet	120								
Pallet Layers	6								

System Requirements

What's Included

- Computer with a USB 3.0 or USB 2.0 port
- Latest version of Windows® 7, Windows 8 / Mac OS® X 10.5 and later
- Minimum free disk space: 600 MB recommended
- LaCie Rugged Mini drive
- USB 3.0 cable (USB 2.0 compatible)
- Quick Install Guide

Region	Model Number	Capacity	Limited Warranty (months)	UPC Code	EAN Code	Multi-Pack UPC
ww	LAC301556	500 GB	24	093053827953	3660619315567	10093053827950
ww	LAC301558	1 TB	24	093053827984	3660619315581	10093053827981
ww	LAC9000298	2 TB	24	093053003272	3660619005840	10093053003279
ww	LAC9000633	4 TB	24	093053014117	3660619013814	10093053014114

LACIE.COM

AMERICAS Seagate Technology LLC 10200 South De Anza Boulevard, Cupertino, California 95014, United States, 408-658-1000
ASIA/PACIFIC Seagate Singapore International Headquarters Pte. Ltd. 7000 Ang Mo Kio Avenue 5, Singapore 569877, 65-6485-3888
EUROPE, MIDDLE EAST AND AFRICA Seagate Technology SAS 16-18, rue du Dôme, 92100 Boulogne-Billancourt, France, 33 1-4186 10 00

© 2015 Seagate Technology LLC. All rights reserved. Seagate, Seagate Technology, LaCie, and the LaCie logo are trademarks or registered trademarks of Seagate Technology LLC or one of its affiliated companies in the United States and/or other countries. All other trademarks or registered trademarks are the property of their respective owners. Actual data rates may vary depending on operating environment and other factors, such as disk capacity. When referring to hard drive capacity, one gigabyte, or GB, equals one billion bytes and one terabyte, or TB, equals one trillion bytes. Your computer's operating system may use a different standard of measurement and report a lower capacity. In addition, some of the listed capacity is used for formatting and other functions, and thus will not be available for data storage. Complying with all applicable copyright laws is the responsibility of the user. Seagate reserves the right to change, without notice, product offerings or specifications. DS1871.1-1509US