

MultiSync® P242W LCD 24" Professional Display

Datasheet



The NEC MultiSync® P242W delivers outstanding image quality with class-leading ergonomics for demanding professional applications. 15 cm height adjust, latest DisplayPort connector, Digital Uniformity Control, integrated USB hub and Picture-in-Picture give advanced users all the flexibility and image quality to ensure highest personal productivity. This outstanding display cabinet has won the prestigious iF Design Award.

The ideal display for professional design, CAD-CAM, finance, demanding office and industrial applications (e.g. NDT).

Benefits

Ergonomic Office – full height adjustability (150 mm), tilt and flat mode ensures perfect individual ergonomic set-up.

Extraordinary Features – such as Digital Uniformity Control, Picture-in-Picture, USB Hub, 3D LUT colour space emulation, backlight ageing correction, DisplayPort.

Future-proof Connectivity – as well as easier support of high resolution and HDMI signals, 10-bit colour input signals is assured with the DisplayPort connector.

Improved Productivity and Reduced Desk Clutter – through easy multi-platform support and input following USB hub. Picture-by-picture allows two different platforms to be simultaneously viewed. A single mouse and keyboard can be switched to the active operating system.

Image display – 24inch 16:10 IPS with LED backlight.

DICOM preset – for medical radiological review applications.

Product Information

| | |
|---------------|------------------------------|
| Product Name | MultiSync® P242W |
| Product Group | LCD 24" Professional Display |
| Order Code | 60003419 (BK), 60003418 (WH) |

Display

| | |
|--|---|
| Panel Technology | IPS TFT with W-LED backlight |
| Screen Size [inch/cm] | 24 / 61 |
| Colour Gamuts | 75% AdobeRGB, 75.2% NTSC |
| Pixel Pitch [mm] | 0.270 |
| Brightness (typ.) [cd/m ²] | 350 |
| Contrast Ratio (typ.) | 1000:1 |
| Viewing Angle [°] | 178 horizontal / 178 vertical (typ. at contrast ratio 10:1) |
| Response Time (typ.) [ms] | 16 (8 white / black; 8 black / white); 8 (grey-to-grey) |
| Colours [Mio.] | 16.77 |

Synchronisation Rate

| | |
|----------------------------|---|
| Horizontal Frequency [kHz] | 31.5 - 91.1 and 118.4 (digital); 31.5 - 93.8 and 118.4 (analog) |
| Vertical Frequency [Hz] | 50 - 85 |

Resolution

| | |
|--------------------|--|
| Optimum Resolution | 1920 x 1200 at 60 Hz |
| Supported | 1920 x 1080p; 1600 x 1200; 1280 x 1024; 1280 x 960; 1280 x 720p; 1200 x 1920; 1152 x 870; 1152 x 864; 1024 x 768; 832 x 624; 800 x 600; 720 x 576p; 720 x 480p; 720 x 400; 640 x 480; 640 x 480p |

Connectivity

| | |
|---------|--------------------------------------|
| Digital | 1 x DisplayPort; 1 x DVI-D; 1 x HDMI |
| Analog | 1 x D-sub 15 pin |

Electrical

| | |
|-------------------------------|---|
| Power Consumption on Mode [W] | 17 (Eco Mode); 22 (typ.); 30 (max.) |
| Power Savings Mode [W] | 1 |
| Power Supply | 0.83 A/0.47 A; 100-240 V; integrated power supply |

Environmental Conditions

| | |
|----------------------------|-----------|
| Operating Temperature [°C] | +5 to +35 |
| Operating Humidity [%] | 30 to 80 |

Ergonomics

| | |
|------------------------------|--------------------------------------|
| Height adjustable stand [mm] | 110; 150 (Landscape mode); Pivot 90° |
| Screen Tilt / Swivel [°] | -5 to 30; -45 to 45 |

Mechanical

| | |
|-----------------------------|---|
| Bezel Width [mm] | 18.2; 18.2 (left and right); 18.2 (top and bottom) |
| Dimensions (W x H x D) [mm] | 556.8 x 378 - 528 x 227.6 (Landscape mode); Without stand: 556.8 x 362.4 x 85 |
| Weight [kg] | 10.2; Without stand: 7.4 |
| VESA Mounting [mm] | 100 x 100 (4 points); 200 x 100 (5 points) |

Additional Features

| | |
|--------------------------|--|
| Special Characteristics | 14 Bit Look Up Table for 14 Bit smooth Gamma curves; Advanced NTAA; AmbiBright; Auto Black Level; Auto Brightness; Auto Contrast; Backlight Ageing Correction; CableComp with Sync Continuity Detection; ColorComp; DDC/CI compatible; DICOM preset; Direct Brightness and Contrast; EcoModes; LED Backlight Technology; NaViSet Administrator 2; OmniColor™: sRGB and 6-Axis-Colour-Control; Overdrive; Quick release Stand and Handle; Rapid Response Technology; RapidMotion; Self Diagnostics; TileComp; TileMatrix; TORO™ Design; Viewing Angle Stability |
| Colour Versions | Black Front Bezel, Black Back Cabinet; Silver Front Bezel; White Back Cabinet |
| Cable Management | yes |
| Kensington security slot | yes |
| Plug and Play | EDID Standard; VESA DDC/CI; VESA DDC2B |
| Adjust Functions | Advanced NTAA (Advanced Non-Touch-Auto-Adjustment); Advanced User Menu; Auto Adjust; Black Level; Brightness; Colour Temperature Control; Contrast; Expansion Mode; Fine Adjust (analog); Hotkeys; Intelligent Power Management; Language Select; Monitor Information; OmniColor™: sRGB and 6-axis-colour-control; On-Screen-Display (OSD) lock-out; Sharpness |
| Shipping Content | Monitor; Power Cable; Setup Guide; Signal Cable DisplayPort Signal Cable: [value1] x DVI-D; VGA - VGA |
| Safety and Ergonomics | C-tick; CCC; CE; ErP; FCC Class B; ISO 9241-307 (pixel failure class I); MPR II/ MPR III; PCBC/B-mark; PCT/Gost; PSB; RoHS; TCO 6.0; TÜV Ergonomics; TÜV GS; UL/C-UL or CSA |
| Warranty | 3 years warranty incl. backlight |

Green Features

| | |
|----------------------|--|
| Energy Efficiency | Ambient light sensor; Auto brightness; Carbon Footprint Meter / Carbon Savings Meter; ECOMode; Energy efficiency class: A; Intelligent Power Management; Reduced consumption |
| Ecological Materials | 100% recyclable packaging; Arsenic-free panel module; Black model built from recycled plastics |
| Ecological Standards | ErP compliant; ISO 14001; RoHS compliant; WEEE |



CE



C-tick



ErP



FCC Class B



MPR II/ MPR III



ME06
PCT/Gost



RoHS



TÜV
Ergonomics



TÜV GS



TCO 6.0

This document is © 2018 NEC Display Solutions Europe GmbH.

All rights reserved in favour of their respective owners. All hardware and software names are brand names and/or registered trademarks of the respective manufacturers. All specifications are subject to change without notice. Errors and omissions are excepted. 23.03.2018