



Fix & Glue Gel

METHOXYETHYL CYANOACRYLATE GEL

Date: 30 March 2022

Fact Sheet No.: TDS02086

YOUR SMART ADVANTAGES

- Ultra strong, fast setting, and water & heat resistant
- Safer formulation, odourless and solvent-free
- Slightly flexible so it resists knocks & drops

USES

Bostik Fix & Glue Gel uses the latest technology in super glues. It is ultra strong and fast setting, yet does not stick your fingers together immediately. It is water and heat resistant, slightly flexible, and its safer formulation means it has no hazard warnings on pack.

Bostik Fix & Glue Gel's consistency makes it ideal for applications in any orientation and bonds to 99.9% of materials including porcelain, ceramic, glass, wood, fabric, concrete and much more.

Bostik Fix & Glue is user-friendly thanks to its solvent free, non-lachrymatory and non-irritant formula, which does not immediately stick to fingers.

PRODUCT CHARACTERISTICS

Colour	Transparent
Specific Gravity	1.13g/ml
Composition	Methoxyethyl Cyanoacrylate
Product Code	30614762 Fix & Glue Gel 3 x 1g x 6 blister cards 30614763 Fix & Glue Gel 3g x 6 blister cards
Storage/Shelf Life	12 months in its sealed original packaging, stored at 5°C to 20°C. Once opened, your product will

	keep for several months stored vertically away from light in a cool dry place. Protect from frost.
Odour	Nil
Viscosity	Gel (17 .000-25. 000 cP)

TYPICAL PERFORMANCE DATA (Approx.)

Fixture Time	5 seconds
Application Temperature	-20°C to +80°C
Final Strength (after 24 hours)	Beech Wood:120 to 140 kg/cm ² (SF*) Mild Steel Grit-Blasted: 160-180 kg/cm ²
Full Cure	17 to 24 hours at 25°C

SF=substrate failure

DIRECTIONS FOR USE

IMPORTANT: Before using Bostik Fix & Glue Gel refer to the relevant Health & Safety Data Sheet, available at www.bostik.com/uk

PREPARATION

1. For best results, ensure both surfaces are dry, clean and free from dust and grease.
2. Before first use, screw the nozzle onto the tube & remove the cap to use.

APPLICATION

3. Carefully apply a small amount of Bostik Fix & Glue Liquid to one surface only. Do not use items like tissues or a brush to spread the adhesive.

4. Bring the surfaces together and apply pressure firmly until a bond is achieved.
5. Allow the adhesive to achieve maximum bond strength (typically 24 to 72 hours after application) before subjecting the surfaces to use.
6. Clean the nozzle after each use and screw the cap on tightly.

CLEANING

Acetone will slowly soften the set Bostik Fix & Glue Gel. Before attempting to use, check that it is safe to use a highly flammable solvent and that the solvent does not damage the surfaces to which the super glue is adhered. Do not use acetone or solvents on the skin.

PRECAUTIONS IN USE

CAUTION: Cyanoacrylate. Danger. Bonds skin and eyes in seconds. Keep out of the reach of children. Read label before use.

For any application not covered please contact Technical Services on +44 (0)1785 272625 or visit www.bostik.com/uk for advice.

Recommendations and suggestions are for guidance only, since conditions of use are completely beyond our control.

For health and safety instruction, first aid measures and spillage and disposal instructions, see separate Health and Safety Data sheet for Bostik Fix & Glue Gel, available at www.bostik.com/uk



This disclaimer is issued by Bostik Limited ("the Company") and applies to the use of any products supplied by the Company ("the Products") displayed on this Technical Data Sheet ("TDS"). Please read this disclaimer carefully before using any of the Products. Using this TDS and/or the Product constitutes your acceptance of this disclaimer. Its contents shall prevail over any directions of use and any disclaimer and/or exclusion or limitation of liability of the Company which may appear on the packaging of the Products.

This disclaimer sets out the entire financial liability of the Company (including any liability for the acts or omissions of its employees, agents and sub-contractors) to any user of the Products ("Product User") in respect of any use made or resale by the Product User, of any of the Products in this TDS.

This disclaimer does not affect the Company's liability for death or personal injury arising from the Company's negligence in respect of the Products, nor its liability for fraud, or fraudulent misrepresentation, nor any other liability which cannot be excluded or limited under applicable law.

The Company's total liability however arising and whether caused by tort (including negligence and breach of statutory duty), breach of contract or otherwise, arising in connection with the use made or resale by the Product User of any of the Products in this TDS shall be limited to the price paid for the Product by the Product User.

The Company shall not be liable to the Product User for any pure economic loss, loss of profit, loss of business, depletion of goodwill or otherwise, in each case whether direct, indirect or consequential, or any claims (including in respect of personal injury insofar as not caused by the Company's negligence) for consequential compensation whatsoever (howsoever caused) which arise out of or in connection with the use made or resale by the Product User of any of the Products in this TDS.

The Company shall not be liable to the Product User in relation to any loss for any use which is inappropriate or use which is otherwise than in accordance with the relevant instructions for use of the Products in this TDS or on the Product. Product Users are advised to confirm the suitability of the Products by their own tests.

This TDS covers just one of a large range of products supplied by the Company.

Full information on these products and advice on application is freely available from our fully trained staff throughout the country. In addition, specialist technical advice is available from our Technical Services Department. This TDS supersedes all previous TDSs relating to the Products, and users of it must ensure that it is the current issue. Destroy all previous TDS, and if in any doubt, contact the Company, quoting the code number in the top right hand corner on the front of this document.

Sales	Tel: 0844 371 1192	customer.service@bostik.com
Technical Advice	Tel: 0844 371 1197	technical.service@bostik.com
Safety Data Sheets	Tel: 01785 272625	sds.box-eu@bostik.com