

USB-C to HDMI Adapter Cable - 1m (3 ft.) - 4K at 30 Hz

Product ID: CDP2HDMM1MB



This USB-C[™] to HDMI® adapter cable offers a convenient solution for directly connecting your DisplayPort over USB Type-C[™] device to your HDMI monitor, television or projector. The adapter supports a connection distance of up to 1 m (3 ft.) and works with USB-C devices that support DP alt mode, such as the MacBook, ChromeBook Pixel[™] and Dell[™] XPS[™] models 15 and 13. It's also compatible with Thunderbolt[™] 3 ports.

Clutter-free installation

At 1 m (3 ft.) in length, this adapter cable delivers a direct connection that eliminates excess adapters and cabling, ensuring a tidy, professional installation. For longer installations, we also offer a 2 m (6 ft.) USB-C to HDMI cable, enabling you to choose the right cable length for your custom installation needs.



Data Sheet

Hassle-free connection with USB Type-C

The adapter cable is easy to connect, through the versatility and convenience of the USB Type-C port on your device. USB-C is a reversible connector, so it doesn't matter which way you plug it in, the adapter will always connect. This saves you the frustration of trying to insert it correctly when you're docking your computer to your workstation or office hot desk.

Astonishing picture quality

At four times the resolution of high-definition 1080p, you'll be amazed at the picture quality of a 4K monitor or television. This adapter cable lets you harness the video capabilities that are built into your USB Type-C connection to deliver the astonishing quality of Ultra HD to your 4K display.

The adapter is backward compatible with 1080p displays, ensuring the adapter will also work for HD applications at your home or office.

The CDP2HDMM1MB is backed by a 3-year StarTech.com warranty and free lifetime technical support.

Note:

Your USB-C equipped device must support video (DP alt mode) to work with this adapter.



Data Sheet

Certifications, Reports and Compatibility









Applications

- Connect a USB Type-C computer to an HDMI projector or display in your classroom, auditorium or boardroom
- Install at your home workstation or office hot desk to make your USB-C computer compatible with your HDMI display

Features

- Reduce clutter with a compact 1 m (3 ft.) adapter cable
- Hassle-free connection with the reversible USB-C connector
- Astonishing video quality with support for video resolutions up to 4K at 30 Hz
- Plug-and-play installation
- No power adapter required
- Thunderbolt 3 port compatible



Hard-to-find made easy*

Data Sheet

HardwareWarranty3 YearsHardwareAdapter StyleCable AdaptersAV InputUSB-CAV OutputHDM1-1.4Chipset IDNXP - PTN5100Ports1Maximum Analog ResolutionsHDM1 - 7.1 Channel AudioMaximum Digital Resolutions1920x1200 or 1080pMaximum Digital Resolutions1024x768Supported Resolutions1024x768Supported Resolutions1280x220 (High-definition 720p)1920x12001920x12002560x1400
AV Input USB-C AV Output HDMI - 1.4 Chipset ID Parade - P5171 NXP - PTN5100 Ports 1 Performance Audio Specifications Maximum Analog Resolutions 1920x1200 or 1080p Maximum Digital Resolutions 3840x2160 @ 30 Hz Supported Resolutions 1024x768 1280x720 (High-definition 720p) 1920x1200 2560x1440 2560x1400 2560x1400 2560x1400 2560x1600 3840x2160 (Ultra HD 4K) Video Revision HDMI 1.4 Wide Screen Supported Yes Connector (s) Connector A 1 - USB-C (24 pin) DisplayPort Alt Mode Male Input 1 - HDMI (19 pin) Male Output Special Notes / Requirements Note Your USB-C quipped device must support video (DP Alt Mode) to work with this adapter.
AV Output HDMI - 1.4 Chipset ID Parade - PS171 NXP - PTN5100 Ports 1 Reaformance Audio Specifications HDMI - 7.1 Channel Audio Maximum Analog Resolutions 1920x1200 or 1080p Maximum Digital Resolutions 3840x2160 @ 30 Hz Supported Resolutions 1024x768 1280x720 (High-definition 720p) 1920x1080 (High-definition 1080p) 1920x1000 2560x1600 3840x2160 (Ultra HD 4K) Video Revision HDMI 1.4 Wide Screen Supported Yes Connector (s) Connector A 1 - USB-C (24 pin) DisplayPort Alt Mode Male Input Connector B Special Notes / Requirements Note Your USB-C equipped device must support video (DP Alt Mode) to work with this adapter.
Chipset ID Parade - PS171 NXP - PTNS100 Ports 1 Reformance Audio Specifications HDMI - 7.1 Channel Audio Maximum Analog Resolutions 1920x1200 or 1080p Maximum Digital Resolutions 3840x2160 @ 30 Hz Supported Resolutions 1024x768 1280x720 (High-definition 720p) 1920x1080 (High-definition 1080p) 1920x1080 (High-definition 1080p) 1920x1080 (High-definition 1080p) 1920x1200 2560x1440 2560x1600 3840x2160 (Ultra HD 4K) Video Revision HDMI 1.4 Wide Screen Supported Yes Connector (s) Connector A 1 - USB-C (24 pin) DisplayPort Alt Mode Male Input Connector B Special Notes / Requirements Note System and Cable Requirements System and Cable Requirements
NXP - PTN5100 Ports 1 Performance Audio Specifications HDMI - 7.1 Channel Audio Maximum Analog Resolutions 1920x1200 or 1080p Maximum Digital Resolutions 3840x2160 @ 30 Hz Supported Resolutions 1024x768 1280x720 (High-definition 720p) 1920x1080 (High-definition 1080p) 1920x1200 2560x1440 2560x1440 2560x1440 2560x1440 2560x1440 2560x1440 2560x1600 3840x2160 (Ultra HD 4K) Video Revision HDMI 1.4 Wide Screen Supported Yes Connector (s) Connector A 1 - USB-C (24 pin) DisplayPort Alt Mode Male Input Connector B Sour USB-C equipped device must support video (DP Alt Mode) to work with this adapter. Special Notes / Requirements Note Your USB-C port must support DisplayPort over USB-C (PA Att mode) in order to work with this adapter.
Performance Audio Specifications HDMI - 7.1 Channel Audio Maximum Analog Resolutions 1920x1200 or 1080p Maximum Digital Resolutions 3840x2160 @ 30 Hz Supported Resolutions 1024x768 1280x720 (High-definition 720p) 1920x1200 1920x1200 2560x1600 2560x1600 1.4 Wide Screen Supported Yes Connector A 1 - USB-C (24 pin) DisplayPort Alt Mode Male Input Connector B 1 - HDMI (19 pin) Male Output Special Notes / Note Your USB-C equipped device must support video (DP Alt Mode) to work with this adapter.
Maximum Analog Resolutions1920x1200 or 1080pMaximum Digital Resolutions3840x2160 @ 30 HzSupported Resolutions1024x768 1280x720 (High-definition 720p) 1920x1080 (High-definition 1080p) 1920x1200 2560x1440 2560x1600 3840x2160 (Ultra HD 4K)Video RevisionHDMI 1.4 Yide Screen SupportedWide Screen SupportedYesConnector(s)Connector A Connector BNoteYour USB-C (24 pin) DisplayPort Alt Mode Male Input 1 - HDMI (19 pin) Male OutputSpecial Notes / RequirementsNote System and Cable RequirementsSystem and Cable RequirementsYour USB-C port must support DisplayPort over USB-C (DF Alt mode) in order to work with this adapter.
Maximum Digital Resolutions3840x2160 @ 30 HzSupported Resolutions1024x768 1280x720 (High-definition 720p) 1920x1080 (High-definition 1080p) 1920x1200 2560x1440 2560x1600 3840x2160 (Ultra HD 4K)Video RevisionHDMI 1.4 Video Screen SupportedWide Screen SupportedYesConnector (s)Connector A Connector BNote1 - USB-C (24 pin) DisplayPort Alt Mode Male Input 1 - HDMI (19 pin) Male OutputSpecial Notes / RequirementsNoteSystem and Cable RequirementsYour USB-C port must support DisplayPort over USB-C (DF Alt mode) in order to work with this adapter.
Supported Resolutions1024x768 1280x720 (High-definition 720p) 1920x1080 (High-definition 1080p) 1920x1200 2560x1440 2560x1600 3840x2160 (Ultra HD 4K)Video RevisionHDMI 1.4Wide Screen SupportedYesConnector(s)Connector AConnector B1 - USB-C (24 pin) DisplayPort Alt Mode Male Input 1 - HDMI (19 pin) Male OutputSpecial Notes / RequirementsNoteSystem and Cable RequirementsYour USB-C equipped device must support video (DP Alt Mode) to work with this adapter.
1280x720 (High-definition 720p) 1920x1080 (High-definition 1080p) 1920x1200 2560x1400 2560x1600 3840x2160 (Ultra HD 4K) Video Revision HDMI 1.4 Wide Screen Supported Yes Connector (s) Connector B I - USB-C (24 pin) DisplayPort Alt Mode Male Input Connector B I - HDMI (19 pin) Male Output Special Notes / Requirements System and Cable Requirements Your USB-C port must support DisplayPort over USB-C (DF Alt mode) in order to work with this adapter.
Wide Screen SupportedYesConnector(s)Connector A1 - USB-C (24 pin) DisplayPort Alt Mode Male Input 1 - HDMI (19 pin) Male OutputSpecial Notes / RequirementsNoteYour USB-C equipped device must support video (DP Alt Mode) to work with this adapter.System and Cable RequirementsYour USB-C port must support DisplayPort over USB-C (DF Alt mode) in order to work with this adapter.
Connector(s)Connector A Connector B1 - USB-C (24 pin) DisplayPort Alt Mode Male Input 1 - HDMI (19 pin) Male OutputSpecial Notes / RequirementsNote System and Cable RequirementsYour USB-C equipped device must support video (DP Alt Mode) to work with this adapter.System and Cable RequirementsYour USB-C port must support DisplayPort over USB-C (DF Alt mode) in order to work with this adapter.
Connector B 1 - HDMI (19 pin) Male Output Special Notes / Requirements Note Your USB-C equipped device must support video (DP Alt Mode) to work with this adapter. System and Cable Requirements Your USB-C port must support DisplayPort over USB-C (DF Alt mode) in order to work with this adapter.
Special Notes / Requirements Note Your USB-C equipped device must support video (DP Alt Mode) to work with this adapter. System and Cable Requirements Your USB-C port must support DisplayPort over USB-C (DF Alt mode) in order to work with this adapter.
Requirements Mode) to work with this adapter. System and Cable Requirements Your USB-C port must support DisplayPort over USB-C (DF Alt mode) in order to work with this adapter.
Alt mode) in order to work with this adapter.
Environmental Humidity 5%-80% RH (no condensation)
Operating Temperature 0°C to 35°C (32°F to 95°F)
Storage Temperature -10°C to 80°C (14°F to 176°F)
Physical Accent Color Black Characteristics
Cable Length 3.3 ft [1 m]
Color Black
Product Height 0.6 in [1.4 cm]
Product Height0.6 in [1.4 cm]Product Length3.3 ft [1 m]



Hard-to-find made easy*

Data Sheet

	Weight of Product	2.8 oz [79 g]
Packaging Information	Package Height	1 in [25 mm]
	Package Length	8.9 in [22.5 cm]
	Package Width	4.9 in [12.5 cm]
	Shipping (Package) Weight	3 oz [84 g]
What's in the Box	Included in Package	1 - USB-C to HDMI adapter cable

Product appearance and specifications are subject to change without notice.