

USB-C Multiport Adapter with HDMI - USB 3.0 Port - 60W PD - White

Product ID: CDP2HDUACPW



This USB-C™ multiport adapter with HDMI lets you add vital connections to your MacBook or Windows laptop, through a single USB-C port.

Connect a UHD 4K HDMI Monitor

For maximum productivity, connect your USB-C or Thunderbolt 3 laptop to a 4K 30Hz monitor, using this USB-C to 4K HDMI adapter. You can also connect to an HDMI projector or TV in a boardroom or other meeting space, to deliver presentations on a shared screen.

Charge Your Laptop

The USB-C adapter lets you power and charge your USB-C laptop during a presentation or while you're working, with a USB-C Power Delivery port. Even if your laptop has only a single USB-C port available, you can keep your laptop powered.





Add a USB 3.0 Port

This USB-C multiport adapter offers a USB 3.0 port that's backward compatible with older USB devices - ideal for data transfers, syncing, or charging your mobile devices.

Travel-Friendly Design

The compact all-in-one adapter is a vital accessory for your USB-C laptop. With its small-footprint design, you can take it with you anywhere you would use your laptop.

CDP2HDUACPW is backed by a StarTech.com 3-year warranty and free lifetime technical support.

Note: To ensure full adapter functionality, your laptop's USB-C port must support USB Power Delivery and DP Alt Mode.





Certifications, Reports and Compatibility











Applications

- Multitask faster with an additional, 4K HDMI monitor
- Deliver presentations from your laptop on an HDMI TV or projector
- Charge your laptop with your laptop's USB-C charger, even while the adapter is connected

Features

- Deliver your presentation on a UHD 4K HDMI monitor with this USB-C video adapter
- Power your laptop with 60W Power Delivery using this multiport adapter and a USB Type-C power adapter
- Connect a USB 3.0 Type-A device, like a flash drive or a mouse, to your Windows or MacBook Pro laptop
- Carry the portable USB-C all-in-one adapter with you wherever you go



Data Sheet

	Warranty	3 Years
Hardware	4K Support	Yes
	Bus Type	USB-C
	Chipset ID	VIA/VLI - VL100 VIA/VLI - VL210 Parade - PS176
	Displays Supported	1
	Fast-Charge Port(s)	No
	Industry Standards	USB 3.0 - Backward compatible with USB 2.0 and 1.1
Performance	Maximum Data Transfer Rate	5 Gbps (USB 3.0)
	Maximum Digital Resolutions	$4096 \times 2160 p @ 24Hz / 3840 \times 2160 p @ 30Hz$ Lower resolutions are also supported.
	Type and Rate	USB 3.0 - 5 Gbit/s
	UASP Support	Yes
Connector(s)	Connector Type(s)	1 - USB Type-C (24 pin) USB 3.0 (5Gbps) Male
		1 - USB-C (24 pin) USB Power Delivery only Female
		1 - HDMI (19 pin) Female
		1 - USB Type-A (9 pin) USB 3.0 (5 Gbps) Female
Special Notes / Requirements	Note	Not all USB-C ports support the full functionality of the USB Type-C standard. Ensure that your host USB-C port supports USB Power Delivery 2.0 and DP alt mode.
		The adapter can connect to a host laptop's USB-C port that doesn't support USB Power Delivery 2.0. However, in this configuration if a power adapter is connected to the multifunction adapter, it will not pass power through to your host laptop.
		A 4K-capable display is required to achieve 3840 x 2160p resolution (4K is also known as 4K x 2K)
		·
	System and Cable Requirements	resolution (4K is also known as 4K x 2K) USB 3.0 is also known as USB 3.1 Gen 1; this connectivity
	System and Cable Requirements	resolution (4K is also known as 4K x 2K) USB 3.0 is also known as USB 3.1 Gen 1; this connectivity standard offers speeds up to 5Gbps. A host laptop with an available USB-C port (to ensure full adapter functionality, the host USB-C port must support
Power	System and Cable Requirements Power Delivery	resolution (4K is also known as 4K x 2K) USB 3.0 is also known as USB 3.1 Gen 1; this connectivity standard offers speeds up to 5Gbps. A host laptop with an available USB-C port (to ensure full adapter functionality, the host USB-C port must support USB Power Delivery 2.0 and DP alt mode). Optional: USB-C power adapter (for example, your laptop's



Data Sheet

Environmental	Humidity	0~90% RH (Non-condensing)
	Operating Temperature	0°C to 40°C (32°F to 104°F)
	Storage Temperature	-20°C to 70°C (-4°F to 158°F)
Physical Characteristics	Cable Length	4 in [101 mm]
	Color	White
	Material	Plastic
	Product Height	0.4 in [1.1 cm]
	Product Length	2.4 in [60 mm]
	Product Width	2 in [50 mm]
	Weight of Product	1.3 oz [36 g]
Packaging Information	Package Height	1.3 in [32 mm]
	Package Length	6.9 in [17.5 cm]
	Package Width	5.7 in [14.5 cm]
	Shipping (Package) Weight	4.1 oz [117 g]
What's in the Box	Included in Package	1 - USB-C to 4K HDMI multifunction adapter

Product appearance and specifications are subject to change without notice.