

# DisplayPort to HDMI Converter Cable - 5m (16 ft) - 4K

Product ID: DP2HDMM5MB



This 5-meter (16 ft.) DisplayPort to HDMI® adapter cable lets you connect your DisplayPort equipped Ultrabook™, laptop or desktop computer to an HDMI television, monitor or projector, with no additional adapters or cables required. The passive adapter supports video resolutions up to Ultra HD 4K, ensuring support for high-resolution applications.

### **Astonishing picture quality**

This adapter cable ensures you can maintain an astonishing 4K picture quality, four times the resolution of 1080p, when converting DisplayPort to HDMI. The adapter is also backward-compatible with lower-resolution displays and video sources. With support for high-definition resolutions of 1080p and 720p, you can future-proof your existing setup for 4K video.





### Hassle-free setup

For the simplest and most discreet installation, this DP to HDMI adapter connects directly from your DisplayPort video source to the HDMI port on your display. It doesn't need a power source, unlike some converter dongles that require active power and separate bulky video cabling.

### **Clutter-free installation**

With a built-in DP to HDMI adapter, this 5 m cable delivers a direct connection that eliminates the need for additional adapters, ensuring a tidy, professional installation. Plus, because the cable is 5 meters (16 feet) in length, the cable is ideal when connecting your computer to a display that's much further away than a standard 6 ft. (2 m) cable.

For shorter installations, we also offer a <u>1 m DP to HDMI cable (DP2HDMM1MB)</u>, <u>2 m DP to HDMI cable (DP2HDMM2MB)</u> and a <u>3 m DP to HDMI cable (DP2HDMM3MB)</u>, enabling you to choose the right cable length for your custom installation needs.

The DP2HDMM5MB is backed by a 3-year StarTech.com warranty and free lifetime technical support.





# Certifications, Reports and Compatibility











### **Applications**

- Connect a DisplayPort computer to an HDMI display at your classroom desk or workstation
- Use in your boardroom or office workstations for installations requiring 5 m (16 ft.) of cable
- Install in your home workstation to make your DisplayPort computer compatible with your HDMI display
- Connect your DP video source to a 4K HDMI display

#### **Features**

- Astonishing video quality with support for video resolutions up to 4K at 30 Hz
- Reduce clutter with a compact 5 m (16 ft.) adapter cable
- Avoid the hassle of converters that require additional cabling and power adapters with a plug-and-play cable adapter
- Supports HDMI 4K @ 30 Hz
- Plug-and-play installation
- No power adapter required



## **Data Sheet**

	Warranty	3 Years
Hardware	Active or Passive Adapter	Passive
	Adapter Style	Adapters
	Audio	Yes
	AV Input	DisplayPort - 1.2
	AV Output	HDMI - 1.4
	Industry Standards	DPCP (DisplayPort Content Protection) HDCP (High Definition Content Protection) DisplayPort 1.2 HDMI 1.4
	Ports	1
Performance	Audio Specifications	HDMI - 7.1 Channel Audio
	Maximum Digital Resolutions	4K x 2K @ 30 Hz
	MTBF	2,183,131 hours
	Supported Resolutions	4k x 2K (Ultra HD) 1920x1200 1920x1080 (1080p) 1280x720 (720p)
	Wide Screen Supported	Yes
	Wide Screen Supported	163
Connector(s)	Connector A	1 - DisplayPort (20 pin) Male Input
Connector(s)		
Connector(s)  Environmental	Connector A	1 - DisplayPort (20 pin) Male Input
	Connector A Connector B	1 - DisplayPort (20 pin) Male Input 1 - HDMI (19 pin) Male Output
	Connector A Connector B Humidity	1 - DisplayPort (20 pin) Male Input 1 - HDMI (19 pin) Male Output 10%-85%
	Connector A Connector B Humidity Operating Temperature	1 - DisplayPort (20 pin) Male Input 1 - HDMI (19 pin) Male Output  10%-85%  0°C to 70°C (32°F to 158°F)
Environmental  Physical	Connector A  Connector B  Humidity  Operating Temperature  Storage Temperature	1 - DisplayPort (20 pin) Male Input 1 - HDMI (19 pin) Male Output  10%-85%  0°C to 70°C (32°F to 158°F)  -10°C to 70°C (14°F to 158°F)
Environmental  Physical	Connector A  Connector B  Humidity  Operating Temperature  Storage Temperature  Cable Length	1 - DisplayPort (20 pin) Male Input 1 - HDMI (19 pin) Male Output  10%-85%  0°C to 70°C (32°F to 158°F)  -10°C to 70°C (14°F to 158°F)  16.4 ft [5 m]
Environmental  Physical	Connector A  Connector B  Humidity  Operating Temperature  Storage Temperature  Cable Length  Color	1 - DisplayPort (20 pin) Male Input 1 - HDMI (19 pin) Male Output  10%-85%  0°C to 70°C (32°F to 158°F)  -10°C to 70°C (14°F to 158°F)  16.4 ft [5 m]  Black
Environmental  Physical	Connector A  Connector B  Humidity  Operating Temperature  Storage Temperature  Cable Length  Color  Product Height	1 - DisplayPort (20 pin) Male Input 1 - HDMI (19 pin) Male Output  10%-85%  0°C to 70°C (32°F to 158°F)  -10°C to 70°C (14°F to 158°F)  16.4 ft [5 m]  Black  0.4 in [1.1 cm]
Environmental  Physical	Connector A Connector B Humidity Operating Temperature Storage Temperature Cable Length  Color Product Height Product Length	1 - DisplayPort (20 pin) Male Input 1 - HDMI (19 pin) Male Output  10%-85%  0°C to 70°C (32°F to 158°F)  -10°C to 70°C (14°F to 158°F)  16.4 ft [5 m]  Black  0.4 in [1.1 cm]  16.4 ft [5 m]
Environmental  Physical	Connector A Connector B Humidity Operating Temperature Storage Temperature Cable Length  Color Product Height Product Length Product Width	1 - DisplayPort (20 pin) Male Input 1 - HDMI (19 pin) Male Output  10%-85%  0°C to 70°C (32°F to 158°F)  -10°C to 70°C (14°F to 158°F)  16.4 ft [5 m]  Black  0.4 in [1.1 cm]  16.4 ft [5 m]  0.9 in [22 mm]
Environmental  Physical Characteristics  Packaging	Connector A Connector B Humidity Operating Temperature Storage Temperature Cable Length  Color Product Height Product Length Product Width Weight of Product	1 - DisplayPort (20 pin) Male Input 1 - HDMI (19 pin) Male Output  10%-85%  0°C to 70°C (32°F to 158°F)  -10°C to 70°C (14°F to 158°F)  16.4 ft [5 m]  Black  0.4 in [1.1 cm]  16.4 ft [5 m]  0.9 in [22 mm]  7.5 oz [211.3 g]



## **Data Sheet**

	Shipping (Package) Weight	7.8 oz [222 g]
What's in the Box	Included in Package	1 - DisplayPort to HDMI cable

Product appearance and specifications are subject to change without notice.