

## USB 3.0 to VGA Adapter with 1-Port USB Hub - 1920x1200

Product ID: USB32VGAEH



The USB32VGAEH USB 3.0 to VGA Adapter is TAA compliant and turns a USB 3.0 port into a VGA output port with 1920x1200 (WUXGA) video support. The adapter features built-in USB 3.0 pass-through, which offers a connection port in place of the USB port used for connecting the VGA adapter – an ideal workaround for Ultrabook™ or laptop users where only a limited number of USB ports are available.

Functioning as an external graphics card, this USB to VGA adapter provides a convenient way to add multi-monitor capability to a USB 3.0-enabled desktop or laptop computer (optimal performance from USB 3.0, backward compatible with USB 2.0).

Leveraging the high-bandwidth (5 Gbps) SuperSpeed USB 3.0 interface, the adapter delivers smooth, high-definition content to your VGA display / projector. The adapter can be used to mirror your primary desktop, showing the same image on each display, or to extend your desktop to double your workspace and increase your productivity.

Backed by a StarTech.com 2-year warranty and free lifetime technical support.

**Recommended System Requirements:**

CPU: Quad Core 2.4GHz or Higher (i5 recommended)

RAM: 4GB or higher

### Certifications, Reports and Compatibility



### Applications

- Add a secondary VGA display and extend your desktop
- Add multi-monitor capability to a single computer, to create engaging multimedia presentations
- Run multiple applications on different screens - check your email on one display and search the web on the other
- Simultaneously view large or multiple spreadsheets across several displays
- Connect your PC to your VGA-equipped projector or display for viewing family pictures and movies
- Great for boosting productivity for researchers and writers, offering the ability to have reference material on one display and a working document copy on the other

### Features

- TAA Compliant
- Supports resolutions up to 1920x1200
- Built in 1-Port USB 3.0 Hub
- SuperSpeed USB 3.0 (5 Gbps) Interface, backward compatible with USB 2.0
- Quick, easy installation
- USB-powered - No external power adapter required
- Choose between Mirrored, Extended or Primary display configurations
- Driver software supports display rotation
- Supports the use of multiple USB32VGAEH adapters on a single system (up to 5)

<b>Hardware</b>	Warranty	2 Years
	Audio	No
	AV Input	USB 3.0
	AV Output	VGA
	Bus Type	USB 3.0
	Chipset ID	Trigger - T5-302
	Displays Supported	1
	Industry Standards	SuperSpeed USB 3.0, USB 2.0
	Memory	16MB
	USB Pass-Through	Yes
<b>Performance</b>	General Specifications	This USB video adapter uses a Trigger family chipset. If you're connecting this device to a computer along with additional USB video adapters or docking stations, please avoid using devices with a DisplayLink or Fresco family chipset.
	Maximum Analog Resolutions	1920x1200
	Supported Resolutions	Widescreen(16/32 bit): 1920x1200, 1920x1080, 1680x1050, 1600x900, 1440x900, 1360x768, 1280x800, 1280x768, 1280x720  Standard(16/32 bit): 1600x1200, 1400x1050, 1280x1024, 1280x960, 1152x864, 1024x768, 800x600
	Wide Screen Supported	Yes
<b>Connector(s)</b>	Connector A	1 - USB Type-A (9 pin) USB 3.0 Male Input
	Connector B	1 - USB Type-A (9 pin) USB 3.0 Female  1 - VGA (15 pin, High Density D-Sub) Female Output
<b>Software</b>	Microsoft WHQL Certified	Yes
	OS Compatibility	Windows® 10 (32/64) Windows 8 / 8.1 (32/64) Windows 7(32/64) Windows Vista (32/64) Windows XP (32/64)
<b>Special Notes / Requirements</b>	<b>Note</b>	This USB video adapter uses a Trigger family chipset. If you're connecting this device to a computer along with additional USB video adapters or docking stations, avoid using devices with different family chipsets, such as DisplayLink® or Fresco Logic®

		Connect a maximum of five USB video adapters on a single computer. Support for multiple adapters will vary depending upon your system resources
		This USB video adapter is not intended for graphical intensive applications, such as gaming
	System and Cable Requirements	System Processor: Quad Core 2.4GHz (i5 recommended) System Memory: 4GB
<b>Power</b>	Power Source	USB-Powered
<b>Environmental</b>	Humidity	< 85% non-condensing
	Operating Temperature	0°C to 50°C (32°F to 158°F)
	Storage Temperature	-10°C to 75°C (14°F to 167°F)
<b>Physical Characteristics</b>	Cable Length	6.3 in [160 mm]
	Color	Black
	Material	Plastic
	Product Height	0.7 in [1.7 cm]
	Product Length	3.3 in [85 mm]
	Product Width	1.9 in [49 mm]
	Weight of Product	2.6 oz [74 g]
<b>Packaging Information</b>	Package Height	1.6 in [41 mm]
	Package Length	5.8 in [14.8 cm]
	Package Width	8.2 in [20.9 cm]
	Shipping (Package) Weight	8 oz [227 g]
<b>What's in the Box</b>	Included in Package	1 - USB 3.0 to DVI Adapter
		1 - Software CD
		1 - Manual

Product appearance and specifications are subject to change without notice.