

H117ST

Go big! Short throw HD Ready home entertainment projector









- Lights on viewing 3800 ANSI lumens
- Short throw lens 100" image from just over a metre away
- Easy connectivity HDMI, VGA, USB power
- Clear, powerful audio 10W speaker

Project a 100" image from just over a metre away with the bright H117ST HD Ready short throw projector.

Feel the action and experience every moment on the big screen for immersive gaming and live sports with a dedicated gaming and sport mode.

Convenient and easy to set up, this compact high brightness projector is ideal for well-lit environments so sports fans can enjoy live action with family or friends with the lights on. Boasting Amazing colour technology, it delivers accurate true-to-life colour reproduction for movie lovers. It also supports low input latency – perfect for games that rely on rapid reactions.



Specifications

Power consumption (min)

Power consumption (max)
Weight and dimensions

Dimensions (W x D x H)

mm

Gross weight

Net weight

Opecinications	
Display/image	
Display technology	DLP™
Resolution	WXGA (1280x800)
Brightness	3,800 lumens
Contrast ratio	30,000:1
Native aspect ratio	16:10
Aspect ratio - compatible	4:3,16:9
Keystone correction -	+/-40°
vertical	
Horizontal scan rate	15.38 ~ 91.15Khz
Vertical scan rate	50 ~ 85(120 for 3D)Hz
Uniformity	75%
Screen size	0,91m ~ 7,7m (35,64" ~ 302,98") diagonal
Lamp info	
Light source type	Lamp
Lamp watts	203
Lamp life hours (up to)	6000 (Bright), 12000 (Dynamic), 10000 (Eco), 15000 (Eco+)
Optical	
Throw ratio	0,52:1
Projection distance (m)	0,4m - 3,4m
Focal length (mm)	7.51
Native offset	112%
Connectivity	
Connections	Inputs 1 x HDMI 1.4a 3D support, 1 x VGA (YPbPr/RGB),
	1 x Composite video, 1 x Audio 3.5mm
	Outputs 1 x VGA, 1 x Audio 3.5mm, 1 x USB-A power 1A
	Control 1 x RS232
General	
Noise level (typical)	26dB
Noise level (max)	28dB
, ,	
PC compatibility	FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac
2D compatibility	NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p,
	576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz)
3D compatibility	Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack:
	1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60
3D	Full 3D
Security	Security bar, Kensington Lock, Password protected interface
OSD / display languages	25 languages: Arabic, Czech, Danish, Dutch, English, Farsi,
ooz, aopa, angaego	Finnish, French, German, Greek, Hungarian, Indonesian,
	Italian, Japanese, Norwegian, Polish, Portuguese, Romanian
	Russian, Chinese (simplified), Spanish, Swedish, Chinese
	(traditional), Turkish, Vietnamese
Operating conditions	5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m
Remote control	Card style
Speaker count	1
Watts per speaker	10W
In the box	AC power cord
	Remote control Battery
	Basic user manual
Input lag	33,00ms
Optional wireless models	WHD200
Power	*** 10200
Power supply	100 ~ 240V, 50 ~ 60Hz
Power consumption	0.5W
(standby)	5.5vv
Power consumption (min)	187\//

187W

3,83 kg

3,26 kg

316 x 244 x 108



