

USB-C to 2.5G Ethernet Adapter

Part Number: K38285WW | UPC Code: 085896382850


Increase productivity and decrease down time.

Increase productivity and decrease down time. The USB-C to 2.5G Ethernet Adapter delivers transfer speeds up to 2.5 times faster than current solutions, providing a reliable connection and rapid data transfer speeds.* Bus-powered, with no power supply needed — simply connect it, and it works. Two-year warranty.

Features include:

- Up to 2.5 times faster than current 1Gbps speeds
- · Increased productivity, decreased down time
- · Bus-powered
- 2-year warranty







^{*} Your network must support 2.5Gbps Ethernet speeds over Cat5e or greater cabling.

Kensington

USB-C to 2.5G Ethernet Adapter

Part Number: K38285WW | UPC Code: 085896382850







Connect to a wired network via USB-C

Connecting the USB-C (male) connector to your device's USB-C or Thunderbolt 3 port, and the Ethernet cable to the RJ45 (female) port, will provide a secure hard-wired connection.

Up to 2.5 times faster than current 1Gbps speeds

Provides a reliable connection and rapid data transfer speeds*

Increased productivity, decreased down time

Faster upload and download speeds, lower latency and better reliability than wifi means less time waiting and more time doing





Bus-powered

No power supply needed — simply connect it, and it works

2-year warranty

Rest assured knowing you're covered by Kensington

^{*} Your network must support 2.5Gbps Ethernet speeds over Cat5e or greater cabling.

Kensington

USB-C to 2.5G Ethernet Adapter

Part Number: K38285WW | UPC Code: 085896382850

Cuctor	Dog	uirom	onto
System	INCO	unen	ICIILS

system Requirements	Operating Systems Supported	Windows 7 or greater, macOS 10.6 or greater
nput/ Output Connector	- F	22.1.2.1.2.1.0.1.1.1.1.1.1.1.1.1.1.1.1.1
	la purt	Tuno C Molo v1
	Input	Type-C Male ×1
	Output	RJ45 Female ×1
RJ45 Basic Specifications		
	Supported communication rate	10Mbps/100Mbps/1Gbps/2.5Gbps
	Main features supported	WOL(Wake-On-LAN) Full Duplex flow(10M/100M/1G/2.5G Rate) Auto-Negotiation
Product Dimensions		
	Product Unit Dimensions	Length: 2.93in / 74.5mm Width: 1.37in / 35mm Height: 0.61in / 15.5mm
	Weight	.07lbs / 34g
Environmental		
	Operating Temperature	0°C to 40°C / 32°F to 104°F
	Operating Humidity	10% to 85 % RH (no condensation)
	Storage Temperature	-10°C to 70°C / 14°F to 158°F
	Storage Humidity	5% to 90 % RH (no condensation)
Power Consumption		
·	Voltage	4.75V ~ 5.25V
	Standby Power	<60mA (When Ethernet cable is not connected
	Normal Operating Power	<80mA 10Mbps <130mA 100Mbps <300mA 1Gbps <460mA 2.5Gbps
Country of Origin, Regulatory	, and Warranty	
	Country of Origin	Vietnam
	Certifications	FCC,CE
	Warranty year	2 years
Package		
	Package Contents	Main unit x1, User Manual x1
	Packaging dimension	5.16 x 4.01 x .94 in (131 x 102 x 24 mm)
	Packaging weight	3 oz (0.085 kg)



