# Eaton 5P850IRBS

# Catalog Number: 5P850IRBS

Eaton 5P UPS, 850 VA, 600 W, Input: C14, Outputs: (4) C13, Rack, 1U, with BS input cord

# General specifications

Product Name	Catalog Number
Eaton 5P UPS	5P850IRBS
Model Code	EAN
Eaton 5P 850i Rack1U w/ BS Cord 10A	3553340620140
Product Length/Depth	Product Height
509 mm	43.2 mm
Product Width	Product Weight
438 mm	13.8 kg
Compliances CE Marked TUV	Certifications IEC/EN 62040-1 UL 1778 IEC/EN 62040-2 CE EAC cTUVus



Photo is representative



# Battery

#### Runtime graph

View runtime graph

Battery type Lead-acid maintenance-free (replaceable)

Battery replacement

User replaceable

Battery quantity

#### 2

#### Battery management

ABM or constant voltage charging method (user selectable), automatic battery test, deep discharge protection

#### Battery rating

12 V / 7 Ah

#### Extended battery capability

No

# Electrical output

Voltage

230V

Receptacle

(4) C13

Wattage 600 W

Output voltage range 230 V (+6%/-10%)

#### **Output frequency**

50/60 Hz

Output nominal voltage 230V default (200/208/220/230/240V)

#### Topology

Line-interactive

# Electrical input

Input connection

C14

Input nominal voltage 230V default (200/208/220/230/240V)

Nominal frequency

50-60 Hz

Input voltage range 160-294 V (adjustable to 150 V-294 V)

#### Input frequency range

47-70 Hz (50 Hz system), 56.5-70 Hz (60 Hz system), 40 Hz in low sensitivity mode

# Communications

#### Communication

USB port (HID compliant) Serial port (RS232) Mini-terminal block for remote On/Off and Remote

#### Environmental

Altitude 2000 m

Noise level
<40 dB at 1 meter</pre>

Temperature range

Power Off Dry contacts (2 outputs, optocoupler, RJ)

Ethernet interface

No

Potential free switch contact

Yes

Expansion slots One slot for optional communication card

Software compatibility

Eaton Intelligent Power Manager, Eaton Intelligent Power Protector

Type of interface

Other

0-90% non-condensing

BTU Rating Online: 123

Relative humidity 0-90% non-condensing

# Additional specifications

Form factor

Rack

Construction type 482.6 mm (19 inch) device

Enclosure

Black/silver

# Package contents

Rack-mounting kit Cable locking system USB cable Serial cable (2) IEC-IEC cables Quickstart guide Safety instructions BS input cord

#### Phase (output)

1

Auto shutdown function

Yes

Rack size

1U

Color Black/silver

Rack mounting kit

Yes

Efficiency

97

Phase (input)

1

# Resources

## Brochures

Eaton UPS and battery services - EN Eaton UPS Services Quick Guide - EN

Compliance information EC DoC Eaton 5P

#### Manuals and user guides

Eaton 5P UPS installation and user manual

Eaton 5P UPS Quick Start Guide

Eaton 5P UPS - Installation and user manual

#### Technical data sheets

Eaton 5P UPS Datasheet



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com © 2024 Eaton. All rights reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia