

# Eaton 5PX2200IRT3UG2BS

Catalog Number: 5PX2200IRT3UG2BS

Eaton 5PX Gen2 UPS, 2200 VA, 2200 W, Input: C20, Output: (8) C13, (2) C19, Rack/tower, 3U, with BS input cord

## General specifications



Photo is representative

Product Name	Catalog Number
Eaton 5PX Gen2 UPS	5PX2200IRT3UG2BS

Model Code	EAN
Eaton 5PX 2200i RT3U G2 w/ BS Cord 16A	3553340620874

Product Length/Depth
483 mm

Product Height
129 mm

Product Width
438 mm

Product Weight
27.5 kg

Compliances
IEC/EN 62040-1
IEC/EN 62040-2
IEC/EN 62040-3
RoHS Compliant
REACH
UL 1778
CSA 22.2

Certifications
CE
cTUVus
EAC
Cm
UKCA
Ukr
ENERGY STAR certified

## Battery

### Battery type

Lead-acid maintenance-free (replaceable)

### Runtime graph

View runtime graph

### Battery replacement

User replaceable

### Battery quantity

6

### Battery management

ABM & Temperature compensated charging method (user selectable), Automatic battery test, deep discharge protection, automatic recognition of external battery units

### Battery rating

12 V / 7 Ah

### Extended battery capability

Yes

## Electrical output

### Receptacle

(8) C13, (2) C19

### Voltage

230V

### Wattage

2200 W

### Output power factor

1

### Output voltage range

230 V (+6%/-10%)

### Output waveform

Sine wave

### Output nominal voltage

230V default (200/208/220/230/240V)

### Feed type

1

### Topology

Line-interactive

### VA rating

2200 VA

## Electrical input

### Input connection

C20

### Input nominal voltage

230V default (200/208/220/230/240V)

### Nominal frequency

50-60 Hz

### Input cord length

1.8m

### Input voltage range

160-294 V (adjustable to 150 V-294 V)

### Input frequency range

47-70 Hz (50 Hz system), 56.5-70 Hz (60 Hz system), 40 Hz in low sensitivity mode

## Communications

### Includes network card

No

### Communication

USB port (HID compliant)

Serial port (RS232)

Mini-terminal block for remote On/Off and Remote

Power Off

Mini-terminal block for output relay

Dry contacts (3 outputs, 1 input, optocoupler, DB9)

### User interface

Multilingual graphical LCD display

#### Potential free switch contact

Yes

#### Expansion slots

One slot for optional communication card

#### Software compatibility

Eaton Intelligent Power Manager, Eaton Intelligent Power Protector

#### Type of interface

Other

## Environmental

#### Altitude

3000 m

#### Noise level

<40 dB at 1 meter

#### Temperature range

0° to 40°C (32° to 104°F), batteries recommended max. 25°C (77°F)

#### Relative humidity

0-90% non-condensing

## Additional specifications

#### Construction type

482.6 mm (19 inch) device

#### Package contents

Input cable  
Rack-mounting kit  
(2) Supports for tower mounting  
Cable locking system  
USB cable  
Serial cable  
(2) IEC-IEC cables  
Quickstart guide  
Safety instructions  
BS input cord

#### Phase (output)

1

#### Auto shutdown function

Yes

#### Color

Black/silver

#### Efficiency

98

#### Rack mounting kit

Yes

#### Phase (input)

1

## Resources

#### Brochures

[Eaton UPS and battery services - EN](#)



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2024 Eaton. All rights reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)