

# Product datasheet

Specifications



Device monitoring and management, Network Management Cards, NMC3 with Environmental Monitoring and Modbus, secure remote UPS monitoring and management

AP9643

## Overview

Lead time Usually in Stock

## Main

Range of product Network Management Cards

Range compatibility  
Galaxy VM  
Galaxy VX  
Symmetra PX  
Smart-UPS  
Smart-UPS Ultra  
Smart-UPS On-Line  
Smart-UPS Modular Ultra  
Smart-UPS Battery Systems  
Back-UPS SX3  
Refurbished Smart-UPS

Provided equipment  
Temperature sensor  
Micro-USB cable  
Installation manual

Number of input phases  
1  
3

Product or component type Device monitoring and management

## General

Variant option Environmental monitoring with Modbus

## Physical

Net weight 0.14 kg

Width 12.1 cm

Height 3.8 cm

Depth 10.8 cm

## Conformance

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

<b>Standards</b>	EN 61000-4-2 BS EN 61000-4-2 EN 61000-4-3 BS EN 61000-4-3 EN 61000-4-4 BS EN 61000-4-4 EN 61000-4-5 BS EN 61000-4-5 EN 61000-4-6 BS EN 61000-4-6 EN 61000-4-8 BS EN 61000-4-8 EN 61000-4-11 BS EN 61000-4-11 BS EN 55024 EN 55035 BS EN 55035 EN 62040-2 BS EN 62040-2 VCCI class A
------------------	--

<b>Product certifications</b>	FCC Class A BS EN 55011 AS/NZS BS EN 55032
-------------------------------	---

<b>Standards</b>	EN 61000-4-2 BS EN 61000-4-2 EN 61000-4-3 BS EN 61000-4-3 EN 61000-4-4 BS EN 61000-4-4 EN 61000-4-5 BS EN 61000-4-5 EN 61000-4-6 BS EN 61000-4-6 EN 61000-4-8 BS EN 61000-4-8 EN 61000-4-11 BS EN 61000-4-11 BS EN 55024 EN 55035 BS EN 55035 EN 62040-2 BS EN 62040-2 VCCI class A EN 55011:A1 EN 55024:A1 EN 55032:class A
------------------	--

## Environmental

<b>Storage Relative Humidity</b>	0...95 %
<b>Relative humidity</b>	0...95 %
<b>Ambient air temperature for storage</b>	-15...65 °C
<b>Ambient air temperature for operation</b>	-5...45 °C
<b>Storage altitude</b>	0.0000000000...15240.0000000000 m
<b>Operating altitude</b>	0...10000 ft

## Communications & Management

<b>Communication network type</b>	10/100/1000BASE-T
<b>Authentication</b>	Radius Lightweight Directory Access Protocol (LDAP)

---

<b>Communication port protocol</b>	HTTP over secure sockets Layer (HTTPS) SSH FTP HTTP SNMP DHCP BOOTP (Bootstrap Protocol) TCP/IP
------------------------------------	---

## Packing Units

---

<b>Unit Type of Package 1</b>	PCE
-------------------------------	-----

---

<b>Number of Units in Package 1</b>	1
-------------------------------------	---

---

<b>Package 1 Height</b>	5.1 cm
-------------------------	--------

---

<b>Package 1 Width</b>	15.9 cm
------------------------	---------

---

<b>Package 1 Length</b>	23.5 cm
-------------------------	---------

---

<b>Package 1 Weight</b>	0.91 kg
-------------------------	---------

## Contractual warranty

---

<b>Warranty</b>	18 months
-----------------	-----------

## Sustainability

**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

[Learn more about Green Premium >](#)



Transparency RoHS/REACH

## Well-being performance

- Reach Free Of Svhc
- Toxic Heavy Metal Free
- Mercury Free
- Rohs Exemption Information Yes

## Certifications & Standards

<b>Reach Regulation</b>	<a href="#">REACH Declaration</a>
<b>Eu Rohs Directive</b>	Compliant <a href="#">EU RoHS Declaration</a>
<b>China Rohs Regulation</b>	<a href="#">China RoHS declaration</a> Pro-active China RoHS declaration (out of China RoHS legal scope)
<b>Environmental Disclosure</b>	<a href="#">Product Environmental Profile</a>
<b>Weee</b>	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
<b>Circularity Profile</b>	<a href="#">End of Life Information</a>