



Technical Data Sheet



Technical Data Sheet
Ref: PR26000
Issued: 13.10.22
Number of pages: 2

Pritt Multi-Purpose Glue

CHARACTERISTICS

Water based, clear, washable, poly vinyl alcohol based adhesive
Solvent free
Can be completely washed out of fabrics

APPLICATION FIELD

Suitable for sticking a wide range of art and craft materials including paper, card, fabric, wood and pasta.

INSTRUCTIONS FOR USE

Pretreatment

Not necessary. In general, surfaces have to be clean, dry and free of dust and grease.

TECHNICAL DATA

Composition	Water, poly vinyl alcohol, antifoam and preservative.
Appearance	Clear, viscous liquid
Solids content	15 – 20%
Temperature range	+5° to +30°C
Cure type	Water evaporation
Open time*	Up to 10 minutes, dependent on type and porosity of substrates to be bonded.
Setting time*	1 to 2 hours, dependant on type and porosity of substrates to be bonded. Fully dry within 24 hours.
Colour	Clear
Shelf Life	12 months at 20°C

* parameter depends on ambient temperature, moisture content and thickness (characteristic) of the materials.





LIMITATIONS

Not suitable for bonding plastics or for bonding non-porous surfaces to non-porous surfaces. May wrinkle very thin decorative papers and vellum.

Should only be applied to clean, dry surfaces free of dust, grease, polish and moisture.

Storage

Keep tightly closed and store in a dry and cool place. Avoid temperatures below 5°C and over 50°C.

HEALTH AND SAFETY

Before using the product please see related Material Safety Data Sheet that is available on request.

"The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. The product can have a variety of different applications as well as differing application and working conditions in your environment that are beyond our control. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product.

Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law."

Henkel Limited

Wood Lane End, Hemel Hempstead, Hertfordshire HP2 4RQ

Phone: +44 (0) 1606 593 933

Internet: www.henkel.co.uk

email: technical.services@henkel.co.uk