

# SAFETY DATA SHEET



Vanish Carpet Foam Deep Cleaner

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

**Product name** : Vanish Carpet Foam Deep Cleaner  
**SDS no.** : PSDS9804180  
**Formulation #** : FRM 50004032 / 3271448  
**Product type** : Aerosol.

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

#### Identified uses

Cleaning Products, Consumer use

### 1.3 Details of the supplier of the safety data sheet

#### Supplier

##### The United Kingdom:

RB UK Hygiene Home Commercial Ltd  
Wellcroft House  
Wellcroft Road  
Slough, Berkshire  
SL1 4AQ  
Tel: 0800 376 8181  
Email: ConsumerCare\_UK@reckitt.com

##### The Republic Of Ireland:

RB Ireland Hygiene Home Commercial Ltd  
7 Riverwalk  
Citywest Business Campus  
Dublin 24  
Ireland  
Tel: 01 661 7318  
Email: ConsumerHealth\_IE@reckitt.com

### 1.4 Emergency telephone number

#### National advisory body/Poison Centre

**Telephone number** : **GB** - NHS 111/NHS 24 Tel: 111  
**NI** - [www.gpoutofhours.hscni.net/](http://www.gpoutofhours.hscni.net/)  
**IE** - Poisons Information Centre of Ireland: 01 809 2166 8am-10pm 7 days a week

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

**Product definition** : Mixture

#### Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Aerosol 1, H222, H229

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.


See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

PSDS9804180

SECTION 2: Hazards identification

2.2 Label elements

|   |   |
|---|---|
| Hazard pictograms                                       | :    |
| Signal word   | : Danger  |
| Hazard statements                                       | : Extremely flammable aerosol. Pressurised container: may burst if heated.  |
| <u>Precautionary statements</u>                         |   |
| General   | : Keep out of reach of children. If medical advice is needed, have product container or label at hand.  |
| Prevention  | : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Wash hands thoroughly after handling. Do not pierce or burn, even after use. |
| Response  | : Not applicable.   |
| Storage   | : Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.  |
| Disposal  | : Not applicable  |
| Hazardous ingredients                                   | : Not applicable.   |
| Supplemental label elements                             | : <b>Ingredient declaration:</b><br><br>< 5%: Aliphatic Hydrocarbons, Anionic surfactants, Polycarboxylates, Phosphates, Perfumes, Limonene.  |
| <u>Special packaging requirements</u>                   |   |
| Containers to be fitted with child-resistant fastenings | : Not applicable.   |
| Tactile warning of danger                               | : Not applicable.   |

2.3 Other hazards

|   |   |
|---|---|
| Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII | : This mixture does not contain any substances that are assessed to be a PBT or a vPvB. |
| Other hazards which do not result in classification   | : None known.   |

SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture

| Product/ingredient name                               | Identifiers   | %       | Classification   | Specific Conc. Limits, M-factors and ATEs                                   | Type |
|---|---|---------|--|---|------|
| BUTANE  | REACH #:<br>01-2119474691-32<br>EC: 203-448-7<br>CAS: 106-97-8<br>Index: 601-004-00-0 | ≥3 - ≤5 | Flam. Gas 1A, H220<br>Press. Gas (Comp.),<br>H280  | -   | [2]  |
| Sulfuric acid, mono-C12-14-alkyl esters, sodium salts | REACH #:<br>01-2119489463-28<br>EC: 287-809-4<br>CAS: 85586-07-8                      | ≥1 - ≤3 | Acute Tox. 4, H302<br>Skin Irrit. 2, H315<br>Eye Dam. 1, H318<br>Aquatic Chronic 3, H412 | ATE [Oral] = 1800 mg/kg<br>Eye Dam. 1, H318: C ≥ 20%<br>Eye Irrit. 2, H319: | [1]  |

PSDS9804180

### SECTION 3: Composition/information on ingredients

|                               |  |           |  |  |     |
|-------------------------------|--|-----------|--|--|-----|
| PROPANE                       | REACH #:<br>01-2119486944-21<br>EC: 200-827-9<br>CAS: 74-98-6<br>Index: 601-003-00-5 | ≥1 - ≤3   | Flam. Gas 1A, H220<br>Press. Gas (Comp.),<br>H280  | 10% ≤ C < 20%<br>-   | [2] |
| SODIUM LAUROYL<br>SARCOSINATE | REACH #:<br>01-2119527780-39<br>EC: 205-281-5<br>CAS: 137-16-6                       | ≥0.3 - <1 | Acute Tox. 2, H330<br>Skin Irrit. 2, H315<br>Eye Dam. 1, H318<br><br><b>See Section 16 for<br/>the full text of the H<br/>statements declared<br/>above.</b> | ATE [Inhalation<br>(dusts and mists)]<br>= 0.05 mg/l<br>Skin Irrit. 2, H315:<br>C ≥ 30%<br>Eye Dam. 1, H318:<br>C ≥ 30%<br>Eye Irrit. 2, H319:<br>1% ≤ C < 30% | [1] |

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

#### Type

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Get medical attention if irritation occurs.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing.
- Skin contact** : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur.
- Ingestion** : Wash out mouth with water. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Do not induce vomiting unless directed to do so by medical personnel.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training.

#### 4.2 Most important symptoms and effects, both acute and delayed

##### Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:  
irritation  
redness
- Inhalation** : Adverse symptoms may include the following:  
respiratory tract irritation  
coughing
- Skin contact** : No specific data.
- Ingestion** : No specific data.

#### 4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

PSDS9804180

## SECTION 4: First aid measures

**Specific treatments** : No specific treatment.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

**Suitable extinguishing media** : Use an extinguishing agent suitable for the surrounding fire.

**Unsuitable extinguishing media** : None known.

### 5.2 Special hazards arising from the substance or mixture

**Hazards from the substance or mixture** : Extremely flammable aerosol. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Gas may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back, causing fire or explosion. Bursting aerosol containers may be propelled from a fire at high speed.

**Hazardous combustion products** : Decomposition products may include the following materials:  
carbon dioxide  
carbon monoxide  
sulfur oxides  
metal oxide/oxides

### 5.3 Advice for firefighters

**Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

**Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

**For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. In the case of aerosols being ruptured, care should be taken due to the rapid escape of the pressurised contents and propellant. If a large number of containers are ruptured, treat as a bulk material spillage according to the instructions in the clean-up section. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Put on appropriate personal protective equipment.

**For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

### 6.2 Environmental precautions

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

### 6.3 Methods and material for containment and cleaning up

**Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

SECTION 6: Accidental release measures

- Large spill

: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product.
- 6.4 Reference to other sections

: See Section 1 for emergency contact information.  
See Section 8 for information on appropriate personal protective equipment.  
See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

- Protective measures

: Put on appropriate personal protective equipment (see Section 8). Pressurised container: protect from sunlight and do not expose to temperature exceeding 50°C. Do not pierce or burn, even after use. Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing gas. Avoid breathing vapour or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Empty containers retain product residue and can be hazardous.
- Advice on general occupational hygiene

: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store away from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Eliminate all ignition sources. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Seveso Directive - Reporting thresholds (in tonnes)

| Danger criteria |                                 |                         |
|-----------------|---------------------------------|-------------------------|
| Category        | Notification and MAPP threshold | Safety report threshold |
| P3a             | 150                             | 500                     |

7.3 Specific end use(s)

- Recommendations

: Cleaning Products, Consumer use
- Industrial sector specific solutions

: Not available.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits

| Product/ingredient name | Exposure limit values  |
|-------------------------|--|
| BUTANE                  | NAOSH (Ireland, 5/2021). [butane] Notes: Advisory Occupational Exposure Limit Values (OELVs)<br>OELV-15min: 1000 ppm 15 minutes. |
| PROPANE                 | NAOSH (Ireland, 5/2021). Oxygen Depletion [Asphyxiant]. Notes: Advisory Occupational Exposure Limit Values (OELVs)               |

**Recommended monitoring procedures** : Reference should be made to monitoring standards, such as the following:  
European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy)  
European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents)  
European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents)  
Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

| Product/ingredient name                               | Type | Exposure             | Value              | Population                     | Effects  |
|---|------|----------------------|--------------------|--------------------------------|----------|
| Sulfuric acid, mono-C12-14-alkyl esters, sodium salts | DNEL | Long term Dermal     | 4060 mg/kg bw/day  | Workers                        | Systemic |
|   | DNEL | Long term Inhalation | 285 mg/m³          | Workers                        | Systemic |
|   | DNEL | Long term Oral       | 24 mg/kg bw/day    | General population [Consumers] | Systemic |
|   | DNEL | Long term Inhalation | 85 mg/m³           | General population [Consumers] | Systemic |
|   | DNEL | Long term Dermal     | 2440 mg/kg bw/day  | General population [Consumers] | Systemic |
|   | DNEL | Long term Oral       | 24 mg/kg bw/day    | General population             | Systemic |
|   | DNEL | Long term Inhalation | 85 mg/m³           | General population             | Systemic |
|   | DNEL | Long term Inhalation | 285 mg/m³          | Workers                        | Systemic |
|   | DNEL | Long term Dermal     | 2440 mg/kg bw/day  | General population             | Systemic |
|   | DNEL | Long term Dermal     | 4060 mg/kg bw/day  | Workers                        | Systemic |
| SODIUM LAUROYL SARCOSINATE                            | DNEL | Long term Inhalation | 70.53 mg/m³        | Workers                        | Systemic |
|   | DNEL | Long term Dermal     | 20 mg/kg bw/day    | Workers                        | Systemic |
|   | DNEL | Long term Inhalation | 17.39 mg/kg bw/day | General population [Consumers] | Systemic |
|   | DNEL | Long term Dermal     | 10 mg/kg bw/day    | General population [Consumers] | Systemic |
|   | DNEL | Long term Oral       | 10 mg/kg bw/day    | General population [Consumers] | Systemic |

PSDS9804180

SECTION 8: Exposure controls/personal protection

|  |      |                      |                 |                    |          |
|--|------|----------------------|-----------------|--------------------|----------|
|  | DNEL | Long term Oral       | 10 mg/kg bw/day | General population | Systemic |
|  | DNEL | Long term Dermal     | 10 mg/kg bw/day | General population | Systemic |
|  | DNEL | Long term Inhalation | 17.39 mg/m³     | General population | Systemic |
|  | DNEL | Long term Dermal     | 20 mg/kg bw/day | Workers            | Systemic |
|  | DNEL | Long term Inhalation | 70.53 mg/m³     | Workers            | Systemic |

PNECs

| Product/ingredient name                               | Compartment Detail     | Value          | Method Detail            |
|---|------------------------|----------------|--------------------------|
| Sulfuric acid, mono-C12-14-alkyl esters, sodium salts | Fresh water            | 0.131 mg/l     | -                        |
|   | Marine water           | 0.0131 mg/l    | -                        |
|   | Fresh water sediment   | 4.61 mg/kg     | -                        |
|   | Marine water sediment  | 0.461 mg/kg    | -                        |
|   | Soil                   | 0.846 mg/kg    | -                        |
|   | Sewage Treatment Plant | 1.35 mg/l      | -                        |
| SODIUM LAUROYL SARCOSINATE                            | Fresh water            | 0.03 mg/l      | Assessment Factors       |
|   | Marine water           | 0.003 mg/l     | Assessment Factors       |
|   | Sewage Treatment Plant | 10 mg/l        | Assessment Factors       |
|   | Fresh water sediment   | 0.034 mg/l     | Equilibrium Partitioning |
| ACRYLIC ACID  | Marine water sediment  | 0.003 mg/l     | Equilibrium Partitioning |
|   | Soil                   | 0.012 mg/kg dw | Equilibrium Partitioning |
|   | Fresh water            | 0.003 mg/kg dw | Assessment Factors       |
|   | Sewage Treatment Plant | 0.9 mg/l       | Assessment Factors       |
| BHT   | Fresh water sediment   | 0.024 mg/kg dw | Equilibrium Partitioning |
|   | Marine water sediment  | 0.002 mg/kg dw | Equilibrium Partitioning |
|   | Soil                   | 1 mg/kg dw     | Assessment Factors       |
|   | Fresh water            | 0.199 µg/l     | Assessment Factors       |
|   | Marine water           | 0.02 µg/l      | Assessment Factors       |
|   | Soil                   | 47.69 µg/kg ww | Equilibrium Partitioning |

8.2 Exposure controls

**Appropriate engineering controls** : Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapour or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Individual protection measures

**Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

**Eye/face protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.

Skin protection

## SECTION 8: Exposure controls/personal protection

- Hand protection** : EN 16523-1:2015  
Tested for protection against chemical permeation.  
Low chemical resistant or waterproof gloves.  
(EN 16523-1:2015 supersedes EN 374-3:2003)  
EN 374-2:2003  
Tested for protection against liquid penetration and micro-organisms.  
EN 388:2003  
Tested for protection against mechanical risks (abrasion, blade cut resistance, tear resistance and puncture resistance).  
ISO 374-1:2016/Type A  
Protective glove with permeation resistance of at least 30 minutes each for at least 6 test chemicals.  
ISO 374-1:2016/Type B  
Protective glove with permeation resistance of at least 30 minutes each for at least 3 test chemicals.  
ISO 374-1:2016/Type C  
Protective glove with permeation resistance of at least 10 minutes for at least 1 test chemical. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves. Refer to European Standard EN 1149 for further information on material and design requirements and test methods.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

## SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

### 9.1 Information on basic physical and chemical properties

#### Appearance

- Physical state** : Liquid.
- Colour** : Not determined
- Odour** : Fragrant.
- Melting point/freezing point** : Not relevant/applicable due to nature of the product.
- Initial boiling point and boiling range** : Not relevant/applicable due to nature of the product.
- Flammability (solid, gas)** : Not relevant/applicable due to nature of the product.
- Upper/lower flammability or explosive limits** : Not relevant/applicable due to nature of the product.
- Flash point** : Not relevant/applicable due to nature of the product.
- Auto-ignition temperature** : Not relevant/applicable due to nature of the product.

PSDS9804180

SECTION 9: Physical and chemical properties

|   |   |
|---|---|
| Decomposition temperature               | : Not relevant/applicable due to nature of the product. |
| pH                                      | : 10.09 to 10.49  |
| Viscosity                               | : Not relevant/applicable due to nature of the product. |
| Solubility in water                     | : Not relevant/applicable due to nature of the product. |
| Partition coefficient: n-octanol/ water | : Not relevant/applicable due to nature of the product. |
| Vapour pressure                         | : Not relevant/applicable due to nature of the product. |
| Relative density                        | : 0.96 to 0.98  |
| Density                                 | : 0.96 to 0.98 g/cm³                                    |
| Vapour density                          | : Not relevant/applicable due to nature of the product. |
| Particle characteristics                |   |
| Median particle size                    | : Not relevant/applicable due to nature of the product. |
| 9.2 Other information                   |   |
| Heat of combustion                      | : 2.398 kJ/g  |
| Aerosol product                         |   |
| Type of aerosol                         | : Foam  |

SECTION 10: Stability and reactivity

|   |  |
|---|--|
| 10.1 Reactivity                         | : No specific test data related to reactivity available for this product or its ingredients.           |
| 10.2 Chemical stability                 | : The product is stable.   |
| 10.3 Possibility of hazardous reactions | : Under normal conditions of storage and use, hazardous reactions will not occur.                      |
| 10.4 Conditions to avoid                | : Avoid all possible sources of ignition (spark or flame).   |
| 10.5 Incompatible materials             | : No specific data.  |
| 10.6 Hazardous decomposition products   | : Under normal conditions of storage and use, hazardous decomposition products should not be produced. |

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

| Product/ingredient name                               | Result                          | Species | Dose         | Exposure |
|---|---------------------------------|---------|--------------|----------|
| BUTANE  | LC50 Inhalation Vapour          | Rat     | 658000 mg/m³ | 4 hours  |
| Sulfuric acid, mono-C12-14-alkyl esters, sodium salts | LD50 Oral                       | Rat     | 1800 mg/kg   | -        |
| SODIUM LAUROYL SARCOSINATE                            | LC50 Inhalation Dusts and mists | Rat     | 0.05 mg/l    | 4 hours  |

Conclusion/Summary

: Based on available data, the classification criteria are not met.

Acute toxicity estimates

PSDS9804180

SECTION 11: Toxicological information

| Product/ingredient name                               | Oral (mg/kg) | Dermal (mg/kg) | Inhalation (gases) (ppm) | Inhalation (vapours) (mg/l) | Inhalation (dusts and mists) (mg/l) |
|---|--------------|----------------|--------------------------|-----------------------------|-------------------------------------|
| FIL,VANSH,CC, PET FOAM_FRM50004032 (PSDS9804180)_EU   | 136364.2     | N/A            | N/A                      | N/A                         | 5.9                                 |
| BUTANE  | N/A          | N/A            | N/A                      | 658                         | N/A                                 |
| Sulfuric acid, mono-C12-14-alkyl esters, sodium salts | 1800         | N/A            | N/A                      | N/A                         | N/A                                 |
| SODIUM LAUROYL SARCOSINATE                            | N/A          | N/A            | N/A                      | N/A                         | 0.05                                |

Irritation/Corrosion

| Product/ingredient name                               | Result                 | Species    | Score | Exposure | Observation |
|---|------------------------|------------|-------|----------|-------------|
| Sulfuric acid, mono-C12-14-alkyl esters, sodium salts | Eyes - Severe irritant | Rabbit     | -     | -        | -           |
|   | Skin - Erythema/Eschar | Guinea pig | 0     | -        | -           |
|   | Skin - Irritant        | Rabbit     | -     | -        | -           |

Conclusion/Summary

- Skin : Based on available data, the classification criteria are not met.
- Eyes : Based on available data, the classification criteria are not met.
- Respiratory : Based on available data, the classification criteria are not met.

Sensitisation

Conclusion/Summary

- Skin : Based on available data, the classification criteria are not met.
- Respiratory : Based on available data, the classification criteria are not met.

Mutagenicity

| Product/ingredient name                               | Test     | Experiment  | Result   |
|---|----------|---|----------|
| Sulfuric acid, mono-C12-14-alkyl esters, sodium salts | OECD 476 | Experiment: In vitro<br>Subject: Mammalian-Animal | Negative |
|   | OECD 471 | Subject: Bacteria                                 | Negative |
|   | OECD 474 | Subject: Mammalian-Animal                         | Negative |

- Conclusion/Summary : Based on available data, the classification criteria are not met.

Carcinogenicity

- Conclusion/Summary : Based on available data, the classification criteria are not met.

Reproductive toxicity

- Conclusion/Summary : Based on available data, the classification criteria are not met.

Teratogenicity

- Conclusion/Summary : Based on available data, the classification criteria are not met.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Information on likely routes of exposure : Not available.

Potential acute health effects

- Eye contact : No known significant effects or critical hazards.

PSDS9804180

SECTION 11: Toxicological information

Inhalation : No known significant effects or critical hazards.  
Skin contact : No known significant effects or critical hazards.  
Ingestion : No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : Adverse symptoms may include the following:  
irritation  
redness  
Inhalation : Adverse symptoms may include the following:  
respiratory tract irritation  
coughing  
Skin contact : No specific data.  
Ingestion : No specific data.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure

Potential immediate effects : Not available.  
Potential delayed effects : Not available.

Long term exposure

Potential immediate effects : Not available.  
Potential delayed effects : Not available.

Potential chronic health effects

Not available.

Conclusion/Summary : Based on available data, the classification criteria are not met.  
General : No known significant effects or critical hazards.  
Carcinogenicity : No known significant effects or critical hazards.  
Mutagenicity : No known significant effects or critical hazards.  
Reproductive toxicity : No known significant effects or critical hazards.

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

11.2.2 Other information

Not available.

SECTION 12: Ecological information

12.1 Toxicity

Conclusion/Summary : Based on available data, the classification criteria are not met.

12.2 Persistence and degradability

| Product/ingredient name                               | Test      | Result                     | Dose | Inoculum |
|---|-----------|----------------------------|------|----------|
| Sulfuric acid, mono-C12-14-alkyl esters, sodium salts | OECD 301B | 75.7 % - Readily - 28 days | -    | -        |

PSDS9804180

SECTION 12: Ecological information

**Conclusion/Summary** : The surfactant(s) contained in this preparation complies(comply) with the biodegradability criteria as laid down in Regulation (EC) No.648/2004 on detergents. Data to support this assertion are held at the disposal of the competent authorities of the Member States and will be made available to them, at their direct request or at the request of a detergent manufacturer.

| Product/ingredient name                               | Aquatic half-life | Photolysis | Biodegradability |
|---|-------------------|------------|------------------|
| Sulfuric acid, mono-C12-14-alkyl esters, sodium salts | -                 | -          | Readily          |

12.3 Bioaccumulative potential

| Product/ingredient name                               | LogP <sub>ow</sub> | BCF | Potential |
|---|--------------------|-----|-----------|
| BUTANE  | 2.89               | -   | low       |
| Sulfuric acid, mono-C12-14-alkyl esters, sodium salts | -2.42              | -   | low       |
| PROPANE   | 1.09               | -   | low       |

12.4 Mobility in soil

**Soil/water partition coefficient (K<sub>oc</sub>)** : Not available.

**Mobility** : Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Endocrine disrupting properties

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

**Product**

**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

**Hazardous waste** : The classification of the product may meet the criteria for a hazardous waste.





**Packaging**

**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

**Special precautions** : This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Do not puncture or incinerate container.

## SECTION 14: Transport information

For long distance transport of bulk material or shrunk pallet take into consideration sections 7 and 10.

|                                 | ADR/RID  | ADN  | IMDG  | IATA   |
|---------------------------------|--|--|---|--|
| 14.1 UN number or ID number     | UN1950   | UN1950   | UN1950  | UN1950   |
| 14.2 UN proper shipping name    | AEROSOLS   | AEROSOLS   | AEROSOLS  | Aerosols, flammable  |
| 14.3 Transport hazard class(es) | 2<br> | 2<br> | 2.1<br> | 2.1<br> |
| 14.4 Packing group              | -  | -  | -   | -  |
| 14.5 Environmental hazards      | No.  | No.  | No.   | No.  |

### Additional information

- ADR/RID** : **Limited quantity** 1 L  
**Special provisions** 190, 327, 625, 344  
**Tunnel code** (D)
- ADN** : **Special provisions** 190, 327, 625, 344
- IMDG** : **Emergency schedules** F-D, S-U  
**Special provisions** 63, 190, 277, 327, 344, 381, 959
- IATA** : **Quantity limitation** Passenger and Cargo Aircraft: 75 kg. Packaging instructions: 203. Cargo Aircraft Only: 150 kg. Packaging instructions: 203. Limited Quantities - Passenger Aircraft: 30 kg. Packaging instructions: Y203.  
**Special provisions** A145, A167, A802
- 14.6 Special precautions for user** : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

**14.7 Maritime transport in bulk according to IMO instruments** : Not available.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU Regulation (EC) No. 1907/2006 (REACH)

##### Annex XIV - List of substances subject to authorisation

###### Annex XIV

None of the components are listed.

###### Substances of very high concern

None of the components are listed.

**Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles** : None.

##### Other EU regulations

PSDS9804180

SECTION 15: Regulatory information

Industrial emissions (integrated pollution prevention and control) - Air

: Listed

Ozone depleting substances (1005/2009/EU)

Not listed.

Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

Persistent Organic Pollutants

Not listed.

Aerosol dispensers

:

3



Extremely flammable

Seveso Directive

This product is controlled under the Seveso Directive.

Danger criteria

| Category |
|----------|
| P3a      |

15.2 Chemical safety assessment : No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and acronyms : ATE = Acute Toxicity Estimate  
CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]  
DMEL = Derived Minimal Effect Level  
DNEL = Derived No Effect Level  
EUH statement = CLP-specific Hazard statement  
PBT = Persistent, Bioaccumulative and Toxic  
PNEC = Predicted No Effect Concentration  
RRN = REACH Registration Number  
vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

| Classification        | Justification         |
|-----------------------|-----------------------|
| Aerosol 1, H222, H229 | On basis of test data |

Full text of abbreviated H statements


PSDS9804180

SECTION 16: Other information

|                    |  |
|--------------------|--|
| H220<br>H222, H229 | Extremely flammable gas.<br>Extremely flammable aerosol. Pressurised container: may burst if heated. |
| H280               | Contains gas under pressure; may explode if heated.  |
| H302               | Harmful if swallowed.  |
| H315               | Causes skin irritation.  |
| H318               | Causes serious eye damage.   |
| H330               | Fatal if inhaled.  |
| H412               | Harmful to aquatic life with long lasting effects.   |

Full text of classifications [CLP/GHS]

|   |  |
|---|--|
| Acute Tox. 2<br>Acute Tox. 4<br>Aerosol 1<br>Aquatic Chronic 3<br>Eye Dam. 1<br>Flam. Gas 1A<br>Press. Gas (Comp.)<br>Skin Irrit. 2 | ACUTE TOXICITY - Category 2<br>ACUTE TOXICITY - Category 4<br>AEROSOLS - Category 1<br>LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3<br>SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1<br>FLAMMABLE GASES - Category 1A<br>GASES UNDER PRESSURE - Compressed gas<br>SKIN CORROSION/IRRITATION - Category 2 |
|---|--|

**Date of printing** : 09/08/2024  
**Date of issue/ Date of revision** : 17/05/2024  
**Date of previous issue** :  No previous validation  
**Version** : 1

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.  
Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.