

Specifications

Photo is representative

Eaton 5SC2200IRTBS

Eaton 5SC UPS, 2200 VA, 1980 W, Input: C20, Outputs: (8) C13, (1) C19, Rack/tower, 2U, with BS input cord

General specifications

PRODUCT NAME	Eaton 5SC UPS
CATALOG NUMBER	5SC2200IRTBS
MODEL CODE	Eaton 5SC 2200i RT2U w/ BS Cord 16A
EAN	3553340620355
PRODUCT LENGTH/DEPTH	441 mm
PRODUCT HEIGHT	86.2 mm
PRODUCT WIDTH	522 mm
PRODUCT WEIGHT	26.7 kg
COMPLIANCES	CE Marked TUV
CERTIFICATIONS	IEC/EN 62040-1 UL 1778 IEC/EN 62040-2 CE EAC cTUVus



Battery

BATTERY TYPE	Lead-acid maintenance-free (replaceable)
RUNTIME GRAPH	View runtime graph
BATTERY REPLACEMENT	User replaceable
BATTERY QUANTITY	4
BATTERY MANAGEMENT	ABM or constant voltage charging method (user selectable), automatic battery test, deep discharge protection
BATTERY RATING	12 V / 9 Ah
EXTENDED BATTERY CAPABILITY	No

Electrical output

RECEPTACLE	(8) C13, (1) C19
VOLTAGE	230V
WATTAGE	1980 W
OUTPUT POWER FACTOR	0.9
OUTPUT VOLTAGE RANGE	230 V (+6%/-10%)
OUTPUT WAVEFORM	Sine wave
OUTPUT NOMINAL VOLTAGE	230V default (220/230/240V)
FEED TYPE	1
TOPOLOGY	Line-interactive
VA RATING	2200 VA

Electrical input	
INPUT CONNECTION	C20
INPUT NOMINAL VOLTAGE	230V default (220/230/240V)
NOMINAL FREQUENCY	50-60 Hz
INPUT CORD LENGTH	1.8m
INPUT VOLTAGE RANGE	184-276 V
INPUT FREQUENCY RANGE	45-55 Hz (50 Hz system), 55-65 Hz (60 Hz system)

Environmental	
ALTITUDE	3000 m
NOISE LEVEL	<40 dB at 1 meter
TEMPERATURE RANGE	0-90% non-condensing
RELATIVE HUMIDITY	0-90% non-condensing

Resources	
BROCHURES	Eaton UPS and battery services - EN
	Eaton UPS Services Quick Guide - EN

Communications	
INCLUDES NETWORK CARD	No
COMMUNICATION	<ul style="list-style-type: none"> • USB port (HID compliant) • Serial port (RS232) • Mini-terminal block for remote On/Off and Remote Power Off • Dry contacts (2 outputs, optocoupler, RJ)
ETHERNET INTERFACE	No
USER INTERFACE	LCD Display
POTENTIAL FREE SWITCH CONTACT	Yes
EXPANSION SLOTS	One slot for optional communication card
SOFTWARE COMPATIBILITY	Eaton Intelligent Power Manager, Eaton Intelligent Power Protector
TYPE OF INTERFACE	Other

Additional specifications	
CONSTRUCTION TYPE	482.6 mm (19 inch) device
ENCLOSURE	Black
PACKAGE CONTENTS	<ul style="list-style-type: none"> • Input cable • Rack-mounting kit • Cable locking system • USB cable • Serial cable • (2) IEC-IEC cables • Quickstart guide • Safety instructions • BS input cord
PHASE (OUTPUT)	1
AUTO SHUTDOWN FUNCTION	Yes
COLOR	Black
EFFICIENCY	97
RACK MOUNTING KIT	Yes
PHASE (INPUT)	1

	Eaton 5SC UPS - 500/3000VA - Datasheet
COMPLIANCE INFORMATION	EU DoC Eaton 5SC
MANUALS AND USER GUIDES	Eaton 5SC Rack-RT UPS - 1000i Rack2U/1500i Rack2U/2200i RT2U/3000i RT2U - Installation and user manual

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights
Reserved.

Eaton is a registered trademark.

All other trademarks are property of
their respective owners.

Follow us on social media to get the latest
product and support information.

