

PRODUCT DATA SHEET

Extreme Duty Silicone, 10 Wt Oz Part Number: 03030

Product Description Silicone fluid with superior lubrication and temperature

viscosity characteristics. Use on all metallic and non-metallic surfaces. Reduces friction and galling even on

metal-to-metal contact areas.

Applications Plant conveyors, guides and rails, mold release agents,

vending machines, electric motors and rollers and sliding

mechanisms

Unit Package Description 16 Ounce Aerosol

Brand CRC

Generic Description 1 Premium Grade Silicone Lubricant

Net Fill 10 Wt Oz

UPC Code 078254030302

Unit Dimensions 7.75H x 2.63W x 2.63D in

Units Per Case 12

Case Dimensions 8.1H x 8.3W x 11.1D in

Cases Per Pallet 133
Case Weight 11 lbs

1 2 of 5 Code 30078254030303

Appearance Clear Water-White Liquid

Base Type Silicone Flash point (F) <0°F Flash point (C) <-18°C

Flammability Class - CPSC Extremely Flammable

Spec Gravity Concentrate 0.6699

Plastic Safe Safe on Most Plastics

Film Type Dry Film

Film Thickness Not Determined

Evaporation Rate Fast

Dielectric Strength Not Determined

Last revised: 5/4/2016

Page 1 of 2



xtreme Duty

Silicona para Tareas Extremas

^{lad}uce la Fricción y el Desgaste por Roc^a lexide Altas Presiones Andre es

lo Rango de Temperatura

leduces Friction And Galling Vibstinds High Pressure

Vide Temperature Range

CRC Industries is a worldwide leader in the production of specialty chemicals for maintenance and repair professionals serving industrial, electrical, aviation, automotive and marine markets. CRC is ISO 9001:2008 certified

and adheres to the strictest guidelines for quality in all facets of research, development and production.



PRODUCT DATA SHEET



-100 to 450°F

Working Temp (C)

204.4°C

Propellant

HFC-152a

NSF Category Code

H2

NSF Number

116808

Aerosol Flammability Level

Ш

DOT Proper Shipping Name

Aerosols, Flammable, Limited Quantity

VOC % (Federal)

60

VOC g/L (Federal)

400.2

VOC Lbs./Gal. (Federal)

3.34

VOC Category

Silicone Based Multi-Purpose Lubricant

Removal (How To)

Mineral Spirits

^{olio} Rango de Temperatura

CRC

Silicone

letuces Friction And Galling Vitasinds High Pressure Mic lemperature Range

Extreme Duty

Silicona para Tareas Extremas

Biduce la Fricción y el Desgaste por Ruce Basiste Altas Presiones

Last revised: 5/4/2016

Page 2 of 2



CRC Industries is a worldwide leader in the production of specialty chemicals for maintenance and repair professionals serving industrial, electrical, aviation, automotive and marine markets. CRC is ISO 9001:2008 certified

and adheres to the strictest guidelines for quality in all facets of research, development and production.