

PRODUCT DATA SHEET

Dry Moly Lube, 11 Wt Oz Part Number: 03084

Product Description Lowers friction, prevents galling and helps to reduce

torque and energy consumption. High anti-friction and anti-seizure properties. Fast drying film resists dirt and

dust build-up.

Applications Gaskets, transfer belts, conveyor belts, motors, plant

machinery and handling equipment, rubber moldings, high temperature, low load, or high rpm slides, rollers, wheels,

gears, chains & hoists

Unit Package Description 16 Ounce Aerosol

Brand CRC

Generic Description 1 Dry Film Lubricant

Net Fill 11 Wt Oz

UPC Code 078254030845

Unit Dimensions 7.75H x 2.63W x 2.63D in

Units Per Case 12

Case Dimensions 8.6H x 8.4W x 11.3D in

Cases Per Pallet 133
Case Weight 12 lbs

1 2 of 5 Code 30078254030846

Appearance Dark Gray Viscous Liquid

Base Type Molybdenum Disulfide

Flash point (F) -20° F Flash point (C) -29° C

Flammability Class - CPSC Extremely Flammable

Spec Gravity Concentrate 0.71
Plastic Safe No

Film Type Dry
Evaporation Rate Fast

Working Temp (F) 650°F (Continuous) / 750°F (Intermittent)
Working Temp (C) 343.3°C (Continuous) 398.9°C (Intermittent)

Last revised: 11/29/2016

Page 1 of 2



Dry Moly Lube

de Molibdeno

to-Conductive, Dry Film

of with High Temperature

le es Conductor, Capa Seca Vest para las Altas Temperaturas



PRODUCT DATA SHEET



Hydrocarbon

Aerosol Flammability Level

111

DOT Proper Shipping Name

Aerosols, Flammable, Limited Quantity

VOC % (Federal)

61.8

VOC g/L (Federal)

438.78

VOC Lbs./Gal. (Federal)

3.66

VOC Category

Dry Lubricant

Removal (How To)

Remove with a heavy duty degreaser.

Dry Moly Lube de Molibdeno las-Conductive, Dry Film tal with High Temperature lit ts Conductor, Capa Seca ites para las Altas Temperaturas

Last revised: 11/29/2016

Page 2 of 2

