

Plymouth

Friction, Duct, and Bundling Tapes



100 ASTM Friction Tape

A high quality cotton fabric coated on both sides with a black rubber adhesive compound which provides good adhesion to all types of surfaces. A 15 mil (0,38mm) general purpose tape that provides excellent protection against abrasion. ASTM-D-4514, Communication Industry Specification 6747, HHT 101A.

UPC/Cat.	Color	Dimensions		Packaging	Weight
1004	black	3/4" x .015" x 30'	19mm x 0,38mm x 9m	200/case C	34 lbs 15kg
1002	black	3/4" x .015" x 60'	19mm x 0,38mm x 18m	100/case C	29 lbs 13kg
1038	black	1 1/2" x .015" x 60'	38mm x 0,38mm x 18m	50/case C	29 lbs 13kg
1039	black	2" x .015" x 60'	51mm x 0,38mm x 18m	40/case C	33 lbs 15kg
1012	black	3/4" x .015" x 82.5'	19mm x 0,38mm x 25m	100/case C	44 lbs 20kg
1047	black	1 1/2" x .015" x 82.5'	38mm x 0,38mm x 25m	50/case C	41 lbs 19kg
1049	black	2" x .015" x 82.5'	51mm x 0,38mm x 25m	40/case C	45 lbs 20kg

170 BROWN Friction Tape

A high quality cotton fabric coated on both sides with a brown rubber adhesive compound which provides good adhesion to all types of surfaces. Distinctive natural rubber color, excellent tack. Provides excellent protection against abrasion for cable and splices.

UPC/Cat.	Color	Dimensions		Packaging	Weight
1008	brown	3/4" x .015" x 70'	19mm x 0,38mm x 21m	100/case C	36 lbs 16kg
1057	brown	2" x .015" x 70'	51mm x 0,38mm x 21m	40/case C	40 lbs 18kg
1077	brown	1" x .015" x 70'	25mm x 0,38mm x 21m	80/case C	41 lbs 19kg

PLYDUCT® 48 - Commercial Grade Cloth Duct Tape

An all purpose duct tape that provides excellent adhesion to all types of surfaces. Laminated cloth construction provides superior mechanical strength. Plyduct 48 will conform to irregular surfaces. Use for sealing joints on all types of duct work. Excellent for heavy duty applications.

UPC/Cat.	Color	Dimensions		Packaging	Weight
3150	grey	2" x .011" x 60 yds.	51mm x 0,3mm x 55m	24/case C	39 lbs 18kg

PLYDUCT® 49 - Economy Grade Cloth Duct Tape

An economy grade duct tape that provides excellent adhesion to all types of surfaces. Laminated cloth construction provides mechanical strength. Plyduct 49 will conform to irregular surfaces. Use for sealing joints on all types of duct work.

UPC/Cat.	Color	Dimensions		Packaging	Weight
3149	grey	2" x .009" x 60 yds.	51mm x 0,2mm x 55m	24/case C	33 lbs 15kg

VINYL BUNDLING TAPE

A specially formulated vinyl plastic tape used for general bundling and binding use. When removed, Plymouth's Vinyl Bundling Tape does not leave the sticky adhesive residue that other tapes leave behind. Tears straight and easily across both directions of the tape. Lead-free and conforms to irregular surfaces. Note: Not to be used for electrical insulation.

UPC/Cat.	Color	Dimensions		Packaging	Weight
3160	silver-grey	2" x 150' 50mm x 46m		12/case C	13 lbs 6kg