

PRODUCT DATA SHEET

Zinc-It® Instant Cold Galvanize, 13 Wt Oz Part Number: 18412

Product Description

Applications

Unit Package Description

Generic Description 1

Brand

Net Fill

UPC Code

Unit Dimensions Units Per Case

Case Dimensions

Cases Per Pallet

Case Weight

I 2 of 5 Code

Appearance

Plastic Safe

Recoat

Coverage

Flash point (F)

Flash point (C)

Spec Gravity Concentrate

Dry Time - Fully Dry

Dry Time - Tack Free

High-performance coating of >93% pure zinc that electrochemically bonds with ferrous metals to form a galvanic cell. It actively fights rust and corrosion. Use as a touch-up for damaged galvanized coatings. Dries quickly. Outdoor protection: 1 - 2 years.

On threads, exposed edges, fasteners, conduit, strapping, welds, fencing, railings, grates, electrical poles, breaker panel housings, rain spouts, signs, doors, trailers, waste containers, catwalks, and guard rails.

16 Ounce Aerosol CRC Instant Cold Galvanized Coating 13 Wt Oz 078254184128 7.75H x 2.63W x 2.63D in 12 8.69H x 8.44W x 11.31D in 75 14 lbs 30078254184129 Gray Viscous Liquid -2°F -19°:C Flammability Class - CPSC **Extremely Flammable** 0.77 to 0.85 Yes 8 Hours 20 Minutes Before 1 Hour or After 48 Hours 28 to 32 Sq Ft at 3 Mil Dry

> Last revised: 5/6/2016 Page 1 of 2



Customer Care: 800-556-5074 Technical Assistance: 800-521-3168 www.crcindustries.com



and adheres to the strictest guidelines for quality in all facets of research, development and production. $CRC^{\circledast}, K\&W^{\circledast}, Sta-Lube^{\circledast}, Marykate^{\circledast} and products denoted with <math display="inline">^{\circledast}$ and $^{\intercal}$ are trademarks

of CRC Industries, Inc.

CRC Industries is a worldwide leader in the production of specialty chemicals for maintenance and repair

ively Fights Corrosion bate Energicamente la Corrosión

Zinc-It°

Instant Cold Galvanize

Galvanizador Frio Instantâne





PRODUCT DATA SHEET



Instant Cold Galvanize

Galvanizador Frio Instantáneo

ile Entrojcamente la Corrosión

Working Temp (C) Propellant Aerosol Flammability Level Ш Military Specification Number DOT Proper Shipping Name VOC % (Federal) 45.6 VOC g/L (Federal) 555.6 4.64 VOC Lbs./Gal. (Federal) **VOC Category** 1.9 **MIR** Limit

Removal (How To)

Working Temp (F)

130°F (Continuous) / 150°F (Intermittent)

54.4°C (Continuous) / 65.6°C (Intermittent)

Hydrocarbon

Meets requirements of Mil-P-21035B, Meets requirements of Mil-P-26915, Meets requirements of Mil-P-46105

Aerosols, Flammable, Limited Quantity

Metallic Coating

Remove with aromatic solvents, Xylene. Toluene can be used, but is not recommended.

CRC

Zinc-It[®]

Evely Fights Corrosion



Customer Care: 800-556-5074 Technical Assistance: 800-521-3168 www.crcindustries.com



 $CRC^{\circledast}, K\&W^{\circledast}, Sta-Lube^{\circledast}, Marykate^{\circledast} and products denoted with <math display="inline">^{\circledast}$ and $^{\intercal}$ are trademarks of CRC Industries, Inc.

CRC Industries is a worldwide leader in the production of specialty chemicals for maintenance and repair

and adheres to the strictest guidelines for quality in all facets of research, development and production.

Last revised: 5/6/2016 Page 2 of 2