



PRODUCT DATA SHEET

Zinc-It® Instant Cold Galvanize™ Zinc Rich Galvanize
Coating, 1 Gal
No. 18413



| | |
|---------------------------|---|
| Product Description | High-performance coating of >92% pure zinc that electrochemically bonds with ferrous metals to form a galvanic cell. It actively fights rust and corrosion. Use as a touch-up for damaged galvanized coatings. Dries quickly. Outdoor protection: 1 - 2 years |
| Applications | On threads, exposed edges, fasteners, conduit, strapping, welds, fencing, railings, grates, electrical poles, breaker panel housings, rain spouts, signs, doors, trailers, waste containers, catwalks, and guard rails. |
| Unit Package Description | 1 Gallon Can |
| Brand | CRC |
| Generic Description 1 | Instant Cold Galvanized Coating |
| Net Fill | 1 Gal |
| UPC Code | 078254184135 |
| Unit Dimensions | 7.88H x 8W x 8D in |
| Units Per Case | 1 |
| Case Dimensions | 9.8H x 9.4W x 9.1D in |
| Cases Per Pallet | 60 |
| Case Weight | 22 lbs |
| I 2 of 5 Code | 30078254184136 |
| Appearance | Gray Viscous Liquid |
| Flash point (F) | 45°F |
| Flash point (C) | 7°C |
| Flammability Class - CPSC | Flammable |
| Spec Gravity Concentrate | 2.47 |
| Plastic Safe | May Harm Sensitive Plastics |
| Evaporation Rate | Slow |
| Dry Time - Fully Dry | 72 Hours |
| Dry Time - Tack Free | 30 Minutes |

Last revised: 8/9/2016
Page 1 of 2



Customer Care: 800-556-5074
Technical Assistance: 800-521-3168
www.crcindustries.com

CRC Industries is a worldwide leader in the production of specialty chemicals for maintenance and repair professionals serving industrial, electrical, aviation, automotive and marine markets. CRC is ISO 9001:2008 certified and adheres to the strictest guidelines for quality in all facets of research, development and production.



CRC®, K&W®, Sta-Lube®, Marykate® and products denoted with ® and ™ are trademarks of CRC Industries, Inc.



PRODUCT DATA SHEET



| | |
|-------------------------------|--|
| Recoat | 8 Hours |
| Coverage | 674 Sq Ft at 1 Mil Dry |
| Working Temp (F) | 250 to 300°F (Continuous), Up to 450°F (Intermittent) |
| Working Temp (C) | 121.1 to 148.9°C (Continuous), 232.2°C (Intermittent) |
| Propellant | None |
| Military Specification Number | Meets requirements of Mil-P-26915, Meets requirements of Mil-P-46105 |
| DOT Proper Shipping Name | Paint, Limited Quantity |
| VOC % (Federal) | 19.95 |
| VOC g/L (Federal) | 493.36 |
| VOC Lbs./Gal. (Federal) | 4.11 |
| VOC Category | Not Regulated |
| Restricted from Sale In: | CA |
| Removal (How To) | Paint stripper or other solvent |

Last revised: 8/9/2016
Page 2 of 2



Customer Care: 800-556-5074
Technical Assistance: 800-521-3168
www.crcindustries.com



CRC®, K&W®, Sta-Lube®, Marykate® and products denoted with ® and ™ are trademarks of CRC Industries, Inc.

CRC Industries is a worldwide leader in the production of specialty chemicals for maintenance and repair professionals serving industrial, electrical, aviation, automotive and marine markets. CRC is ISO 9001:2008 certified and adheres to the strictest guidelines for quality in all facets of research, development and production.