

Features:

- The use of an Air King™ safety clip or wire type retainer is necessary to ensure couplings will not become accidentally disconnected. This guarantees the fittings are properly connected as the pin will not go through the holes in the mating flanges until couplings are locked in place.
- only one Air King™ safety clip or wire type retainer is required for each Air King™ universal coupling
- sold in package quantities only

Standard Safety Clip**Feature:**

- same size clip can be used for all coupling sizes

Wire Diameter	Part #	Price/E	Pkg Qty
.080	AC1	\$0.30	25

Air King™ Safety Pins**Feature:**

- heavy duty, oversized

Wire Diameter	Part #	Price/E
.058	AKSP1	\$1.30
.091	AKSP25	1.45

Synthetic Lanyard**Features:**

- synthetic cord
- same size for all coupling sizes

Part #	Price/E	Pkg Qty
ACL8	\$0.40	25

Air King™ 2-Lug Washers

AWR4



AWS6

**Features:**

- 2 lug couplings use the same size washer, part #'s **AWR4**, **AWS6**
- rubber temperature range: **-20°F to 160°F (-29°C to 71°C)**
- neoprene temperature range: **-20°F to 190°F (-29°C to 88°C)**
- neoprene is oil resistant

Material	Style	Part #	Price/E	Pkg Qty
<i>rubber</i>	2 lug	AWR4¹	\$0.60	50
<i>neoprene</i>	2 lug	AWS6	0.80	50

¹ made from Styrene-butadiene (SBR)

Air King™ 4-Lug Washer**Features:**

- rubber temperature range: **-20°F to 160°F (-29°C to 71°C)**
- 4 lug couplings use the same size washer, part # **AWR14**

Material	Style	Part #	Price/E
<i>rubber</i>	4 lug	AWR14	\$4.40