



**MCR
SAFETY**

9676 UltraTech Cut Protection Specification Sheet

PRODUCT DESCRIPTION:

One of the most distinguishing DSM Dyneema® characteristics is its cool-to-touch property. DSM Dyneema® fiber's inherent ability to dissipate body heat and pass moisture from inside of the glove to the outside, results in longer wear time which promotes greater hand protection. The 9676 UltraTech Dyneema® PU glove features a 13 gauge certified DSM Dyneema® blended shell with PU coated palm and fingers.

FEATURES:

- 13 Gauge Certified DSM Dyneema Salt & Pepper Blended Shell
- Gray PU Coated Palm and Fingers
- Cool and Comfortable

APPLICATIONS:

Automotive Assembly, Farming, Landscaping, Carpentry, Glass handling, HVAC, Janitorial , Sheet metal industry, Roofing



TECHNICAL DATA FOR: 9676

Series	UltraTech	EN 388 : CE Score - Abrasion	4
Material Group	Strings	EN 388 : CE Score - Cut	3
Product Type	Cut Protection	EN 388 : CE Score - Tear	4
Glove Size	Large	EN 388 : CE Score - Puncture	3
Gauge	13 Gauge	ANSI Cut	ANSI Cut A3
Material	Dyneema	ANSI Abrasion	ANSI Abrasion 6
		ANSI Puncture	ANSI Puncture 3

MCR Safety - 1255 Schilling Blvd. W. - Collierville, TN 38017 - USA

Phone: 901-795-5810 - Toll Free: 800-955-6887 - Fax: 800-999-3908 - Web: www.mcrcsafety.com

©2017 MCR Safety - All Rights Reserved



MCR
SAFETY

9676

UltraTech

Cut Protection

Specification Sheet



Item No:	Size:	A:	B:	C:	Case Weight	UOM Weight
9676L	Large	12.20	4.84	2.95	22.464 lb.	1.872
9676M	Medium	11.62	4.52	2.76	20.580 lb.	1.715
9676S	Small	11.22	4.12	2.76	19.596 lb.	1.633
9676XL	X - Large	12.60	5.19	2.95	24.888 lb.	2.074
9676XS	X - Small	10.63	3.96	2.56	18.684 lb.	1.557
9676XXL	XX - Large	12.98	5.47	2.95	26.244 lb.	2.187

MCR Safety - 1255 Schilling Blvd. W. - Collierville, TN 38017 - USA

Phone: 901-795-5810 - Toll Free: 800-955-6887 - Fax: 800-999-3908 - Web: www.mcrcsafety.com

©2017 MCR Safety - All Rights Reserved