

SAFETY DATA SHEET

1. Identification

Product identifier	Technical Grade 3-36® Multi-Purpose Precision Lubricant	
Other means of identification		
Product code	03003	
Recommended use	Multi-purpose lubricant	
Recommended restrictions	None known.	
Manufacturer/Importer/Supplier Manufactured or sold by:	r/Distributor information	
Company name	CRC Industries, Inc.	
Address	885 Louis Dr.	
	Warminster, PA 18974 US	
Telephone		
General Information	215-674-4300	
Technical Assistance	800-521-3168	
Customer Service	800-272-4620	
24-Hour Emergency	800-424-9300 (US)	
(CHEMTREC)	703-527-3887 (International)	
Website	www.crcindustries.com	
2. Hazard(s) identification	n	
Physical hazards	Flammable aerosols	Category 1
	Gases under pressure	Compressed gas
Health hazards	Skin corrosion/irritation	Category 2
	Specific target organ toxicity, single exposure	Category 3 narcotic effects
	Aspiration hazard	Category 1
Environmental hazards	Not classified.	
OSHA defined hazards	Not classified.	
Label elements		
Signal word	Danger	
Hazard statement	Extremely flammable aerosol. Contains gas un swallowed and enters airways. Causes skin in	nder pressure; may explode if heated. May be fatal if ritation. May cause drowsiness or dizziness.
Precautionary statement		
Prevention	Keep away from heat/sparks/open flames/hot surfaces No smoking. Do not spray on an open flame or other ignition source. Do not apply while equipment is energized. Pressurized container: Do not pierce or burn, even after use. Extinguish all flames, pilot lights and heaters. Vapors will accumulate readily and may ignite. Use only with adequate ventilation; maintain ventilation during use and until all vapors are gone. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Avoid breathing mist or vapor. Avoid breathing gas. Wash thoroughly after handling. Wear protective gloves.	
Response	If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. If on skin: Wash with plenty of water. If skin irritation occurs: Get medical attention. Take off contaminated clothing and wash before reuse. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell.	
Storage	Store locked up. Protect from sunlight. Store in a well-ventilated place. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Exposure to high temperature may cause can to burst.	

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Distillates (petroleum), hydrotreated light		64742-47-8	60 - 70
Light mineral oil		8042-47-5	10 - 20
n-Butyl stearate		123-95-5	3 - 5
Carbon dioxide		124-38-9	1 - 3
Petrolatum		8009-03-8	1 - 3
Sorbitan monooleate		68910-94-1	1 - 3

Specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures		
Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.	
Skin contact	Rinse skin with water/shower. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse.	
Eye contact	Rinse with water. Get medical attention if irritation develops and persists.	
Ingestion	Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Aspiration may cause pulmonary edema and pneumonitis.	
Most important symptoms/effects, acute and delayed	Diarrhea. Irritation of eyes and mucous membranes. Irritation of nose and throat. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. May cause redness and pain.	
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.	
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.	
5. Fire-fighting measures		
Suitable extinguishing media	Powder. Alcohol resistant foam. Dry chemicals. Carbon dioxide (CO2).	
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.	
Specific hazards arising from the chemical	Contents under pressure. Pressurized container may rupture when exposed to heat or flame.	
Special protective equipment and precautions for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.	
Fire-fighting equipment/instructions	In case of fire: Stop leak if safe to do so. Move containers from fire area if you can do so without risk. Cool containers exposed to heat with water spray and remove container, if no risk is involved. Containers should be cooled with water to prevent vapor pressure build up.	
• · • ·		

General fire hazards Extremely flammable aerosol.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Avoid inhalation of vapors or mists. Avoid breathing gas. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up	Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. This product is miscible in water. Stop the flow of material, if this is without risk. Prevent entry into waterways, sewer, basements or confined areas. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid discharge into drains, water courses or onto the ground.
7. Handling and storage	
Precautions for safe handling	Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Use caution around energized equipment. The metal container will conduct electricity if it contacts a live source. This may result in injury to the user from electrical shock and/or flash fire. Avoid breathing mist or vapor. Avoid breathing gas. Avoid contact with eyes, skin, and clothing. Avoid prolonged or repeated contact with skin. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices. For product usage instructions, please see the product label.
Conditions for safe storage, including any incompatibilities	Level 3 Aerosol.
	Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	, Value	Form
Carbon dioxide (CAS 124-38-9)	PEL	9000 mg/m3	
		5000 ppm	
Light mineral oil (CAS 8042-47-5)	PEL	5 mg/m3	Mist.
Petrolatum (CAS 8009-03-8)	PEL	5 mg/m3	Mist.
US. ACGIH Threshold Limit Value	es		
Components	Туре	Value	Form
Carbon dioxide (CAS 124-38-9)	STEL	30000 ppm	
	TWA	5000 ppm	
Light mineral oil (CAS 8042-47-5)	TWA	5 mg/m3	Inhalable fraction.
n-Butyl stearate (CAS 123-95-5)	TWA	10 mg/m3	
Petrolatum (CAS 8009-03-8)	TWA	5 mg/m3	Inhalable fraction.
US. NIOSH: Pocket Guide to Che	mical Hazards		
Components	Туре	Value	Form
Carbon dioxide (CAS 124-38-9)	STEL	54000 mg/m3	
,		30000 ppm	
	TWA	9000 mg/m3	
		5000 ppm	
Distillates (petroleum), hydrotreated light (CAS 64742-47-8)	TWA	100 mg/m3	
Light mineral oil (CAS 8042-47-5)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
Petrolatum (CAS 8009-03-8)	STEL	10 mg/m3	Mist.

US.	NIOSH:	Pocket	Guide to	Chemical	Hazards
-					_

Components	Туре	Value	Form
	TWA	5 mg/m3	Mist.
Biological limit values	No biological exposure limits noted fo	r the ingredient(s).	
Appropriate engineering controls	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.		
ndividual protection measure	es, such as personal protective equipme	ent	
Eye/face protection	Wear safety glasses with side shields (or goggles).		
Skin protection			
Hand protection	Wear protective gloves such as: Nitrile	e. Neoprene.	
Other	Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.		
Respiratory protection	Wear positive pressure self-contained breathing apparatus (SCBA). Air monitoring is needed to determine actual employee exposure levels.		
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.		
General hygiene considerations	When using, do not eat, drink or smoke. Always observe good personal hygiene measures as washing after handling the material and before eating, drinking, and/or smoking. Routin wash work clothing and protective equipment to remove contaminants.		and/or smoking. Routinely

9. Physical and chemical properties

Odor thresholdNot available.pHNot available.Melting point/freezing point-72.4 °F (-58 °C) estimatedInitial boiling point and boiling rangeNot available.Flash point200 °F (93.3 °C) Tag Closed CupEvaporation rateSlow.Flammability (solid, gas)Not available.Upper/lower flammability or explosive limitsFlammability limit - lower (%)0.6 % estimatedFlammability limit - lower (%)0.5 % estimatedVapor pressure1557.7 hPa estimatedVapor density> 1 (air = 1)Relative density0.84 estimatedSolubility (water)Negligible.Partition coefficient (n-octanol/water)Not available.Decomposition temperature392 °F (200 °C) estimatedDecomposition temperatureNot available.	Appearance	
ColorAmber.OdorMild petroleum.Odor thresholdNot available.pHNot available.Melting point/freezing point-72.4 °F (-58 °C) estimatedInitial boiling point and boiling rangeNot available.Flash point200 °F (93.3 °C) Tag Closed CupEvaporation rateSlow.Flammability (solid, gas)Not available.Upper/lower flammability or expl>vive limitsFlammability limit - lower (%)0.6 % estimatedflammability limit - upper (%)5.5 % estimatedVapor pressure1557.7 hPa estimatedVapor density> 1 (air = 1)Relative density0.84 estimatedOlubility (water)Negligible.Partition coefficient (n-octanol/water)Not available.Partition coefficient (n-octanol/water)Not available.Pocomposition temperature392 °F (200 °C) estimatedDecomposition temperatureNot available.	Physical state	Liquid.
OddrMild petroleum.Oddr thresholdNot available.pHNot available.Melting point/freezing point-72.4 °F (-58 °C) estimatedInitial boiling point and boiling rangeNot available.Flash point200 °F (93.3 °C) Tag Closed CupEvaporation rateSlow.Flammability (solid, gas)Not available.Upper/lower flammability or explusive limitsFlammability limit - lower (%)0.6 % estimatedflammability limit - lower (%)5.5 % estimated(%)557.7 hPa estimatedVapor pressure1557.7 hPa estimatedVapor density> 1 (air = 1)Relative density0.84 estimatedSolubility (water)Not available.Partition coefficient (n-octanol/water)Not available.Auto-ignition temperature392 °F (200 °C) estimatedDecomposition temperatureNot available.	Form	Aerosol.
Odr thresholdNot available.pHNot available.Melting point/freezing point~72.4 °F (-58 °C) estimatedInitial boiling point and boilingNot available.ranger200 °F (93.3 °C) Tag Closed CupFlam-to nateSlow.Flam-mability (solid, gas)Not available.Upper/lower flammability or expireNot available.f lammability limit - lower (%)0.6 % estimatedf lammability limit - lower (%)0.5 % estimatedf lammability limit - lower (%)5.5 % estimatedv por density1557.7 hPa estimatedVapor density> 1 (air = 1)Relative density0.84 estimatedNot available.Not available.Partition coefficient (n-ctanol/water)Not available.Auto - Ling intion temperature30 °F (200 °C) estimatedDecomposition temperatureNot available.	Color	Amber.
pH Not available. Melting point/freezing point -72.4 °F (-58 °C) estimated Initial boiling point and boiling Not available. range 200 °F (93.3 °C) Tag Closed Cup Flash point 200 °F (93.3 °C) Tag Closed Cup Evaporation rate Slow. Flammability (solid, gas) Not available. Upper/lower flammability or explosure limits Slow. Flammability limit - lower 0.6 % estimated (%) 5.5 % estimated Flammability limit - upper 5.5 % estimated (%) 5.5 % estimated Vapor pressure 1557.7 hPa estimated Vapor density > 1 (air = 1) Relative density 0.84 estimated Solubility (water) Not available. Partition coefficient Not available. (n-octanol/water) Solubile. Auto-ignition temperature 392 °F (200 °C) estimated Decomposition temperature Not available.	Odor	Mild petroleum.
Melting point/freezing point-72.4 °F (-58 °C) estimatedMelting point and boiling rangeNot available.Flash point200 °F (93.3 °C) Tag Closed CupEvaporation rateSlow.Flammability (solid, gas)Not available.Upper/lower flammability or explosive limitsImmability limit - lower (%)Flammability limit - lower (%)0.6 % estimatedFlammability limit - upper (%)5.5 % estimatedVapor pressure1557.7 hPa estimatedVapor density> 1 (air = 1)Relative density0.84 estimatedSolubility (water)Negligible.Partition coefficient (n-octanol/water)Not available.Auto-ignition temperature392 °F (200 °C) estimatedDecomposition temperatureNot available.	Odor threshold	Not available.
Initial boiling point and boiling rangeNot available.Flash point200 °F (93.3 °C) Tag Closed CupEvaporation rateSlow.Flammability (solid, gas)Not available.Upper/lower flammability or explored flammability or explored flammability limit - lower (%)0.6 % estimatedFlammability limit - lower (%)0.5 % estimatedFlammability limit - upper (%)5.5 % estimatedVapor pressure1557.7 hPa estimatedVapor density> 1 (air = 1)Relative density0.84 estimatedSolubility (water)Negligible.Partition coefficient (n-octanol/water)Not available.Auto-ignition temperature392 °F (200 °C) estimatedDecomposition temperatureNot available.	рН	Not available.
rangeFlash point200 °F (93.3 °C) Tag Closed CupEvaporation rateSlow.Flammability (solid, gas)Not available.Upper/lower flammability or explosive limits0.6 % estimatedflammability limit - lower0.6 % estimated(%)5.5 % estimatedFlammability limit - upper5.5 % estimated(%)1557.7 hPa estimatedVapor pressure1557.7 hPa estimatedVapor density> 1 (air = 1)Relative density0.84 estimatedSolubility (water)Negligible.Partition coefficient (n-octanol/water)Not available.Auto-ignition temperature392 °F (200 °C) estimatedDecomposition temperatureNot available.	Melting point/freezing point	-72.4 °F (-58 °C) estimated
Evaporation rateSlow.Flammability (solid, gas)Not available.Upper/lower flammability or explosive limitsFlammability limit - lower0.6 % estimated(%)5.5 % estimatedFlammability limit - upper5.5 % estimated(%)1557.7 hPa estimatedVapor pressure1557.7 hPa estimatedVapor density> 1 (air = 1)Relative density0.84 estimatedSolubility (water)Negligible.Partition coefficient (n-octanol/water)Not available.Auto-ignition temperature392 °F (200 °C) estimatedDecomposition temperatureNot available.	Initial boiling point and boiling range	Not available.
Flammability (solid, gas) Not available. Upper/lower flammability or explosive limits Flammability limit - lower 0.6 % estimated (%) S.5 % estimated Flammability limit - upper 5.5 % estimated (%) S.5 % estimated Vapor pressure 1557.7 hPa estimated Vapor density > 1 (air = 1) Relative density 0.84 estimated Solubility (water) Negligible. Partition coefficient Not available. (n-octanol/water) 392 °F (200 °C) estimated Decomposition temperature Not available.	Flash point	200 °F (93.3 °C) Tag Closed Cup
Upper/lower flammability or explosive limitsFlammability limit - lower (%)0.6 % estimatedFlammability limit - upper (%)5.5 % estimatedVapor pressure1557.7 hPa estimatedVapor density> 1 (air = 1)Relative density0.84 estimatedSolubility (water)Negligible.Partition coefficient (n-octanol/water)Not available.Auto-ignition temperature392 °F (200 °C) estimatedDecomposition temperatureNot available.	Evaporation rate	Slow.
Flammability limit - lower (%)0.6 % estimatedFlammability limit - upper (%)5.5 % estimatedVapor pressure1557.7 hPa estimatedVapor density> 1 (air = 1)Relative density0.84 estimatedSolubility (water)Negligible.Partition coefficient (n-octanol/water)Not available.Auto-ignition temperature392 °F (200 °C) estimatedDecomposition temperatureNot available.	Flammability (solid, gas)	Not available.
(%)Flammability limit - upper (%)5.5 % estimatedVapor pressure1557.7 hPa estimatedVapor density> 1 (air = 1)Relative density0.84 estimatedSolubility (water)Negligible.Partition coefficient (n-octanol/water)Not available.Auto-ignition temperature392 °F (200 °C) estimatedDecomposition temperatureNot available.	Upper/lower flammability or exp	losive limits
(%)Vapor pressure1557.7 hPa estimatedVapor density> 1 (air = 1)Relative density0.84 estimatedSolubility (water)Negligible.Partition coefficient (n-octanol/water)Not available.Auto-ignition temperature392 °F (200 °C) estimatedDecomposition temperatureNot available.		0.6 % estimated
Vapor density> 1 (air = 1)Relative density0.84 estimatedSolubility (water)Negligible.Partition coefficient (n-octanol/water)Not available.Auto-ignition temperature Decomposition temperature392 °F (200 °C) estimatedNot available.Not available.		5.5 % estimated
Relative density0.84 estimatedSolubility (water)Negligible.Partition coefficient (n-octanol/water)Not available.Auto-ignition temperature Decomposition temperature392 °F (200 °C) estimatedNot available.Not available.	Vapor pressure	1557.7 hPa estimated
Solubility (water)Negligible.Partition coefficientNot available.(n-octanol/water)392 °F (200 °C) estimatedAuto-ignition temperature392 °F (200 °C) estimatedDecomposition temperatureNot available.	Vapor density	> 1 (air = 1)
Partition coefficient (n-octanol/water) Not available. Auto-ignition temperature 392 °F (200 °C) estimated Decomposition temperature Not available.	Relative density	0.84 estimated
(n-octanol/water)Auto-ignition temperature392 °F (200 °C) estimatedDecomposition temperatureNot available.	Solubility (water)	Negligible.
Decomposition temperature Not available.	Partition coefficient (n-octanol/water)	Not available.
	Auto-ignition temperature	392 °F (200 °C) estimated
Viscosity (kinematic) Not available.	Decomposition temperature	Not available.
	Viscosity (kinematic)	Not available.
Percent volatile 88.4 % estimated	Percent volatile	88.4 % estimated

10. Stability and reactivity

Reactivity

The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Heat, flames and sparks. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition products	Carbon oxides.

11. Toxicological information

Information on likely routes of exposure

Ingestion	May be fatal if swallowed and enters airways.	
Inhalation	Prolonged inhalation may be harmful. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.	
Skin contact	Causes skin irritation.	
Eye contact	Direct contact with eyes may cause temporary irritation.	
Symptoms related to the physical, chemical and toxicological characteristics	Diarrhea. Irritation of nose and throat. Irritation of eyes and mucous membranes. May cause redness and pain. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.	

Information on toxicological effects

Acute toxicity

Product	Species	Test Results
Technical Grade 3-36® Mu	Iti-Purpose Precision Lubricant	
Acute		
Dermal		
LD50	Rabbit	2581.9119 mg/kg estimated
Inhalation		
LC50	Rat	58741.2031 ppm, 4 hours estimated
Oral		
LD50	Rat	7007.0728 mg/kg estimated

* Estimates for product may be based on additional component data not shown.

······································			
Skin corrosion/irritation	Causes skin irritation.		
Serious eye damage/eye irritation	Direct contact with eyes may cause temporary irritation.		
Respiratory sensitization	Not available.		
Skin sensitization	This product is not expected to cause skin sensitization.		
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.		
Carcinogenicity	This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.		
IARC Monographs. Overall E	valuation of Carcinogenicity		
Light mineral oil (CAS 804	2-47-5) 3 Not classifiable as to carcinogenicity to humans.		
Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.		
Specific target organ toxicity - single exposure	May cause drowsiness or dizziness.		
Specific target organ toxicity - repeated exposure	Not classified.		
Aspiration hazard	May be fatal if swallowed and enters airways.		
Chronic effects	Prolonged inhalation may be harmful.		

12. Ecological information

Ecotoxicity

The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

		Species	Test Results
Technical Grade 3-36® Multi-P	urpose Precisi	ion Lubricant	
Aquatic			
Acute			
Crustacea E	EC50	Daphnia	71386.8828 mg/l, 48 hours estimated
Fish L	_C50	Fish	4949.4907 ppm, 96 hours estimated
Components		Species	Test Results
Distillates (petroleum), hydrotre	eated light (CA	S 64742-47-8)	
Aquatic			
Acute			
Fish L	.C50	Bluegill (Lepomis macrochirus)	2.2 mg/l, 96 hours
* Estimates for product may be	based on add	litional component data not shown.	
ersistence and degradability		ailable on the degradability of this produc	t.
ioaccumulative potential	No data availa		-
lobility in soil	No data availa		
ther adverse effects		erse environmental effects (e.g. ozone de	nletion photochemical ozone creation
		locrine disruption, global warming potentia	
13. Disposal consideration	IS		
isposal of waste from		d liquid product is not a RCRA bazardous	s waste (See 40 CFR Part 261.20 - 261.33
esidues / unused products			before disposal. Contents under pressure.
•	-	ure, incinerate or crush. Dispose in accord	dance with all applicable regulations.
azardous waste code	Not regulated	l.	
ontaminated packaging	Empty contain	ners should be taken to an approved was	te handling site for recycling or disposal.
	emptied.	d containers may retain product residue, 1	follow label warnings even after container
14. Transport information			
-			
от			
OT UN number	UN1950		
OT UN number UN proper shipping name		nmable, Limited Quantity	
OT UN number UN proper shipping name Transport hazard class(es)	Aerosols, flan	nmable, Limited Quantity	
OT UN number UN proper shipping name Transport hazard class(es) Class		nmable, Limited Quantity	
OT UN number UN proper shipping name Transport hazard class(es)	Aerosols, flan	nmable, Limited Quantity	
OT UN number UN proper shipping name Transport hazard class(es) Class Subsidiary risk Label(s)	Aerosols, flan 2.1		
OT UN number UN proper shipping name Transport hazard class(es) Class Subsidiary risk Label(s) Packing group	Aerosols, flan 2.1 - 2.1 Not applicable		ures before handling.
OT UN number UN proper shipping name Transport hazard class(es) Class Subsidiary risk Label(s) Packing group	Aerosols, flan 2.1 - 2.1 Not applicable Read safety in N82	e.	ures before handling.
OT UN number UN proper shipping name Transport hazard class(es) Class Subsidiary risk Label(s) Packing group Special precautions for user	Aerosols, flan 2.1 - 2.1 Not applicable Read safety in	e.	ures before handling.
OT UN number UN proper shipping name Transport hazard class(es) Class Subsidiary risk Label(s) Packing group Special precautions for user Special provisions	Aerosols, flan 2.1 - 2.1 Not applicable Read safety in N82	e.	ures before handling.
OT UN number UN proper shipping name Transport hazard class(es) Class Subsidiary risk Label(s) Packing group Special precautions for user Special provisions Packaging exceptions	Aerosols, flan 2.1 - 2.1 Not applicable Read safety in N82 306	e.	ures before handling.
OT UN number UN proper shipping name Transport hazard class(es) Class Subsidiary risk Label(s) Packing group Special precautions for user Special provisions Packaging exceptions Packaging non bulk	Aerosols, flan 2.1 - 2.1 Not applicable Read safety in N82 306 None None	e.	ures before handling.
OT UN number UN proper shipping name Transport hazard class(es) Class Subsidiary risk Label(s) Packing group Special precautions for user Special provisions Packaging exceptions Packaging non bulk Packaging bulk	Aerosols, flan 2.1 - 2.1 Not applicable Read safety in N82 306 None None UN1950	e. nstructions, SDS and emergency procedu	ures before handling.
OT UN number UN proper shipping name Transport hazard class(es) Class Subsidiary risk Label(s) Packing group Special precautions for user Special provisions Packaging exceptions Packaging non bulk Packaging bulk ATA UN number UN proper shipping name	Aerosols, flan 2.1 - 2.1 Not applicable Read safety in N82 306 None None UN1950	e.	ures before handling.
OT UN number UN proper shipping name Transport hazard class(es) Class Subsidiary risk Label(s) Packing group Special precautions for user Special provisions Packaging exceptions Packaging exceptions Packaging non bulk Packaging bulk ATA UN number UN proper shipping name Transport hazard class(es)	Aerosols, flan 2.1 - 2.1 Not applicable Read safety in N82 306 None None UN1950 Aerosols, flan	e. nstructions, SDS and emergency procedu	ures before handling.
OT UN number UN proper shipping name Transport hazard class(es) Class Subsidiary risk Label(s) Packing group Special precautions for user Special provisions Packaging exceptions Packaging non bulk Packaging bulk ATA UN number UN proper shipping name Transport hazard class(es) Class	Aerosols, flan 2.1 - 2.1 Not applicable Read safety in N82 306 None None UN1950	e. nstructions, SDS and emergency procedu	ures before handling.
OT UN number UN proper shipping name Transport hazard class(es) Class Subsidiary risk Label(s) Packing group Special precautions for user Special provisions Packaging exceptions Packaging non bulk Packaging bulk ATA UN number UN proper shipping name Transport hazard class(es) Class Subsidiary risk	Aerosols, flan 2.1 - 2.1 Not applicable Read safety in N82 306 None None UN1950 Aerosols, flan 2.1 -	e. nstructions, SDS and emergency procedu	ures before handling.
OT UN number UN proper shipping name Transport hazard class(es) Class Subsidiary risk Label(s) Packing group Special precautions for user Special provisions Packaging exceptions Packaging non bulk Packaging bulk ATA UN number UN proper shipping name Transport hazard class(es) Class Subsidiary risk Packing group	Aerosols, flan 2.1 - 2.1 Not applicable Read safety in N82 306 None None UN1950 Aerosols, flan 2.1 - Not applicable	e. nstructions, SDS and emergency procedu	ures before handling.
OT UN number UN proper shipping name Transport hazard class(es) Class Subsidiary risk Label(s) Packing group Special precautions for user Special provisions Packaging exceptions Packaging exceptions Packaging bulk Packaging bulk ATA UN number UN proper shipping name Transport hazard class(es) Class Subsidiary risk Packing group Environmental hazards	Aerosols, flan 2.1 - 2.1 Not applicable Read safety in N82 306 None None UN1950 Aerosols, flan 2.1 - Not applicable No.	e. nstructions, SDS and emergency procedu	ures before handling.
OT UN number UN proper shipping name Transport hazard class(es) Class Subsidiary risk Label(s) Packing group Special precautions for user Special provisions Packaging exceptions Packaging exceptions Packaging bulk Packaging bulk ATA UN number UN proper shipping name Transport hazard class(es) Class Subsidiary risk Packing group Environmental hazards ERG Code	Aerosols, flan 2.1 - 2.1 Not applicable Read safety in N82 306 None None UN1950 Aerosols, flan 2.1 - Not applicable No. 10L	e. nstructions, SDS and emergency procedu	
OT UN number UN proper shipping name Transport hazard class(es) Class Subsidiary risk Label(s) Packing group Special precautions for user Special provisions Packaging exceptions Packaging exceptions Packaging bulk Packaging bulk ATA UN number UN proper shipping name Transport hazard class(es) Class Subsidiary risk Packing group Environmental hazards ERG Code	Aerosols, flan 2.1 - 2.1 Not applicable Read safety in N82 306 None None UN1950 Aerosols, flan 2.1 - Not applicable No. 10L Read safety in	e. nstructions, SDS and emergency procedu nmable, Limited Quantity e.	
OT UN number UN proper shipping name Transport hazard class(es) Class Subsidiary risk Label(s) Packing group Special precautions for user Special provisions Packaging exceptions Packaging exceptions Packaging bulk ATA UN number UN proper shipping name Transport hazard class(es) Class Subsidiary risk Packing group Environmental hazards ERG Code Special precautions for user Other information Passenger and cargo	Aerosols, flan 2.1 - 2.1 Not applicable Read safety in N82 306 None None UN1950 Aerosols, flan 2.1 - Not applicable No. 10L	e. nstructions, SDS and emergency procedu nmable, Limited Quantity e.	
OT UN number UN proper shipping name Transport hazard class(es) Class Subsidiary risk Label(s) Packing group Special precautions for user Special provisions Packaging exceptions Packaging exceptions Packaging non bulk Packaging bulk ATA UN number UN proper shipping name Transport hazard class(es) Class Subsidiary risk Packing group Environmental hazards ERG Code Special precautions for user Other information Passenger and cargo aircraft	Aerosols, flan 2.1 - 2.1 Not applicable Read safety in N82 306 None None UN1950 Aerosols, flan 2.1 - Not applicable No. 10L Read safety in Allowed.	e. nstructions, SDS and emergency procedu nmable, Limited Quantity e.	
OT UN number UN proper shipping name Transport hazard class(es) Class Subsidiary risk Label(s) Packing group Special precautions for user Special provisions Packaging exceptions Packaging exceptions Packaging bulk ATA UN number UN proper shipping name Transport hazard class(es) Class Subsidiary risk Packing group Environmental hazards ERG Code Special precautions for user Other information Passenger and cargo	Aerosols, flan 2.1 - 2.1 Not applicable Read safety in N82 306 None None UN1950 Aerosols, flan 2.1 - Not applicable No. 10L Read safety in	e. nstructions, SDS and emergency procedu nmable, Limited Quantity e.	

Transport hazard class(es) 2 Class 2 Subsidiary risk - Packing group Not applicable. Environmental hazards No. EmS F-D, S-U	UN proper shipping name	AEROSOLS, LIMITED QUANTITY
Subsidiary risk - Packing group Not applicable. Environmental hazards Marine pollutant Marine pollutant No. EmS F-D, S-U	Transport hazard class(es)	
Packing group Not applicable. Environmental hazards No. Marine pollutant No. EmS F-D, S-U	Class	2
Environmental hazards Marine pollutant No. EmS F-D, S-U	Subsidiary risk	-
Marine pollutant No. EmS F-D, S-U	Packing group	Not applicable.
EmS F-D, S-U	Environmental hazards	
	Marine pollutant	No.
	EmS	F-D, S-U
Special precautions for user Read safety instructions, SDS and emergency procedures before handling.	Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

15. Regulatory information

15. Regulatory informatio		
US federal regulations	This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200. All components are on the U.S. EPA TSCA Inventory List.	
TSCA Section 12(b) Export	Notification (40 CFR 707, Subpt. D)	
Not regulated.		
SARA 304 Emergency relea	ase notification	
Not regulated.		
	ulated Substances (29 CFR 1910.1001-1050)	
Not listed. US EPCRA (SARA Title III) \$	Section 313 - Toxic Chemical: Listed substance	
Not listed.		
CERCLA Hazardous Substa	ance List (40 CFR 302.4)	
Not listed.		
CERCLA Hazardous Substa	ances: Reportable quantity	
Not listed.		
	ng in the loss of any ingredient at or above its RQ require immediate notification to the National .24-8802) and to your Local Emergency Planning Committee.	
Clean Air Act (CAA) Section	n 112 Hazardous Air Pollutants (HAPs) List	
Not regulated.		
	n 112(r) Accidental Release Prevention (40 CFR 68.130)	
Not regulated.		
Safe Drinking Water Act (SDWA)	Not regulated.	
Food and Drug Administration (FDA)	Not regulated.	
Superfund Amendments an	nd Reauthorization Act of 1986 (SARA)	
Section 311/312 Hazard categories	Immediate Hazard - Yes Delayed Hazard - No Fire Hazard - Yes Pressure Hazard - Yes Reactivity Hazard - No	
SARA 302 Extremely hazardous substance	No	
US state regulations		
US. California Controlled S	ubstances. CA Department of Justice (California Health and Safety Code Section 11100)	
Not listed. US. New Jersev Worker and	d Community Right-to-Know Act	
Carbon dioxide (CAS 124-38-9)		
Distillates (petroleum), hydrotreated light (CAS 64742-47-8) US. Massachusetts RTK - Substance List		
Carbon dioxide (CAS 124-38-9)		
Light mineral oil (CAS 80		
Carbon dioxide (CAS 124-38-9)		
Distillates (petroleum), hydrotreated light (CAS 64742-47-8) Light mineral oil (CAS 8042-47-5)		

US. Rhode Island RTK

None.

US. California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

Volatile organic compounds (VOC) regulations

EPA	-,	
VOC content (40 CFR 51.100(s))	97.3 %	
Consumer products (40 CFR 59, Subpt. C)	Not regulated	
State		
Consumer products	This product is regulated as a Multi-Purpose Lubricant. This product is compliant for use in all 50 states.	
VOC content (CA)	0 %	
VOC content (OTC)	0 %	
International Inventories		
Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	Yes
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	10-10-2014
Revision date	11-20-2014
Prepared by	Allison Cho
Version #	02
Further information	CRC # 591B-C
HMIS® ratings	Health: 2 Flammability: 3 Physical hazard: 0 Personal protection: B
NFPA ratings	Health: 2 Flammability: 3 Instability: 0
NFPA ratings	20

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety professional, or CRC Industries.