

KIT - SAFETY DATA SHEET

Product identifier used on the label: Kit Name Stock No.:

DEVCON® Floor Patch™ 13120

Other means of identification:

Recommended use of the chemical and restrictions on use:

 Chemical manufacturer address and telephone number:

 Manufacturer Name:
 ITW Polymers Adhesives, North America

 Address:
 30 Endicott Street Danvers, MA 01923

Component list	
Component A	FLOOR PATCH RESIN
Component C	FLOOR PATCH SAND
Component B	FLOOR RESURFACER HARDENER
Kit SDS Revision Date	12/20/2015

Component A - SDS

SECTION 1 : IDENTIFICATION

<u>Product identifier used on the label:</u> Product Name:	FLOOR PATCH RESIN
Other means of identification: Synonyms:	None.
Recommended use of the chemical and restr Product Use/Restriction:	i <u>ctions on use:</u> Not applicable.
Chemical manufacturer address and telephor Manufacturer Name:	<u>ne number:</u> ITW
Address:	30 Endicott Street Danvers, MA 01923
General Phone Number:	(978) 777-1100
Emergency phone number: Emergency Phone Number:	(800) 424-9300
CHEMTREC:	For emergencies in the US, call CHEMTREC: 800-424-9300

SECTION 2 : HAZARD(S) IDENTIFICATION

Classification of the chemical in accordance with CFR 1910.1200(d)(f):		
GHS Pictograms:		
Signal Word:	WARNING.	
GHS Class:	Eye Irritation. Category 2. Skin Irritation. Category 2. Skin Sensitization. Category 1. Specific Target Organ Toxicity - STOT, Single Exposure SE. Category 3.	
Hazard Statements:	H319 - Causes serious eye irritation. H315 - Causes skin irritation. H317 - May cause an allergic skin reaction. H335 - May cause respiratory irritation.	
Precautionary Statements:	P261 - Avoid breathing dust/fume/gas/mist/vapours/spray. P264 - Wash hands thoroughly after handling. P271 - Use only outdoors or in a well-ventilated area. P272 - Contaminated work clothing should not be allowed out of the workplace. P280 - Wear protective gloves/protective clothing/eye protection/face protection. P302+P352 - IF ON SKIN: Wash with plenty of water. P304+P340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for	

Product: DEVCON® Floor Patch™ | Manufacturer: | Revison:12/20/2015, Version:0

	breathing. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P312 - Call a POISON CENTER or doctor/physician if you feel unwell. P321 - Specific treatment (see on this label). P332+P313 - If skin irritation or curs: Get medical advice/attention. P333+P313 - If skin irritation or rash occurs: Get medical advice/attention. P337+P313 - If eye irritation persists: Get medical advice/attention. P362+P364 - Take off contaminated clothing and wash it before reuse. P403+P233 - Store in a well-ventilated place. Keep container tightly closed. P405 - Store locked up. P501 - Dispose of contents/container in accordance with Local, State, Federal and Provincial regulations.
Route of Exposure:	Eyes. Skin. Inhalation. Ingestion.
Potential Health Effects:	
Eye:	Can cause moderate irritation, burning sensation, tearing, redness, and swelling. Overexposure may cause lacrimation, conjunctivitis, corneal damage and permanent injury.
Skin:	Can cause skin irritation; itching, redness, rashes, hives, burning, and swelling. Allergic reactions are
	possible. May cause skin sensitization, an allergic reaction, which becomes evident on reexposure to this material.
Inhalation:	Respiratory tract irritant. High concentration may cause dizziness, headache, and anesthetic effects.
Ingestion:	Causes irritation, a burning sensation of the mouth, throat and gastrointestinal tract and abdominal pain.
Chronic Health Effects:	Prolonged skin contact may lead to burning associated with severe reddening, swelling, and possible tissue destruction.
Signs/Symptoms:	Overexposure can cause headaches, dizziness, nausea, and vomiting.
Target Organs:	Eyes. Skin. Respiratory system. Digestive system.
Aggravation of Pre-Existing Conditions:	Individuals with pre-existing skin disorders, asthma, allergies or known sensitization may be more susceptible to the effects of this product.

SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS

<u>Mixtures:</u> Chemical Name	CA S#	Ingredient Percent	EC Num.
Bisphenol A diglycidyl ether resin	25068-38-6	70 - 80 by weight	
Titanium dioxide Alkyl Glycidyl Ether	13463-67-7 68609-97-2	1 - 10 by weight 10 - 20 by weight	

SECTION 4 : FIRST AID MEASURES

Description of necessary measures:

Eye Contact:	Immediately flush eyes with plenty of water for at least 15 to 20 minutes. Ensure adequate flushing of the eyes by separating the eyelids with fingers. Get immediate medical attention.
Skin Contact:	Immediately wash skin with plenty of soap and water for 15 to 20 minutes, while removing contaminated clothing and shoes. Get medical attention if irritation develops or persists.
Inhalation:	If inhaled, remove to fresh air. If not breathing, give artificial respiration or give oxygen by trained personnel. Seek immediate medical attention.
Ingestion:	If swallowed, do NOT induce vomiting. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person.

SECTION 5 : FIRE FIGHTING MEASURES

	Suitable and unsuitable extinguishi	ng media:	
	Suitable Extinguishing Media:	Use carbon dioxide (CO2) or dry chemical when fighting fires involving this material.	
	Unsuitable extinguishing media:	Water or foam may cause frothing.	
	Unusual Fire Hazards:	Sealed containers at elevated temperatures may rupture explosively and spread fire due to polymerization. Heating above 300 deg F in the presence of air may cause slow oxidative decomposition and above 500 deg F may cause polymerization.	
Special protective equipment and precautions for fire-fighters:			
	Protective Equipment:	As in any fire, wear Self-Contained Breathing Apparatus (SCBA), MSHA/NIOSH (approved or equivalent and full protective gear.	t)
	Fire Fighting Instructions:	Evacuate area of unprotected personnel. Use cold water spray to cool fire exposed containers to	
	Produ	uct: DEVCON® Floor Patch™ Manufacturer: Revison:12/20/2015, Version:0	
		·	De

SECTION 6 : ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures:		
Personal Precautions:	Evacuate area and keep unnecessary and unprotected personnel from entering the spill area.	
Environmental precautions:		
Environmental Precautions:	Avoid runoff into storm sewers, ditches, and waterways.	
Methods and materials for containment and cleaning up:		
Spill Cleanup Measures:	Absorb spill with inert material (e,g., dry sand or earth), then place in a chemical waste container. Provide ventilation. Clean up spills immediately observing precautions in the protective equipment section. After removal, flush spill area with soap and water to remove trace residue. Avoid personal contact and breathing vapors or mists. Ventilate area. Use proper personal protective equipment as listed in Section 8.	
Reference to other sections:		
Other Precautions:	Pump or shovel to storage/salvage vessels.	

SECTION 7 : HANDLING and STORAGE

Precautions for safe handling:	
Handling:	Use with adequate ventilation. Avoid breathing vapor, aerosol or mist.
Hygiene Practices:	Wash thoroughly after handling.
Special Handling Procedures:	Provide appropriate ventilation/respiratory protection against decomposition products (see Section 10) during welding/flame cutting operations and to protect against dust during sanding/grinding of cured product.
Conditions for safe storage, including any incompatibilities:	
Storage:	Store in a cool, dry, well ventilated area away from sources of heat and incompatible materials. Keep container tightly closed when not in use.

SECTION 8: EXPOSURE CONTROLS, PERSONAL PROTECTION

EXPOSURE GUIDELINES:	
<u>Titanium dioxide</u> :	
Guideline ACGIH:	TLV-TWA: 10 mg/m3
Appropriate engineering controls:	
Engineering Controls:	Use appropriate engineering control such as process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Good general ventilation should be sufficient to control airborne levels. Where such systems are not effective wear suitable personal protective equipment, which performs satisfactorily and meets OSHA or other recognized standards. Consult with local procedures for selection, training, inspection and maintenance of the personal protective equipment.
Individual protection measures:	
Eye/Face Protection:	Wear appropriate protective glasses or splash goggles as described by 29 CFR 1910.133, OSHA eye and face protection regulation, or the European standard EN 166.
Skin Protection Description:	Wear appropriate protective gloves and other protective apparel to prevent skin contact. Consult manufacturer's data for permeability data.
Respiratory Protection:	A NIOSH approved air-purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection.
Other Protective:	Facilities storing or utilizing this material should be equipped with an eyewash and a deluge shower safety station.
Notes :	Only established PEL and TLV values for the ingredients are listed.

SECTION 9 : PHYSICAL and CHEMICAL PROPERTIES

PHYSICAL AND CHEMICAL PROPERTIES:

Physical State Appearance:	Viscous. Liquid.
Odor:	Slight. odor.
Boiling Point:	>500°F (260°C)
Melting Point:	Not determined.
Specific Gravity:	1.1-1.3
Solubility:	negligible.
Vapor Density:	>1 (air = 1)
Vapor Pressure:	0.03 mmHa @171°F
	Product: DEVCON® Floor Patch™ Manufacturer: Revison:12/20/2015, Version:0

Percent Volatile:	0
Evaporation Rate:	<<1 (butyl acetate = 1)
pH:	Neutral.
Molecular Formula:	Mixture
Molecular Weight:	Mixture
Flash Point:	>300°F (148.8°C)
Flash Point Method:	Estimated.
Lower Flammable/Explosive Limit:	Not determined.
Upper Flammable/Explosive Limit:	Not determined.
Auto Ignition Temperature:	Not determined.
VOC Content:	0 g/L
9.2. Other information:	
Percent Solids by Weight	100

SECTION 10 : STABILITY and REACTIVITY

Chemical Stability:	
Chemical Stability:	Stable under normal temperatures and pressures.
Possibility of hazardous reactions:	
Hazardous Polymerization:	Not reported.
Conditions To Avoid:	
Conditions to Avoid:	Extreme heat, sparks, and open flame. Incompatible materials, oxidizers and oxidizing conditions. Heating resin above 300 F in the presence of air may cause slow oxidative decomposition.
Incompatible Materials:	
Incompatible Materials:	Strong Lewis or mineral acids, strong oxidizing agents, strong mineral and organic bases (especially primary and secondary aliphatic amines).

SECTION 11 : TOXICOLOGICAL INFORMATION

TOXICOLOGICAL INFORMATION:

Bisphenol A diglycidyl ether resin :	
Eye :	Administration into the eye - Rabbit Standard Draize test: 100 mg [Mild] Administration into the eye - Rabbit Standard Draize test: 20 mg/24H [Moderate] Administration into the eye - Rabbit Standard Draize test: 5 mg/24H [Severe] (RTECS)
Skin:	Administration onto the skin - Rabbit LD50 - Lethal dose, 50 percent kill: >20 mL/kg [Details of toxic effects not reported other than lethal dose value] Administration onto the skin - Rat LD50 - Lethal dose, 50 percent kill: >1200 mg/kg [Details of toxic effects not reported other than lethal dose value] (RTECS)
Ingestion:	Oral - Rat LD50 - Lethal dose, 50 percent kill: 10700 uL/kg [Details of toxic effects not reported other than lethal dose value] Oral - Rat LD50 - Lethal dose, 50 percent kill: 13600 mg/kg [Behavioral - Somnolence (general depressed activity) Lungs, Thorax, or Respiration - Dyspnea Nutritional and Gross Metabolic - Weight loss or decreased weight gain] Oral - Rat LD50 - Lethal dose, 50 percent kill: 13.6 gm/kg [Details of toxic effects not reported other than lethal dose value] Oral - Rat LD50 - Lethal dose, 50 percent kill: 11.4 gm/kg [Details of toxic effects not reported other than lethal dose value] Oral - Rat LD50 - Lethal dose, 50 percent kill: 30 gm/kg [Behavioral - Somnolence (general depressed activity) Lungs, Thorax, or Respiration - Dyspnea Nutritional and Gross Metabolic - Weight loss or decreased weight gain] Oral - Rat LD50 - Lethal dose, 50 percent kill: 30 gm/kg [Details of toxic effects not reported other than lethal dose value] Oral - Rat LD50 - Lethal dose, 50 percent kill: 30 gm/kg [Details of toxic effects not reported other than lethal dose value] Oral - Rat LD50 - Lethal dose, 50 percent kill: 30 gm/kg [Details of toxic effects not reported other than lethal dose value] Oral - Rat LD50 - Lethal dose, 50 percent kill: >1 gm/kg [Details of toxic effects not reported other than lethal dose value] Oral - Rat LD50 - Lethal dose, 50 percent kill: >1 gm/kg [Details of toxic effects not reported other than lethal dose value] Oral - Rat LD50 - Lethal dose, 50 percent kill: >1 gm/kg [Details of toxic effects not reported other than lethal dose value]
Titanium dioxide :	
Chronic Effects:	Normal application procedures for this product pose minimal hazard as to the release of respirable titanium dioxide dust, but grinding or sanding dried films of this product may yield some respirable titanium dioxide. Although IARC has classified titanium dioxide as possible carcinogenic to human (2B), their summary concludes: "No significant exposure to titanium dioxide is thought to occur during the use of products which titanium dioxide is bound to other materials". OSHA does not regulate titanium dioxide as a carcinogen. However, under 29CFR 1910.1200 the SDS must convey the fact that titanium dioxide is a potential carcinogen to rats.
Carcinogenicity:	Animal evidence shows that high concentrations of pigment-grade (powdered) and ultrafine titanium dioxide dust caused respiratory tract cancer in rats exposed by inhalation.
Alkyl Glycidyl Ether :	
Ingestion:	Oral - Rat LD50 - Lethal dose, 50 percent kill: 17100 mg/kg [Details of toxic effects not reported other than lethal dose value] Oral - Rat LD50 - Lethal dose, 50 percent kill: 19.2 mL/kg [Details of toxic effects not reported other than lethal dose value] (RTECS)

SECTION 12 : ECOLOGICAL INFORMATION

Ecotoxicity:

Ecotoxicity:

Environmental Fate:

No ecotoxicity data was found for the product.

No environmental information found for this product.

SECTION 13 : DISPOSAL CONSIDERATIONS

Description of waste:	
Waste Disposal:	Consult with the US EPA Guidelines listed in 40 CFR Part 261.3 for the classifications of hazardous waste prior to disposal. Furthermore, consult with your state and local waste requirements or guidelines, if applicable, to ensure compliance. Arrange disposal in accordance to the EPA and/or state and local guidelines.
RCRA Number:	Not determined.

SECTION 14 : TRANSPORT INFORMATION

DOT Shipping Name:	Refer to Bill of Lading
DOT UN Number:	Refer to Bill of Lading
IATA Shipping Name:	Refer to Bill of Lading
IATA UN Number:	Refer to Bill of Lading
IMDG UN NUmber :	Refer to Bill of Lading
IMDG Shipping Name :	Refer to Bill of Lading

SECTION 15 : REGULATORY INFORMATION

Safety, health and environmental regulations specific for the product:	
Bisphenol A diglycidyl ether resin :	
TSCA Inventory Status:	Listed
Canada DSL:	Listed
<u>Titanium dioxide</u> :	
TSCA Inventory Status:	Listed
Canada DSL:	Listed
Alkyl Glycidyl Ether :	
TSCA Inventory Status:	Listed
Canada DSL:	Listed
Canadian Regulations.	WHMIS Hazard Class(es): D2B All components of this product are on the Canadian Domestic Substances List.
WHMIS Pictograms:	\bigcirc

SECTION 16 : ADDITIONAL INFORMATION

HMIS Ratings:			
HMIS Health Hazard:	2*	Health Hazard	2*
HMIS Fire Hazard:	1	Fire Hazard	1
HMIS Reactivity:	1	Reactivity	1
HMIS Personal Protection:	X	Personal Protection	x
		* Chronic Health Effects	
SDS Revision Date:	March 17, 2015		
MSDS Revision Notes:	GHS Update		
SDS Format:	In accordance to OSHA GHS 1910.1200		
MSDS Author:	Actio Corporation		
Disclaimer: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. ITW Polymers Adhesives, NA, MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the ITW Polymers Adhesives, NA product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a ITW Polymers Adhesives, NA product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the ITW Polymers Adhesives, NA product to determine whether it is			

fit for a particular purpose and suitable for user's method of use or application. ITW Polymers Adhesives, NA provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, ITW Polymers Adhesives, NA makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the MSDS available directly from ITW Polymers Adhesives, NA

Copyright© 1996-2015 Actio Corporation. All Rights Reserved.

Component C - SDS

SECTION 1 : IDENTIFICATION

Product identifier used on the label: Product Name:

FLOOR PATCH SAND

Other means of identification:

Recommended use of the chemical and restrictions on use:

Chemical manufacturer address and telephor	ne number:
Manufacturer Name:	ITW
Address:	30 Endicott Street Danvers, MA 01923
General Phone Number:	(978) 777-1100
Emergency phone number:	
Emergency Phone Number:	(800) 424-9300
CHEMTREC:	For emergencies in the US, call CHEMTREC: 800-424-9300

SECTION 2 : HAZARD(S) IDENTIFICATION

Classification of the chemical in accordance with CFR 1910.1200(d)(f):

GHS Pictograms:	
Signal Word:	DANGER.
GHS Class:	Specific Target Organ Toxicity -STOT Repeated exposure RE. Category 1 (Inhalation, Lung). Carcinogenicity. Category 1A.
Hazard Statements:	H372 - Causes damage to organs through prolonged or repeated exposure. H350 - May cause cancer.
Precautionary Statements:	 P201 - Obtain special instructions before use. P202 - Do not handle until all safety precautions have been read and understood. P260 - Do not breathe dust/fume/gas/mist/vapours/spray. P264 - Wash hands thoroughly after handling. P270 - Do not eat, drink or smoke when using this product. P280 - Wear protective gloves/protective clothing/eye protection/face protection. P308+P313 - IF exposed or concerned: Get medical advice/attention. P314 - Get medical advice/attention if you feel unwell. P405 - Store locked up. P501 - Dispose of contents/container in accordance with Local, State, Federal and Provincial regulations.
Hazards not otherwise classified that	at have been identified during the classification process:
Emergency Overview:	CAUTION! Irritant.
Route of Exposure:	Eyes. Skin. Inhalation. Ingestion.
Potential Health Effects:	
Eye:	May cause irritation.
Skin:	May cause irritation.
Inhalation:	Prolonged or excessive inhalation may cause respiratory tract irritation.
Ingestion:	May be harmful if swallowed. May cause vomiting.
Chronic Health Effects:	Prolonged or repeated contact may cause skin irritation.
Signs/Symptoms:	Overexposure may cause headaches and dizziness.
Target Organs:	Eyes. Skin. Respiratory system. Digestive system.
Aggravation of Pre-Existing Conditions:	None generally recognized.

SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS

Mixtures:

14808-60-7

Ingredient Percent

60 - 100 by weight

SECTION 4 : FIRST AID MEASURES

Description of necessary measures	<u>.</u>
Eye Contact:	Immediately flush eyes with plenty of water for at least 15 to 20 minutes. Ensure adequate flushing of the eyes by separating the eyelids with fingers. Get immediate medical attention.
Skin Contact:	Immediately wash skin with plenty of soap and water for 15 to 20 minutes, while removing contaminated clothing and shoes. Get medical attention if irritation develops or persists.
Inhalation:	If inhaled, remove to fresh air. If not breathing, give artificial respiration or give oxygen by trained personnel. Seek immediate medical attention.
Ingestion:	If swallowed, do NOT induce vomiting. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person.

SECTION 5 : FIRE FIGHTING MEASURES

Suitable and unsuitable extinguishing media:

Suitable Extinguishing Media:	Use carbon dioxide (CO2) or dry chemical when fighting fires involving this material.
Special protective equipment and	precautions for fire-fighters:
Protective Equipment:	As in any fire, wear Self-Contained Breathing Apparatus (SCBA), MSHA/NIOSH (approved or equivalent) and full protective gear.
Fire Fighting Instructions:	Evacuate area of unprotected personnel. Use cold water spray to cool fire exposed containers to minimize risk of rupture. Do not enter confined fire space without full protective gear. If possible, contain fire run-off water.

SECTION 6 : ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures:	
Personal Precautions:	Evacuate area and keep unnecessary and unprotected personnel from entering the spill area.
Environmental precautions:	
Environmental Precautions:	Avoid runoff into storm sewers, ditches, and waterways.
Methods and materials for containment and cleaning up:	
Spill Cleanup Measures:	Shovel or sweep up for re-use or disposal. Avoid creating dusty conditions. Provide ventilation. Clean up spills immediately observing precautions in the protective equipment section. After removal, flush spill area with soap and water to remove trace residue. Avoid personal contact and breathing dust. Ventilate area. Use proper personal protective equipment as listed in Section 8.
Reference to other sections:	
Other Precautions:	Pump or shovel to storage/salvage vessels.

SECTION 7 : HANDLING and STORAGE

Precautions for safe handling:				
Handling:	Use with adequate ventilation. Avoid breathing dust or particulates.			
Hygiene Practices:	Wash thoroughly after handling.			
Conditions for safe storage, including any incompatibilities:				
Storage:	Store in a cool, dry, well ventilated area away from sources of heat and incompatible materials. Keep container tightly closed when not in use.			

SECTION 8: EXPOSURE CONTROLS, PERSONAL PROTECTION

EXPOSURE GUIDELINES:	
Crystalline silica :	
Guideline ACGIH:	0.025 mg/m3 TLV-TWA: 0.025 mg/m3 Respirable fraction (R)
Guideline OSHA:	[10 mg/m3]/[{% SiO2} + 2]
Appropriate engineering controls:	

Engineering Controls:	Use appropriate engineering control such as process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Good general ventilation should be sufficient to control airborne levels. Where such systems are not effective wear suitable personal protective equipment, which performs satisfactorily and meets OSHA or other recognized standards. Consult with local procedures for selection, training, inspection and maintenance of the personal protective equipment.
Individual protection measures:	
Eye/Face Protection:	Wear appropriate protective glasses or splash goggles as described by 29 CFR 1910.133, OSHA eye and face protection regulation, or the European standard EN 166.
Skin Protection Description:	Wear appropriate protective gloves and other protective apparel to prevent skin contact. Consult manufacturer's data for permeability data.
Respiratory Protection:	A NIOSH approved air-purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection.
Other Protective:	Facilities storing or utilizing this material should be equipped with an eyewash and a deluge shower safety station.
Notes :	Only established PEL and TLV values for the ingredients are listed.

SECTION 9 : PHYSICAL and CHEMICAL PROPERTIES

PHYSICAL AND CHEMICAL PROPERTIES:

Physical State Appearance:	Granular
Color:	light brown
Odor:	Odorless
Boiling Point:	4046°F (2230°C)
Melting Point:	2930°F (1610°C)
Specific Gravity:	2.65
Solubility:	negligible.
Vapor Density:	No vapor
Vapor Pressure:	Not determined.
Percent Volatile:	0
Evaporation Rate:	Not determined.
pH:	Neutral.
Molecular Formula:	Mixture
Molecular Weight:	Mixture
Flash Point:	Not determined.
Lower Flammable/Explosive Limit:	Not determined.
Upper Flammable/Explosive Limit:	Not determined.
Auto Ignition Temperature:	Not determined.
VOC Content:	0 g/L
9.2. Other information:	
Percent Solids by Weight	100

SECTION 10 : STABILITY and REACTIVITY

Chemical Stability:	
Chemical Stability:	Stable under normal temperatures and pressures.
Possibility of hazardous reactions:	
Hazardous Polymerization:	Not reported.
Conditions To Avoid:	
Conditions to Avoid:	None known.
Incompatible Materials:	
Incompatible Materials:	Oxidizing agents. Strong acids and alkalis.

SECTION 11 : TOXICOLOGICAL INFORMATION

TOXICOLOGICAL INFORMATION:

Crystalline silica :

RTECS Number:

VV7330000

SECTION 12 : ECOLO	GICAL INFORMATION	
Ecotoxicity:		
Ecotoxicity:	No ecotoxicity data was found for the product.	

Environmental Fate:

No environmental information found for this product.

SECTION 13 : DISPOSAL CONSIDERATIONS

Waste Disposal:	Consult with the US EPA Guidelines listed in 40 CFR Part 261.3 for the classifications of hazardous waste prior to disposal. Furthermore, consult with your state and local waste requirements or guideline: if applicable, to ensure compliance. Arrange disposal in accordance to the EPA and/or state and local guidelines.
RCRA Number:	Not determined.

SECTION 14 : TRANSPORT INFORMATION

DOT Shipping Name:	Non regulated.
DOT UN Number:	Not applicable.
DOT Hazard Class:	Not applicable.
DOT Packing Group:	Not applicable.

SECTION 15 : REGULATORY INFORMATION

Safety, health and environmental regulations specific for the product:

Crystalline silica :	
TSCA Inventory Status:	Listed
Massachusetts:	Listed
Pennsylvania:	Listed
Canada DSL:	Listed
Canadian Regulations.	WHMIS Hazard Class(es): D2B; D2A All components of this product are on the Canadian Domestic Substances List.
WHMIS Pictograms:	$\overline{\mathbf{O}}$

SECTION 16 : ADDITIONAL INFORMATION

HMIS Ratings:				
HMIS Health Hazard:	1*		Health Hazard	1*
HMIS Fire Hazard:	0		Fire Hazard	0
HMIS Reactivity:	0		Reactivity	0
HMIS Personal Protection:	X		Personal Protection	x
		* Chronic I	Health Effects	
SDS Revision Date:	November 30, 2015			
MSDS Revision Notes:	GHS Update			
SDS Format:	In accordance to OSHA GHS 1910.1200			
MSDS Author:	Actio Corporation			
Disclaimer:	The information in this Safety Data Sheet (SDS) is belie Polymers Adhesives, NA, MAKES NO WARRANTIES, EXPR LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTAB OR COURSE OF PERFORMANCE OR USAGE OF TRADE. U ITW Polymers Adhesives, NA product is fit for a particul- use or application. Given the variety of factors that can Polymers Adhesives, NA product, some of which are uni is essential that the user evaluate the ITW Polymers Ad- fit for a particular purpose and suitable for user's meth- Adhesives, NA provides information in electronic form a possibility that electronic transfer may have resulted in information, ITW Polymers Adhesives, NA makes no rej accuracy. In addition, information obtained from a data in the MSDS available directly from ITW Polymers Adhe	ESSED OR IMPLIED, ILITY OR FITNESS F ser is responsible fo ar purpose and suita affect the use and a quely within the use dhesives, NA product od of use or applicai s a service to its cus errors, omissions on presentations as to base may not be as	INCLUDING, BUT NOT OR A PARTICULAR PUR r determining whether t able for user's method of application of a ITW r's knowledge and conti t to determine whether tion. ITW Polymers itomers. Due to the rem r alterations in this r completeness or	POSE the of rol, it it is note

Component B - SDS

SECTION 1 : IDENTIFICATION

Product identifier used on the label: Product Name:	FLOOR RESURFACER HARDENER
Other means of identification:	
Synonyms:	None.
Recommended use of the chemical and restric	ctions on use:
Product Use/Restriction:	Not applicable.
Chemical manufacturer address and telephon	e number:
Manufacturer Name:	ITW
Address:	30 Endicott Street Danvers, MA 01923
General Phone Number:	(978) 777-1100
Emergency phone number:	
Emergency Phone Number:	(800) 424-9300
CHEMTREC:	For emergencies in the US, call CHEMTREC: 800-424-9300

SECTION 2 : HAZARD(S) IDENTIFICATION

<u>Classification</u>	of the	chemical	in	accordance	with	CFR	1910.1200)(d)(f):

GHS Pictograms: Signal Word: DANGER GHS Class: Acute Inhalation Toxicity. Category 2. Serious Eye Damage. Category 1. Skin corrosion. Category 1. Reproductive toxicity. Category 2. Skin Sensitization. Category 1. Acute Dermal Toxicity. Category 4. Acute Oral Toxicity. Category 4. Specific Target Organ Toxicity - STOT, Single Exposure SE. Category 3. Hazard Statements: H330 - Fatal if inhaled. H318 - Causes serious eve damage. H314 - Causes server skin burns and eye damage. H361 - Suspected of damaging fertility or the unborn child. H317 - May cause an allergic skin reaction. H312 - Harmful in contact with skin. H302 - Harmful if swallowed. H335 - May cause respiratory irritation. P201 - Obtain special instructions before use. P202 - Do not handle until all safety precautions have been read and understood. P260 - Do not breathe dust/fume/gas/mist/vapours/spray. P261 - Avoid breathing dust/fume/gas/mist/vapours/spray. Precautionary Statements: P264 - Wash hands thoroughly after handling. P270 - Do not eat, drink or smoke when using this product. P271 - Use only outdoors or in a well-ventilated area. P272 - Contaminated work clothing should not be allowed out of the workplace. P280 - Wear protective gloves/protective clothing/eye protection/face protection. P284 - In case of inadequate ventilation wear respiratory protection. P301+P312 - IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell. P301+P330+P331 - IF SWALLOWED: Rinse mouth. Do not induce vomiting. P302+P352 - IF ON SKIN: Wash with plenty of water. P303+P361+P353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower P304+P340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. breathing. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P308+P313 - IF exposed or concerned: Get medical advice/attention. P310 - Immediately call a POISON CENTER or doctor/physician. P312 - Call a POISON CENTER or doctor/physician if you feel unwell. P320 - Specific treatment is urgent (see ... on this label). P321 - P330 - Rinse mouth. P333+P313 - If skin irritation or rash occurs: Get medical advice/attention. P362+P364 - Take off contaminated clothing and wash it before reuse. P363 - Wash contaminated clothing before reuse. P403+P233 - Store in a well-ventilated place. Keep container tightly closed. P363 - Wash contaminated clothing before lease. P403+P233 - Store in a well-ventilated place. Keep container tightly closed. P405 - Store locked up. P501 - Dispose of contents/container in accordance with Local, State, Federal and Provincial regulations. Hazards not otherwise classified that have been identified during the classification process:

Route of Exposure: Eyes. Skin. Inhalation. Ingestion.

Potential Health Effects:

Eye:	Corrosive. Will cause eye burns, permanent tissue damage, and blindness.
Skin:	Contact causes severe skin irritation and possible burns. may cause permanent skin damage. Allergic reactions are possible. May cause skin sensitization, an allergic reaction, which becomes evident on reexposure to this material.
Inhalation:	Very toxic by inhalation. May cause severe respiratory system irritation.
Ingestion:	Harmful if swallowed. Corrosive to the gastrointestinal tract.
Chronic Health Effects:	Prolonged skin contact causes burns. Repeated or prolonged inhalation may cause toxic effects.
Signs/Symptoms:	Repeated and/or prolonged exposure to low concentrations of vapors and/or aerosols may cause sore throat, asthma, eye disease, kidney and liver disorders, and skin disorders and allergies.
Target Organs:	Eyes. Skin. Respiratory system. Digestive system.
Aggravation of Pre-Existing Conditions:	Individuals with pre-existing skin disorders, asthma, allergies or known sensitization may be more susceptible to the effects of this product.

SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS

<u>Mixtures:</u> Chemical Name	CA S#	Ingredient Percent	EC Num.
Proprietary Ingredient(s)	No Data	40 - 50 by weight	
Diethylenetriamine	111-40-0	20 - 30 by weight	
Bisphenol A	80-05-7	20 - 30 by weight	

SECTION 4 : FIRST AID MEASURES

Description of necessary measures:			
Eye Contact:	Hold eyelids apart, initiate and maintain gentle and continuous irrigation until the patient receives medical care If medical care is not promptly available, continue to irrigate for one hour		
Skin Contact:	Immediately remove contaminated clothing, and any extraneous chemical, if possible to do so without delay Initiate and maintain continuous irrigation until the patient receives medical care If medical care is not promptly available, continue to irrigate for one hour		
Inhalation:	If inhaled, remove to fresh air. If not breathing, give artificial respiration or give oxygen by trained personnel. Seek immediate medical attention.		
Ingestion:	If swallowed, do NOT induce vomiting. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person. Prevent aspiration of vomit. Turn patient's head to the side.		
Most important symptoms/effects, acute and delayed:			
Other First Aid:	Repeated and/or prolonged exposure to low concentrations of vapors and/or aerosols may cause sore throat, asthma, eye disease, kidney and liver disorders, and skin disorders and allergies. Neoprene gloves. Nitrile rubber or natural rubber gloves are recommended.		

 $\underline{Indication \ of \ immediate \ medical \ attention \ and \ special \ treatment \ needed:}$

Note to Physicians: Application of corticosteroid cream has been effective in treating skin irritation.

SECTION 5 : FIRE FIGHTING MEASURES

Suitable and unsuitable extinguishing media:		
Suitable and unsuitable extinguist		
Suitable Extinguishing Media:	Use carbon dioxide (CO2) or dry chemical when fighting fires involving this material.	
Unsuitable extinguishing media:	No information.	
Unusual Fire Hazards:	May generate ammonia gas. May generate toxic nitrogen oxide gases. Use of water may result in the formation of very toxic aqueous solutions. Incomplete combustion may form carbon monoxide. Downstream personnel must be evacuated.	
Special protective equipment and precautions for fire-fighters:		
Protective Equipment:	As in any fire, wear Self-Contained Breathing Apparatus (SCBA), MSHA/NIOSH (approved or equivalent) and full protective gear.	
Fire Fighting Instructions:	Evacuate area of unprotected personnel. Use cold water spray to cool fire exposed containers to minimize risk of rupture. Do not enter confined fire space without full protective gear. If possible, contain fire run-off water.	

SECTION 6 : ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures:		
Personal Precautions:	Evacuate area and keep unnecessary and unprotected personnel from entering the spill area.	
Environmental precautions:		
Environmental Precautions:	Avoid runoff into storm sewers, ditches, and waterways.	
Methods and materials for containment and cleaning up:		
Spill Cleanup Measures:	Absorb spill with inert material (e,g., dry sand or earth), then place in a chemical waste container. Provide ventilation. Clean up spills immediately observing precautions in the protective equipment section. After removal, flush spill area with soap and water to remove trace residue. Corrosive. Avoid personal contact and breathing vapors or mists. Ventilate area. Use proper personal protective equipment as listed in Section 8.	
Reference to other sections:		
Other Precautions:	Pump or shovel to storage/salvage vessels.	

SECTION 7 : HANDLING and STORAGE

Precautions for safe handling:		
Handling:	Do not use sodium nitrite or other nitrosating agents in formulations containing this product. Suspected cancercausing nitrosamines could be formed. Use with adequate ventilation. Avoid breathing vapor, aerosol or mist. Avoid contact with eyes and skin. Do not reuse containers without proper cleaning or reconditioning. When using, do not eat, drink or smoke.	
Hygiene Practices:	Wash thoroughly after handling.	
Special Handling Procedures:	Provide appropriate ventilation/respiratory protection against decomposition products (see Section 10) during welding/flame cutting operations and to protect against dust during sanding/grinding of cured product.	
Conditions for safe storage, including any incompatibilities:		
Storage:	Store in a cool, dry, well ventilated area away from sources of heat and incompatible materials. Keep container tightly closed when not in use. Do not store in reactive metal containers. Keep away from acids, oxidizers.	

SECTION 8: EXPOSURE CONTROLS, PERSONAL PROTECTION

EXPOSURE GUIDELINES:	
Diethylenetriamine :	
Guideline ACGIH:	Skin: Yes. TLV-TWA: 1 ppm
Appropriate engineering controls	<u>.</u>
Engineering Controls:	Use appropriate engineering control such as process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Good general ventilation should be sufficient to control airborne levels. Where such systems are not effective wear suitable personal protective equipment, which performs satisfactorily and meets OSHA or other recognized standards. Consult with local procedures for selection, training, inspection and maintenance of the personal protective equipment.
Individual protection measures:	
Eye/Face Protection:	Wear appropriate protective glasses or splash goggles as described by 29 CFR 1910.133, OSHA eye and face protection regulation, or the European standard EN 166.
Skin Protection Description:	Chemical-resistant gloves and chemical goggles, face-shield and synthetic apron or coveralls should be used to prevent contact with eyes, skin or clothing.
Hand Protection Description:	Butyl rubber. Nitrile rubber. Neoprene gloves. Impervious gloves. Consult glove manufacturer for permeability data.
Respiratory Protection:	A NIOSH approved air-purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection.
Other Protective:	Facilities storing or utilizing this material should be equipped with an eyewash and a deluge shower safety station.
Notes :	Only established PEL and TLV values for the ingredients are listed.

SECTION 9 : PHYSICAL and CHEMICAL PROPERTIES

PHYSICAL AND CHEMICAL PROPERTIES:		
Physical State Appearance:	Liquid.	
Color:	Amber.	
Odor:	Ammonia like.	
Boiling Point:	401°F (205°C)	
Melting Point:	< -0.4°F (-18°C)	
Product DEV(CON)® Book Date TMI Manufacturer Devis and 2/20/2045 \ Arrian 0		

Specific Gravity:	1.03
Solubility:	1.4% W/W @ 68 F
Vapor Density:	3.5 (DETA) (air = 1)
Vapor Pressure:	<0.1 mmHg @77°F
Percent Volatile:	0
Evaporation Rate:	Not determined.
pH:	alkaline
Molecular Formula:	Mixture
Molecular Weight:	Mixture
Flash Point:	217°F (102.7°C)
Flash Point Method:	Pensky-Martens Closed Cup
Lower Flammable/Explosive Limit:	Not determined.
Upper Flammable/Explosive Limit:	Not determined.
Auto Ignition Temperature:	Alcohol resistant foam, carbon dioxide, dry chemical, dry sand, and limestone powder
VOC Content:	0 g/L
9.2. Other information:	
Percent Solids by Weight	100

SECTION 10 : STABILITY and REACTIVITY

Chemical Stability:	
Chemical Stability:	Stable under normal temperatures and pressures.
Possibility of hazardous reactions:	
Hazardous Polymerization:	Not reported.
Conditions To Avoid:	
Conditions to Avoid:	Extreme heat, sparks, and open flame. Incompatible materials, oxidizers and oxidizing conditions. Product may slowly corrode copper, aluminum, zinc and galvanized surfaces.
Incompatible Materials:	
Incompatible Materials:	Oxidizers, acids, and chlorinated organic compounds. Reactive metals (e.g. sodium, calcium, zinc). Sodium/calcium hypochlorite. Nitrous acid/ oxide, nitrites. Peroxides. Materials reactive with hydroxyl compounds. Oxidizing agents and isocyanates and polyurethanes should be avoided as these will cause exothermic polymerization. Avoid extreme heat WARNING: Use with nitrites will form cancer causing nitrosamines
Hazardous Decomposition Products	<u>.</u>
Special Decomposition Products:	Nitric acid Ammonia Nitrogen oxide can react with water vapors to form corrosive nitric acid. Aldehydes Flammable hydrocarbon fragments. Nitrosamine. Oxides of carbon (carbon dioxide and monoxide).

SECTION 11 : TOXICOLOGICAL INFORMATION

TOXICOLOGICAL INFORMATION:

Diethylenetriamine :	
Skin:	Administration onto the skin - Rabbit LD50 - Lethal dose, 50 percent kill: 1090 mg/kg [Details of toxic effects not reported other than lethal dose value] (RTECS)
Ingestion:	Oral - Rat LD50 - Lethal dose, 50 percent kill: 1080 mg/kg [Behavioral - Convulsions or effect on seizure threshold] (RTECS)
Bisphenol A :	
Eye:	Administration into the eye - Rabbit Standard Draize test: 250 ug/24H [Severe] (RTECS)
Skin:	Administration onto the skin - Rabbit LD50 - Lethal dose, 50 percent kill: 3 mL/kg [Details of toxic effects not reported other than lethal dose value] (RTECS)
Inhalation:	Inhalation - Rat LC50 - Lethal concentration, 50 percent kill: >170 mg/m3/6H [Details of toxic effects not reported other than lethal dose value] Inhalation - Rat LC50 - Lethal concentration, 50 percent kill: >170 mg/m3 [Details of toxic effects not reported other than lethal dose value] (RTECS)
Ingestion:	Oral - Rat LD50 - Lethal dose, 50 percent kill: 1200 mg/kg [Reproductive - Fertility - female fertility index (e.g., number females pregnant per number sperm positive females; number females pregnant per number females mated)] Oral - Rat LD50 - Lethal dose, 50 percent kill: 4240 mg/kg [Kidney/Ureter/Bladder - Other changes in urine composition] Oral - Rat LD50 - Lethal dose, 50 percent kill: 3250 mg/kg [Details of toxic effects not reported other than lethal dose value] (RTECS)
Reproductive Toxicity:	May impair fertility.

SECTION 12 : ECOLOGICAL INFORMATION

No ecotoxicity data was found for the product.

Environmental Fate:

No environmental information found for this product.

SECTION 13 : DISPOSAL CONSIDERATIONS

Description of waste:

Waste Disposal:

Consult with the US EPA Guidelines listed in 40 CFR Part 261.3 for the classifications of hazardous waste prior to disposal. Furthermore, consult with your state and local waste requirements or guidelines, if applicable, to ensure compliance. Arrange disposal in accordance to the EPA and/or state and local guidelines.

SECTION 14 : TRANSPORT INFORMATION

DOT Shipping Name:	Refer to Bill of Lading
DOT UN Number:	Refer to Bill of Lading
IATA Shipping Name:	Refer to Bill of Lading
IATA UN Number:	Refer to Bill of Lading
IMDG UN NUmber :	Refer to Bill of Lading
IMDG Shipping Name :	Refer to Bill of Lading

SECTION 15 : REGULATORY INFORMATION

Safety, health and environmental regulations specific for the product:

Diethylenetriamine :	
TSCA Inventory Status:	Listed
Canada DSL:	Listed
Bisphenol A :	
TSCA Inventory Status:	Listed
Section 313:	EPCRA - 40 CFR Part 372 - (SARA Title III) Section 313 Listed Chemical.
California PROP 65:	Listed: developmental.
Canada DSL:	Listed
Canadian Regulations.	WHMIS Hazard Class(es): D2B; E All components of this product are on the Canadian Domestic Substances List.
WHMIS Pictograms:	\bigcirc

SECTION 16 : ADDITIONAL INFORMATION

HMIS Ratings:			
HMIS Health Hazard:	3*	Health Hazard	3*
HMIS Fire Hazard:	1	Fire Hazard	1
HMIS Reactivity:	1	Reactivity	1
HMIS Personal Protection:	X	Personal Protection	x
	* Chronic	Health Effects	
SDS Revision Date:	July 25, 2015		
MSDS Revision Notes:	GHS Update		
SDS Format:	In accordance to OSHA GHS 1910.1200		
MSDS Author:	Actio Corporation		
Disclaimer:	The information in this Safety Data Sheet (SDS) is believed to be correct a Polymers Adhesives, NA, MAKES NO WARRANTIES, EXPRESSED OR IMPLIED LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible f ITW Polymers Adhesives, NA product is fit for a particular purpose and sui use or application. Given the variety of factors that can affect the use and Polymers Adhesives, NA product, some of which are uniquely within the us is essential that the user evaluate the ITW Polymers Adhesives, NA product fit for a particular purpose and suitable for user's method of use or applic Adhesives, NA provides information in electronic form as a service to its cc possibility that electronic transfer may have resulted in errors, omissions of information, ITW Polymers Adhesives, NA makes no representations as to accuracy. In addition, information obtained from a database may not be a in the MSDS available directly from ITW Polymers Adhesives, NA	b) INCLUDING, BUT NOT FOR A PARTICULAR PUR for determining whether table for user's method application of a ITW er's knowledge and cont ct to determine whether ation. ITW Polymers istomers. Due to the rer or alterations in this its completeness or	POSE the of trol, it it is note

 ${\tt Copyright} \circledast$ 1996-2015 Actio Corporation. All Rights Reserved.