SAFETY DATA SHEET



Issuing Date 22-Jul-2014 Revision Date 22-Jul-2014 Revision Number 0

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY/UNDERTAKING

GHS product identifier

Product Name Cross Check™ (All Colors)

Other means of identification

Part Number 83314, 83315, 83316, 83317, 83318

Formula Code A498M, A991M, A992M, A993M, A994M

UN-Number UN1993

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use Inspection Paint

Uses advised against No information available

Supplier's details

Supplier Address ITW PRO BRANDS 805 E. Old 56 Highway Olathe, KS 66061 TEL: 1-800-443-9536

Emergency telephone number

Emergency Telephone

800-535-5053 Infotrac

Number

2. HAZARDS IDENTIFICATION

Classification

This chemical is considered hazardous according to the OSHA Hazard Communication Standard 2012 (29 CFR 1910.1200)

Serious Eye Damage/Eye Irritation	Category 1
Skin Sensitization	Category 1
Germ Cell Mutagenicity	Category 1B
Carcinogenicity	Category 2
Aspiration Toxicity	Category 1
Flammable liquids	Category 3

GHS Label elements, including precautionary statements

Emergency Overview

Signal Word Danger

Hazard Statements

- Causes serious eye damage
- May cause an allergic skin reaction
- May cause genetic defects
- Suspected of causing cancer
- May be fatal if swallowed and enters airways
- Flammable liquid and vapor.



Appearance Opaque, Varies

Physical State Viscous liquid.

Odor Mild

Precautionary Statements

Prevention

- · Obtain special instructions before use.
- Do not handle until all safety precautions have been read and understood.
- Use personal protective equipment as required.
- Avoid breathing dust/fume/gas/mist/vapors/spray.
- Contaminated work clothing should not be allowed out of the workplace.
- Keep away from heat/sparks/open flames/hot surfaces No smoking.
- · Keep container tightly closed.
- · Ground/bond container and receiving equipment.
- Use explosion-proof electrical/ventilating/lighting/equipment.
- Use only non-sparking tools.
- Take precautionary measures against static discharge.
- Wear protective gloves/protective clothing/eye protection/face protection.

General Advice

- If exposed or concerned: Get medical attention/advice
- Specific treatment (see supplemental first aid instructions on this label)

Eves

- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- Immediately call a POISON CENTER or doctor/physician.

Skin

- If skin irritation or rash occurs: Get medical advice/attention.
- Wash contaminated clothing before reuse.
- IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

Ingestion

- IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
- · Do NOT induce vomiting.

Fire

• In case of fire: Use CO2, dry chemical, or foam for extinction.

Storage

- Store locked up.
- Store in a well-ventilated place. Keep cool.

Disposal

• Dispose of contents/container to an approved waste disposal plant.

Hazard Not Otherwise Classified (HNOC)

Not applicable

Other information

Harmful to aquatic life with long lasting effects

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS-No	Weight %	Trade secret
Stoddard solvent	8052-41-3	30-60	*
Methyl ethyl ketoxime	96-29-7	1-5	*
Diacetone alcohol	123-42-2	1-5	*
Ethylbenzene	100-41-4	0.1-1	*

^{*}The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

Description of necessary first-aid measures

General Advice Immediate medical attention is required. Show this safety data sheet to the doctor in

attendance.

Eye Contact Keep eye wide open while rinsing. Immediately flush with plenty of water. After initial

flushing, remove any contact lenses and continue flushing for at least 15 minutes. If

symptoms persist, call a physician.

Skin Contact Wash off immediately with soap and plenty of water removing all contaminated clothes and

shoes. In the case of skin irritation or allergic reactions see a physician.

Inhalation Move to fresh air. If symptoms persist, call a physician.

Ingestion Rinse mouth. Do NOT induce vomiting. Never give anything by mouth to an unconscious

person. Drink plenty of water. If symptoms persist, call a physician.

Protection of First-aiders Remove all sources of ignition.

Most important symptoms/effects, acute and delayed

Most Important Symptoms/Effects No information available.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to Physician May cause sensitization of susceptible persons.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Carbon dioxide (CO₂). Foam. Dry chemical. Water fog.

Unsuitable Extinguishing Media CAUTION: Use of water spray when fighting fire may be inefficient.

Specific Hazards Arising from the Chemical

May cause sensitization by inhalation and skin contact. Thermal decomposition can lead to release of irritating gases and vapors. In the event of fire and/or explosion do not breathe fumes. Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks).

Explosion Data

Sensitivity to Mechanical Impact Sensitivity to Static Discharge None. Yes.

Protective Equipment and Precautions for Firefighters

Cool closed containers exposed to fire with water spray. As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions Evacuate personnel to safe areas. Use personal protective equipment. Ensure adequate

ventilation. Remove all sources of ignition. Stop leak if you can do it without risk.

Environmental Precautions

Environmental Precautions Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. Do

not flush into surface water or sanitary sewer system. Avoid release to the environment.

See Section 12 for additional Ecological Information.

Methods and materials for containment and cleaning up

Methods for Containment Prevent further leakage or spillage if safe to do so.

Methods for Cleaning Up Small spillage: Take up with sand or other noncombustible absorbent material and place

into containers for later disposal. Large spillage: Pump or vacuum transfer spilled product to

clean containers for recovery. Absorb unrecoverable product.

7. HANDLING AND STORAGE

Precautions for safe handling

Handling Avoid contact with skin, eyes and clothing. Keep away from open flames, hot surfaces and

sources of ignition. Take precautionary measures against static discharges. Use only in an area containing flame proof equipment. Ensure adequate ventilation. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld

containers.

Conditions for safe storage, including any incompatibilities

Storage Keep away from open flames, hot surfaces and sources of ignition. Keep containers tightly

closed in a cool, well-ventilated place. Keep out of the reach of children. Keep container

closed when not in use. Keep away from incompatible materials.

Incompatible Products Strong oxidizing agents. Strong acids. Strong reducing agents. Strong alkalis.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH

Stoddard solvent 8052-41-3	TWA: 100 ppm	TWA: 500 ppm TWA: 2900 mg/m³ (vacated) TWA: 100 ppm (vacated) TWA: 525 mg/m³	IDLH: 20000 mg/m ³ Ceiling: 1800 mg/m ³ 15 min TWA: 350 mg/m ³
Diacetone alcohol 123-42-2	TWA: 50 ppm	TWA: 50 ppm TWA: 240 mg/m³ (vacated) TWA: 50 ppm (vacated) TWA: 240 mg/m³	IDLH: 1800 ppm TWA: 50 ppm TWA: 240 mg/m³
Ethylbenzene 100-41-4	TWA: 20 ppm	TWA: 100 ppm TWA: 435 mg/m³ (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m³ (vacated) STEL: 125 ppm (vacated) STEL: 545 mg/m³	IDLH: 800 ppm TWA: 100 ppm TWA: 435 mg/m³ STEL: 125 ppm STEL: 545 mg/m³

Immediately Dangerous to Life or Health. ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value. OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits. NIOSH IDLH:

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 **Other Exposure Guidelines**

(11th Cir., 1992).

Appropriate engineering controls

Engineering Measures Showers

Eyewash stations Ventilation systems

Individual protection measures, such as personal protective equipment

Eye/Face Protection Safety glasses with side-shields. If splashes are likely to occur, wear: Chemical splash

Skin and Body Protection

Risk of contact: Chemical resistant gloves. Apron. Boots.

No special protective equipment required. If exposure limits are exceeded or irritation is **Respiratory Protection**

experienced, NIOSH/MSHA approved respiratory protection should be worn.

When using, do not eat, drink or smoke. Provide regular cleaning of equipment, work area **Hygiene Measures**

and clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical State Viscous liquid **Appearance** Opaque, Varies. Odor Mild **Odor Threshold** No information available

Property Values Remarks/ - Method None known No data available pН **Melting Point/Range** None known No data available 136.1-251.7 °C / 277-485 °F **Boiling Point/Boiling Range** None known 40.6 °C / 105 °F **Flash Point** None known < 1 (BuAc = 1)**Evaporation rate** None known Flammability (solid, gas) No data available None known

Flammability Limits in Air

upper flammability limit No data available 7.0 lower flammability limit No data available 1.10

None known **Vapor Pressure** No data available **Vapor Density** > 1 (air = 1)None known **Specific Gravity** No data available. None known **Water Solubility** Negligible None known Solubility in other solvents No data available None known Partition coefficient: n-octanol/waterNo data available None known **Autoignition Temperature** No data available None known **Decomposition Temperature** No data available None known No data available **Viscosity** None known

Flammable Properties Flammable; may be ignited by heat, sparks or flames.

Fundacing Departure No data qualible

Explosive PropertiesNo data available **Oxidizing Properties**No data available

Other information

VOC Content (%) A498M Orange: 42.28%

A991M Green: 38.74% A992M Red: 39.94% A993M Yellow: 40.08% A994M Blue: 37.62% A498M Orange: 430 g/L

A991M Green: 377 g/L A992M Red: 385 g/L A993M Yellow: 374 g/L A994M Blue: 364 g/L

10. STABILITY AND REACTIVITY

Reactivity

VOC (g/l)

No data available.

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

Hazardous Polymerization

Hazardous polymerization does not occur.

Conditions to avoid

Heat, flames and sparks. Incompatible products.

Incompatible materials

Strong oxidizing agents. Strong acids. Strong reducing agents. Strong alkalis.

Hazardous decomposition products

Carbon oxides. Smoke Soot.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Inhalation Inhalation of vapors in high concentration may cause irritation of respiratory system.

Eye Contact Causes serious eye damage.

Skin Contact May cause irritation.

Ingestion May be fatal if swallowed and enters airways. Ingestion may cause nausea and vomiting.

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Methyl ethyl ketoxime	= 930 mg/kg (Rat)	= 0.2 mg/kg (Rabbit)	= 20 mg/L (Rat) 4 h
Diacetone alcohol	= 4 g/kg (Rat)	= 13500 mg/kg (Rabbit)	-
Ethylbenzene	= 3500 mg/kg (Rat)	= 15354 mg/kg (Rabbit)	= 17.2 mg/L (Rat) 4 h

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms No information available.

Delayed and immediate effects and also chronic effects from short and long term exposure

Sensitization May cause an allergic skin reaction.

Mutagenic Effects May cause genetic defects.

Carcinogenicity This product contains one or more substances which are classified by IARC as

carcinogenic to humans (Group I), probably carcinogenic to humans (Group 2A) or possibly

carcinogenic to humans (Group 2B).

Chemical Name	ACGIH	IARC	NTP	OSHA
Ethylbenzene	A3	Group 2B		X

ACGIH: (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC: (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans

OSHA: (Occupational Safety & Health Administration)

X - Present

Reproductive Toxicity
STOT - single exposure
STOT - repeated exposure
No information available.
No information available.

Chronic Toxicity Avoid repeated exposure. Repeated contact may cause allergic reactions in very

susceptible persons. Ethylbenzene has been classified by the International Agency for Research on Cancer (IARC) as possibly carcinogenic to humans (Group 2B). Prolonged or repeated overexposure to ethylbenzene may result in adverse effects to the kidneys, liver, respiratory system, thyroid, testicles, and pituitary glands. May cause adverse liver effects.

Target Organ Effects Liver. Kidney. Respiratory system. Eyes. Skin. Central nervous system (CNS).

Aspiration Hazard May be fatal if swallowed and enters airways

Numerical measures of toxicity - Product

The following values are calculated based on chapter 3.1 of the GHS document:

LD50 Oral25144 mg/kg; Acute toxicity estimate **LD50 Dermal**32284 mg/kg; Acute toxicity estimate

Inhalation

dust/mist 615 mg/L; Acute toxicity estimate mg/L

12. ECOLOGICAL INFORMATION

This product contains a chemical which is listed as a marine pollutant according to DOT.

Ecotoxicity

The environmental impact of this product has not been fully investigated.

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Methyl ethyl ketoxime 96-29-7	EC50 72 h: = 83 mg/L (Desmodesmus subspicatus)	LC50 96 h: 777 - 914 mg/L flow-through (Pimephales promelas) LC50 96 h: = 760 mg/L static (Poecilia reticulata) LC50 96 h: 320 - 1000 mg/L static (Leuciscus idus)		EC50 48 h: = 750 mg/L (Daphnia magna)
Diacetone alcohol 123-42-2		LC50 96 h: = 420 mg/L static (Lepomis macrochirus) LC50 96 h: = 420 mg/L (Lepomis macrochirus)		EC50 24 h: = 8750 mg/L (Daphnia magna)

Ethylbenzene	EC50 72 h: = 4.6 mg/L	LC50 96 h: 11.0 - 18.0 mg/L	EC50 = 9.68 mg/L 30 min	EC50 48 h: 1.8 - 2.4 mg/L
100-41-4	(Pseudokirchneriella	static (Oncorhynchus	EC50 = 96 mg/L 24 h	(Daphnia magna)
	subcapitata) EC50 96 h: >	mykiss) LC50 96 h: = 4.2		
	438 mg/L	mg/L semi-static		
	(Pseudokirchneriella	(Oncorhynchus mykiss)		
	subcapitata) EC50 72 h: 2.6	LC50 96 h: 7.55 - 11 mg/L		
	- 11.3 mg/L static	flow-through (Pimephales		
	(Pseudokirchneriella	promelas) LC50 96 h: = 32		
	subcapitata) EC50 96 h: 1.7	mg/L static (Lepomis		
	- 7.6 mg/L static	macrochirus) LC50 96 h:		
	(Pseudokirchneriella	9.1 - 15.6 mg/L static		
	subcapitata) EC50 72 h: =	(Pimephales promelas)		
	11 mg/L	LC50 96 h: = 9.6 mg/L static		
	(Pseudokirchneriella	(Poecilia reticulata)		
	subcapitata)			

Persistence and Degradability

No information available.

Bioaccumulation

Chemical Name	Log Pow
Methyl ethyl ketoxime	0.65
Diacetone alcohol	1.03
Ethylbenzene	3.118

Other Adverse Effects

No information available.

13. DISPOSAL CONSIDERATIONS

Waste Disposal Methods Dispose of in accordance with federal, state, and local regulations

Contaminated Packaging Do not re-use empty containers.

US EPA Waste Number U122

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Ethylbenzene - 100-41-4		Included in waste stream: F039		
Formaldehyde - 50-00-0	U122	Included in waste streams: K009, K010, K038, K040, K156, K157		U122

14. TRANSPORT INFORMATION

DOT

UN-Number UN1993

Proper shipping name Flammable liquids, n.o.s.

Hazard Class 3
Packing Group

Marine Pollutant This product contains a chemical which is listed as a marine pollutant according to DOT.

Description UN1993, Flammable liquids, n.o.s. (Stoddard solvent, Diacetone alcohol), 3, III

Emergency Response Guide 128

Number

TDG

UN-Number UN1993

Proper Shipping Name Flammable liquid, n.o.s.

Hazard Class 3
Packing Group III

Description UN1993, Flammable liquid, n.o.s. (Stoddard solvent, Diacetone alcohol), 3, III

MEX

UN-Number UN1993

Proper Shipping Name Flammable liquid, n.o.s.

Hazard Class 3 Packing Group III

Description UN1993, Flammable liquid, n.o.s. (Stoddard solvent, Diacetone alcohol), 3, III

ICAO

UN-Number UN1993

Proper shipping name Flammable liquid, n.o.s.

Hazard Class 3
Packing Group

Description UN1993, Flammable liquid, n.o.s. (Stoddard solvent, Diacetone alcohol), 3, III

<u>IATA</u>

UN-Number UN1993

Proper Shipping Name Flammable liquid, n.o.s.

Hazard Class 3
Packing Group III
ERG Code 3L

Description UN1993, Flammable liquid, n.o.s. (Stoddard solvent, Diacetone alcohol), 3, III

IMDG/IMO

UN-Number UN1993

Proper Shipping Name Flammable liquid, n.o.s.

Hazard Class 3
Packing Group III

EmS No. F-E, S-E

Description UN1993, Flammable liquid, n.o.s. (Stoddard solvent, Diacetone alcohol), 3, III, (40.6°C c.c.)

RID

UN-Number UN1993

Proper Shipping Name Flammable liquid, n.o.s.

Hazard Class 3
Packing Group III
Classification Code F1

Description UN1993, Flammable liquid, n.o.s. (Stoddard solvent, Diacetone alcohol), 3, III

<u>ADR</u>

UN-Number UN1993

Proper Shipping Name Flammable liquid, n.o.s.

Hazard Class 3
Packing Group III
Classification Code F1
Tunnel Restriction Code (D/E)

Description UN1993, Flammable liquid, n.o.s. (Stoddard solvent, Diacetone alcohol), 3, III, (D/E)

ADN

Proper Shipping Name Flammable liquid, n.o.s.

Hazard Class 3
Packing Group III
Classification Code F1

Special Provisions 274, 601, 640E

Description UN1993, Flammable liquid, n.o.s. (Stoddard solvent, Diacetone alcohol), 3, III

Limited Quantity 5 L Ventilation VE01

15. REGULATORY INFORMATION

International Inventories

TSCA Complies

<u>Legend</u>

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

U.S. Federal Regulations

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

SARA 311/312 Hazard Categories

Acute Health Hazard Yes
Chronic Health Hazard Yes
Fire Hazard Yes
Sudden Release of Pressure Hazard No
Reactive Hazard No

Clean Water Act

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42):

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Ethylbenzene	1000 lb	X	X	X

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302):

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
Ethylbenzene	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ

U.S. State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals:

Chemical Name	CAS-No	California Prop. 65
Ethylbenzene	100-41-4	Carcinogen
Formaldehyde	50-00-0	Carcinogen
2-Ethylhexanoic acid	149-57-5	Developmental
Quartz	14808-60-7	Carcinogen

U.S. State Right-to-Know Regulations

"X" designates that the ingredients are listed on the state right to know list.

Chemical Name	New Jersey	Massachusetts	Pennsylvania	Illinois	Rhode Island
Stoddard solvent	X	X	X		X
Diacetone alcohol	X	Х	Х		X
Ethylbenzene	Х	Х	Х	Х	Х

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

16. OTHER INFORMATION						
NFPA	Health Hazard 2	Flammability 2	Instability 0	Physical and Chemical Hazards -		
<u>HMIS</u>	Health Hazard 2*	Flammability 2	Physical Hazard 0	Personal Protection X		

^{*}Indicates a chronic health hazard.

Prepared By Product Stewardship

23 British American Blvd. Latham, NY 12110 1-800-572-6501

Issuing Date22-Jul-2014Revision Date22-Jul-2014Revision NoteInitial Release.

General Disclaimer

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of Safety Data Sheet
