



# SAFETY DATA SHEET

Issuing Date 16-Sep-2014

Revision Date 08-May-2015

Revision Number 1

## 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY/UNDERTAKING

### GHS product identifier

**Product Name** Rinz Off (Wash-Out) All Colors

### Other means of identification

**Part Number** Black (91109), Blue (44105, 91105), Green (91108), Red (44106, 91106), White (44709), Yellow (44757, 91757)

**Formula Code** A511M (Black), N105 (Blue), N108 (Green), N106 (Red), Y709 (White), Y756 (Yellow)

**UN-Number** UN1263

**Synonyms** None

### Recommended use of the chemical and restrictions on use

**Recommended Use** Solvent based marker

**Uses advised against** No information available

### Supplier's details

**Supplier Address**  
ITW PRO BRANDS  
805 E. Old 56 Highway  
Olathe, KS 66061  
TEL: 1-800-443-9536

### Emergency telephone number

**Emergency Telephone Number** 800-535-5053 Infotrac


## 2. HAZARDS IDENTIFICATION

### Classification

This chemical is considered hazardous according to the OSHA Hazard Communication Standard 2012 (29 CFR 1910.1200)

Acute Oral Toxicity	Category 4
Serious Eye Damage/Eye Irritation	Category 1
Carcinogenicity	Category 2
Specific Target Organ Systemic Toxicity (Single Exposure)	Category 3
Flammable liquids	Category 3

**GHS Label elements, including precautionary statements****Emergency Overview**

<b>Signal Word</b>	<b>Danger</b>		
<b>Hazard Statements</b>			
<ul style="list-style-type: none"> <li>• Harmful if swallowed</li> <li>• Causes serious eye damage</li> <li>• Suspected of causing cancer</li> <li>• May cause drowsiness or dizziness</li> <li>•</li> <li>• Flammable liquid and vapor.</li> </ul>			
			
<b>Appearance</b>	Varies, Thin viscosity,	<b>Physical State</b>	Liquid.
			<b>Odor</b> Alcohol, Mild

**Precautionary Statements****Prevention**

- Wash face, hands and any exposed skin thoroughly after handling.
- Do not eat, drink or smoke when using this product.
- Obtain special instructions before use.
- Do not handle until all safety precautions have been read and understood.
- Use personal protective equipment as required.
- Wear eye/face protection.
- Avoid breathing dust/fume/gas/mist/vapors/spray.
- Use only outdoors or in a well-ventilated area.
- Keep away from heat/sparks/open flames/hot surfaces - No smoking.
- Keep container tightly closed.
- Ground/bond container and receiving equipment.
- Use explosion-proof electrical/ventilating/lighting/equipment.
- Use only non-sparking tools.
- Take precautionary measures against static discharge.
- Keep cool.

**General Advice**

- If exposed or concerned: Get medical attention/advice

**Eyes**

- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- Immediately call a POISON CENTER or doctor/physician.

**Skin**

- IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

**Inhalation**

- IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

**Ingestion**

- IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.
- Rinse mouth.

**Fire**

- In case of fire: Use CO<sub>2</sub>, dry chemical, or foam for extinction.

**Storage**

- Store locked up.
- Store in a well-ventilated place. Keep container tightly closed.

**Disposal**

- Dispose of contents/container to an approved waste disposal plant.

**Hazard Not Otherwise Classified (HNOC)**

Not applicable

**Other information**

30.3778% of the mixture consists of ingredient(s) of unknown toxicity.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS-No	Weight %	Trade secret
Propanol	71-23-8	60-100	*
Diacetone alcohol	123-42-2	15-40	*
Titanium dioxide	13463-67-7	10-30	*
Xanthylum,9-(2-carboxyphenyl)-3,6-bis(diethyl amino)-, hydrogenbis[3-[(4,5-dihydro-3-methyl-5...	84962-27-6	1-5	*
Silicon dioxide	7631-86-9	1-5	*
Aluminum hydroxide	21645-51-2	1-5	*

*\*The exact percentage (concentration) of composition has been withheld as a trade secret.*

### 4. FIRST AID MEASURES

**Description of necessary first-aid measures**

<b>Eye Contact</b>	Rinse thoroughly with plenty of water, also under the eyelids. If symptoms persist, call a physician.
<b>Skin Contact</b>	Flush with cool water. If skin irritation persists, call a physician.
<b>Inhalation</b>	Move to fresh air. If breathing is difficult, give oxygen. If symptoms persist, call a physician.
<b>Ingestion</b>	Rinse mouth. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Drink plenty of water. Consult a physician if necessary
<b>Protection of First-aiders</b>	Use personal protective equipment. Remove all sources of ignition.

**Most important symptoms/effects, acute and delayed**

**Most Important Symptoms/Effects** No information available.

**Indication of immediate medical attention and special treatment needed, if necessary**

**Notes to Physician** Treat symptomatically.

### 5. FIRE-FIGHTING MEASURES

**Suitable Extinguishing Media**

Carbon dioxide (CO<sub>2</sub>). Foam. Dry chemical.

**Unsuitable Extinguishing Media** No information available.

**Specific Hazards Arising from the Chemical**

Flammable. Keep product and empty container away from heat and sources of ignition. Risk of ignition

**Explosion Data**

Sensitivity to Mechanical Impact None.  
 Sensitivity to Static Discharge Yes.

**Protective Equipment and Precautions for Firefighters**

Wear self contained breathing apparatus for fire fighting if necessary.

**6. ACCIDENTAL RELEASE MEASURES**

**Personal precautions, protective equipment and emergency procedures**

**Personal Precautions** Remove all sources of ignition. Evacuate personnel to safe areas. Ensure adequate ventilation. Use personal protective equipment. Stop leak if you can do it without risk.

**Environmental Precautions**

**Environmental Precautions** Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. Do not flush into surface water or sanitary sewer system.

**Methods and materials for containment and cleaning up**

**Methods for Containment** Prevent further leakage or spillage if safe to do so.

**Methods for Cleaning Up** Small spillage: Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Large spillage: Pump or vacuum transfer spilled product to clean containers for recovery. Absorb unrecoverable product.

**7. HANDLING AND STORAGE**

**Precautions for safe handling**

**Handling** Avoid contact with skin, eyes and clothing. Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharges. Use only in an area containing flame proof equipment. Ensure adequate ventilation. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers.

**Conditions for safe storage, including any incompatibilities**

**Storage** Keep away from open flames, hot surfaces and sources of ignition. Keep containers tightly closed in a cool, well-ventilated place. Keep out of the reach of children. Keep container closed when not in use. Keep away from incompatible materials.

**Incompatible Products** Strong oxidizing agents. Strong reducing agents. Strong alkalis. Strong acids.

**8. EXPOSURE CONTROLS / PERSONAL PROTECTION**

**Control parameters**

**Exposure Guidelines**

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
---------------	-----------	----------	------------

Propanol 71-23-8	TWA: 100 ppm	TWA: 200 ppm TWA: 500 mg/m <sup>3</sup> (vacated) TWA: 200 ppm (vacated) TWA: 500 mg/m <sup>3</sup> (vacated) STEL: 250 ppm (vacated) STEL: 625 mg/m <sup>3</sup>	IDLH: 800 ppm TWA: 200 ppm TWA: 500 mg/m <sup>3</sup> STEL: 250 ppm STEL: 625 mg/m <sup>3</sup>
Diacetone alcohol 123-42-2	TWA: 50 ppm	TWA: 50 ppm TWA: 240 mg/m <sup>3</sup> (vacated) TWA: 50 ppm (vacated) TWA: 240 mg/m <sup>3</sup>	IDLH: 1800 ppm TWA: 50 ppm TWA: 240 mg/m <sup>3</sup>
Titanium dioxide 13463-67-7	TWA: 10 mg/m <sup>3</sup>	TWA: 15 mg/m <sup>3</sup> total dust (vacated) TWA: 10 mg/m <sup>3</sup> total dust	IDLH: 5000 mg/m <sup>3</sup>
Silicon dioxide 7631-86-9	10 mg/m <sup>3</sup>	20 mppcf TWA; ((80)/(% SiO <sub>2</sub> )) mg/m <sup>3</sup> )	IDLH: 3000 mg/m <sup>3</sup> TWA: 6 mg/m <sup>3</sup>
Aluminum hydroxide 21645-51-2	TWA: 1 mg/m <sup>3</sup> respirable fraction	-	-

**Appropriate engineering controls**

**Engineering Measures**                      Showers  
     Eyewash stations  
     Ventilation systems

**Individual protection measures, such as personal protective equipment**

**Eye/Face Protection**                      Safety glasses with side-shields. If splashes are likely to occur, wear: Chemical splash goggles.  
**Skin and Body Protection**                Chemical resistant gloves. Risk of contact: Boots. Apron.  
**Respiratory Protection**                    No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn.

**Hygiene Measures**                            Handle in accordance with good industrial hygiene and safety practice.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

**Information on basic physical and chemical properties**

<b>Physical State</b>	Liquid	<b>Appearance</b>	Varies Thin viscosity,
<b>Odor</b>	Alcohol, Mild	<b>Odor Threshold</b>	No information available

<u>Property</u>	<u>Values</u>	<u>Remarks/ - Method</u>
pH	No data available	None known
Melting Point/Range	No data available	None known
Boiling Point/Boiling Range	97.22 °C / 207 °F	None known
Flash Point	No data available 25 77	None known
Evaporation rate	1.3 (BuAc = 1)	None known
Flammability (solid, gas)	No data available	None known
Flammability Limits in Air		
upper flammability limit	13.7	
lower flammability limit	2.1	
Vapor Pressure	No data available	None known
Vapor Density	> 1 (air = 1)	None known
Specific Gravity	< 1 @ 70°F	None known
Water Solubility	70-80%	None known
Solubility in other solvents	No data available	None known
Partition coefficient: n-octanol/water	No data available	None known
Autoignition Temperature	No data available	None known
Decomposition Temperature	No data available	None known
Viscosity	No data available	None known

**Flammable Properties**                      Not flammable

**Explosive Properties**                        No data available  
**Oxidizing Properties**                        No data available

**Other information**

<b>VOC Content (%)</b>	A511M Black: 88.89% N106 Red: 91.52% N105 Blue: 91.62% Y709 White: 73.39% N108 Green: 91.42% Y756 Yellow: 77.07%
<b>VOC (g/l)</b>	A511M Black: 786 g/L N106 Red: 802 g/L N105 Blue: 799 g/L Y709 White: 758 g/L N108 Green: 804 g/L Y756 Yellow: 757 g/L

<b>10. STABILITY AND REACTIVITY</b>
-------------------------------------

**Reactivity**

No data available.

**Chemical stability**

Stable under recommended storage conditions.

**Possibility of hazardous reactions**

None under normal processing.

**Hazardous Polymerization**

Hazardous polymerization does not occur.

**Conditions to avoid**

Heat, flames and sparks. Incompatible products.

**Incompatible materials**

Strong oxidizing agents. Strong reducing agents. Strong alkalis. Strong acids.

**Hazardous decomposition products**

Carbon oxides. Soot. Smoke

<b>11. TOXICOLOGICAL INFORMATION</b>
--------------------------------------

**Information on likely routes of exposure****Product Information****Inhalation**

May cause drowsiness and dizziness. Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal

**Eye Contact**

Causes serious eye irritation. Causes serious eye damage.

**Skin Contact**

May be harmful in contact with skin.

**Ingestion**

Harmful if swallowed.

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
---------------	-----------	-------------	-----------------

Propanol	= 1870 mg/kg ( Rat )	= 4049 mg/kg ( Rabbit )	> 13548 ppm ( Rat ) 4 h
Diacetone alcohol	= 4 g/kg ( Rat )	= 13500 mg/kg ( Rabbit )	-
Titanium dioxide	> 10000 mg/kg ( Rat )	-	-
Silicon dioxide	> 5000 mg/kg ( Rat )	> 2000 mg/kg ( Rabbit )	>2.2 mg/L ( Rat ) 4 h
Aluminum hydroxide	> 5000 mg/kg ( Rat )	-	-

**Symptoms related to the physical, chemical and toxicological characteristics**

**Symptoms** No information available.

**Delayed and immediate effects and also chronic effects from short and long term exposure**

**Sensitization** No information available.

**Mutagenic Effects** No information available.

**Carcinogenicity** This product contains titanium dioxide which is classified as an IARC 2B carcinogen based on laboratory studies where animals were exposed to titanium dioxide dust.

Chemical Name	ACGIH	IARC	NTP	OSHA
Titanium dioxide		Group 2B	-	-
Xanthylum,9-(2-carboxyphe nyl)-3,6-bis(diethyl amino)-, hydrogenbis[3-[(4,5-dihydro- 3-methyl-5...		Group 3		
Silicon dioxide		Group 3		

**IARC: (International Agency for Research on Cancer)**

Group 2B - Possibly Carcinogenic to Humans

Group 3: Not Classifiable as to its Carcinogenicity to Humans

**Reproductive Toxicity** No information available.

**STOT - single exposure** No information available.

**STOT - repeated exposure** No information available.

**Chronic Toxicity** Avoid repeated exposure. May cause adverse liver effects. May cause adverse effects on the bone marrow and blood-forming system.

**Aspiration Hazard** No information available.

**Numerical measures of toxicity - Product**

**Acute Toxicity** 30.3778% of the mixture consists of ingredient(s) of unknown toxicity.

*The following values are calculated based on chapter 3.1 of the GHS document:*

**LD50 Oral** 1217 mg/kg; Acute toxicity estimate

**LD50 Dermal** 2781 mg/kg; Acute toxicity estimate

**12. ECOLOGICAL INFORMATION****Ecotoxicity**

Very toxic to aquatic life with long lasting effects.

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Propanol 71-23-8		LC50 96 h: = 4480 mg/L flow-through (Pimephales promelas)	EC50 = 17700 mg/L 5 min EC50 = 45000 mg/L 5 h EC50 = 8686 mg/L 15 min EC50 = 980 mg/L 12 h	EC50 48 h: = 3642 mg/L (Daphnia magna) EC50 48 h: 3339 - 3977 mg/L Static (Daphnia magna)
Diacetone alcohol 123-42-2		LC50 96 h: = 420 mg/L static (Lepomis macrochirus) LC50 96 h: = 420 mg/L (Lepomis macrochirus)		EC50 24 h: = 8750 mg/L (Daphnia magna)
Silicon dioxide 7631-86-9	EC50 72 h: = 440 mg/L (Pseudokirchneriella subcapitata)	LC50 96 h: = 5000 mg/L static (Brachydanio rerio)		EC50 48 h: = 7600 mg/L (Ceriodaphnia dubia)

**Persistence and Degradability** No information available.

**Bioaccumulation**

Chemical Name	Log Pow
Propanol	0.25 - 0.34
Diacetone alcohol	1.03

**Other Adverse Effects**

No information available.

**13. DISPOSAL CONSIDERATIONS****Waste Disposal Methods** Dispose of in accordance with federal, state, and local regulations**Contaminated Packaging** Do not re-use empty containers.**US EPA Waste Number** D001

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste
Propanol	Toxic Ignitable

**14. TRANSPORT INFORMATION****DOT**

**UN-Number** UN1263  
**Proper shipping name** Paint  
**Hazard Class** 3  
**Packing Group** III  
**Description** UN1263, Paint, 3, III  
**Emergency Response Guide Number** 128

**TDG**

**UN-Number** UN1263  
**Proper Shipping Name** Paint  
**Hazard Class** 3  
**Packing Group** III  
**Description** UN1263, Paint, 3, III

**MEX**

**UN-Number** UN1263  
**Proper Shipping Name** Paint  
**Hazard Class** 3  
**Packing Group** III  
**Description** UN1263, Paint, 3, III

**ICAO**

**UN-Number** UN1263  
**Proper shipping name** Paint  
**Hazard Class** 3  
**Packing Group** III  
**Description** UN1263, Paint, 3, III

**IATA**

**UN-Number** UN1263  
**Proper Shipping Name** Paint  
**Hazard Class** 3  
**Packing Group** III  
**ERG Code** 3L  
**Description** UN1263, Paint, 3, III

**IMDG/IMO**

**UN-Number** UN1263



Proper Shipping Name	Paint
Hazard Class	3
Packing Group	III
EmS No.	F-E, S-E
Description	UN1263, Paint, 3, III, (25°C c.c.)

**RID**

UN-Number	UN1263
Proper Shipping Name	Paint
Hazard Class	3
Packing Group	III
Classification Code	F1
Description	UN1263, Paint, 3, III

**ADR**

UN-Number	UN1263
Proper Shipping Name	Paint
Hazard Class	3
Packing Group	III
Classification Code	F1
Tunnel Restriction Code	(D/E)
Description	UN1263, Paint, 3, III, (D/E)

**ADN**

Proper Shipping Name	Paint
Hazard Class	3
Packing Group	III
Classification Code	F1
Special Provisions	163, 640E, 650
Description	UN1263, Paint, 3, III
Limited Quantity	5 L
Ventilation	VE01

<b>15. REGULATORY INFORMATION</b>
-----------------------------------

**International Inventories****Legend**

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

**U.S. Federal Regulations**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

**SARA 311/312 Hazard Categories**

Acute Health Hazard	Yes
Chronic Health Hazard	Yes
Fire Hazard	Yes
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

**Clean Water Act**

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42):

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances

Xanthylum,9-(2-carboxyphe nyl)-3,6-bis(diethyl amino)-, hydrogenbis[3-[(4,5-dihydro- 3-methyl-5...		X		
---	--	---	--	--

**CERCLA**

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material.

**U.S. State Regulations****California Proposition 65**

This product contains the following Proposition 65 chemicals:

Chemical Name	CAS-No	California Prop. 65
Titanium dioxide	13463-67-7	Carcinogen
Quartz	14808-60-7	Carcinogen

**U.S. State Right-to-Know Regulations**

"X" designates that the ingredients are listed on the state right to know list.

Chemical Name	New Jersey	Massachusetts	Pennsylvania	Illinois	Rhode Island
Propanol	X	X	X		X
Diacetone alcohol	X	X	X		X
Titanium dioxide		X			X
Xanthylum,9-(2-carboxyphe nyl)-3,6-bis(diethyl amino)-, hydrogenbis[3-[(4,5-dihydro- 3-methyl-5...			X	X	

**U.S. EPA Label Information**

EPA Pesticide Registration Number Not applicable

**16. OTHER INFORMATION**

<b><u>NFPA</u></b>	Health Hazard	0	Flammability	0	Instability	0	Physical and Chemical Hazards	-
<b><u>HMIS</u></b>	Health Hazard	0	Flammability	0	Physical Hazard	0	Personal Protection	X

Prepared By Product Stewardship  
23 British American Blvd.  
Latham, NY 12110  
1-800-572-6501

Issuing Date 16-Sep-2014  
Revision Date 08-May-2015  
Revision Note Initial Release.

**General Disclaimer**

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

**End of Safety Data Sheet**