

Revision Date 09-Mar-2015

Version 1

SAFETY DATA SHEET

1. IDENTIFICATION			
Product identifier			
Product Name	THE RIGHT STUFF GASKET MAKER 7 OZ AE		
Other means of identification			
Product Code	25224		
Synonyms	None		
Recommended use of the chemical	and restrictions on use		
Recommended Use	Sealant		
Uses advised against	No information available		
-			
Details of the supplier of the safety			
Manufacturer Address	<u>Distributor</u>		
ITW Permatex	ITW Permatex Canada		
10 Columbus Blvd.	35 Brownridge Road, Unit 1		
Hartford, CT 06106 USA	Halton Hills, ON Canada L7G 0C6		
	Telephone: (800) 924-6994		
Company Phone Number	1-87-Permatex		
. ,	(877) 376-2839		
24 Hour Emergency Phone Number			
	International Emergency:		
	00+1+ 813-248-0585		
	Contract Number: MIS0003453		

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Serious eye damage/eye irritation	Category 2A
Skin sensitization	Category 1
Carcinogenicity	Category 2

Label elements

Emergency Overview

Warning

Causes serious eye irritation May cause an allergic skin reaction Suspected of causing cancer



Physical state Paste

Odor Mild

Precautionary Statements - Prevention

Obtain special instructions before use Do not handle until all safety precautions have been read and understood Use personal protective equipment as required Wash face, hands and any exposed skin thoroughly after handling Avoid breathing dust/fume/gas/mist/vapors/spray Contaminated work clothing should not be allowed out of the workplace Wear protective gloves/protective clothing/eye protection/face protection

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention IF ON SKIN: Wash with plenty of soap and water If skin irritation or rash occurs: Get medical advice/attention Wash contaminated clothing before reuse

Precautionary Statements - Storage

Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Other Information

Harmful to aquatic life with long lasting effects

Unknown acute toxicity

10.294% of the mixture consists of ingredient(s) of unknown toxicity

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance

Chemical Name	CAS No	Weight-%	Trade Secret
CALCIUM CARBONATE	471-34-1	15 - 40	*
POLY (DIMETHYLSILOXANE), HYDROXY TERMINATED	70131-67-8	15 - 40	*
POLYDIMETHYLSILOXANE	63148-62-9	7 - 13	*
VINYL OXIMINOSILANE	2224-33-1	1 - 5	*
NITROGEN	7727-37-9	1 - 5	*
STEARIC ACID	57-11-4	1 - 5	*
CARBON BLACK	1333-86-4	1 - 5	*
2-BUTANONE OXIME	96-29-7	1 - 5	*

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

Description of first aid measures

Description of first and measures	
General advice	Get medical advice/attention if you feel unwell.
Eye contact	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
Skin contact	IF ON SKIN:. Wash with soap and water. If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse.
Inhalation	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If symptoms persist, call a physician.
Ingestion	IF SWALLOWED. Do NOT induce vomiting. Never give anything by mouth to an unconscious person.
Self-protection of the first aider	Use personal protective equipment as required.
Most important symptoms and effe	ects, both acute and delayed
Symptoms	May cause redness and tearing of the eyes. May cause allergic skin reaction.
Indication of any immediate medic	al attention and special treatment needed
Note to physicians	Treat symptomatically.
	5. FIRE-FIGHTING MEASURES
<u>Suitable extinguishing media</u> Carbon dioxide (CO2), Dry chemical,	
Carbon dioxide (CO2), Dry chemical, Unsuitable extinguishing media None. Specific hazards arising from the c	Foam
Carbon dioxide (CO2), Dry chemical, Unsuitable extinguishing media None. Specific hazards arising from the c	Foam :hemical
Carbon dioxide (CO2), Dry chemical, <u>Unsuitable extinguishing media</u> None. <u>Specific hazards arising from the c</u> Heating causes rise in pressure with <u>Explosion data</u> Sensitivity to Mechanical Impact Sensitivity to Static Discharge <u>Protective equipment and precauti</u>	Foam <u> hemical</u> risk of bursting. Keep product and empty container away from heat and sources of ignition. None. None.
Carbon dioxide (CO2), Dry chemical, Unsuitable extinguishing media None. Specific hazards arising from the of Heating causes rise in pressure with Explosion data Sensitivity to Mechanical Impact Sensitivity to Static Discharge Protective equipment and precauti As in any fire, wear self-contained bro	Foam <u>hemical</u> risk of bursting. Keep product and empty container away from heat and sources of ignition. None. None. ons for firefighters
Carbon dioxide (CO2), Dry chemical, <u>Unsuitable extinguishing media</u> None. <u>Specific hazards arising from the o</u> Heating causes rise in pressure with <u>Explosion data</u> <u>Sensitivity to Mechanical Impact</u> <u>Sensitivity to Static Discharge</u> <u>Protective equipment and precauti</u> As in any fire, wear self-contained bro protective gear.	Foam <u> chemical</u> risk of bursting. Keep product and empty container away from heat and sources of ignition. None. None. <u> ons for firefighters</u> eathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full

Environmental precautions

Environmental precautions Do not flush into surface water or sanitary sewer system. Prevent further leakage or spillage if safe to do so. Prevent product from entering drains.

Methods and material for containment and cleaning up

Methods for containment	Prevent further leakage or spillage if safe to do so.		
Methods for cleaning up	Ensure adequate ventilation. Flood with water to complete polymerization and scrape off floor. Sweep up and shovel into suitable containers for disposal. Slippery, can cause falls if walked on.		
Prevention of secondary hazards	Clean contaminated objects and areas thoroughly observing environmental regulations.		
	7. HANDLING AND STORAGE		
Precautions for safe handling			
Advice on safe handling	Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin and eyes. Avoid breathing vapors or mists. Keep away from heat/sparks/open		

Conditions for safe storage, including any incompatibilities

Storage Conditions	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Protect from moisture.
Incompatible materials	Strong oxidizing agents, Acids, Water

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

	· ·		
Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
CALCIUM CARBONATE	-	-	TWA: 10 mg/m ³ total dust
471-34-1			TWA: 5 mg/m ³ respirable dust
CARBON BLACK	TWA: 3 mg/m ³ inhalable fraction	TWA: 3.5 mg/m ³	IDLH: 1750 mg/m ³
1333-86-4	-	(vacated) TWA: 3.5 mg/m ³	TWA: 3.5 mg/m ³
			TWA: 0.1 mg/m ³ Carbon black in
			presence of Polycyclic aromatic
			hydrocarbons PAH

NIOSH IDLH Immediately Dangerous to Life or Health

Other Information

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

flames/hot surfaces. - No smoking. Use personal protective equipment as required.

Appropriate engineering controls

Engineering Controls Showers Eyewash

Showers Eyewash stations Ventilation systems

Individual protection measures, such as personal protective equipment

Eye/face protection	Wear safety glasses with side shields (or goggles).
Skin and body protection	Wear protective gloves and protective clothing.
Respiratory protection	Use NIOSH-approved air-purifying respirator with organic vapor cartridge or canister, as appropriate.
General Hygiene Considerations	Handle in accordance with good industrial hygiene and safety practice. Regular cleaning of equipment, work area and clothing is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state Appearance Odor Odor threshold

Property

pН Melting point / freezing point **Boiling point / boiling range** Flash point **Evaporation rate** Flammability (solid, gas) Flammability Limit in Air Upper flammability limit: Lower flammability limit: Vapor pressure Vapor density **Relative density** Water solubility Solubility in other solvents Partition coefficient Autoignition temperature **Decomposition temperature** Kinematic viscosity Dynamic viscosity **Explosive properties Oxidizing properties**

Other Information

Softening point Molecular weight VOC Content (%) Density Bulk density Paste Black Mild No information available

Values

7-8 No information available Not Applicable > 93 °C / > 199 °F < 1 No information available No information available No information available <5 mmHg @ 70°F 3 1.34 Not applicable No information available No information available

No information available No information available <3% No information available No information available

Remarks • Method

Polymerization Tag Closed Cup Butyl acetate = 1

Air = 1

Polymerization

10. STABILITY AND REACTIVITY

Reactivity No data available

Chemical stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

Risk of explosion if heated under confinement.

Conditions to avoid

Heat, flames and sparks. Exposure to air or moisture over prolonged periods.

Incompatible materials

Strong oxidizing agents, Acids, Water

Hazardous Decomposition Products

Carbon oxides, Nitrogen oxides (NOx), Formaldehyde, May release 2-butanone oxime (ethyl methyl ketoxime) at elevated temperature

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation	May cause irritation of respiratory tract.
Eye contact	Contact with eyes may cause irritation. May cause redness and tearing of the eyes.
Skin contact	May cause skin irritation and/or dermatitis. May cause sensitization by skin contact.
Ingestion	Ingestion may cause irritation to mucous membranes.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
CALCIUM CARBONATE 471-34-1	= 6450 mg/kg (Rat)	-	-
POLY (DIMETHYLSILOXANE), HYDROXY TERMINATED 70131-67-8	-	> 16 mL/kg (Rabbit)	> 8750 mg/m³(Rat)7 h
POLYDIMETHYLSILOXANE 63148-62-9	> 17 g/kg (Rat)	> 2 g/kg (Rabbit)	-
STEARIC ACID 57-11-4	-	> 5 g/kg (Rabbit)	-
CARBON BLACK 1333-86-4	> 15400 mg/kg (Rat)	> 3 g/kg (Rabbit)	-
2-BUTANONE OXIME 96-29-7	= 930 mg/kg (Rat)	= 0.2 mg/kg (Rabbit)	= 20 mg/L (Rat)4 h

Information on toxicological effects

Symptoms

No information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Serious eye damage/eye	irritation Causes	serious eye irritation.		
Sensitization	May cause sensitization by skin contact.			
Germ cell mutagenicity	No infor	rmation available.		
Carcinogenicity	The tab	le below indicates whether ea	ch agency has listed any in	gredient as a carcinogen.
Chemical Name	ACGIH	IARC	NTP	OSHA
CARBON BLACK	A3	Group 2B	-	Х
1333-86-4				
X - Present	inogenic to Humans fety and Health Admii	nistration of the US Departmen	,	
Target Organ Effects	Eyes, L	ymphatic System, Respiratory	/ system, Skin.	
Numerical measures of to	oxicity - Product In	formation		
The following values are ATEmix (oral)	calculated based o 10960	on chapter 3.1 of the GHS do	cument .	
· · · · /		0 0		

A I Emix (oral)	10960 mg/kg
ATEmix (dermal)	8999 mg/kg

12. ECOLOGICAL INFORMATION

Ecotoxicity

None known

Chemical Name	Algae/aquatic plants	Fish	Crustacea
CARBON BLACK	-	-	5600: 24 h Daphnia magna mg/L
1333-86-4			EC50

2-BUTANONE OXIME 96-29-7	83: 72 h Desmodesmus subspicatus mg/L EC50	777 - 914: 96 h Pimephales promelas mg/L LC50 flow-through 320 - 1000: 96 h Leuciscus idus	750: 48 h Daphnia magna mg/L EC50
		mg/L LC50 static 760: 96 h Poecilia reticulata mg/L LC50 static	

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Mobility

No information available.

Chemical Name	Partition coefficient
2-BUTANONE OXIME	0.65
96-29-7	

Other adverse effects

No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods	
Disposal of wastes	Dispos

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Contaminated packaging	Do not reuse container.
------------------------	-------------------------

US EPA Waste Number Not applicable

14. TRANSPORT INFORMATION

DOT UN/ID no Proper shipping name: Hazard Class	UN 1950 Aerosols Limited Quantity (LQ) 2.2
IATA	
UN/ID no	ID 8000
Proper shipping name:	Consumer commodity
Hazard Class	9
ERG Code	9L
Special Provisions	A112
IMDG	
UN/ID no	UN 1950
Proper shipping name:	Aerosols, Limited Quantity (LQ)
Hazard Class	2.2
EmS-No	F-D, S-U
Special Provisions	63, 190, 277, 327, 344, 959

15. REGULATORY INFORMATION

International Inventories

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances ENCS - Japan Existing and New Chemical Substances IECSC - China Inventory of Existing Chemical Substances KECL - Korean Existing and Evaluated Chemical Substances PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

SARA 311/312 Hazard Categories

Yes
No
No
No
No

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals

Chemical Name	California Proposition 65	
CARBON BLACK - 1333-86-4	Carcinogen	

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
NITROGEN 7727-37-9	Х	X	X
CARBON BLACK 1333-86-4	Х	X	X
ALUMINIUM POWDER 7429-90-5	Х	X	X

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

<u>NFPA</u>	Health hazards 2	Flammability 2	Instability 0	-
HMIS	Health hazards 2	Flammability 2	Physical hazards 0	Personal protection B

NFPA (National Fire Protection Association) HMIS (Hazardous Material Information System)

Revision Date

09-Mar-2015

Disclaimer

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet