# **Permatex.**

# SAFETY DATA SHEET

Revision Date 12-Dec-2014 Version 1

# 1. IDENTIFICATION

Product identifier

Product Name 771 NICKEL ANTI-SEIZE LUBRICANT 80Z BT

Other means of identification

Product Code 77124 Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use Lubricant

Uses advised against No information available

Details of the supplier of the safety data sheet

<u>Manufacturer Address</u> <u>Distributor</u>

ITW Permatex Canada
10 Columbus Blvd. 35 Brownridge Road, Unit 1
Hartford, CT 06106 USA Halton Hills, ON Canada L7G 0C6

Telephone: (800) 924-6994

Company Phone Number 1-87-Permatex

(877) 376-2839

24 Hour Emergency Phone Number Chem-Tel: 800-255-3924

International Emergency: 00+1+ 813-248-0585

Contract Number: MIS0003453

E-mail address mail@permatex.com

# 2. HAZARDS IDENTIFICATION

#### Classification

# **OSHA Regulatory Status**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin sensitization	Category 1
Carcinogenicity	Category 2

#### Label elements

#### **Emergency Overview**

#### Warning

May cause an allergic skin reaction Suspected of causing cancer



Appearance Silver Physical state Paste Odor Petroleum odor

#### **Precautionary Statements - Prevention**

Obtain special instructions before use
Do not handle until all safety precautions have been read and understood
Use personal protective equipment as required
Avoid breathing mists or vapors
Wear protective gloves
Contaminated work clothing should not be allowed out of the workplace

#### **Precautionary Statements - Response**

IF exposed or concerned: Get medical advice/attention Specific treatment (see supplemental first aid instructions on this label) IF ON SKIN: Wash with plenty of soap and water If skin irritation or rash occurs: Get medical advice/attention Wash contaminated clothing before reuse

# **Precautionary Statements - Storage**

Store locked up

### **Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

#### Hazards not otherwise classified (HNOC)

Not applicable

# Other Information

Toxic to aquatic life with long lasting effects. The classification as a carcinogen need not apply if it can be shown that the substance contains less than 3 % DMSO extract as measured by IP 346. This note applies only to certain complex oil derived substances in Annex I. No. Respirable dust.

Unknown acute toxicity

34.5% of the mixture consists of ingredient(s) of unknown toxicity

# 3. COMPOSITION/INFORMATION ON INGREDIENTS

#### substance(s)

Chemical Name	CAS No	Weight-%	Trade Secret
DISTILLATES (PETROLEUM), SOLVENT-REFINED HEAVY NAPHTHENIC	64741-96-4	30 - 60	*
GRAPHITE	7782-42-5	10 - 30	*
NICKEL	7440-02-0	5 - 10	*
ALUMINIUM POWDER	7429-90-5	1 - 5	*

<sup>\*</sup>The exact percentage (concentration) of composition has been withheld as a trade secret.

# 4. FIRST AID MEASURES

#### **Description of first aid measures**

Revision Date 12-Dec-2014

**General advice** Get medical advice/attention if you feel unwell.

Eye contact IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. If eye irritation persists: Get medical

advice/attention.

Skin contact IF ON SKIN:. Wash with soap and water. If skin irritation or rash occurs: Get medical

advice/attention. Wash contaminated clothing before reuse.

**Inhalation** IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for

breathing. If symptoms persist, call a physician.

Ingestion IF SWALLOWED:. Do NOT induce vomiting. Never give anything by mouth to an

unconscious person. Call a physician.

Self-protection of the first aider

Use personal protective equipment as required. Avoid contact with skin, eyes or clothing.

Most important symptoms and effects, both acute and delayed

**Symptoms** See section 2 for more information.

Indication of any immediate medical attention and special treatment needed

# 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Carbon dioxide (CO2), Dry chemical, Foam

Unsuitable extinguishing media

Water.

Specific hazards arising from the chemical

None in particular.

**Explosion data** 

Sensitivity to Mechanical Impact None.
Sensitivity to Static Discharge None.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

# 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Ensure adequate ventilation, especially in confined areas. Avoid contact with eyes and skin.

Use personal protective equipment as required.

Environmental precautions

**Environmental precautions**Do not flush into surface water or sanitary sewer system. See Section 12 for additional

ecological information.

Methods and material for containment and cleaning up

**Methods for containment** Prevent further leakage or spillage if safe to do so.

Revision Date 12-Dec-2014

Methods for cleaning up Ensure adequate ventilation. Soak up with inert absorbent material. Sweep up and shovel

into suitable containers for disposal.

**Prevention of secondary hazards** Clean contaminated objects and areas thoroughly observing environmental regulations.

# 7. HANDLING AND STORAGE

#### Precautions for safe handling

Advice on safe handling Handle in accordance with good industrial hygiene and safety practice. Avoid breathing

vapors or mists. Avoid contact with skin, eyes or clothing. Wash thoroughly after handling. Wash contaminated clothing before reuse. Use personal protective equipment as required.

#### Conditions for safe storage, including any incompatibilities

Storage Conditions Keep container tightly closed in a dry and well-ventilated place. Store locked up.

Incompatible materials Strong oxidizing agents

# 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
GRAPHITE	TWA: 2 mg/m³ respirable fraction	TWA: 15 mg/m³ total dust synthetic	IDLH: 1250 mg/m <sup>3</sup>
7782-42-5	all forms except graphite fibers	TWA: 5 mg/m <sup>3</sup> respirable fraction	TWA: 2.5 mg/m³ natural respirable
		synthetic	dust
		(vacated) TWA: 2.5 mg/m <sup>3</sup>	
		respirable dust natural	
		(vacated) TWA: 10 mg/m <sup>3</sup> total dust	
		synthetic	
		(vacated) TWA: 5 mg/m³ respirable	
		fraction synthetic	
		TWA: 15 mppcf natural	
NICKEL	TWA: 1.5 mg/m³ inhalable fraction	TWA: 1 mg/m <sup>3</sup>	IDLH: 10 mg/m <sup>3</sup> Ni
7440-02-0		(vacated) TWA: 1 mg/m <sup>3</sup>	TWA: 0.015 mg/m <sup>3</sup> except Nickel
			carbonyl Ni
ALUMINIUM POWDER	TWA: 1 mg/m³ respirable fraction	TWA: 15 mg/m³ total dust	TWA: 5 mg/m <sup>3</sup> Al
7429-90-5		TWA: 5 mg/m³ respirable fraction	_
		(vacated) TWA: 5 mg/m <sup>3</sup> Al	
		Aluminum	

NIOSH IDLH Immediately Dangerous to Life or Health

Other Information Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962

(11th Cir., 1992).

Appropriate engineering controls

Engineering Controls Showers

Eyewash stations Ventilation systems

Individual protection measures, such as personal protective equipment

**Eye/face protection** Wear safety glasses with side shields (or goggles).

**Skin and body protection** Wear protective gloves and protective clothing.

**Respiratory protection**Use NIOSH-approved air-purifying respirator with organic vapor cartridge or canister, as

appropriate.

**General Hygiene Considerations** 

Handle in accordance with good industrial hygiene and safety practice. Regular cleaning of equipment, work area and clothing is recommended.

Butyl acetate = 1

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

#### Information on basic physical and chemical properties

Physical state Paste
Appearance Silver

Odor Petroleum odor

Odor threshold No information available

Property Values Remarks • Method

PH No information available

Melting point / freezing pointNo information availableBoiling point / boiling rangeNo information availableFlash point> 204 °C / > 400 °F

Evaporation rate < 1

Flammability (solid, gas) No information available

Flammability Limit in Air

Upper flammability limit:No information availableLower flammability limit:No information availableVapor pressureNo information availableVapor densityNo information available

Relative density 1.12
Water solubility Negligible

Solubility in other solvents No information available **Partition coefficient** No information available **Autoignition temperature** No information available **Decomposition temperature** No information available Kinematic viscosity No information available **Dynamic viscosity** No information available **Explosive properties** No information available **Oxidizing properties** No information available

**Other Information** 

Softening pointNo information availableMolecular weightNo information available

VOC Content (%)

DensityNo information availableBulk densityNo information available

# 10. STABILITY AND REACTIVITY

#### Reactivity

No data available

#### Chemical stability

Stable under recommended storage conditions.

#### **Possibility of Hazardous Reactions**

None under normal processing.

#### **Hazardous polymerization**

Hazardous polymerization does not occur.

#### **Conditions to avoid**

Excessive heat.

#### **Incompatible materials**

Strong oxidizing agents

#### **Hazardous Decomposition Products**

Carbon oxides Metal oxides

# 11. TOXICOLOGICAL INFORMATION

#### Information on likely routes of exposure

**Inhalation** May cause irritation of respiratory tract.

**Eye contact** Contact with eyes may cause irritation. May cause redness and tearing of the eyes.

**Skin contact** May cause skin irritation and/or dermatitis. Repeated or prolonged skin contact may cause

allergic reactions with susceptible persons.

**Ingestion** Ingestion may cause irritation to mucous membranes.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
NICKEL	> 9000 mg/kg (Rat)	-	-
7440-02-0			

# Information on toxicological effects

Symptoms No information available.

# Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Sensitization** May cause sensitization by skin contact.

Germ cell mutagenicity No information available.

**Carcinogenicity**The table below indicates whether each agency has listed any ingredient as a carcinogen.

			. agone, nac notou an, mg	
Chemical Name	ACGIH	IARC	NTP	OSHA
DISTILLATES (PETROLEUM), SOLVENT-REFINED HEAVY NAPHTHENIC 64741-96-4	A2	Group 1	-	X
NICKEL 7440-02-0	-	Group 1	Known	Х

ACGIH (American Conference of Governmental Industrial Hygienists)

A2 - Suspected Human Carcinogen

IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans NTP (National Toxicology Program)

Known - Known Carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Target Organ Effects Central Vascular System (CVS), Lungs, Nasal Cavities, Respiratory system, Skin.

#### The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral) 73761 mg/kg

# 12. ECOLOGICAL INFORMATION

# **Ecotoxicity**

37% of the mixture consists of components(s) of unknown hazards to the aquatic environment

Chemical Name	Algae/aquatic plants	Fish	Crustacea

# 77124 - 771 NICKEL ANTI-SEIZE LUBRICANT 80Z BT

DISTILLATES (PETROLEUM), SOLVENT-REFINED HEAVY NAPHTHENIC 64741-96-4	-	5000: 96 h Oncorhynchus mykiss mg/L LC50	1000: 48 h Daphnia magna mg/L EC50
NICKEL 7440-02-0	0.18: 72 h Pseudokirchneriella subcapitata mg/L EC50 0.174 - 0.311: 96 h Pseudokirchneriella subcapitata mg/L EC50 static	100: 96 h Brachydanio rerio mg/L LC50 1.3: 96 h Cyprinus carpio mg/L LC50 semi-static 10.4: 96 h Cyprinus carpio mg/L LC50 static	100: 48 h Daphnia magna mg/L EC50 1: 48 h Daphnia magna mg/L EC50 Static

# Persistence and degradability

No information available.

# **Bioaccumulation**

No information available.

#### **Mobility**

No information available.

# Other adverse effects

No information available

# 13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastes Disposal should be in accordance with applicable regional, national and local laws and

regulations.

Contaminated packaging Do not reuse container.

US EPA Waste Number Not applicable

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
NICKEL	-	Included in waste streams:	-	-
7440-02-0		F006, F039		

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste Status
NICKEL	Toxic powder
7440-02-0	Ignitable powder
ALUMINIUM POWDER	Ignitable powder
7429-90-5	

# 14. TRANSPORT INFORMATION

DOT

Proper shipping name: Not regulated

IATA

Proper shipping name: Not regulated

**IMDG** 

Proper shipping name: Not regulated

# 15. REGULATORY INFORMATION

**International Inventories** 

# 77124 - 771 NICKEL ANTI-SEIZE LUBRICANT 80Z

TSCA Complies
DSL/NDSL Complies
EINECS/ELINCS Complies

ENCS Not Listed. Contains: Natural substance(s)

IECSCCompliesKECLCompliesPICCSCompliesAICSComplies

# Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

**ENCS** - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

# **US Federal Regulations**

#### **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	SARA 313 - Threshold Values %
NICKEL - 7440-02-0	0.1
ALUMINIUM POWDER - 7429-90-5	1.0

# SARA 311/312 Hazard Categories

Acute health hazard Yes
Chronic Health Hazard Yes
Fire hazard No
Sudden release of pressure hazard No
Reactive Hazard No

#### **CWA (Clean Water Act)**

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
NICKEL 7440-02-0	-	X	Х	-

#### **CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
NICKEL	100 lb	-	RQ 100 lb final RQ
7440-02-0			RQ 45.4 kg final RQ

# **US State Regulations**

#### **California Proposition 65**

This product contains the following Proposition 65 chemicals

Chemical Name	California Proposition 65
NICKEL - 7440-02-0	Carcinogen

# U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania

GRAPHITE 7782-42-5	X	X	X
NICKEL 7440-02-0	X	Х	X
ALUMINIUM POWDER 7429-90-5	X	Х	Х

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

NFPAHealth hazards 2Flammability 1Instability 0-HMISHealth hazards 2Flammability 1Physical hazards 0Personal protection B

NFPA (National Fire Protection Association) HMIS (Hazardous Material Information System)

Revision Date 12-Dec-2014

#### **Disclaimer**

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**