# **Permatex.**

# SAFETY DATA SHEET

Revision Date 21-Apr-2015 Version 1

# 1. IDENTIFICATION

Product identifier

Product Name 66BR CLEAR RTV SILICONE ADHESIVE SEALANT 3 OZ

Other means of identification

Product Code 80050 Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use Sealant

Uses advised against No information available

Details of the supplier of the safety data sheet

Manufacturer Address Distributor

ITW Permatex Canada
10 Columbus Blvd. 35 Brownridge Road, Unit 1
Hartford, CT 06106 USA Halton Hills, ON Canada L7G 0C6

Telephone: (800) 924-6994

Company Phone Number 1-87-Permatex

(877) 376-2839

24 Hour Emergency Phone Number Chem-Tel: 800-255-3924

International Emergency: 00+1+ 813-248-0585

Contract Number: MIS0003453

E-mail address mail@permatex.com

# 2. HAZARDS IDENTIFICATION

#### Classification

# **OSHA Regulatory Status**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2A

#### Label elements

#### **Emergency Overview**

#### Warning

Causes skin irritation Causes serious eye irritation



Appearance Clear Physical state Paste Odor Acetic acid

#### **Precautionary Statements - Prevention**

Wash face, hands and any exposed skin thoroughly after handling Wear eye/face protection

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

If eye irritation persists: Get medical advice/attention IF ON SKIN: Wash with plenty of soap and water If skin irritation occurs: Get medical advice/attention Take off contaminated clothing and wash before reuse

#### **Precautionary Statements - Storage**

Protect from sunlight. Store in a well-ventilated place Protect from moisture

#### **Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

#### Hazards not otherwise classified (HNOC)

Not applicable

#### Other Information

Harmful to aquatic life with long lasting effects

The classification as a carcinogen need not apply if the full refining history is known and it can be shown that the substance from which it is produced is not a carcinogen. This note applies only to certain complex oil derived substances in Annex I

Unknown acute toxicity

2.5% of the mixture consists of ingredient(s) of unknown toxicity

# 3. COMPOSITION/INFORMATION ON INGREDIENTS

#### substance(s)

Chemical Name	CAS No	Weight-%	Trade Secret
POLY (DIMETHYLSILOXANE), HYDROXY	70131-67-8	60 - 100	*
TERMINATED			
AMORPHOUS SILICA	7631-86-9	7 - 13	*
DISTILLATES (PETROLEUM), HYDROTREATED	64742-46-7	5 - 10	*
MIDDLE			
METHYLTRIACETOXYSILANE	4253-34-3	1 - 5	*
ETHYLTRIACETOXYSILANE	17689-77-9	1 - 5	*
ACETIC ACID	64-19-7	1 - 5	*

<sup>\*</sup>The exact percentage (concentration) of composition has been withheld as a trade secret.

# 4. FIRST AID MEASURES

## **Description of first aid measures**

**General advice** Get medical advice/attention if you feel unwell.

Revision Date 21-Apr-2015

Eye contact IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. If eye irritation persists: Get medical

advice/attention.

**Skin contact** IF ON SKIN:. Wash skin with soap and water. If skin irritation persists, call a physician.

Wash contaminated clothing before reuse.

Inhalation IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for

breathing. If symptoms persist, call a physician.

Ingestion IF SWALLOWED:. Do NOT induce vomiting. Never give anything by mouth to an

unconscious person. Call a physician.

Self-protection of the first aider

Use personal protective equipment as required. Avoid contact with skin, eyes or clothing.

Most important symptoms and effects, both acute and delayed

**Symptoms** See section 2 for more information.

Indication of any immediate medical attention and special treatment needed

**Note to physicians** Treat symptomatically.

### 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Carbon dioxide (CO2), Dry chemical, Foam

Unsuitable extinguishing media

None.

Specific hazards arising from the chemical

None in particular.

**Explosion data** 

Sensitivity to Mechanical Impact None.
Sensitivity to Static Discharge None.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

# 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

**Personal precautions** Ensure adequate ventilation, especially in confined areas. Avoid contact with eyes and skin.

Use personal protective equipment as required.

Environmental precautions

**Environmental precautions**Do not flush into surface water or sanitary sewer system. Avoid release to the environment.

See Section 12 for additional ecological information.

Methods and material for containment and cleaning up

**Methods for containment** Prevent further leakage or spillage if safe to do so.

Revision Date 21-Apr-2015

Methods for cleaning up Ensure adequate ventilation. Flood with water to complete polymerization and scrape off

floor. Sweep up and shovel into suitable containers for disposal. Slippery, can cause falls if

walked on.

**Prevention of secondary hazards** Clean contaminated objects and areas thoroughly observing environmental regulations.

#### 7. HANDLING AND STORAGE

### Precautions for safe handling

Advice on safe handling Handle in accordance with good industrial hygiene and safety practice. Avoid breathing

vapors or mists. Avoid contact with skin, eyes or clothing. Wash thoroughly after handling. Wash contaminated clothing before reuse. Use personal protective equipment as required.

#### Conditions for safe storage, including any incompatibilities

Storage Conditions Keep container tightly closed in a dry and well-ventilated place. Protect from moisture.

Incompatible materials Strong oxidizing agents, Acids, Water

# 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
AMORPHOUS SILICA	-	(vacated) TWA: 6 mg/m <sup>3</sup> <1%	IDLH: 3000 mg/m <sup>3</sup>
7631-86-9		Crystalline silica	TWA: 6 mg/m <sup>3</sup>
		TWA: 20 mppcf	
		: (80)/(% SiO2) mg/m <sup>3</sup> TWA	
ACETIC ACID	STEL: 15 ppm	TWA: 10 ppm	IDLH: 50 ppm
64-19-7	TWA: 10 ppm	TWA: 25 mg/m <sup>3</sup>	TWA: 10 ppm
		(vacated) TWA: 10 ppm	TWA: 25 mg/m <sup>3</sup>
		(vacated) TWA: 25 mg/m <sup>3</sup>	STEL: 15 ppm
			STEL: 37 mg/m <sup>3</sup>

NIOSH IDLH Immediately Dangerous to Life or Health

Other Information Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962

(11th Cir., 1992).

**Appropriate engineering controls** 

Engineering Controls Showers

Eyewash stations Ventilation systems

# Individual protection measures, such as personal protective equipment

**Eye/face protection** Wear safety glasses with side shields (or goggles).

**Skin and body protection** Wear protective gloves and protective clothing.

**Respiratory protection**Use NIOSH-approved air-purifying respirator with organic vapor cartridge or canister, as

appropriate.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice. Regular cleaning of

equipment, work area and clothing is recommended.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

#### Information on basic physical and chemical properties

# 80050 - 66BR CLEAR RTV SILICONE ADHESIVE SEALANT 3 OZ

Remarks • Method

Polymerization

Air = 1

Polymerization

Tag Closed Cup

Physical state Paste
Appearance Clear
Odor Acetic acid

Odor threshold No information available

<u>Property</u> <u>Values</u>

pH No information availableMelting point / freezing point No information available

Boiling point / boiling range
Flash point > 93 °C / > 200 °F
Evaporation rate No information available
Flammability (solid, gas) No information available

Flammability Limit in Air

Upper flammability limit:
Lower flammability limit:
Vapor pressure

No information available
No information available
10 mm Hg @ 25°C

Vapor density >1 Relative density 1.007

Water solubility Not applicable

Solubility in other solvents No information available **Partition coefficient** No information available **Autoignition temperature** No information available **Decomposition temperature** No information available Kinematic viscosity No information available **Dynamic viscosity** No information available **Explosive properties** No information available **Oxidizing properties** No information available

Other Information

Softening pointNo information availableMolecular weightNo information available

VOC Content (%) <3%

Density No information available Bulk density No information available

# 10. STABILITY AND REACTIVITY

#### Reactivity

No data available

#### Chemical stability

Stable under recommended storage conditions.

#### **Possibility of Hazardous Reactions**

None under normal processing.

#### **Conditions to avoid**

Excessive heat.

#### Incompatible materials

Strong oxidizing agents, Acids, Water

#### **Hazardous Decomposition Products**

Carbon oxides Nitrogen oxides (NOx) Acetic acid Formaldehyde

# 11. TOXICOLOGICAL INFORMATION

#### Information on likely routes of exposure

**Inhalation** May cause irritation of respiratory tract.

Eye contact Contact with eyes may cause irritation. May cause redness and tearing of the eyes.

**Skin contact** May cause skin irritation and/or dermatitis.

**Ingestion** Ingestion may cause irritation to mucous membranes.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
POLY (DIMETHYLSILOXANE), HYDROXY TERMINATED 70131-67-8	-	> 16 mL/kg(Rabbit)	> 8750 mg/m³(Rat)7 h
AMORPHOUS SILICA 7631-86-9	> 5000 mg/kg(Rat)	> 2000 mg/kg ( Rabbit )	> 2.2 mg/L (Rat)1 h
DISTILLATES (PETROLEUM), HYDROTREATED MIDDLE 64742-46-7	= 7400 mg/kg(Rat)	> 2000 mg/kg(Rabbit)	= 4.6 mg/L (Rat) 4 h
METHYLTRIACETOXYSILANE 4253-34-3	= 2060 mg/kg (Rat)	-	-
ACETIC ACID 64-19-7	= 3310 mg/kg (Rat)	= 1060 mg/kg ( Rabbit )	= 11.4 mg/L (Rat) 4 h

#### Information on toxicological effects

Symptoms No information available.

# Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Sensitization Germ cell mutagenicity**No information available.
No information available.

**Carcinogenicity** The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
AMORPHOUS SILICA 7631-86-9	-	Group 3	-	-

IARC (International Agency for Research on Cancer)

Not classifiable as a human carcinogen

**Target Organ Effects** Eyes, Respiratory system, Skin, Teeth.

# The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral) 21001 mg/kg
ATEmix (dermal) 6606 mg/kg
ATEmix (inhalation-dust/mist) 5.5 mg/l

# 12. ECOLOGICAL INFORMATION

# **Ecotoxicity**

81% of the mixture consists of components(s) of unknown hazards to the aquatic environment

Chemical Name	Algae/aquatic plants	Fish	Crustacea
AMORPHOUS SILICA 7631-86-9	440: 72 h Pseudokirchneriella subcapitata mg/L EC50	5000: 96 h Brachydanio rerio mg/L LC50 static	7600: 48 h Ceriodaphnia dubia mg/L EC50
DISTILLATES (PETROLEUM), HYDROTREATED MIDDLE 64742-46-7	-	35: 96 h Pimephales promelas mg/L LC50 flow-through 10000: 96 h Pimephales promelas mg/L LC50 static	-
ACETIC ACID 64-19-7	-	79: 96 h Pimephales promelas mg/L LC50 static 75: 96 h Lepomis macrochirus mg/L LC50 static	65: 48 h Daphnia magna mg/L EC50 Static 47: 24 h Daphnia magna mg/L EC50

# 80050 - 66BR CLEAR RTV SILICONE ADHESIVE SEALANT 3 OZ

#### Persistence and degradability

No information available.

#### **Bioaccumulation**

No information available.

#### **Mobility**

No information available.

Chemical Name	Partition coefficient
ACETIC ACID	-0.31
64-19-7	

# Other adverse effects

No information available

# 13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastes Disposal should be in accordance with applicable regional, national and local laws and

regulations.

**Contaminated packaging** Do not reuse container.

US EPA Waste Number Not applicable

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste Status	
ACETIC ACID	Toxic	
64-19-7	Corrosive	
	Ignitable	

# 14. TRANSPORT INFORMATION

DOT

Proper shipping name: Not regulated

<u>IATA</u>

Proper shipping name: Not regulated

<u>IMDG</u>

Proper shipping name: Not regulated

# 15. REGULATORY INFORMATION

**International Inventories** 

**TSCA** Complies Complies **DSL/NDSL** Not Listed. **EINECS/ELINCS ENCS** Not Listed. Complies **IECSC** Complies **KECL** Complies **PICCS** Complies **AICS** 

# 80050 - 66BR CLEAR RTV SILICONE ADHESIVE **SEALANT 3 OZ**

#### Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

**ENCS** - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

#### **US Federal Regulations**

#### **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

#### SARA 311/312 Hazard Categories

Acute health hazard Yes **Chronic Health Hazard** No Fire hazard No Sudden release of pressure hazard No **Reactive Hazard** Nο

# **CWA (Clean Water Act)**

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
ACETIC ACID 64-19-7	5000 lb	-	-	Х

# **CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
ACETIC ACID	5000 lb	-	RQ 5000 lb final RQ
64-19-7			RQ 2270 kg final RQ

#### **US State Regulations**

#### **California Proposition 65**

This product does not contain any Proposition 65 chemicals

#### U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
AMORPHOUS SILICA 7631-86-9	X	X	X
ACETIC ACID 64-19-7	X	X	X

#### **U.S. EPA Label Information**

**EPA Pesticide Registration Number** Not applicable

NFPA Health hazards 1 Flammability 1 **Instability** 0

HMIS Health hazards 1 Flammability 1 Physical hazards 0 Personal protection B

NFPA (National Fire Protection Association) HMIS (Hazardous Material Information System)

**Revision Date** 21-Apr-2015

#### **Disclaimer**

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**