



# ULTRA HIGH SOLIDS

A single coat of this floor finish is so continuous that it acts as a sealer and a finish. A second coat is necessary only if the flooring has been poorly maintained or otherwise abused. This ultra high solids floor finish is a tough and flexible metal cross-linked acrylic, formulated to dry to a brilliant gloss. Buffing is not required to bring out a shine. However, buffing as a part of regular maintenance procedures prolongs the life of the floor.

**FLOOR FINISH** 

This finish is non-yellowing and detergent resistant. It is easily repairable. Worn-out traffic areas can be recoated at anytime without stripping. Removal of this finish is easy by using an active amine or ammoniated floor stripper.

### **FEATURES**

Time tested polymer technology
Outstanding slip resistance
Positioned as a value floor finish
Acts as a sealer and finish in one
Designed for high traffic
High speed burnishable

# - RELATED BENEFITS

- Long lasting, deep, lustrous gloss
- Reduces liability potential
- Outstanding features for an average price
- Saves time and cost of labor
- Excellent gloss and scuff resistance
- For a conventional maintenance program

### **AREAS OF USE -**

Use with electric burnisher maintenance routines

- Restaurants, hotels, motels, offices
- Hospitals, nursing homes, doctors offices
- Schools, universities, child care centers
- Grocery stores, malls, retail stores

# TO USE -

Apply finish in a uniform, thin coat to stripped floor. Two to four coats are recommended for initial application. For applications, see label for complete directions and use only as directed.

# **SPECIFICATION DATA**

Available Sizes - 4/1G, 5G, 55G Physical State - Liquid
Color - Milky White Fragrance - Acrylic
Total solids - 24.5% Metal Interlocked - Yes

Initial Gloss - Excellent Burnisher Response - Excellent Slip Resistance - Exceeds ASTM 2047 Traffic Area - High

Specific Gravity - 1.04 pH - 8.1

1TEM # **690** 

CARROLL®

COMPANY

2900 W Kingsley Rd., Garland, TX 75041

www.carrollco.com • 1-800-527-5722