

Diversey

Signature®

Ultra High Speed  
Floor finish



---

The floor finish solution for “wet look” appearance throughout your establishment —for floor care that’s simply brilliant.

#### Excellent Performance

- Unsurpassed “wet look” gloss
- Dramatic response to propane, battery and electric equipment
- Designed to excel on vinyl composite, sheet vinyl and terrazzo flooring

#### Easy-to-Use

- Easy to apply, thin or full coats, fast drying
- Restorers and maintainers are not required
- Apply over virtually any finish after deep-scrubbing with
- Diversey UHS™/MC Cleaner and green pads

---

#### Designed For

- Healthcare
  - Government
  - Retail
  - Education
  - Lodging
  - BSC
-

# Use Overview



Signature® Ultra High Speed Floor Finish provides unsurpassed “wet look” gloss, excellent durability and dirt release. It is easy to apply and maintain.

## Preparation

- Blockade areas to be stripped or finished. Floors will be very slippery until dry.
- Strip floors using a Diversey brand stripper per the instructions on the stripper label.

## Coating

- Apply 3 or more medium coats of product using a clean finish mop or the Diversey ProSpeed™/MC or TrailBlazer™/MC Floor Finish Applicator Systems. Apply additional coats until desired gloss is obtained.
- Allow 30–45 minutes drying time between coats. Temperature, humidity and ventilation may affect drying time. Allow finish to cure for 24 hours before burnishing.

## Maintenance

- Dust mop or sweep.
- Clean the floor with a mop or an automatic scrubber using the recommended Diversey brand cleaner according to the label directions.
- Burnish using appropriate pads.

## Recoating

- Dust mop or sweep.
- Clean the floor with a mop or an automatic scrubber using the recommended Diversey brand cleaner according to the label directions.
- Blockade area and apply 1–2 uniform coats of finish using a clean mop.
- Allow finish to cure for 24 hours before burnishing.



**Signature® Ultra High Speed Floor Finish** meets the newest and most stringent VOC standards in North America, including those adopted by the California Air Resources Board (CARB) 2011 regulations. In addition, **Signature® Floor Finish** is formulated with readily biodegradable surfactants and solvents. Also, **Signature® Floor Finish** is not formulated with any endocrine-disrupting plasticizers, dyes, or fragrances. These attributes, combined with numerous others, make this product an excellent choice for your facility under a sustainable facility care program.

## Product Specifications

Description	
Color/Form	White liquid
Flash Point	>200° F (> 93.3° C)
pH	8.35
Scent	Ammonia
Shelf Life	2 years
Solids %	20
Solubility	Dispersible
Specific Gravity	1.032
Slip Resistance	0.5 minimum (ASTM D2047)

## Hazard Rating

HMIS		NFPA
1	Health	1
0	Flammability	0
0	Reactivity	0

4=Very High; 3=High; 2=Moderate; 1=Slight; 0=Insignificant.

## Available Items

Product Code	Description/Package Size	Dilution
5104950	1 x 5 gallon / 18.9 L Envirobox™/MC (TrailBlazer™/MC ready)	Ready-to-Use
4971947	6 x 2.64 U.S. Qt. / 2.5 L ProSpeed™/MC BIB (Bag-in-Box)	Ready-to-Use

## Safety Reminder

Please make sure your employees read and understand the product label and Safety Data Sheet before using this product. The label contains directions for use, and both the label and SDS contain hazard warnings, precautionary statements and first aid procedures. SDSs are available on-line at [www.sealedair.com](http://www.sealedair.com) or by calling 888 352 2249. Improper use or dilution may result in damage to surfaces and may result in health and physical hazards that match those of the concentrate. Please refer to the Diversey HazMat Library, only available through Internet Explorer, <http://naextranet.diversey.com/dot/>, for up to date shipping information.